

NM OIL CONSERVATION

ARTESIA DISTRICT

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy Minerals and Natural Resources
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

JAN 31 2018

Form C-141
Revised April 3, 2017

Submit Copy to appropriate District Office in
conformance with 19.15.29 NMAC.

RECEIVED

Release Notification and Corrective Action

NAB1803253192

OPERATOR

☒ Initial Report ☐ Final Report

Name of Company	OXY USA INC	Contact	WADE DITTRICH
Address	PO BOX 4294; HOUSTON, TX 77210	Telephone No.	575-390-2828
Facility Name	FNR 26 FEDERAL #1 CTB	Facility Type	BATTERY

Surface Owner	BLM	Mineral Owner	BLM	API No.	30-015-30412
---------------	-----	---------------	-----	---------	--------------

LOCATION OF RELEASE

Unit Letter	Section	Township	Range	Feet from the	North/South Line	Feet from the	East/West Line	County
M	26	23S	30E	660	SOUTH	660	WEST	EDDY

Latitude 32.2704697° Longitude -103.8581543° NAD83

NATURE OF RELEASE

Type of Release	OIL & PRODUCE WATER	Volume of Release	4 bbls OIL & 10 bbls PRODUCED WATER	Volume Recovered	0 bbls
Source of Release	2 inch steel Victaulic clamp on the gas sales line failure	Date and Hour of Occurrence	1/8/2018	Date and Hour of Discovery	
Was Immediate Notice Given?	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> Not Required	If YES, To Whom?	MIKE BRATCHER-NMOCD; CRYSTAL WEAVER-NMOCD; SHELLY TUCKER-BLM		
By Whom?	WADE DITTRICH	Date and Hour	01/25/2018 @ 4:43 PM	3:43pm * email	
Was a Watercourse Reached?	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	If YES, Volume Impacting the Watercourse.			

If a Watercourse was Impacted, Describe Fully.*

Describe Cause of Problem and Remedial Action Taken.*

A 2 inch steel Victaulic clamp on the gas sales line failed causing 4 bbls of oil and 10 bbls of produced water. No fluids have been recovered at this time. The clamp has been repaired and returned to service.

Describe Area Affected and Cleanup Action Taken.*

The affected area is approximately 10x20ft (measurements are subject to change with GPS tracking). Remediation will be completed by an approved plan from NMOCD & BLM.

I hereby certify that the information given above is true and complete to the best of my knowledge and understand that pursuant to NMOCD rules and regulations all operators are required to report and/or file certain release notifications and perform corrective actions for releases which may endanger public health or the environment. The acceptance of a C-141 report by the NMOCD marked as "Final Report" does not relieve the operator of liability should their operations have failed to adequately investigate and remediate contamination that pose a threat to ground water, surface water, human health or the environment. In addition, NMOCD acceptance of a C-141 report does not relieve the operator of responsibility for compliance with any other federal, state, or local laws and/or regulations.

Signature:	<u>Wa de DITTRICH</u>		
Printed Name:	WADE DITTRICH		
Title:	ENVIRONMENTAL SPECIALIST		
E-mail Address:	wade.dittrich@oxy.com		
Date:	1-31-18	Phone:	575-390-2828
		OIL CONSERVATION DIVISION	
		Approved by Environmental Specialist: <u>[Signature]</u>	
		Approval Date:	2/1/18
		Expiration Date:	N/A
		Conditions of Approval:	See attached
		Attached:	ARP-4595

* Attach Additional Sheets If Necessary

Operator/Responsible Party,

The OCD has received the form C-141 you provided on 1/31/2018 regarding an unauthorized release. The information contained on that form has been entered into our incident database and remediation case number ARP-4505 has been assigned. **Please refer to this case number in all future correspondence.**

It is the Division's obligation under both the Oil & Gas Act and Water Quality Act to provide for the protection of public health and the environment. Our regulations (19.15.29.11 NMAC) state the following,

The responsible person shall complete division-approved corrective action for releases that endanger public health or the environment. The responsible person shall address releases in accordance with a remediation plan submitted to and approved by the division or with an abatement plan submitted in accordance with 19.15.30 NMAC. [emphasis added]

Release characterization is the first phase of corrective action unless the release is ongoing or is of limited volume and all impacts can be immediately addressed. Proper and cost-effective remediation typically cannot occur without adequate characterization of the impacts of any release. Furthermore, the Division has the ability to impose reasonable conditions upon the efforts it oversees. **As such, the Division is requiring a workplan for the characterization of impacts associated with this release be submitted to the OCD District 2 office in ARTESIA on or before 3/3/2018. If and when the release characterization workplan is approved, there will be an associated deadline for submittal of the resultant investigation report. Modest extensions of time to these deadlines may be granted, but only with acceptable justification.**

The goals of a characterization effort are: 1) determination of the lateral and vertical extents along with the magnitude of soil contamination. 2) determine if groundwater or surface waters have been impacted. 3) If groundwater or surface waters have been impacted, what are the extents and magnitude of that impact. 4) The characterization of any other adverse impacts that may have occurred (examples: impacts on vegetation, impacts on wildlife, air quality, loss of use of property, etc.). To meet these goals as quickly as possible, the following items must, at a minimum, be addressed in the release characterization workplan and subsequent reporting:

- Horizontal delineation of soil impacts in each of the four cardinal compass directions. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. This is not an exclusive list of potential contaminants. Analyzed parameters should be modified based on the nature of the released substance(s). Soil sampling must be both within the impacted area and beyond.

- Vertical delineation of soil impacts. Adsorbed soil contamination must be characterized for the following constituents using the associated laboratory methods: benzene, toluene, ethylbenzene, and total xylenes by either Method 8260 or 8021, total petroleum hydrocarbons by Method 8015 extended range (GRO+DRO+MRO; C₆ thru C₃₆), and for chloride by Method 300. As above, this is not an exclusive list of potential contaminants and can be modified. Vertical characterization samples should be taken at depth intervals no greater than five feet apart. Lithologic description of encountered soils must also be provided. At least ten vertical feet of soils with contaminant concentrations at or below these values must be demonstrated as existing above the water table.

- Nominal detection limits for field and laboratory analyses must be provided.

- Composite sampling is not generally allowed.

- Field screening and assessment techniques are acceptable (headspace, titration, EC [include algorithm for validation purposes], EM, etc.), but the sampling and assay procedures must be clearly defined. Copies of field notes are highly desirable. A statistically significant set of split samples must be submitted for confirmatory laboratory analysis, including the laterally farthest and vertically deepest sets of soil samples. Make sure there are at least two soil samples submitted

for laboratory analysis from each borehole or test pit (highest observed contamination and deepest depth investigated). Copies of the actual laboratory results must be provided including chain of custody documentation.

- Probable depth to shallowest protectable groundwater and lateral distance to nearest surface water. If there is an estimate of groundwater depth, the information used to arrive at that estimate must be provided. If there is a reasonable assumption that the depth to protectable water is 50 feet or less, the responsible party should anticipate the need for at least one groundwater monitoring well to be installed in the area of likely maximum contamination.

- If groundwater contamination is encountered, an additional investigation workplan may be required to determine the extents of that contamination. Groundwater and/or surface water samples, if any, must be analyzed by a competent laboratory for volatile organic hydrocarbons (typically Method 8260 full list), total dissolved solids, pH, major anions and cations including chloride and sulfate, dissolved iron, and dissolved manganese. The investigation workplan must provide the groundwater sampling method(s) and sample handling protocols. To the fullest extent possible, aqueous analyses must be undertaken using nominal method detection limits. As with the soil analyses, copies of the actual laboratory results must be provided including chain of custody documentation.

- Accurately scaled and well-drafted site maps must be provided providing the location of borings, test pits, monitoring wells, potentially impacted areas, and significant surface features including roads and site infrastructure that might limit either the release characterization or remedial efforts. Field sketches may be included in subsequent reporting, but should not be considered stand-alone documentation of the site's layout. Digital photographic documentation of the location and fieldwork is recommended, especially if unusual circumstances are encountered.

Nothing herein should be interpreted to preclude emergency response actions or to imply immediate remediation by removal cannot proceed as warranted. Nonetheless, characterization of impacts and confirmation of the effectiveness of remedial efforts must still be provided to the OCD before any release incident will be closed.

Jim Griswold
OCD Environmental Bureau Chief
1220 South St. Francis Drive
Santa Fe, New Mexico 87505
505-476-3465
jim.griswold@state.nm.us

Bratcher, Mike, EMNRD

From: Wade_Dittrich@oxy.com
Sent: Wednesday, January 31, 2018 1:34 PM
To: Bratcher, Mike, EMNRD; Weaver, Crystal, EMNRD
Cc: stucker@blm.gov
Subject: FNR 26 Federal 31 CTB
Attachments: Initial-Signed C141.pdf

All,

Attached is the **Initial C141**. Please review and let me know if there are any questions. Thank you.

Wade Dittrich
Environmental Specialist
Oxy Permian-New Mexico
575-390-2828 cell
575-397-8214 office
Wade_Dittrich@Oxy.com

Bratcher, Mike, EMNRD

From: Wade_Dittrich@oxy.com
Sent: Thursday, January 25, 2018 3:43 PM
To: Bratcher, Mike, EMNRD; Weaver, Crystal, EMNRD
Cc: stucker@blm.gov; duskie@trinityoilfieldservices.com; ben@trinityoilfieldservices.com; tristan@trinityoilfieldservices.com; Jennifer_Smith@oxy.com
Subject: FNR 26 Federal 1 CTB

All,

This is to inform you that Oxy Permian had a **Reportable** release in **Eddy County** at the **FNR 26 Federal 1 CTB** on **1/8/2018**.

- **Release Location:** Legal -26-23S-30E, API: 30-015-30412
- **Release Volume:** 4 bbls of Oil and 10 bbls of Produced Water.
- **Recovered:** 0 bbls recovered
- **Cause of Release:** 2 inch steel Victaulic clamp on the gas sales line failure
- **Approximate Area impacted by release:** 10x20ft (measurements are subject to change with GPS tracking)
- **GPS Coordinates and Driving Direction:** **32.2704697, -103.8581543** WEST OUT OF JAL ON 128, TURN SOUTH AT MILE MARKER 14, GO 1.5 MILE, TURN WEST GO 1 MILE TO END OF ROAD WHICH DEAD ENDS ON LOCATION. LEAK IS 150 FT SOUTHWEST OF FEDERAL 29 8 BATTERY
- Sorry so late, this one slipped by me somehow.
-

Please let me know if you have any questions.

Wade Dittrich
Environmental Specialist
Oxy Permian-New Mexico
575-390-2828 cell
575-397-8214 office
Wade_Dittrich@Oxy.com