APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103 Revised 1-1-89

DATE MAR 2 9 2004

OIL CONSERVATION DIVISION P.O. Box 1980, Hobbs, NM 88240 WELL API NO. 2040 Pacheco St. Santa Fe, NM 87505 30-015-33011 sladicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 STATE X FEE **DISTRICT III** «State Oil & Gas Lease No. 1000 Rio Brazos Rd., Aztec, NM 87410 V0 - 5379 - 1100 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Seven Rivers "20" Com Type of Well: OIL WELL GAS WELL X «Well No. aName of Operator RECEIVED Pogo Producing Company Address of Operator Pool name or Wildcat MAR 1 8 2004 O. Box 10340, Midland, TX 79702-7340 Cemetery Morrow East OCD-ARTES 4Well Location 1980 Feet From The North Unit Letter _H Feet From The Eddy 25E **20S** NMPM Section Township Range County 10 Elevation (Show whether DF, RKB, RT, GR, etc.) 3490' 11 Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data SUBSEQUENT REPORT OF: NOTICE OF INTENTION TO: PLUG AND ABANDON REMEDIAL WORK ALTERING CASING **PERFORM REMEDIAL WORK** COMMENCE DRILLING OPNS. PLUG AND ANBANDONMENT **TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING** CASING TEST AND CEMENT JOB OTHER: OTHER: *Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. Spud & Set Surface Csg - MIRU Patterson #142. Spud well @ 23:00 hrs 09/28/03. Drld 17-1/2" hole to 400'. TD reached @ 13:00 hrs 09/29/03. Ran 9 jts 13-3/8" 48# H-40 STC csg. Cmt'd w/-200 sks Halliburton Lite Premium Plus + 2% CaCl2 @ 12.7 ppg followed by 200 sks Cl "C" Premium Plus + 2% CaCl2 @ 14.8 ppg. Circ 77 sks to surface. Plug down @ 06:00 hrs 09/30/03. WOC 24 hrs. Make cut-off. Install WH. NU BOP's & test ok. Intermediate Csg - Drld 11" hole to 2630'. TD reached @ 14:30 hrs 10/04/03. Ran 60 jts 8-5/8" 32# J-55 STC csg. Cmt'd w/ 500 sks Halliburton Lite Premium Plus @ 12.7 ppg followed by 200 sks Premium Plus + 1% CaCl2 @ 14.8 ppg. Circ 101 sks to surface. WOC 24 hrs. Make cut-off. Install WH. NU BOP's & test ok. TD & Prod Csg - Drld 7-7/8" hole to 9700'. TD reached @ 08:45 hrs 10/30/03. Logged well w/ Halliburton. Ran 236 jts 5-1/2" 17# L-80 LTC csg. Cmt'd w/ 1200 sks Premium cmt + additives @ 15.7 ppg. Ran CBL 11/17/03. TOC @ 4712'. I hereby certify that the ipformation above is true and complete to the best of my knowledge and belief. τπιε Sr. Operation Tech 03/17/04 SIGNATURE DATE 432-685-8100 Cathy Wright TYPE OR PRINT NAME TELEPHONE NO. (This space for State Use)

FOR RECORDS ONLY