

State of New Mexico
Energy, Minerals and Natural ResourcesForm C-103
Revised June 10, 2003

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM
87505OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.

30-005-63602

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Summers Com

8. Well Number

3

9. OGRID Number

025575

10. Pool name or Wildcat

Wildcat Chester

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Yates Petroleum Corporation

3. Address of Operator

105 S. 4th Street, Artesia, NM 88210

4. Well Location

Unit Letter I : 1980 feet from the South line and 990 feet from the East lineSection 26 Township 9S Range 24E NMPM Chaves County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3566'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐CASING TEST AND CEMENT JOB ☐OTHER: Production casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/23/04 – Reached TD 4835' at 1:00 AM. Set 4-1/2" 11.6# L-80 8rd casing at 4835'. Cemented Stage 1 with 600 sx Pecos Valley Lite with additives. Tested casing to 1652 psi for 5 mins. Circulated 75 sx. Cemented Stage 2 with 600 sx 35:65:6 Class "C" with additives and tailed in with 150 sx Class "C" Neat. Tested casing to 2600 psi for 5 mins. Cement circulated to surface.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Tina Huerta TITLE: Regulatory Compliance Supervisor DATE: June 1, 2004Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471

(This space for State use)

FOR RECORDS ONLY

APPROVED BY _____ TITLE _____ DATE JUN 03 2004
Conditions of approval, if any: