Form 3160-5 (August 2007)

SUNDRY NOTICES AND REPORTS ON WELLS

**UNITED STATES** DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT FORM APPROVED OMB NO. 1004-0135

OCD-Artesia

•	Expires:	July	31
Lease Se	rial No.		
A IR AA IR A	47000		

	IMIMIMIM	17223	
6	If Indian	Allottee or Tribe Na	ne

Do not use thi					
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.				6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side.				7. If Unit or CA/Agree	ement, Name and/or No.
1. Type of Well  ☐ Gas Well ☐ Oth	ner			8. Well Name and No EAST TURKEY	TRACK FED COM 5H
Name of Operator     MYCO INDUSTRIES INCORF		9. API Well No. 30-015-38415-00-X1			
3a. Address 3b. Phone No. Ph: 575.74			ode)	10. Field and Pool, or Exploratory SANTO NINO	
ARTESIA, NM 88211					10
4. Location of Well (Footage, Sec., 7 Sec 26 T18S R29E SESE Lot				11. County or Parish	
360 20 1103 R29E SESE LUI	F 500F3L 133FEL		·	EDDT COONT	T , TVIVI
12. CHECK APPR	ROPRIATE BOX(ES) TO	NDICATE NATURE O	F NOTICE, RE	PORT, OR OTHE	ER DATA
TYPE OF SUBMISSION		ТҮРЕ	OF ACTION		
☐ Notice of Intent	Acidize .	Deepen	_	on (Start/Resume)	☐ Water Shut-Off
Subsequent Report	☐ Alter Casing	☐ Fracture Treat	□ Reclama		□ Well Integrity
_	Casing Repair	New Construction	_		Other Drilling Operations
☐ Final Abandonment Notice	☐ Change Plans ☐ Convert to Injection	☐ Plug and Abandon☐ Plug Back☐	☐ Tempora ☐ Water D	arily Abandon	
13. Describe Proposed or Completed Op					ovimate duration thereof
following completion of the involved testing has been completed. Final Al determined that the site is ready for for 4-24-2011 Set 20? conductor 13-3/8? 48# H-40 STC casing and cement to the pit. Casing and office. WOC 9 hours until cerprep to drill out 12-1/4? hole.  5-2-2011 TD 12-1/4? hole at EconoCem + 400 sxs Cemex (Terry) of running casing and test casing to 1000 psi and Both determined in the strength of the site of	bandonment Notices shall be filed inal inspection.) or pipe to 120? and cement e. Notify BLM of spud via to and cement with 450 sxs led cementing job witnessed lenent reached 500 psi composition. Set 9-5/8? 40# J-5 PP Class ?C? tail. Circulate cementing and intent to testinal inspection.	only after all requirements, in with ready mix back to selephone. TD 17-1/2? he halcem ?C? + 2% CaCL by Jerry Blakely, BLM Caressive strength. Test B 55, LTC casing and ceme te 258 sxs to the surface to BOP?s to 5000 psi. No	cluding reclamation urface. ole at 372?. Se 2. Circulated 1: arisbad Resource OP to 3000 psi ent with 900 sxs. Notify BLM Care	t 33 sxs e high.	
14. Thereby certify that the foregoing is	Electronic Submission #11	1026 verified by the BLM IES INCORPORATED, se			<u> </u>
	nmitted to AFMSS for proces	sing by KURT SIMMONS	on 06/23/2011 (1 <sup>,</sup>		
Name (Printed/Typed) HANNAH	PALOMIN	Title LAN	D MANAGER		
Signature (Electronic S	Submission)	Date 06/2	1/2011		
	THIS SPACE FOR	R FEDERAL OR STAT	E OFFICE US	E	
Approved By ACCEPT	ED		A AMOS RVISOR EPS		Date 06/27/201
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to condition	uitable title to those rights in the s uct operations thereon.	ubject lease Office Carls			
Fitle 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent	U.S.C. Section 1212, make it a constatements or representations as to	rime for any person knowingly o any matter within its jurisdic	and willfully to mation.	ike to any department of	or agency of the United

## Additional data for EC transaction #111026 that would not fit on the form

## 32. Additional remarks, continued

6-12-2011 TD 8-3/4? hole at 12,713? MD. Contacted Cheryl Demontigny, Carlsbad Field Office by telephone of running casing & cementing at 12:45 hours on 6/12/2011. No witness.

Ran 320 joints 5.5? 17# N80 BTC casing. DV tool set at 6940?.

Cement State 1: 1500 sxs Permian Basin Super H Cement-SBM. Yield 1.6 cu ft, Weight 13.2#/gal. 4600 psi Compressive Strength in 2:35 hours. Displace with 162 bbls fresh water, drop plug, displace with 132 bbls fresh water. Bump plug @ 09:15 hours 6/13/2011. Check floats-OK. Drop ball & set packer. Circulate 193 sxs to the surface.

Cement Stage 2: Lead w/ 850 sxs Interfill ?C? SBM. Yield 2.42 cu ft, Weight 11.9#/gal. 3900 psi Compressive Strength in 6:24 hours. Tail w/ 200 sxs CMT-Premium Plus Class ?C?. Yield 1.33 cu ft, Weight 14.8#/gal. 920 psi Compressive Strength in 12:00 hours. Displace w/ 293 bbls fresh water. Circulate 135 sxs cement to the surface.

6-17-2011 Wait on frac date pending contract with oil purchaser.