

District I 1625 N French Dr, Hobbs, NM 88240
District II 1301 W Grand Ave, Artesia, NM 88210
District III 1000 Rio Brazos Rd, Aztec, NM 87410
District IV 1220 S St Francis Dr, Santa Fe, NM 87505

OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

WELL API NO. 30-015-23169
5. Indicate Type of Lease STATE FEE
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Achen Frey DM
8. Well Number 7
9. OGRID Number 025575
10. Pool name or Wildcat Eagle Creek; San Andres


SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)
1. Type of Well: Oil Well Gas Well Other P&A
2. Name of Operator Yates Petroleum Corporation
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210
4. Well Location Unit Letter L : 1650 feet from the South line and 990 feet from the West line Section 13 Township 17S Range 25E NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3460'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK PLUG AND ABANDON TEMPORARILY ABANDON CHANGE PLANS PULL OR ALTER CASING MULTIPLE COMPL DOWNHOLE COMMINGLE OTHER
SUBSEQUENT REPORT OF: REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. P AND A CASING/CEMENT JOB OTHER

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/2/11 - MIRU.
8/3/11 - Pumped 17 bbls to break circulation. Pumped 30 bbls total. NU BOP. Set 4-1/2" CIBP at 1260', could not get CIBP to set. TOH with plug. TIH with open-ended tubing to 1270'. Pumped 35 bbls down tubing and could not break circulation. Spotted 50 sx Class "C" cement with 2% calcium and displaced with 1 bbls fresh water. Did not tag. Spotted 50 sx Class "C" cement with 2% calcium.
8/4/11 - Tagged TOC at 760', pulled up 1'. Circulated 50 sx Class "C" cement to surface. Top off wellbore with cement.
8/10/11 - Dug out cellar and cut off wellhead. Installed dry hole marker. Filled cellar and cut off anchors. Cleaned location. WELL IS PLUGGED AND ABANDONED.



Spud Date: [ ]

Rig Release Date: [ ]

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Compliance Supervisor DATE August 11, 2011

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY [Signature] TITLE DATE 8/16/2011
Conditions of Approval (if any):

Approved for plugging of well bore only. Liability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OED Web Page under Forms. www.emnrd.state.nm.us/oed.

