

Form 3160-3
(June 2015)FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER 1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		5. Lease Serial No. NMNM059383 6. If Indian, Allottee or Tribe Name 7. If Unit or CA Agreement, Name and No. 8. Lease Name and Well No. RANA SALADA FED COM 0504 216H
2. Name of Operator NOVO OIL AND GAS NORTHERN DELAWARE LLC		9. API Well No. 3001547331
3a. Address 1001 West Wilshire Boulevard Suite 206 Oklahoma City O	3b. Phone No. (include area code) (405)404-0414	10. Field and Pool, or Exploratory CORRAL DRAW BONE SPRING
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface NESE / 1441 FSL / 672 FEL / LAT 32.3309832 / LONG -104.0177696 At proposed prod. zone NESE / 2310 FSL / 130 FEL / LAT 32.3334928 / LONG -103.9817014		11. Sec., T. R. M. or Blk. and Survey or Area SEC 6 / T23S / R29E / NMP
14. Distance in miles and direction from nearest town or post office* 5 miles		12. County or Parish EDDY
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 672 feet		16. No of acres in lease 601.92
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 20 feet		17. Spacing Unit dedicated to this well 640
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3041 feet		20. BLM/BIA Bond No. in file FED: NMB001536
22. Approximate date work will start* 10/01/2019		23. Estimated duration 90 days
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- | | |
|---|---|
| 1. Well plat certified by a registered surveyor.
2. A Drilling Plan.
3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
5. Operator certification.
6. Such other site specific information and/or plans as may be requested by the BLM. |
|---|---|

25. Signature (Electronic Submission) Title President	Name (Printed/Typed) BRIAN WOOD / Ph: (505)466-8120	Date 07/16/2019
Approved by (Signature) (Electronic Submission) Title Assistant Field Manager Lands & Minerals	Name (Printed/Typed) Cody Layton / Ph: (575)234-5959 Office CARLSBAD	Date 08/11/2020

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



(Continued on page 2)

*(Instructions on page 2)

Entered - KMS NMOCD

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-9720
District III
1000 Rio Brazos Road, Aztec, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office
☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

¹ API Number 30-015- 47331	² Pool Code 98220	³ Pool Name PURPLE SAGE; WOLFCAMP (GAS)
⁴ Property Code 325748	⁵ Property Name RANA SALADA FED COM 0504	
⁷ OGRID No. 379220	⁸ Operator Name NOVO OIL & GAS NORTHERN DELAWARE, LLC	
		⁶ Well Number 216H
		⁹ Elevation 3041.1

¹⁰ Surface Location



UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
I	6	23 S	29 E		1441	SOUTH	672	EAST	EDDY

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
I	4	23 S	29 E		2310	SOUTH	130	EAST	EDDY

¹² Dedicated Acres 640	¹³ Joint or Infill	¹⁴ Consolidation Code C	¹⁵ Order No.
---	-------------------------------	--	-------------------------

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

<p>NW CORNER SEC. 6 LAT. = 32.3420477°N LONG. = 104.0319449°W NMSP EAST (FT) N = 488299.91 E = 634415.99</p> <p>SECTION CORNER LAT. = 32.3417741°N LONG. = 104.0153768°W NMSP EAST (FT) N = 488215.14 E = 639533.08</p> <p>SECTION CORNER LAT. = 32.3417246°N LONG. = 103.9982714°W NMSP EAST (FT) N = 488213.27 E = 644815.88</p> <p>NE CORNER SEC. 4 LAT. = 32.3416792°N LONG. = 103.9811510°W NMSP EAST (FT) N = 488213.70 E = 650103.34</p>				<p>RANA SALADA FED COM 0504 216H ELEV. = 3041.1 LAT. = 32.3309832°N (NAD83) LONG. = 104.0177696°W NMSP EAST (FT) N = 488217.15 E = 636888.30 E = 638805.67</p> <p>N/4 CORNER SEC. 6 LAT. = 32.3418009°N LONG. = 104.0239405°W NMSP EAST (FT) N = 488217.15 E = 636888.30 E = 638805.67</p> <p>N/4 CORNER SEC. 5 LAT. = 32.3417558°N LONG. = 104.0068255°W NMSP EAST (FT) N = 488216.38 E = 642174.05</p> <p>N/4 CORNER SEC. 4 LAT. = 32.3416986°N LONG. = 103.9897047°W NMSP EAST (FT) N = 488212.18 E = 647461.63</p> <p>BOTTOM OF HOLE LAT. = 32.3334928°N LONG. = 103.9817014°W NMSP EAST (FT) N = 485235.00 E = 649943.11</p>			
<p>W/4 CORNER SEC. 6 LAT. = 32.3348340°N LONG. = 104.0319894°W NMSP EAST (FT) N = 485675.58 E = 634408.64</p> <p>S/4 CORNER SEC. 6 LAT. = 32.3272315°N LONG. = 104.0239843°W NMSP EAST (FT) N = 482916.93 E = 636890.08</p> <p>SW CORNER SEC. 6 LAT. = 32.3275007°N LONG. = 104.0319716°W NMSP EAST (FT) N = 483007.81 E = 634422.64</p> <p>SECTION CORNER LAT. = 32.3269490°N LONG. = 104.0156765°W NMSP EAST (FT) N = 482821.66 E = 639456.52</p> <p>FIRST TAKE POINT 2310' FSL, 330' FWL LAT. = 32.3333074°N LONG. = 104.0144787°W NMSP EAST (FT) N = 485135.88 E = 639819.62</p> <p>SECTION CORNER LAT. = 32.3270813°N LONG. = 103.9985277°W NMSP EAST (FT) N = 482885.93 E = 644753.39</p> <p>S/4 CORNER SEC. 4 LAT. = 32.3271140°N LONG. = 103.9899083°W NMSP EAST (FT) N = 482906.22 E = 647415.75</p> <p>SE CORNER SEC. 4 LAT. = 32.3271459°N LONG. = 103.9812889°W NMSP EAST (FT) N = 482926.50 E = 650078.10</p>				<p>17 OPERATOR CERTIFICATION I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.  Signature BRIAN WOOD Date 7-4-19 Printed Name brian@permitswest.com E-mail Address (505) 466-8120</p> <p>18 SURVEYOR CERTIFICATION I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief. APRIL 18, 2019 Date of Survey  Signature and Seal of Professional Surveyor: FILIMON F. JARAMILLO, PLS 12797 Certificate Number: SURVEY NO. 7192</p>			

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit Original
to Appropriate
District Office

GAS CAPTURE PLAN

Date: 6/30/2019

X Original Operator & OGRID No.: Novo Oil & Gas Northern Delaware, LLC (372920)
☐ Amended - Reason for Amendment: _____

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

Note: A C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule 19.15.18.12.A

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well	API	SHL (ULSTR)	SHL Footages	Expected MCF/D	Flared or Vented	Comments
Rana Salada Fed Com 0504 136H	30-015-	I-6-23S-29E	1442 FSL & 652 FEL	2500	30 days	Time depends on well clean up
Rana Salada Fed Com 0504 213H	30-015-	I-6-23S-29E	1442 FSL & 632 FEL	7500	30 days	Time depends on well clean up
Rana Salada Fed Com 0504 216H	30-015-	I-6-23S-29E	1441 FSL & 672 FEL	7500	30 days	Time depends on well clean up
Rana Salada Fed Com 0504 223H	30-015-	P-6-23S-29E	1240 FSL & 689 FEL	7500	30 days	Time depends on well clean up
Rana Salada Fed Com 0504 226H	30-015-	I-6-23S-29E	1440 FSL & 692 FEL	7500	30 days	Time depends on well clean up
Rana Salada Fed Com 0504 223H	30-015-	P-6-23S-29E	1240 FSL & 709 FEL	7500	30 days	Time depends on well clean up

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is not yet dedicated. However, negotiations are underway. One possible connection is an existing Enterprise line that is 100 yards south. Novo Oil & Gas Northern Delaware, LLC will provide (periodically) to its Gas Transporter a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Novo Oil & Gas Northern Delaware, LLC and its Gas Transporter have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at an as yet undetermined Gas Transporter Processing Plant located in Eddy County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on its Gas Transporter system at that time. Based on current information, it is Novo Oil & Gas Northern Delaware, LLC's belief an existing or new system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

Intent **YES** As Drilled ☐

API #

Operator Name:	Property Name:	Well Number
NOVO OIL & GAS NORTHERN DELAWARE, LLC	RANA SALADA FED COM 0504	216H

Kick Off Point (KOP)

UL I	Section 6	Township 23S	Range 29E	Lot	Feet 1441	From N/S SOUTH	Feet 672	From E/W EAST	County EDDY
Latitude 32.3309832					Longitude 104.0177696			NAD 83	

First Take Point (FTP)

UL L	Section 5	Township 23S	Range 29E	Lot	Feet 2310	From N/S SOUTH	Feet 330	From E/W WEST	County EDDY
Latitude 32.3333074					Longitude 104.0144787			NAD 83	

Last Take Point (LTP)

UL I	Section 4	Township 23S	Range 29E	Lot	Feet 2310	From N/S SOUTH	Feet 330	From E/W EAST	County EDDY
Latitude 32.3334904					Longitude 103.9823488			NAD 83	

Is this well the defining well for the Horizontal Spacing Unit? **NO**

Is this well an infill well? **YES**

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API # 30-015-46087 30-015-46088	Operator Name: Novo Oil & Gas Northern Delaware, LLC	Property Name: Rana Salada Fed Com 0504 (OCD property code 325748)	Well Number 214H 234H
--	--	--	---

KZ 06/29/2018

PECOS DISTRICT

DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	NOVO OIL & GAS NORTHERN DELAWARE
LEASE NO.:	NMNM059383
WELL NAME & NO.:	Rana Salada Fed Com 0504 216H
SURFACE HOLE FOOTAGE:	1441'/S & 672'/E
BOTTOM HOLE FOOTAGE:	2310'/S & 130'/E
LOCATION:	Section 6, T.23 S., R.29 E., NMPM
COUNTY:	Eddy County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input type="radio"/> None	<input type="radio"/> Secretary	<input checked="" type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input checked="" type="radio"/> Multibowl	<input type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

B. CASING

1. The **13-3/8** inch surface casing shall be set at approximately **350** feet (a minimum of **70 feet (Eddy County)** into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of

24 hours in the Potash Area or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)

- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.
2. The minimum required fill of cement behind the **9-5/8** inch 1st intermediate casing is:
- Cement to surface. If cement does not circulate see B.1.a, c-d above.
Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash. Excess cement calculates to 16%, additional cement might be required.

❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.

❖ In R111 Potash Areas if cement does not circulate to surface on the first two salt protection casing strings, the cement on the 3rd casing string must come to surface.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

3. The minimum required fill of cement behind the **7-5/8** inch 2nd intermediate casing is:

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
- b. Second stage above DV tool:
 - Cement to surface. If cement does not circulate, contact the appropriate BLM office. **Excess cement calculates to 16%, additional cement might be required.**

4. The minimum required fill of cement behind the **5-1/2** inch production casing is:
 - Cement should tie-back **200 feet** into the previous casing. Operator shall provide method of verification. **Excess cement calculates to 19%, additional cement might be required.**

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.
- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.
JJP272020

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including

lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.



APD ID: 10400043458

Submission Date: 07/16/2019

Highlighted data
reflects the most
recent changes

Operator Name: NOVO OIL AND GAS NORTHERN DELAWARE LLC

Well Name: RANA SALADA FED COM 0504

Well Number: 216H

[Show Final Text](#)

Well Type: CONVENTIONAL GAS WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
494148	QUATERNARY	3041	0	0		USEABLE WATER	N
494149	RUSTLER ANHYDRITE	2763	278	278		NONE	N
494150	SALADO	2257	784	784	SALT	NONE	N
494137	CASTILE	1610	1431	1431	ANHYDRITE	NONE	N
494138	BASE OF SALT	175	2866	2880		NONE	N
494142	BELL CANYON	175	2866	2880	SANDSTONE	NATURAL GAS, OIL	N
494151	CHERRY CANYON	-920	3961	3998	SANDSTONE	NATURAL GAS, OIL	N
494143	BRUSHY CANYON	-2345	5386	5456	SANDSTONE	NATURAL GAS, OIL	N
494144	BONE SPRING LIME	-3435	6476	6570		NATURAL GAS, OIL	N
494145	BONE SPRING 1ST	-4520	7561	7662	SANDSTONE	NATURAL GAS, OIL	N
494146	BONE SPRING 2ND	-4775	7816	7917	OTHER : Carbonate	NATURAL GAS, OIL	N
494152	BONE SPRING 2ND	-5265	8306	8407	SANDSTONE	NATURAL GAS, OIL	N
494139	BONE SPRING 3RD	-5625	8666	8767	OTHER : Carbonate	NATURAL GAS, OIL	N
494140	BONE SPRING 3RD	-5940	8981	9082	SANDSTONE	NATURAL GAS, OIL	N
494147	WOLFCAMP	-6775	9816	9962	OTHER : XY Carbonate	NATURAL GAS, OIL	N
494141	WOLFCAMP	-6930	9971	11650	OTHER : A Carbonate	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Operator Name: NOVO OIL AND GAS NORTHERN DELAWARE LLC

Well Name: RANA SALADA FED COM 0504

Well Number: 216H

Pressure Rating (PSI): 5M

Rating Depth: 12000

Equipment: A 13.625" 5,000-psi BOP system will be installed on a multi-bowl (speed head) wellhead with a 13.625" flanged casing spool. Top flange of casing spool will be set in a cellar below ground level. The BOP system will consist of a single pipe ram on the bottom, mud cross, double pipe ram with blind rams on bottom and pipe rams on top, and annular preventer. Blowout preventer will be installed on top of the 13.375" surface casing and will remain installed to TD of the well.

Requesting Variance? YES

Variance request: Variance is requested to use a co-flex hose between the BOP system and choke manifold. A co-flex pressure test certificate will be on the location when testing the BOP.

Testing Procedure: BOP system will be isolated with a test plug and tested by an independent tester to 250-psi low and 5000-psi high for 10 minutes. All casing strings will be tested in accordance with Onshore Order 2 III.B.1.h.

Choke Diagram Attachment:

RS_0504_216H_Choke_20200127094256.pdf

BOP Diagram Attachment:

RS_0504_216H_BOP_20190709101202.pdf

Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	17.5	13.75	NEW	API	N	0	350	0	350	3041		350	J-55	54.5	BUTT	1.125	1.125	DRY	1.6	DRY	1.6
2	OTHER	12.25	9.625	NEW	API	N	0	2970	0	2970	3041		2970	J-55	40	BUTT	1.125	1.125	DRY	1.6	DRY	1.6
3	INTERMEDIATE	8.75	7.625	NEW	API	N	0	9500	0	9399	3041		9500	HCL-80	29.7	OTHER - TMK UP Ultra SF semi-FJ	1.125	1.125	DRY	1.6	DRY	1.6
4	PRODUCTION	6.75	5.5	NEW	API	N	0	20444	0	10149	3041		20444	OTHER	20	OTHER - USS Eagle SFH semi-FJ	1.125	1.125	DRY	1.6	DRY	1.6

Casing Attachments

Operator Name: NOVO OIL AND GAS NORTHERN DELAWARE LLC

Well Name: RANA SALADA FED COM 0504

Well Number: 216H

Casing Attachments

Casing ID: 1 **String Type:** SURFACE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

RS_0504_216H_Casing_Design_Assumptions_20190709102227.pdf

Casing ID: 2 **String Type:** OTHER - Salt Protect

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

RS_0504_216H_Casing_Design_Assumptions_20190709102248.pdf

Casing ID: 3 **String Type:** INTERMEDIATE

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

RS_0504_216H_Casing_Design_Assumptions_20190709102334.pdf

7.625_TMK_Ultra_SF_20190709102346.pdf

Operator Name: NOVO OIL AND GAS NORTHERN DELAWARE LLC

Well Name: RANA SALADA FED COM 0504

Well Number: 216H

Casing Attachments

Casing ID: 4 **String Type:** PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

Casing Design Assumptions and Worksheet(s):

RS_0504_216H_Casing_Design_Assumptions_20190709102417.pdf

5.50in__USS_Eagle_SFH_20190709102425.pdf

Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
SURFACE	Lead		0	0	0	0	0	0	0	None	None
SURFACE	Tail		0	350	305	1.62	13.8	494	100	Class C	gel + accelerator + LCM
OTHER	Lead		0	0	0	0	0	0	0	None	None
OTHER	Tail		0	2970	833	1.34	6.33	1116	20	Class C	gel + retarder + LCM
INTERMEDIATE	Lead		0	0	0	0	0	0	0	None	None
INTERMEDIATE	Tail		0	9500	147	2.28	11.9	335	20	Class C or H	gel + extender + LCM
PRODUCTION	Lead		0	0	0	0	0	0	0	None	None
PRODUCTION	Tail		9000	2044 4	667	1.72	13.2	1147	20	Class H	fluid loss + retard + LCM
INTERMEDIATE	Lead	2770	2770	9500	238	2.28	11.9	542	20	Class C or H	gel + extender + LCM
INTERMEDIATE	Tail		2770	9500	200	1.34	14.8	268	20	Class C or H	fluid loss + retarder + LCM

Operator Name: NOVO OIL AND GAS NORTHERN DELAWARE LLC

Well Name: RANA SALADA FED COM 0504

Well Number: 216H

Section 5 - Circulating Medium

Mud System Type: Closed

Will an air or gas system be Used? NO

Description of the equipment for the circulating system in accordance with Onshore Order #2:

Diagram of the equipment for the circulating system in accordance with Onshore Order #2:

Describe what will be on location to control well or mitigate other conditions: All necessary mud products (barite, bentonite, LCM) to control weight and fluid loss will be on site at all times. Mud program may change due to hole conditions.

Describe the mud monitoring system utilized: An electronic PVT mud system will monitor flow rate, pump pressure, stroke rate, and volume.

Circulating Medium Table

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	350	OTHER : Fresh water spud	8.3	8.3							
350	2970	OTHER : Brine or cut brine	9.8	10.2							
2970	9500	OTHER : Brine or LSND	9.8	10.2							
9500	20444	OIL-BASED MUD	8.5	12.5							

Section 6 - Test, Logging, Coring

List of production tests including testing procedures, equipment and safety measures:

A 2-person mud logging program will be used from 3000' to TD. GR will be log will be acquired by MDW tools from the intermediate casing to TD.

List of open and cased hole logs run in the well:

GR

Coring operation description for the well:

No core or drill stem test is planned.

Operator Name: NOVO OIL AND GAS NORTHERN DELAWARE LLC

Well Name: RANA SALADA FED COM 0504

Well Number: 216H

Section 7 - Pressure

Anticipated Bottom Hole Pressure: 6597

Anticipated Surface Pressure: 4364.21

Anticipated Bottom Hole Temperature(F): 165

Anticipated abnormal pressures, temperatures, or potential geologic hazards? NO

Describe:

Contingency Plans geohazards description:

Contingency Plans geohazards attachment:

Hydrogen Sulfide drilling operations plan required? YES

Hydrogen sulfide drilling operations plan:

RS_0504_216H_H2S_Plan_20190709104742.pdf

Section 8 - Other Information

Proposed horizontal/directional/multi-lateral plan submission:

RS_0504_216H_Horizontal_Drill_Plan_20190709121009.pdf

Other proposed operations facets description:

Other proposed operations facets attachment:

RS_0504_216H_Speedhead_Specs_20190709105319.pdf

RS_0504_216H_Alternative_Casing_Spec_Request_20190709105424.pdf

RS_0504_216H_Anti_Collision_Report_20190709121028.pdf

CoFlex_Certs_20200127094413.pdf

Other Variance attachment:

RS_0504_216H_Casing_Cement_Variance_20190709105309.pdf

Novo Oil & Gas Northern Delaware, LLC
Rana Salada Fed Com 0504 216H
SHL 1441' FSL & 672' FEL 6-23S-29E
BHL 2310' FSL & 130' FEL 4-23S-29e
Eddy County, NM

DRILL PLAN PAGE 1

Drilling Program

1. ESTIMATED TOPS

Formation Name	TVD	MD	Bearing
Quaternary	0'	0'	water
Rustler anhydrite	278'	278'	N/A
Salado salt	784'	784'	N/A
Castile anhydrite	1431'	1431'	N/A
Base salt	2866'	2880'	N/A
Bell Canyon sandstone	2866'	2880'	hydrocarbons
Cherry Canyon sandstone	3961'	3998'	hydrocarbons
Brushy Canyon sandstone	5386'	5456'	hydrocarbons
Bone Spring limestone	6476'	6570'	hydrocarbons
1 st Bone Spring sandstone	7561'	7662'	hydrocarbons
2 nd Bone Spring carbonate	7816'	7917'	hydrocarbons
2nd Bone Spring sandstone	8306'	8407'	hydrocarbons
3 rd Bone Spring carbonate	8666'	8767'	hydrocarbons
3 rd Bone Spring sandstone	8981'	9082'	hydrocarbons
(KOP	9467'	9568'	hydrocarbons)
Wolfcamp XY carbonate	9816'	9962'	hydrocarbons
Wolfcamp A carbonate	9971'	11650'	hydrocarbons
TD	10149'	20444'	hydrocarbons

2. NOTABLE ZONES

Wolfcamp XY and A carbonates are the goal. All perforations will be $\geq 130'$ from the dedication perimeter. Closest water well (C 02804) is 0.63 mile southeast. Depth to water was not reported in the 100' deep well.

Novo Oil & Gas Northern Delaware, LLC
Rana Salada Fed Com 0504 216H
SHL 1441' FSL & 672' FEL 6-23S-29E
BHL 2310' FSL & 130' FEL 4-23S-29e
Eddy County, NM

DRILL PLAN PAGE 2

3. PRESSURE CONTROL

A 13.625" 5,000-psi BOP system will be installed on a multi-bowl (speed head) wellhead with a 13.625" flanged casing spool. Top flange of casing spool will be set in a cellar below ground level. The BOP system will consist of a single pipe ram on the bottom, mud cross, double pipe ram with blind rams on bottom and pipe rams on top, and annular preventer. Blowout preventer will be installed on top of the 13.375" surface casing and will remain installed to TD of the well. Wellhead, blowout preventer, and choke manifold diagram are included.

BOP system will be isolated with a test plug and tested by an independent tester to 250-psi low and 5000-psi high for 10 minutes. Variance is requested to use a co-flex hose between the BOP system and choke manifold. A co-flex pressure test certificate will be on the location when testing the BOP.

All casing strings will be tested in accordance with Onshore Order 2 III.B.1.h.

4. CASING & CEMENT

Variance is requested for the option to use a surface rig to drill the surface hole, set the surface casing, and cement the surface casing. If the schedule between rigs would preclude presetting the surface casing, then the primary rig will MIRU and drill all of the well.

All casing will be API and new. See attached casing assumption worksheet.

Novo Oil & Gas Northern Delaware, LLC
Rana Salada Fed Com 0504 216H
SHL 1441' FSL & 672' FEL 6-23S-29E
BHL 2310' FSL & 130' FEL 4-23S-29e
Eddy County, NM

DRILL PLAN PAGE 3

Hole O. D.	Set MD	Set TVD	Casing O. D.	Weight (lb/ft)	Grade	Joint	Collapse	Burst	Tension
17.5"	0' - 350'	0' - 350'	13.375" surface	54.5	J-55	BTC	1.125	1.125	1.6
12.25"	0' - 2970'	0' - 2970'	9.625" other (salt protect)	40	J-55	BTC	1.125	1.125	1.6
8.75"	0' - 9500'	0' - 9399'	7.625" inter.	29.7	HCL-80	TMK UP Ultra SF semi-FJ	1.125	1.125	1.6
6.75"	0' - 20444'	0' - 10149'	5.5" product.	20	P-110 HP	USS Eagle SFH semi-FJ	1.125	1.125	1.6
6.75"	0' - 20444'	0' - 10149'	5.5" alternate product.	23	P-110 HC	TMK UP Ultra SF semi-FJ	1.125	1.125	1.6

Name	Type	Sacks	Yield	Cu. Ft.	Weight	Blend
Surface	Tail	305	1.62	494	13.8	Class C + gel + accelerator + LCM
TOC = GL		100% Excess			Centralizers on every jt to GL	
Other – Salt Protection	Tail	833	1.34	1116	6.33	Class C + gel + retarder + LCM
TOC = GL		20% Excess			Centralizers on bottom 3 jts and then 1 centralizer every 4th jt to GL	
Intermediate stage 1 (stage tool set @ 2770')	Lead	238	2.28	542	11.9	Class C or H + gel + extender + LCM
	Tail	200	1.34	268	14.8	Class C or H+ fluid loss + retarder + LCM
TOC = 2770'		20% Excess			Centralizers on bottom 3 jts and then 1 centralizer every 4th jt to GL	
Intermediate stage 2	Tail	147	2.28	335	11.9	Class C or H + gel + extender + LCM
TOC = GL		20% Excess			Centralizers on bottom 3 jts and then 1 centralizer every 4th jt to TOC	
Production	Tail	667	1.72	1147	13.2	Class H + fluid loss + retard + LCM
TOC = 9000'		20% Excess			No centralizers planned	

Novo Oil & Gas Northern Delaware, LLC
Rana Salada Fed Com 0504 216H
SHL 1441' FSL & 672' FEL 6-23S-29E
BHL 2310' FSL & 130' FEL 4-23S-29e
Eddy County, NM

DRILL PLAN PAGE 4

5. MUD PROGRAM

An electronic PVT mud system will monitor flow rate, pump pressure, stroke rate, and volume. All necessary mud products (barite, bentonite, LCM) to control weight and fluid loss will be on site at all times. Mud program may change due to hole conditions. A closed loop system will be used.

Type	Interval (MD)	lb/gal	Viscosity	Fluid Loss
fresh water spud	0' - 350'	8.3	30 - 60	NC
brine or cut brine	350' - 2970'	9.8 - 10.2	35 - 45	NC
Brine or LSND	2970' - 9500'	9.8 - 10.2	35 - 45	NC
OBM	9500' - 20444'	8.5 - 12.5	35 - 65	4 - 6

6. CORES, TESTS, & LOGS

No core or drill stem test is planned. A 2-person mud logging program will be used from $\approx 3000'$ to TD. GR will be log will be acquired by MDW tools from the intermediate casing to TD.

7. DOWN HOLE CONDITIONS

No abnormal pressure or temperature is expected. Maximum expected bottom hole pressure is ≈ 5321 psi. Expected bottom hole temperature is $\approx 165^{\circ}$ F.

An H2S plan is attached.

8. OTHER INFORMATION

Anticipated spud date is upon approval. It is expected it will take $\approx 3-4$ months to drill and complete the well.


RANA SALADA FED COM 0504 216H



Project: EDDY CO., NEW MEXICO (NM27E)
Site: SEC 06-T23S-R29E
Well: RANA SALADA FED COM 0504 216H
Wellbore: 216H
Design: PLAN 1 V1

WELL DETAILS: RANA SALADA FED COM 0504 216H

3041.10					
+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
0.00	0.00	484287.35	638805.67	32.33098	-104.01777



SECTION DETAILS

MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	Vsect
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
2000.00	0.00	0.00	2000.00	0.00	0.00	0.00	0.00	0.00
2400.00	12.00	32.45	2397.08	35.22	22.39	3.00	32.45	22.74
6707.76	12.00	32.45	6610.71	791.03	502.92	0.00	0.00	510.63
7307.76	0.00	0.00	7206.33	843.86	536.51	2.00	180.00	544.73
9568.06	0.00	0.00	9466.63	843.86	536.51	0.00	0.00	544.73
10308.40	88.84	89.44	9944.00	848.44	1004.30	12.00	89.44	1012.54
20444.11	88.84	89.44	10149.00	947.65	11137.44	0.00	0.00	11146.17

DESIGN TARGET DETAILS

Name	TVD	+N/-S	+E/-W	Northing	Easting
KOP 216H	9466.63	843.86	536.51	485131.21	639342.18
FTP 216H	9944.00	848.53	1013.95	485135.88	639819.62
PBHL 216H	10149.00	947.65	11137.44	485235.00	649943.11



SB Directional Services
D3 DRAFTING & DESIGN



Company:	NOVO OIL & GAS, LLC	Local Co-ordinate Reference:	Well RANA SALADA FED COM 0504 216H
Project:	EDDY CO., NEW MEXICO (NM27E)	TVD Reference:	GE+25' @ 3066.10usft (RKB)
Site:	SEC 06-T23S-R29E	MD Reference:	GE+25' @ 3066.10usft (RKB)
Well:	RANA SALADA FED COM 0504 216H	North Reference:	Grid
Wellbore:	216H	Survey Calculation Method:	Minimum Curvature
Design:	PLAN 1 V1	Database:	EDM 5000.15 Single User Db

Project	EDDY CO., NEW MEXICO (NM27E)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	SEC 06-T23S-R29E		
Site Position:		Northing:	484,087.23usft
From:	Map	Easting:	638,836.04usft
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16"
		Latitude:	32.33043
		Longitude:	-104.01767
		Grid Convergence:	0.17 °

Well	RANA SALADA FED COM 0504 216H		
Well Position	+N/-S	0.00 usft	Northing:
	+E/-W	0.00 usft	Easting:
Position Uncertainty	0.00 usft	Wellhead Elevation:	3,041.10 usft
		Latitude:	32.33098
		Longitude:	-104.01777
		Ground Level:	3,041.10 usft

Wellbore	216H		
Magnetics	Model Name	Sample Date	Declination (°)
	IGRF2015	05/17/19	6.96
			Dip Angle (°)
			60.07
			Field Strength (nT)
			47,760.15178415

Design	PLAN 1 V1		
Audit Notes:			
Version:	Phase:	PLAN	Tie On Depth:
			0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)
	0.00	0.00	0.00
			Direction (°)
			89.44

Survey Tool Program	Date 05/28/19		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name
0.00	20,444.11	PLAN 1 V1 (216H)	MWD
			Description
			OWSG MWD - Standard

Planned Survey							
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00



SB Directional Services
D3 DRAFTING & DESIGN



Company: NOVO OIL & GAS, LLC
Project: EDDY CO., NEW MEXICO (NM27E)
Site: SEC 06-T23S-R29E
Well: RANA SALADA FED COM 0504 216H
Wellbore: 216H
Design: PLAN 1 V1

Local Co-ordinate Reference: Well RANA SALADA FED COM 0504 216H
TVD Reference: GE+25' @ 3066.10usft (RKB)
MD Reference: GE+25' @ 3066.10usft (RKB)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.15 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00
1,900.00	0.00	0.00	1,900.00	0.00	0.00	0.00	0.00
2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00
KOP - 3°/100' DLS							
2,100.00	3.00	32.45	2,099.95	2.21	1.40	1.43	3.00
2,200.00	6.00	32.45	2,199.63	8.83	5.61	5.70	3.00
2,300.00	9.00	32.45	2,298.77	19.84	12.62	12.81	3.00
2,400.00	12.00	32.45	2,397.08	35.22	22.39	22.74	3.00
Hold 12° @ 32.45° Az							
2,500.00	12.00	32.45	2,494.90	52.76	33.55	34.06	0.00
2,600.00	12.00	32.45	2,592.71	70.31	44.70	45.39	0.00
2,700.00	12.00	32.45	2,690.53	87.86	55.86	56.71	0.00
2,800.00	12.00	32.45	2,788.34	105.40	67.01	68.04	0.00
2,900.00	12.00	32.45	2,886.16	122.95	78.17	79.36	0.00
3,000.00	12.00	32.45	2,983.97	140.49	89.32	90.69	0.00
3,100.00	12.00	32.45	3,081.79	158.04	100.48	102.02	0.00
3,200.00	12.00	32.45	3,179.60	175.58	111.63	113.34	0.00
3,300.00	12.00	32.45	3,277.41	193.13	122.79	124.67	0.00
3,400.00	12.00	32.45	3,375.23	210.67	133.94	135.99	0.00
3,500.00	12.00	32.45	3,473.04	228.22	145.10	147.32	0.00
3,600.00	12.00	32.45	3,570.86	245.76	156.25	158.65	0.00
3,700.00	12.00	32.45	3,668.67	263.31	167.41	169.97	0.00
3,800.00	12.00	32.45	3,766.49	280.85	178.56	181.30	0.00
3,900.00	12.00	32.45	3,864.30	298.40	189.72	192.62	0.00
4,000.00	12.00	32.45	3,962.12	315.94	200.87	203.95	0.00
4,100.00	12.00	32.45	4,059.93	333.49	212.03	215.28	0.00
4,200.00	12.00	32.45	4,157.75	351.04	223.18	226.60	0.00
4,300.00	12.00	32.45	4,255.56	368.58	234.34	237.93	0.00
4,400.00	12.00	32.45	4,353.38	386.13	245.49	249.25	0.00
4,500.00	12.00	32.45	4,451.19	403.67	256.65	260.58	0.00
4,600.00	12.00	32.45	4,549.01	421.22	267.80	271.91	0.00
4,700.00	12.00	32.45	4,646.82	438.76	278.96	283.23	0.00
4,800.00	12.00	32.45	4,744.64	456.31	290.11	294.56	0.00
4,900.00	12.00	32.45	4,842.45	473.85	301.27	305.88	0.00
5,000.00	12.00	32.45	4,940.27	491.40	312.42	317.21	0.00
5,100.00	12.00	32.45	5,038.08	508.94	323.58	328.54	0.00
5,200.00	12.00	32.45	5,135.90	526.49	334.73	339.86	0.00
5,300.00	12.00	32.45	5,233.71	544.03	345.89	351.19	0.00
5,400.00	12.00	32.45	5,331.52	561.58	357.04	362.51	0.00



SB Directional Services
D3 DRAFTING & DESIGN



Company: NOVO OIL & GAS, LLC
Project: EDDY CO., NEW MEXICO (NM27E)
Site: SEC 06-T23S-R29E
Well: RANA SALADA FED COM 0504 216H
Wellbore: 216H
Design: PLAN 1 V1

Local Co-ordinate Reference: Well RANA SALADA FED COM 0504 216H
TVD Reference: GE+25' @ 3066.10usft (RKB)
MD Reference: GE+25' @ 3066.10usft (RKB)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.15 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)
5,500.00	12.00	32.45	5,429.34	579.13	368.20	373.84	0.00
5,600.00	12.00	32.45	5,527.15	596.67	379.35	385.16	0.00
5,700.00	12.00	32.45	5,624.97	614.22	390.51	396.49	0.00
5,800.00	12.00	32.45	5,722.78	631.76	401.66	407.82	0.00
5,900.00	12.00	32.45	5,820.60	649.31	412.82	419.14	0.00
6,000.00	12.00	32.45	5,918.41	666.85	423.97	430.47	0.00
6,100.00	12.00	32.45	6,016.23	684.40	435.13	441.79	0.00
6,200.00	12.00	32.45	6,114.04	701.94	446.28	453.12	0.00
6,300.00	12.00	32.45	6,211.86	719.49	457.44	464.45	0.00
6,400.00	12.00	32.45	6,309.67	737.03	468.59	475.77	0.00
6,500.00	12.00	32.45	6,407.49	754.58	479.75	487.10	0.00
6,600.00	12.00	32.45	6,505.30	772.12	490.90	498.42	0.00
6,707.76	12.00	32.45	6,610.71	791.03	502.92	510.63	0.00
Start Drop 2°/100' DLS							
6,800.00	10.16	32.45	6,701.22	805.99	512.43	520.28	2.00
6,900.00	8.16	32.45	6,799.95	819.41	520.97	528.95	2.00
7,000.00	6.16	32.45	6,899.16	829.92	527.65	535.74	2.00
7,100.00	4.16	32.45	6,998.75	837.51	532.47	540.63	2.00
7,200.00	2.16	32.45	7,098.60	842.15	535.42	543.63	2.00
7,307.76	0.00	0.00	7,206.33	843.86	536.51	544.73	2.00
Hold 0° Inc							
7,400.00	0.00	0.00	7,298.57	843.86	536.51	544.73	0.00
7,500.00	0.00	0.00	7,398.57	843.86	536.51	544.73	0.00
7,600.00	0.00	0.00	7,498.57	843.86	536.51	544.73	0.00
7,700.00	0.00	0.00	7,598.57	843.86	536.51	544.73	0.00
7,800.00	0.00	0.00	7,698.57	843.86	536.51	544.73	0.00
7,900.00	0.00	0.00	7,798.57	843.86	536.51	544.73	0.00
8,000.00	0.00	0.00	7,898.57	843.86	536.51	544.73	0.00
8,100.00	0.00	0.00	7,998.57	843.86	536.51	544.73	0.00
8,200.00	0.00	0.00	8,098.57	843.86	536.51	544.73	0.00
8,300.00	0.00	0.00	8,198.57	843.86	536.51	544.73	0.00
8,400.00	0.00	0.00	8,298.57	843.86	536.51	544.73	0.00
8,500.00	0.00	0.00	8,398.57	843.86	536.51	544.73	0.00
8,600.00	0.00	0.00	8,498.57	843.86	536.51	544.73	0.00
8,700.00	0.00	0.00	8,598.57	843.86	536.51	544.73	0.00
8,800.00	0.00	0.00	8,698.57	843.86	536.51	544.73	0.00
8,900.00	0.00	0.00	8,798.57	843.86	536.51	544.73	0.00
9,000.00	0.00	0.00	8,898.57	843.86	536.51	544.73	0.00
9,100.00	0.00	0.00	8,998.57	843.86	536.51	544.73	0.00
9,200.00	0.00	0.00	9,098.57	843.86	536.51	544.73	0.00
9,300.00	0.00	0.00	9,198.57	843.86	536.51	544.73	0.00
9,400.00	0.00	0.00	9,298.57	843.86	536.51	544.73	0.00
9,500.00	0.00	0.00	9,398.57	843.86	536.51	544.73	0.00
9,568.06	0.00	0.00	9,466.63	843.86	536.51	544.73	0.00
KOP - 12°/100' DLS - KOP 216H							



SB Directional Services
D3 DRAFTING & DESIGN



Company: NOVO OIL & GAS, LLC
Project: EDDY CO., NEW MEXICO (NM27E)
Site: SEC 06-T23S-R29E
Well: RANA SALADA FED COM 0504 216H
Wellbore: 216H
Design: PLAN 1 V1

Local Co-ordinate Reference: Well RANA SALADA FED COM 0504 216H
TVD Reference: GE+25' @ 3066.10usft (RKB)
MD Reference: GE+25' @ 3066.10usft (RKB)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.15 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)
9,575.00	0.83	89.44	9,473.57	843.86	536.56	544.78	12.00
9,600.00	3.83	89.44	9,498.55	843.87	537.58	545.80	12.00
9,625.00	6.83	89.44	9,523.44	843.89	539.90	548.12	12.00
9,650.00	9.83	89.44	9,548.17	843.93	543.52	551.75	12.00
9,675.00	12.83	89.44	9,572.68	843.98	548.44	556.66	12.00
9,700.00	15.83	89.44	9,596.90	844.04	554.62	562.85	12.00
9,725.00	18.83	89.44	9,620.76	844.11	562.07	570.29	12.00
9,750.00	21.83	89.44	9,644.20	844.20	570.76	578.98	12.00
9,775.00	24.83	89.44	9,667.15	844.29	580.66	588.88	12.00
9,800.00	27.83	89.44	9,689.56	844.40	591.74	599.97	12.00
9,825.00	30.83	89.44	9,711.35	844.52	603.99	612.21	12.00
9,850.00	33.83	89.44	9,732.47	844.65	617.36	625.58	12.00
9,875.00	36.83	89.44	9,752.86	844.79	631.81	640.04	12.00
9,900.00	39.83	89.44	9,772.47	844.95	647.32	655.54	12.00
9,925.00	42.83	89.44	9,791.24	845.11	663.82	672.05	12.00
9,950.00	45.83	89.44	9,809.12	845.28	681.29	689.52	12.00
9,975.00	48.83	89.44	9,826.06	845.46	699.67	707.90	12.00
10,000.00	51.83	89.44	9,842.02	845.65	718.91	727.14	12.00
10,025.00	54.83	89.44	9,856.95	845.84	738.96	747.19	12.00
10,050.00	57.83	89.44	9,870.80	846.05	759.77	768.00	12.00
10,075.00	60.83	89.44	9,883.55	846.26	781.27	789.50	12.00
10,100.00	63.83	89.44	9,895.16	846.47	803.40	811.64	12.00
10,125.00	66.83	89.44	9,905.59	846.70	826.12	834.35	12.00
10,150.00	69.83	89.44	9,914.82	846.92	849.35	857.59	12.00
10,175.00	72.83	89.44	9,922.82	847.16	873.03	881.27	12.00
10,200.00	75.83	89.44	9,929.57	847.39	897.10	905.34	12.00
10,225.00	78.83	89.44	9,935.05	847.63	921.48	929.73	12.00
10,250.00	81.83	89.44	9,939.25	847.87	946.13	954.37	12.00
10,275.00	84.83	89.44	9,942.15	848.11	970.95	979.20	12.00
10,300.00	87.83	89.44	9,943.75	848.36	995.90	1,004.14	12.00
10,308.40	88.84	89.44	9,944.00	848.44	1,004.29	1,012.54	12.00
LP 10308.40' MD & 9944.00' TVD							
10,318.06	88.84	89.44	9,944.19	848.53	1,013.95	1,022.19	0.00
FTP 216H							
10,400.00	88.84	89.44	9,945.85	849.34	1,095.87	1,104.12	0.00
10,500.00	88.84	89.44	9,947.87	850.32	1,195.84	1,204.10	0.00
10,600.00	88.84	89.44	9,949.89	851.29	1,295.82	1,304.08	0.00
10,700.00	88.84	89.44	9,951.92	852.27	1,395.79	1,404.06	0.00
10,800.00	88.84	89.44	9,953.94	853.25	1,495.77	1,504.04	0.00
10,900.00	88.84	89.44	9,955.96	854.23	1,595.74	1,604.02	0.00
11,000.00	88.84	89.44	9,957.99	855.21	1,695.72	1,704.00	0.00
11,100.00	88.84	89.44	9,960.01	856.19	1,795.69	1,803.98	0.00
11,200.00	88.84	89.44	9,962.03	857.17	1,895.67	1,903.96	0.00
11,300.00	88.84	89.44	9,964.05	858.15	1,995.64	2,003.93	0.00
11,400.00	88.84	89.44	9,966.08	859.12	2,095.62	2,103.91	0.00



SB Directional Services
D3 DRAFTING & DESIGN



Company: NOVO OIL & GAS, LLC
Project: EDDY CO., NEW MEXICO (NM27E)
Site: SEC 06-T23S-R29E
Well: RANA SALADA FED COM 0504 216H
Wellbore: 216H
Design: PLAN 1 V1

Local Co-ordinate Reference: Well RANA SALADA FED COM 0504 216H
TVD Reference: GE+25' @ 3066.10usft (RKB)
MD Reference: GE+25' @ 3066.10usft (RKB)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.15 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)
11,500.00	88.84	89.44	9,968.10	860.10	2,195.59	2,203.89	0.00
11,600.00	88.84	89.44	9,970.12	861.08	2,295.57	2,303.87	0.00
11,700.00	88.84	89.44	9,972.14	862.06	2,395.54	2,403.85	0.00
11,800.00	88.84	89.44	9,974.17	863.04	2,495.52	2,503.83	0.00
11,900.00	88.84	89.44	9,976.19	864.02	2,595.49	2,603.81	0.00
12,000.00	88.84	89.44	9,978.21	865.00	2,695.47	2,703.79	0.00
12,100.00	88.84	89.44	9,980.23	865.98	2,795.44	2,803.77	0.00
12,200.00	88.84	89.44	9,982.26	866.96	2,895.42	2,903.75	0.00
12,300.00	88.84	89.44	9,984.28	867.93	2,995.39	3,003.73	0.00
12,400.00	88.84	89.44	9,986.30	868.91	3,095.37	3,103.71	0.00
12,500.00	88.84	89.44	9,988.32	869.89	3,195.34	3,203.69	0.00
12,600.00	88.84	89.44	9,990.35	870.87	3,295.31	3,303.67	0.00
12,700.00	88.84	89.44	9,992.37	871.85	3,395.29	3,403.65	0.00
12,800.00	88.84	89.44	9,994.39	872.83	3,495.26	3,503.63	0.00
12,900.00	88.84	89.44	9,996.41	873.81	3,595.24	3,603.61	0.00
13,000.00	88.84	89.44	9,998.44	874.79	3,695.21	3,703.59	0.00
13,100.00	88.84	89.44	10,000.46	875.76	3,795.19	3,803.57	0.00
13,200.00	88.84	89.44	10,002.48	876.74	3,895.16	3,903.55	0.00
13,300.00	88.84	89.44	10,004.50	877.72	3,995.14	4,003.53	0.00
13,400.00	88.84	89.44	10,006.53	878.70	4,095.11	4,103.51	0.00
13,500.00	88.84	89.44	10,008.55	879.68	4,195.09	4,203.48	0.00
13,600.00	88.84	89.44	10,010.57	880.66	4,295.06	4,303.46	0.00
13,700.00	88.84	89.44	10,012.59	881.64	4,395.04	4,403.44	0.00
13,800.00	88.84	89.44	10,014.62	882.62	4,495.01	4,503.42	0.00
13,900.00	88.84	89.44	10,016.64	883.60	4,594.99	4,603.40	0.00
14,000.00	88.84	89.44	10,018.66	884.57	4,694.96	4,703.38	0.00
14,100.00	88.84	89.44	10,020.69	885.55	4,794.94	4,803.36	0.00
14,200.00	88.84	89.44	10,022.71	886.53	4,894.91	4,903.34	0.00
14,300.00	88.84	89.44	10,024.73	887.51	4,994.89	5,003.32	0.00
14,400.00	88.84	89.44	10,026.75	888.49	5,094.86	5,103.30	0.00
14,500.00	88.84	89.44	10,028.78	889.47	5,194.84	5,203.28	0.00
14,600.00	88.84	89.44	10,030.80	890.45	5,294.81	5,303.26	0.00
14,700.00	88.84	89.44	10,032.82	891.43	5,394.78	5,403.24	0.00
14,800.00	88.84	89.44	10,034.84	892.40	5,494.76	5,503.22	0.00
14,900.00	88.84	89.44	10,036.87	893.38	5,594.73	5,603.20	0.00
15,000.00	88.84	89.44	10,038.89	894.36	5,694.71	5,703.18	0.00
15,100.00	88.84	89.44	10,040.91	895.34	5,794.68	5,803.16	0.00
15,200.00	88.84	89.44	10,042.93	896.32	5,894.66	5,903.14	0.00
15,300.00	88.84	89.44	10,044.96	897.30	5,994.63	6,003.12	0.00
15,400.00	88.84	89.44	10,046.98	898.28	6,094.61	6,103.10	0.00
15,500.00	88.84	89.44	10,049.00	899.26	6,194.58	6,203.08	0.00
15,600.00	88.84	89.44	10,051.02	900.24	6,294.56	6,303.06	0.00
15,700.00	88.84	89.44	10,053.05	901.21	6,394.53	6,403.03	0.00
15,800.00	88.84	89.44	10,055.07	902.19	6,494.51	6,503.01	0.00



SB Directional Services

D3 DRAFTING & DESIGN



Company: NOVO OIL & GAS, LLC
Project: EDDY CO., NEW MEXICO (NM27E)
Site: SEC 06-T23S-R29E
Well: RANA SALADA FED COM 0504 216H
Wellbore: 216H
Design: PLAN 1 V1

Local Co-ordinate Reference: Well RANA SALADA FED COM 0504 216H
TVD Reference: GE+25' @ 3066.10usft (RKB)
MD Reference: GE+25' @ 3066.10usft (RKB)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.15 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)
15,900.00	88.84	89.44	10,057.09	903.17	6,594.48	6,602.99	0.00
16,000.00	88.84	89.44	10,059.11	904.15	6,694.46	6,702.97	0.00
16,100.00	88.84	89.44	10,061.14	905.13	6,794.43	6,802.95	0.00
16,200.00	88.84	89.44	10,063.16	906.11	6,894.41	6,902.93	0.00
16,300.00	88.84	89.44	10,065.18	907.09	6,994.38	7,002.91	0.00
16,400.00	88.84	89.44	10,067.20	908.07	7,094.36	7,102.89	0.00
16,500.00	88.84	89.44	10,069.23	909.04	7,194.33	7,202.87	0.00
16,600.00	88.84	89.44	10,071.25	910.02	7,294.30	7,302.85	0.00
16,700.00	88.84	89.44	10,073.27	911.00	7,394.28	7,402.83	0.00
16,800.00	88.84	89.44	10,075.30	911.98	7,494.25	7,502.81	0.00
16,900.00	88.84	89.44	10,077.32	912.96	7,594.23	7,602.79	0.00
17,000.00	88.84	89.44	10,079.34	913.94	7,694.20	7,702.77	0.00
17,100.00	88.84	89.44	10,081.36	914.92	7,794.18	7,802.75	0.00
17,200.00	88.84	89.44	10,083.39	915.90	7,894.15	7,902.73	0.00
17,300.00	88.84	89.44	10,085.41	916.88	7,994.13	8,002.71	0.00
17,400.00	88.84	89.44	10,087.43	917.85	8,094.10	8,102.69	0.00
17,500.00	88.84	89.44	10,089.45	918.83	8,194.08	8,202.67	0.00
17,600.00	88.84	89.44	10,091.48	919.81	8,294.05	8,302.65	0.00
17,700.00	88.84	89.44	10,093.50	920.79	8,394.03	8,402.63	0.00
17,800.00	88.84	89.44	10,095.52	921.77	8,494.00	8,502.61	0.00
17,900.00	88.84	89.44	10,097.54	922.75	8,593.98	8,602.58	0.00
18,000.00	88.84	89.44	10,099.57	923.73	8,693.95	8,702.56	0.00
18,100.00	88.84	89.44	10,101.59	924.71	8,793.93	8,802.54	0.00
18,200.00	88.84	89.44	10,103.61	925.68	8,893.90	8,902.52	0.00
18,300.00	88.84	89.44	10,105.63	926.66	8,993.88	9,002.50	0.00
18,400.00	88.84	89.44	10,107.66	927.64	9,093.85	9,102.48	0.00
18,500.00	88.84	89.44	10,109.68	928.62	9,193.83	9,202.46	0.00
18,600.00	88.84	89.44	10,111.70	929.60	9,293.80	9,302.44	0.00
18,700.00	88.84	89.44	10,113.72	930.58	9,393.77	9,402.42	0.00
18,800.00	88.84	89.44	10,115.75	931.56	9,493.75	9,502.40	0.00
18,900.00	88.84	89.44	10,117.77	932.54	9,593.72	9,602.38	0.00
19,000.00	88.84	89.44	10,119.79	933.52	9,693.70	9,702.36	0.00
19,100.00	88.84	89.44	10,121.81	934.49	9,793.67	9,802.34	0.00
19,200.00	88.84	89.44	10,123.84	935.47	9,893.65	9,902.32	0.00
19,300.00	88.84	89.44	10,125.86	936.45	9,993.62	10,002.30	0.00
19,400.00	88.84	89.44	10,127.88	937.43	10,093.60	10,102.28	0.00
19,500.00	88.84	89.44	10,129.90	938.41	10,193.57	10,202.26	0.00
19,600.00	88.84	89.44	10,131.93	939.39	10,293.55	10,302.24	0.00
19,700.00	88.84	89.44	10,133.95	940.37	10,393.52	10,402.22	0.00
19,800.00	88.84	89.44	10,135.97	941.35	10,493.50	10,502.20	0.00
19,900.00	88.84	89.44	10,138.00	942.32	10,593.47	10,602.18	0.00
20,000.00	88.84	89.44	10,140.02	943.30	10,693.45	10,702.16	0.00
20,100.00	88.84	89.44	10,142.04	944.28	10,793.42	10,802.13	0.00
20,200.00	88.84	89.44	10,144.06	945.26	10,893.40	10,902.11	0.00



SB Directional Services
D3 DRAFTING & DESIGN



Company: NOVO OIL & GAS, LLC
Project: EDDY CO., NEW MEXICO (NM27E)
Site: SEC 06-T23S-R29E
Well: RANA SALADA FED COM 0504 216H
Wellbore: 216H
Design: PLAN 1 V1

Local Co-ordinate Reference: Well RANA SALADA FED COM 0504 216H
TVD Reference: GE+25' @ 3066.10usft (RKB)
MD Reference: GE+25' @ 3066.10usft (RKB)
North Reference: Grid
Survey Calculation Method: Minimum Curvature
Database: EDM 5000.15 Single User Db

Planned Survey

MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	V. Sec (usft)	DLeg (°/100usft)
20,300.00	88.84	89.44	10,146.09	946.24	10,993.37	11,002.09	0.00
20,400.00	88.84	89.44	10,148.11	947.22	11,093.35	11,102.07	0.00
20,444.11	88.84	89.44	10,149.00	947.65	11,137.44	11,146.17	0.00
PTD 20444.11' MD & 10149.00' TVD - PBHL 216H							

Plan Annotations

Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
2,000.00	2,000.00	0.00	0.00	KOP - 3°/100' DLS
2,400.00	2,397.08	35.22	22.39	Hold 12° @ 32.45° Az
6,707.76	6,610.71	791.03	502.92	Start Drop 2°/100' DLS
7,307.76	7,206.33	843.86	536.51	Hold 0° Inc
9,568.06	9,466.63	843.86	536.51	KOP - 12°/100' DLS
10,308.40	9,944.00	848.44	1,004.29	LP 10308.40' MD & 9944.00' TVD
20,444.11	10,149.00	947.65	11,137.44	PTD 20444.11' MD & 10149.00' TVD

Checked By: _____ Approved By: _____ Date: _____



H₂S Drilling Operations Plan

- a. All personnel will be trained in H₂S working conditions as required by Onshore Order 6 before drilling out of the surface casing.
- b. Two briefing areas will be established. Each will be at least 150' from the wellhead, perpendicular from one another, and easily entered and exited. See H₂S page 5 for more details.
- c. H₂S Safety Equipment/Systems:
 - i. Well Control Equipment
 - Flare line will be $\geq 150'$ from the wellhead and ignited by a pilot light.
 - Beware of SO₂ created by flaring.
 - Choke manifold will include a remotely operated choke.
 - Mud gas separator
 - ii. Protective Equipment for Essential Personnel
 - Every person on site will be required to wear a personal H₂S and SO₂ monitor at all times while on site. Monitors will not be worn on hard hats. Monitors will be worn on the front of the chest.
 - One self-contained breathing apparatus (SCBA) 30-minute rescue pack will be at each briefing area. Two 30-minute SCBA packs will be stored in the safety trailer.
 - Four work/escape packs will be on the rig floor. Each pack will have a long enough hose to allow unimpaired work activity.
 - Four emergency escape packs will be in the doghouse for emergency evacuation.
 - Hand signals will be used when wearing protective breathing apparatus.
 - Stokes litter or stretcher
 - Two full OSHA compliant body harnesses
 - A 100-foot long x 5/8" OSHA compliant rope
 - One 20-pound ABC fire extinguisher

iii. H₂S Detection & Monitoring Equipment

- Every person on site will be required to wear a personal H₂S and SO₂ monitor at all times while on site. Monitors will not be worn on hard hats. Monitors will be worn on the front of the chest.
- A stationary detector with three sensors will be in the doghouse.
- Sensors will be installed on the rig floor, bell nipple, and at the end of the flow line or where drilling fluids are discharged.
- Visual alarm will be triggered at 10 ppm.
- Audible alarm will be triggered at 10 ppm.
- Calibration will occur at least every 30 days. Gas sample tubes will be kept in the safety trailer.

iv. Visual Warning System

- Color-coded H₂S condition sign will be set at the entrance to the pad.
- Color-coded condition flag will be installed to indicate current H₂S conditions.
- Two wind socks will be installed that will be visible from all sides.

v. Mud Program

- A water based mud with a pH of ≥ 10 will be maintained to control corrosion, H₂S gas returns to the surface, and minimize sulfide stress cracking and embrittlement.
- Drilling mud containing H₂S gas will be degassed at an optimum location for the rig configuration.
- This gas will be piped into the flare system.
- Enough mud additives will be on location to scavenge and/or neutralize H₂S where formation pressures are unknown.

vi. Metallurgy

- All equipment that has the potential to be exposed to H₂S will be suitable for H₂S service.
- Equipment that will meet these metallurgical standards include the drill string, casing, wellhead, BOP assembly, casing head and spool, rotating head, kill lines, choke, choke manifold and lines, valves, mud-gas separators, DST tools, test units, tubing, flanges, and other related equipment (elastomer packings and seals).

vii. Communication from well site

- Cell phones and/or two-way radios will be used to communicate from the well site.

d. A remote-controlled choke, mud-gas separator, and a rotating head will be installed before drilling or testing any formation expected to contain H₂S.

Company Personnel to be Notified

Kurt Shipley, Vice-President - Operations	Office: (405) 609-1596
---	------------------------

Local & County Agencies

Loving Fire Department	911 or (575) 745-3600
Eddy County Sheriff (Carlsbad)	911 (575) 887-7551
Eddy County Emergency Management (Carlsbad)	(575) 887-9511
Carlsbad Medical Center Hospital	(575) 887-4100
Eddy County South Road Department (Carlsbad)	(575) 885-4835

State Agencies

NM State Police (Carlsbad)	(575) 885-3138
NM Oil Conservation (Artesia)	(575) 748-1283
NM Oil Conservation (Santa Fe)	(505) 476-3440
NM Dept. of Transportation (Roswell)	(575) 637-7201

Federal Agencies

BLM Carlsbad Field Office	(575) 234-5972
National Response Center	(800) 424-8802
US EPA Region 6 (Dallas)	(800) 887-6063
	(214) 665-6444

Residents within 2 miles

none

Air Evacuation

Med Flight Air Ambulance (Albuquerque)	(800) 842-4431
--	----------------

Lifeguard (Albuquerque)	(888) 866-7256
-------------------------	----------------

Veterinarians

Desert Willow Veterinary Services (Carlsbad)	(575) 885-3399
--	----------------

Animal Care Center (Carlsbad)	(575) 885-5352
-------------------------------	----------------

PLAN VIEW

highest ground to the north

flare line (straight) & flare >150' from well head

PRIMARY safety briefing area >150' from well head

egress (exit) >150' from well head

3:1 SLOPE (TYP.)

wind socks on rig floor & at mud tanks

V-door to east

warning signs & windsock

prevailing wind blows from S

safety briefing area >150' from well head

secondary exit

SCALE 1" = 120'

JOVO OIL & GAS NORTHERN DELAWARE, LLC
PAD GRADING AND CROSS SECTIONS
FOR RANA SALADA FED COM 0504 233H
SECTION 6, TOWNSHIP 23 SOUTH,
RANGE 29 EAST, N.M.P.M.
EDDY COUNTY, STATE OF NEW MEXICO

APRIL 18, 2019

MADRON SURVEYING, INC. CARLSBAD, NEW MEXICO

SHEET 1-2
SURVEY NO. 7195

A	-	RANA	SALADA	FED	COM	0504	116H
B	-	RANA	SALADA	FED	COM	0504	113H
C	-	RANA	SALADA	FED	COM	0504	236H
D	-	RANA	SALADA	FED	COM	0504	226H
E	-	RANA	SALADA	FED	COM	0504	216H
F	-	RANA	SALADA	FED	COM	0504	136H
G	-	RANA	SALADA	FED	COM	0504	213H
H	-	RANA	SALADA	FED	COM	0504	133H
I	-	RANA	SALADA	FED	COM	0504	114H
J	-	RANA	SALADA	FED	COM	0504	224H
K	-	RANA	SALADA	FED	COM	0504	233H
L	-	RANA	SALADA	FED	COM	0504	223H
M	-	RANA	SALADA	FED	COM	0504	234H
N	-	RANA	SALADA	FED	COM	0504	214H
O	-	RANA	SALADA	FED	COM	0504	134H


CUT	FILL	NET
12106 CU. YD	5117 CU. YD	6989 CU. YD (CUT)

EARTHWORK QUANTITIES ARE ESTIMATED

Novo Oil and Gas & Northern Delaware

Rana Salada Fed Com 0504 Pad E
H2S Contingency Plan
1 & 2 Mile Radius Map

Section 5, Township 23S, Range 29E
Eddy County, New Mexico





Surface Hole Location




NAD 1983 New Mexico State Plane East
FIPS 3001 Feet



Prepared by Permits West, Inc., July 3, 2019
for Novo Oil and Gas & Northern Delaware, LLC





Schematic Closed Loop Drilling Rig*

1. Pipe Rack
2. Drill Rig
3. House Trailers/ Offices
4. Generator/Fuel/Storage
5. Overflow-Frac Tank
6. Skids
7. Roll Offs
8. Hopper or Centrifuge
9. Mud Tanks
10. Loop Drive
11. Generator (only for use with centrifuge)

*Not drawn to scale: Closed loop system requires at least 30 feet beyond mud tanks. Ideally 60 feet would be available



Above: Centrifugal Closed Loop System



Closed Loop Drilling System: Mud tanks to right (1)
 Hopper in air to settle out solids (2)
 Water return pipe (3)
 Shaker between hopper and mud tanks (4)
 Roll offs on skids (5)

Flow Chart for Drilling Fluids and Solids

