Submit 1 Copy To Appropriate District State of New Mexico Rec'd 10	
District I – (575) 393-6161 Energy, Minerals and Natural Resources	Revised July 18, 2013 WELL API NO.
District II – (575) 748-1283 811 S. First St., Artesia, NM 88210 OIL CONSERVATION DIVISION	30-015-47124
<u>District III</u> – (505) 334-6178 1220 South St. Francis Dr.	5. Indicate Type of Lease STATE 🗹 FEE
1000 Rio Brazos Rd., Aztec, NM 87410 District IV – (505) 476-3460 Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	
87505 SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	Remuda South 25 State
1. Type of Well: Oil Well 🔲 Gas Well 🗹 Other	8. Well Number 703H
2. Name of Operator	9. OGRID Number
XTO Energy 3. Address of Operator	005380 10. Pool name or Wildcat
6401 Holiday Hill Rd. Bldg 5, Midland, TX 79707	Forty Niner Ridge Bone Spring W
4. Well Location	Torty Miller Ridge Bone Spring W
Unit Letter F : 2354 feet from the North line and ¹¹	980 feet from the West line
Section 25 Township 23S Range 29E	NMPM County Eddy
11. Elevation (Show whether DR, RKB, RT, GR, et	Ş
3075	,
12. Charle Annuantista Dars to Indiante Nature of Natio	Barrant an Othan Data
12. Check Appropriate Box to Indicate Nature of Notice	e, Report or Other Data
NOTICE OF INTENTION TO: SU	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK 🗌 PLUG AND ABANDON 🗌 🛛 REMEDIAL WO	
	RILLING OPNS. 🗹 PAND A
	NT JOB
CLOSED-LOOP SYSTEM	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date	
15. Describe proposed of completed operations. (Creatly state an pertinent details, a	and give pertinent dates, including estimated date
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C	Completions: Attach wellbore diagram of
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion.	Completions: Attach wellbore diagram of
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced	Completions: Attach wellbore diagram of
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of the second sec	completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th	completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 9 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft.	completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 9 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565	completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 9 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft.	completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 9 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565	completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 9 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20.	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of y 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20. Spud Date: 08/21/20 Rig Release Date: 10/24/20	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20.	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of v 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20. Spud Date: 08/21/20 Rig Release Date: 10/24/20 I hereby certify that the information above is true and complete to the best of my knowled.	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of v 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20. Spud Date: 08/21/20 Rig Release Date: 10/24/20 I hereby certify that the information above is true and complete to the best of my knowled.	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 920 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement, CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20. Spud Date: 08/21/20 Rig Release Date: 10/24/20. Thereby certify that the information above is true and complete to the best of my knowled SIGNATURE/McLance Colluins TITLE Regulatory Analyst	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 120 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20. Spud Date: 08/21/20 Rig Release Date: 10/24/20 I hereby certify that the information above is true and complete to the best of my knowled SIGNATURE///Linear Colling E-mail address: melanie_colling	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 920 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20. Spud Date: 08/21/20 Rig Release Date: 10/24/20. Thereby certify that the information above is true and complete to the best of my knowled SIGNATURE/McLance Colluins_TITLE_Regulatory Analyst	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20. Spud Date: 08/21/20 Rig Release Date: 10/24/20 Thereby certify that the information above is true and complete to the best of my knowled SIGNATURE////////////////////////////////////	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail dge and belief. DATE 10/27/20 S@xtoenergy.com PHONE: 432-218-3709
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C proposed completion or recompletion. XTO Energy, Inc. respectfully submits this sundry notice to report drilling operations of the referenced 10/14/20-10/24/20 MIRU on 10/14/20. 10/15/20 Test 8.625 inch casing to 1500psi for 30 minutes. Good test. Drill 7.875 inch hole to TD of f 20 lb FHTQ casing to 16567. Cenent with 505sx/ 125 bbls/ 1.39 yld Class 35/65 Poz Lead cement, th cement. CTOC at 3100 ft. 10/21/20 PBTD 16565 Production casing test will be run prior to well completion. RD drilling rig at 1500 hrs on 10/24/20. Spud Date: 08/21/20 Rig Release Date: 10/24/20 T hereby certify that the information above is true and complete to the best of my knowled SIGNATURE///Linearchines//Linearchi	Completions: Attach wellbore diagram of well. well at 16,621 on 10/21/20. Run 5.5 inch CYP/P-110 ien 1205 sx/ 298 bbls/ 1.39 yld Class 35/65 Poz Tail