

Submit 3 Copies To Appropriate District Office
District I
1625 N French Dr., Hobbs, NM 88240
District II
1301 W Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd, Aztec, NM 87410
District IV
1220 S. St Francis Dr, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-38513
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name JEFFERS STATE ✓
8. Well Number #3 ✓
9. OGRID Number 255333 ✓
10. Pool name or Wildcat: Artesia, Glorieta-Yeso (96830)
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3677' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
LIME ROCK RESOURCES A, L.P.

3. Address of Operator
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

4. Well Location
Unit Letter J: 2310 feet from the SOUTH line and 2032 feet from the EAST line
Section 32 Township 17-S Range 28-E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

OTHER: Spud & Surface & Production Casings ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spud well on 9/7/11. Drilled 12-1/4" hole to 366'. Landed 8-5/8" 24# J-55 csg @ 350'. Cmted lead w/300 sx (402 cf) "C" cmt w/2% CaCl2 & 1/4#/sx cello-flake. Tailed w/200 sx (264 cf) "C" cmt w/2% CaCl2. Circ 136 sx cmt to pit. On 9/8/11, PT 8-5/8" csg to 600 psi for 30 min - OK.

Drilled 7-7/8" hole to TD5093' on 9/13/11. Ran open hole logs. Landed 5-1/2" 17# J-55 csg @ 5076'. Cmted lead w/550 sx (1150 cf) 35/65 poz "C" cmt w/0.125#/sx cello-flake & 5% salt. Tailed w/650 sx (865 cf) "C" cmt w/0.125#/sx cello-flake, 2% CaCl2, Circ 264 sx cmt to pit. Released drilling rig on 9/15/11. Plan to pressure test the 5-1/2" csg before completion operations.

Spud Date: 9/7/11

Drilling Rig Release Date: 9/15/11

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 9/16/11

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573
For State Use Only

APPROVED BY: David Gray TITLE Field Supervisor DATE 10-4-11
Conditions of Approval (if any):

