

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-39429
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☐ FEE ☒
2. Name of Operator LIME ROCK RESOURCES II-A, L.P.		6. State Oil & Gas Lease No.
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401		7. Lease Name or Unit Agreement Name WALDROP 13 P FEE
4. Well Location Unit Letter <u>P</u> : <u>990</u> feet from the <u>SOUTH</u> line and <u>330</u> feet from the <u>EAST</u> line Section <u>13</u> Township <u>18-S</u> Range <u>26-E</u> NMPM Eddy County		8. Well Number #1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3291' GL		9. OGRID Number 277558
		10. Pool name or Wildcat Red Lake: Glorieta-Yeso NE (96836)

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: Completion ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/2/12: MIRUSU. CO to new PBTD 4262'. Set CIBP @ 4256'. On 3/7/12, PT 5-1/2" csg to 4000 psi for 30 min-OK. Perfed Yeso @ 3920', 25', 30', 35', 40', 45', 50', 55', 60', 65', 70', 75', 80', 85', 90', 95', 4000', 05', 10', 15', 19', 23', 29', 35', 40', 45', 50', 55', 60', 65', 70', 75', 80', 95', 4105', 11', 15', 22', 28', 34', 38', 45', 50', 57', 62', 67', 82', 92', 99', 4205', 14', 19', 22', 26' w/1-0.41" spf. Total 54 holes. Treated w/3000 gal 7.5% HCL acid & 81 perf balls. On 3/8/12, fraced Yeso w/71,604# 16/30 Brady & 26,408# 16/30 siber prop sand in X-linked gel.
CO to PBTD4256'. On 3/12/12, landed 2-7/8" 6.5# J-55 tbg @ 3851'. Ran pump & rods. Released completion rig on 3/13/12.

Spudded well on: 1/25/12

Drilling Rig Released on: 2/6/12

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Pippin TITLE Petroleum Engineer - Agent DATE 3/14/12

Type or print name Mike Pippin E-mail address: mike@pippinllc.com PHONE: 505-327-4573
For State Use Only

APPROVED BY: T. C. Shapard TITLE Geologist DATE 3/19/2012
Conditions of Approval (if any):

