

Elk Wallow 11 State #5

API# 30-015-38388
Sec 11, T25S, R29E
1600' FSL & 1000' FEL
Eddy County, NM



SPUD TD
DRILLING 4/27/2011 5/8/2011
LAST REVISED 8/8/2011 KKC
WI 100.00% NRI

GL 3,111'		KB 3,141'		Hole	AFE #																								
13-3/8" 54.5# J55 STC	710'	17-1/2"	TOC at Surface.																										
9-5/8" 40# J55 LTC	3,172' 3,200'	12-1/4"	TOC at Surface.																										
	3,350'		TOC from CBL/GR/CCL on 5/28/2011.																										
	3,642'		3-1/2" 9.3# J55 8RD EUE IPC Inj. Tbg with 7" Inj Packer @ 3,642'. EOT @ 3,653' Injection Interval - 3,700'-4,080'. (310', 4 spf, 1240 holes) (3,700'-3,785'; 3,795'-3,820'; 3,845'-3,875'; 3,890'-3,925'; 3,930'-4,040'; 4,055'-4,080')																										
	4,855' 4,890'		Injection Interval - 4,150'-4,350'. (125', 4 spf, 500 holes) (4,150'-4,175'; 4,235'-4,305'; 4,320'-4,350') Injection Interval - 4,430'-4,590'. (130', 4 spf, 520 holes) (4,430'-4,445'; 4,455'-4,480'; 4,490'-4,530'; 4,540'-4,590')																										
	6,465' 6,500'		35' Class H Bailed cmt plug 7" CIBP @ 4,890'																										
			35' Class H Bailed cmt plug 7" CIBP @ 6,500'																										
PBTD 7" 26# HC L80 LTC	7,992' 8,086'	8-3/4"																											
				<table><tr><th>Tubular Dimensions</th><th>Burst</th><th>Collapse</th><th>ID</th><th>Drift</th><th>bbl/ft</th></tr><tr><td>13-3/8" 54.5# J55</td><td>2730</td><td>1130</td><td>12.615</td><td>12.459</td><td>0.1545</td></tr><tr><td>9-5/8" 40# J55</td><td>3950</td><td>2570</td><td>8.835</td><td>8.679</td><td>0.0758</td></tr><tr><td>7" 26# HC L80</td><td>7240</td><td>7800</td><td>6.276</td><td>6.151</td><td>0.0382</td></tr></table>	Tubular Dimensions	Burst	Collapse	ID	Drift	bbl/ft	13-3/8" 54.5# J55	2730	1130	12.615	12.459	0.1545	9-5/8" 40# J55	3950	2570	8.835	8.679	0.0758	7" 26# HC L80	7240	7800	6.276	6.151	0.0382	
Tubular Dimensions	Burst	Collapse	ID	Drift	bbl/ft																								
13-3/8" 54.5# J55	2730	1130	12.615	12.459	0.1545																								
9-5/8" 40# J55	3950	2570	8.835	8.679	0.0758																								
7" 26# HC L80	7240	7800	6.276	6.151	0.0382																								