

Submit 1 Copy To Appropriate District  
Office  
District I  
1625 N. French Dr , Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd , Aztec, NM 87410  
District IV  
1220 S St Francis Dr , Santa Fe, NM  
87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
October 13, 2009

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-39833
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. B-7717-13
7. Lease Name or Unit Agreement Name Zircon 1 State
8. Well Number 2H
9. OGRID Number 14744
10. Pool name or Wildcat Turkey Track; Bone Spring 60660

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  
PROPOSALS)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator  
Mewbourne Oil Company

3. Address of Operator  
PO Box 5270, Hobbs, NM 88241

4. Well Location

Unit Letter A : 750' feet from the North line and 330' feet from the East line  
Section 1 Township 19S Range 29E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR. etc.)  
3428' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS ☐ P AND A ☐  
CASING/CEMENT JOB ☒


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

03/13/12...TD'd 8 3/4" hole @ 8435'. Ran 8435' 7" 26# P110 LT & C & BT&C Csg. Cemented with 800 sks BJ Lite Class H (35:65:5) with additives. Mixed @ 12.5 /g w/ 2.07 yd. Tail with 400 sks Class H w/additives. Mixed @ 15.6 #/g w/ 1.19 yd. Plug down @ 7:15 PM 03/12/12. Circ 84 sks of cmt to the pit. Set wellhead slips w/140k#. Tested csg spool pack-off to 2500#. Dilled out with 6 1/8" bit.

Spud Date: 02/20/2012

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 03/19/12

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: JD Wade TITLE Dir. H. Spawor DATE 03/30/2012

Conditions of Approval (if any):