Submit 3 Copies To Appropriate District Office	State of New Mexico		Form C-103
District 1	Energy, Minerals and Natural Resources		June 19, 2008 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 District II	OIL CONSERVATION DIVISION		0-015-40028
1301 W Grand Ave., Artesia, NM 88210 District III	1220 South St. Francis Dr.		. Indicate Type of Lease
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, NM 87505		STATE S FEE
1220 S. St Francis Dr., Santa Fe, NM			
87505 SUNDRY NOTICES AND REPORTS ON WELLS			. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)			ANTHONEY STATE
1. Type of Well: Oil Well Gas Well Other			3. Well Number #4
2. Name of Operator			O. OGRID Number 281994
LRE OPERATING, LLC 3. Address of Operator		1	0. Pool name or Wildcat
c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401		l l	Red Lake, Glorieta-Yeso NE (96836)
4. Well Location			
Unit Letter P: 540 feet from the SOUTH line and 837 feet from the EAST line			
Section 30 Township 17-S Range 28-E NMPM Eddy County			
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3643' GL			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WOR			☐ ALTERING CASING ☐
TEMPORARILY ABANDON DULL OR ALTER CASING			
DOWNHOLE COMMINGLE	MOLTIFLE COMPL	CASING/CEWENT 3	OB 🔼
_	····		
OTHER:	leted operations (Clearly state all r		Casings ive pertinent dates including estimated date
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.			
Spud well on 5/13/12. Drilled 12-1/4" hole to 479'. Landed 8-5/8" 24# J-55 csg @ 479'. Cmted w/300 sx (405 cf) "C" cmt w/2% Cacl2 & 0.25# CF. Circ 83 sx cmt to surface. On 5/14/12, PT 8-5/8" csg to 1000 psi for 30 min-OK.			
Drilled 7-7/8" hole from 8-5/8" csg shoe to MD4865' on 5/25/12. Ran open hole logs. On 5/26/12, landed 5-1/2" 17# J-55 csg @			
MD4865'. Cmted lead w/350 sx (665 cf) 35/65 poz "C" cmt w/1/8#/sx CF, 5% salt, 5# LCM-1 & 0.3% R-3. Tailed w/600 sx (798 cf)			
"C" cmt w/0.125#/sx CF, 0.06% R-3. Circ 86 sx cmt to pit. Released drilling rig on 5/26/12. Plan to pressure test the 5-1/2" csg before completion operations.			
Bottom Hole Location is 977' FSL & 939' FEL Sec.30 T17S R28E			
Spud Date: 5/13/12	Drilling	g Rig Release Date:	5/26/12
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE Mike typeix TITLE Petroleum Engineer - Agent DATE 5/27/12			
Type or print name Mike Pippin	E-mail address:	mike@pippinllc.c	com PHONE: 505-327-4573
For State Use Only	0 /	7 /	/ /
APPROVED BY: 1. WASAU TITLE 6600X/51 DATE 6/5/2017			
Conditions of Approval (if any):	TILE OF	1/1/2011	DATEDATE
11	•	V	/ '