

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-39147
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. VO-0228
7. Lease Name or Unit Agreement Name Gopher BRG State
8. Well Number 1
9. OGRID Number 025575
10. Pool name or Wildcat Empire; Glorieta-Yeso

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS)	
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐	
2. Name of Operator Yates Petroleum Corporation	
3. Address of Operator 105 South Fourth Street, Artesia, NM 88210	
4. Well Location Unit Letter <u>L</u> : <u>1850</u> feet from the <u>South</u> line and <u>330</u> feet from the <u>West</u> line Section <u>13</u> Township <u>17S</u> Range <u>28E</u> NMPM <u>Eddy</u> County	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3643'GR	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: Surface and production casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/9/12 - Resumed drilling at 12:00 AM. TD 14-3/4" hole to 300'. Set 9-5/8" 36# K-55 ST&C casing at 300'. Cemented with 322 sx Class "C" + 2% CaCl (yld 1.34, wt 14.8). Tested casing to 1500 psi, held good. WOC 28 hrs. Reduced hole to 7-7/8" and resumed drilling.


7/17/12 - Reached TD 7-7/8" hole to 5195' at 8:30 AM. Set 5-1/2" 15.5# J-55 LT&C casing at 5195'. Float collar at 5154'. Cemented with 700 sx 35:65:6 Poz "C" + 6% PF020 + 0.125#/sx PF029 + 0.25#/sx PF046 + 0.2% PF013 + 5% PF044 (yld 1.48, wt 13). Tailed in with 400 sx PVL + 0.1% PF153 + 0.25#/sx PF046 + 5% PF174 + 0.5% PF606 + 0.2% PF013 + 1.3% PF044 (yld 2.03, wt 12.6). Circulated 94 bbls to surface.

Spud Date:

7/5/12

Rig Release Date:

7/19/12



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Tina Huerta TITLE Regulatory Reporting Supervisor DATE July 30, 2012

Type or print name Tina Huerta E-mail address: tinah@yatespetroleum.com PHONE: 575-748-4168

For State Use Only

APPROVED BY: RDade TITLE Dist. Rep. Supervisor DATE 8/3/12

Conditions of Approval (if any):