



A GYRO TECHNOLOGIES INC. COMPANY

P.O. Box 261021
Corpus Christi, Texas 78426
(361) 767-0602 • (800) 606-GYRO • Fax (361) 767-0612

30-015-39394

February 24, 2012

Devon Energy Production Company
20 North Broadway
Oklahoma City, OK 73102

Attn: Mark Cooper

Re: **Rigel 20 Fed Com 2H**

Please find enclosed a copy of the survey from 0' to 8,234.77' ran on the above referenced well.


If I can be of any further service, please do not hesitate to call me at 800-606-4976.

Sincerely,

Keith Havelka
Operations

STATE OF TEXAS §
COUNTY OF NUECES §

This instrument was acknowledged before me on the 29th day of February, A.D., 2012, by Keith Havelka.



Laura Ballew
Laura Ballew
Notary Public, State of Texas



Company: Devon Energy
Lease/Well: Rigel 20 Fed Com/2H
Location: S20 T19S R31E
Rig Name: McVay 10
State/County: New Mexico/Eddy
Latitude: 32.65
GRID North is 0.23 Degrees East of True North
VS-Azi: 0.00 Degrees



RKB : 20 Feet

DRILLOG MS GYRO SURVEY CALCULATIONS

Filename: rigel20fedcom-01_ed.ut

Minimum Curvature Method

Report Date/Time: 2/24/2012 / 15:07

Vaughn Energy Services

Gardendale, Texas

817-741-3610

Surveyor: Ray Seago

Rigel 20 Fed Com 2H / API 30-015-39394


Measured Depth FT	Incl Angle Deg	Drift Direction Deg	TVD FT	+N/-S FT	+E/-W FT	Vertical Section FT	Closure Distance FT	Closure Direction Deg	Dogleg Severity Deg/100
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	****
178.29	0.38	84.61	178.29	0.05	0.58	0.05	0.58	84.61	0.21
271.97	0.50	88.24	271.97	0.10	1.29	0.10	1.30	85.75	0.13
365.65	0.52	79.29	365.64	0.19	2.11	0.19	2.12	84.94	0.09
459.33	1.17	72.93	459.31	0.55	3.45	0.55	3.49	80.98	0.71
553.01	1.95	81.37	552.96	1.07	5.94	1.07	6.04	79.81	0.87
646.69	2.41	80.71	646.57	1.63	9.46	1.63	9.60	80.25	0.49
740.37	2.04	80.04	740.18	2.23	13.04	2.23	13.23	80.29	0.40
834.05	1.65	76.19	833.81	2.84	15.99	2.84	16.24	79.93	0.44
927.73	1.83	60.88	927.45	3.89	18.60	3.89	19.01	78.19	0.53
1021.41	1.70	52.40	1021.08	5.47	21.01	5.47	21.71	75.42	0.31
1115.09	1.78	32.74	1114.72	7.54	22.90	7.54	24.11	71.78	0.64
1208.77	1.87	32.04	1208.35	10.06	24.50	10.06	26.49	67.67	0.10
1302.45	1.87	27.65	1301.98	12.72	26.03	12.72	28.97	63.96	0.15
1396.13	1.95	40.22	1395.61	15.29	27.77	15.29	31.70	61.16	0.45
1489.81	3.25	38.70	1489.19	18.59	30.46	18.59	35.68	58.61	1.38
1583.49	3.01	44.21	1582.73	22.42	33.83	22.42	40.59	56.47	0.41
1677.17	3.29	52.01	1676.27	25.84	37.67	25.84	45.68	55.55	0.55
1770.85	3.74	54.01	1769.77	29.29	42.26	29.29	51.42	55.28	0.49

measured Depth FT	Angle Deg	Direction Deg	TVD FT	+N/-S FT	+E/-W FT	Section FT	Distance FT	Direction Deg	Severity Deg/100
1864.53	3.70	65.32	1863.26	32.35	47.48	32.35	57.45	55.73	0.78
1958.21	3.71	77.76	1956.74	34.25	53.18	34.25	63.26	57.22	0.86
2051.89	2.90	71.13	2050.27	35.66	58.38	35.66	68.41	58.59	0.96
2145.57	2.22	81.19	2143.85	36.70	62.42	36.70	72.41	59.54	0.86
2239.25	1.85	84.69	2237.48	37.12	65.72	37.12	75.48	60.54	0.41
2332.93	1.79	77.17	2331.11	37.58	68.66	37.58	78.27	61.30	0.26
2426.61	1.52	49.42	2424.75	38.72	71.03	38.72	80.90	61.40	0.89
2520.29	1.45	68.55	2518.40	39.96	73.08	39.96	83.30	61.33	0.53
2613.97	1.49	87.77	2612.05	40.45	75.41	40.45	85.57	61.79	0.53
2707.65	1.80	90.17	2705.69	40.49	78.10	40.49	87.97	62.60	0.33
2801.33	1.84	87.70	2799.32	40.55	81.06	40.55	90.64	63.43	0.09
2895.01	1.73	93.32	2892.96	40.52	83.98	40.52	93.24	64.24	0.22
2988.69	2.02	108.11	2986.59	39.93	86.95	39.93	95.68	65.34	0.60
3082.37	2.05	98.54	3080.21	39.17	90.18	39.17	98.32	66.52	0.36
3176.05	2.09	113.86	3173.83	38.23	93.39	38.23	100.91	67.74	0.59
3269.73	2.03	123.62	3267.45	36.62	96.33	36.62	103.06	69.19	0.38
3363.41	1.72	113.54	3361.08	35.14	99.00	35.14	105.05	70.46	0.48
3457.09	1.49	120.88	3454.72	33.95	101.34	33.95	106.87	71.48	0.33
3550.77	1.21	112.22	3548.38	32.95	103.30	32.95	108.43	72.31	0.37
3644.45	0.67	104.57	3642.04	32.44	104.74	32.44	109.65	72.79	0.60
3738.13	1.11	115.40	3735.71	31.92	106.09	31.92	110.79	73.26	0.50
3831.81	1.06	128.02	3829.38	31.00	107.59	31.00	111.96	73.93	0.26
3925.49	1.09	117.13	3923.04	30.06	109.06	30.06	113.13	74.59	0.22
4019.17	0.92	161.28	4016.71	28.93	110.10	28.93	113.84	75.28	0.83
4112.85	0.64	153.32	4110.38	27.75	110.58	27.75	114.01	75.91	0.33
4206.53	0.60	174.87	4204.05	26.80	110.85	26.80	114.05	76.41	0.25
4300.21	0.48	163.81	4297.73	25.93	111.01	25.93	114.00	76.85	0.17
4393.89	0.53	184.26	4391.40	25.12	111.08	25.12	113.89	77.26	0.20
4487.57	0.57	149.56	4485.08	24.28	111.29	24.28	113.91	77.69	0.35
4581.25	0.74	131.51	4578.75	23.48	111.98	23.48	114.42	78.16	0.28
4674.93	0.53	159.83	4672.43	22.67	112.58	22.67	114.84	78.61	0.40
4768.61	0.42	156.16	4766.10	21.95	112.87	21.95	114.99	78.99	0.12
4862.29	0.55	178.30	4859.78	21.19	113.02	21.19	114.99	79.38	0.24
4955.97	0.32	157.30	4953.46	20.50	113.14	20.50	114.98	79.73	0.30
5049.65	0.17	122.04	5047.14	20.18	113.35	20.18	115.14	79.90	0.22
5143.33	0.34	101.02	5140.82	20.06	113.74	20.06	115.50	80.00	0.21
5237.01	0.66	90.55	5234.49	20.00	114.56	20.00	116.29	80.10	0.36
5330.69	1.46	71.04	5328.16	20.38	116.23	20.38	118.01	80.05	0.93
5424.37	1.23	47.27	5421.81	21.46	118.11	21.46	120.04	79.70	0.64

Depth FT	Angle Deg	Direction Deg	TVD FT	+N/-S FT	+E/-W FT	Section FT	Distance FT	Direction Deg	Severity Deg/100
5518.05	1.36	29.77	5515.47	23.11	119.40	23.11	121.62	79.05	0.44
5611.73	1.60	22.69	5609.12	25.28	120.46	25.28	123.08	78.15	0.32
5705.41	1.57	6.14	5702.76	27.76	121.10	27.76	124.24	77.09	0.49
5799.09	1.36	7.86	5796.41	30.13	121.39	30.13	125.07	76.06	0.22
5892.77	1.38	356.28	5890.06	32.36	121.46	32.36	125.70	75.08	0.30
5986.45	1.12	343.20	5983.72	34.36	121.13	34.36	125.91	74.16	0.41
6080.13	1.19	357.03	6077.38	36.21	120.81	36.21	126.12	73.31	0.31
6173.81	0.72	351.87	6171.05	37.77	120.68	37.77	126.45	72.62	0.51
6267.49	0.39	350.55	6264.73	38.67	120.54	38.67	126.59	72.21	0.36
6361.17	0.32	338.48	6358.40	39.23	120.39	39.23	126.62	71.95	0.11
6454.85	0.27	196.18	6452.08	39.26	120.23	39.26	126.48	71.92	0.60
6548.53	0.54	244.44	6545.76	38.86	119.77	38.86	125.92	72.03	0.44
6642.21	0.63	257.92	6639.44	38.56	118.88	38.56	124.97	72.03	0.17
6735.89	0.86	284.19	6733.11	38.62	117.69	38.62	123.87	71.83	0.43
6829.57	1.08	269.44	6826.77	38.79	116.13	38.79	122.43	71.53	0.36
6923.25	1.19	256.17	6920.44	38.55	114.30	38.55	120.63	71.36	0.30
7016.93	1.01	262.11	7014.10	38.20	112.54	38.20	118.85	71.25	0.23
7110.61	0.70	272.23	7107.77	38.11	111.15	38.11	117.50	71.07	0.36
7204.29	0.42	288.77	7201.44	38.24	110.26	38.24	116.70	70.87	0.35
7297.97	0.59	281.45	7295.12	38.45	109.46	38.45	116.02	70.65	0.20
7391.65	0.82	268.20	7388.79	38.52	108.31	38.52	114.96	70.42	0.30
7485.33	0.61	242.44	7482.47	38.27	107.20	38.27	113.83	70.35	0.40
7579.01	1.20	251.97	7576.13	37.74	105.83	37.74	112.35	70.37	0.64
7672.69	1.45	247.03	7669.79	36.97	103.81	36.97	110.20	70.40	0.29
7766.37	1.47	257.65	7763.44	36.26	101.55	36.26	107.83	70.35	0.29
7860.05	0.44	245.78	7857.11	35.85	100.05	35.85	106.28	70.29	1.11
7953.73	0.31	229.47	7950.78	35.54	99.53	35.54	105.68	70.35	0.18
8047.41	0.29	268.08	8044.46	35.37	99.09	35.37	105.21	70.36	0.21
8141.09	0.22	268.50	8138.14	35.35	98.67	35.35	104.82	70.29	0.08
8234.77	0.10	269.80	8231.82	35.35	98.41	35.35	104.57	70.24	0.12



Vaughn Energy Services
Gardendale, Texas
817-741-3610
Surveyor: Ray Seago
Rigel 20 Fed Com 2H / API 30-015-39394



VES Survey Date: 02/18/2012

Pathfinder

6213 WGB 112
Midland, Texas 79706
Tel: (432) 687-1647
Fax: (432) 687-1544



March 26, 2012

Devon Energy
20 N. Broadway
Oklahoma City, OK

RE: Devon Energy
Rigel 20 Fed Com #2H
API: 30-015-39394
Eddy County, NM
RIG: MCVAY 10
FIELD: Hackberry; Bone Spring, NW
PES FILE NO.: 700005143-WT-WT

To whom it may concern:

We hereby certify that the enclosed Original Field Survey Data contained in this report represents to the best of our knowledge, a true and accurate survey of the well at the time the survey was run.

DIRECTIONAL SURVEY DATA
1 – Original survey report
2 – Survey report copies

We appreciate the opportunity to work with you and we look forward to your business support. If you have any questions, I can be reached at (432) 687-1647

Sincerely,

A handwritten signature in black ink, appearing to read "Steve Bibb".

STEVE BIBB
M/LWD Service Coordinator
PathFinder Energy Services

ML:sh



A Schlumberger Company

DIRECTIONAL SURVEY REPORT

DEVON ENERGY

RIGEL 20 FED COM #2H

EDDY COUNTY, NEW MEXICO

PREPARED BY: STEVE BIBB

Pathfinder

6213 WCR 112
Midland, Texas 79706
Tel (432)687-1647
Fax (432)687-1544




DIRECTIONAL SURVEY COMPANY REPORT:

1. NAME OF SURVEYING COMPANY: PATHFINDER ENERGY SERVICES
2. NAME OF PERSON(S) PERFORMING SURVEY:
A) GEORGE SAKAS
3. POSITION OF SAID PERSON(S): (A-F) SURVEYORS (FIELD ENGINEERS)
4. DATE(S) ON WHICH SURVEY WAS PERFORMED: 02-19-12 TO 02-28-12
5. STATE IN WHICH SURVEY WAS PERFORMED: NEW MEXICO
6. LOCATION OF WELL: EDDY COUNTY
7. TYPE OF SURVEY(S) PERFORMED: GAMMA-RAY
8. COMPLETE IDENTIFICATION OF WELL:

DEVON ENERGY
RIGEL 20 FEDERAL COM #2H
EDDY COUNTY, NM
RIG: MCVAY 10

9. SURVEY CERTIFIED FROM: 8278 TO 13032 FEET MEASURED DEPTH.

THIS IS TO VERIFY THAT ATTACHED DOCUMENTS SHOWING THE WELL TO BE DISPLACED AT 4602.65 FEET ON A BEARING OF 89.43 DEGREES FROM THE CENTER OF THE ROTARY TABLE AT A PROJECTED BIT DEPTH OF 13117 FEET, ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE.



STEVE BIBB
M/LWD SERVICE COORDINATOR

PathFinder Energy Services, Inc.

BHL Report

Page 01/01
Tie-in Date: 02/18/2012
Date Completed: 02/28/2012

DEVON ENERGY
RIGEL 20 FEDERAL COM #2H
EDDY COUNTY, NM
Rig:MCVAY 10
PathFinder Office Supervisor: STEVE BIBB
PathFinder Field Engineers:G.SAKAS
S.CARRILLO

Survey Horiz. Reference:WELLHEAD
Ref Coordinates: LAT:32.38.52.9225 N LON:103.53.56.2007 W
GRID Reference:NAD83 new mexico east Transverse Mercator
Ref GRID Coord: X: 675037.6700 Y: 599759.1400
North Aligned To:GRID NORTH
Total Magnetic Correction: 7.46° EAST TO GRID
Vertical Section Plane: 89.68
Survey Vert. Reference: 20.00' Kelly Bushing To Ground
Altitude:3413.30' Ground To MSL

Measured Depth	13117.00	(feet)
Inclination	91.19	(deg)
Azimuth	87.56	(deg)
True Vertical Depth	8898.73	(feet)
Vertical Section	4602.60	(feet)
Survey X cord	679640.07	(feet)
Survey Y cord	599805.28	(feet)
Survey Lat	32.64810821 N	(deg)
Survey Lon	103.88399131 W	(deg)
Rectangular Corr. N/S	46.16 N	(feet)
Rectangular Corr. E/W	4602.42 E	(feet)
Closure Distance	4602.65	(feet)
Direction of Closure	89.43	(deg)
Dogleg Severity	0.00	(deg/100ft)

PathFinder Energy Services, Inc.

Survey Report

DEVON ENERGY
RIGEL 20 FEDERAL COM #2H
EDDY COUNTY, NM
Rig:MCVAY 10
PathFinder Office Supervisor: STEVE BIBB
PathFinder Field Engineers: G.SAKAS
S.CARRILLO

Page 01/03
Tie-in Date: 02/18/2012
Date Completed: 02/28/2012

Survey Horiz. Reference:WELLHEAD
Ref Coordinates: LAT:32.38.52.9225 N LON:103.53.56.2007 W
GRID Reference:NAD83 new mexico east Transverse Mercator
Ref GRID Coord: X: 675037.6700 Y: 599759.1400
North Aligned To:GRID NORTH
Total Magnetic Correction: 7.46° EAST TO GRID
Vertical Section Plane: 89.68
Survey Vert. Reference: 20.00' Kelly Bushing To Ground
Altitude:3413.30' Ground To MSL

Survey Calculations by RX5 V6.03E using Minimum Curvature

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
TIED INTO MULTI SHOT GYRO SURVEY @ 8234.77'MD.										
8234.77	0.10	269.80	8231.82	0.00	98.61	35.35 N	98.41 E	104.57@	70.24	0.00
THE FOLLOWING ARE PATHFINDER MWD SURVEYS.										
8278.00	1.06	128.03	8275.05	43.23	98.88	35.10 N	98.69 E	104.74@	70.42	2.64
8310.00	3.87	98.79	8307.02	32.00	100.18	34.76 N	99.99 E	105.86@	70.83	9.34
8342.00	7.30	94.77	8338.86	32.00	103.27	34.42 N	103.08 E	108.68@	71.53	10.78
8374.00	10.55	91.56	8370.47	32.00	108.23	34.17 N	108.04 E	113.31@	72.45	10.27
8405.00	13.54	88.24	8400.78	31.00	114.69	34.21 N	114.50 E	119.50@	73.37	9.90
8437.00	15.83	85.89	8431.74	32.00	122.79	34.64 N	122.60 E	127.40@	74.23	7.39
8469.00	18.73	85.75	8462.29	32.00	132.28	35.33 N	132.08 E	136.72@	75.03	9.06
8501.00	22.34	87.07	8492.25	32.00	143.48	36.02 N	143.28 E	147.74@	75.89	11.37
8533.00	26.03	88.45	8521.44	32.00	156.58	36.52 N	156.38 E	160.59@	76.85	11.67
8564.00	29.37	89.30	8548.88	31.00	170.99	36.80 N	170.78 E	174.70@	77.84	10.85
8596.00	33.06	88.58	8576.24	32.00	187.57	37.11 N	187.36 E	191.00@	78.80	11.59
8628.00	35.61	88.62	8602.66	32.00	205.61	37.55 N	205.40 E	208.81@	79.64	7.97
8660.00	38.78	89.14	8628.15	32.00	224.95	37.93 N	224.74 E	227.92@	80.42	9.95
8691.00	41.59	89.55	8651.83	31.00	244.95	38.15 N	244.74 E	247.70@	81.14	9.10
8723.00	43.79	90.03	8675.35	32.00	266.65	38.23 N	266.44 E	269.17@	81.83	6.95
8755.00	45.55	90.80	8698.11	32.00	289.14	38.07 N	288.93 E	291.43@	82.49	5.75
8786.00	48.10	91.26	8719.32	31.00	311.74	37.66 N	311.54 E	313.80@	83.11	8.30
8818.00	50.47	91.46	8740.19	32.00	335.98	37.08 N	335.78 E	337.82@	83.70	7.42
8850.00	53.38	91.80	8759.92	32.00	361.16	36.36 N	360.96 E	362.79@	84.25	9.13
8882.00	56.98	93.25	8778.19	32.00	387.39	35.20 N	387.20 E	388.79@	84.81	11.85
8914.00	60.50	94.04	8794.80	32.00	414.67	33.46 N	414.49 E	415.84@	85.39	11.20
8945.00	63.66	93.42	8809.31	31.00	441.99	31.68 N	441.82 E	442.96@	85.90	10.35
8977.00	67.36	93.17	8822.57	32.00	471.05	30.00 N	470.89 E	471.85@	86.35	11.58

PathFinder Energy Services, Inc.

Survey Report

DEVON ENERGY
RIGEL 20 FEDERAL COM #2H
EDDY COUNTY, NM
RIG:MCVAY 10

Page 02/03

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
9009.00	70.26	92.50	8834.14	32.00	500.84	28.53 N	500.69 E	501.50@	86.74	9.27
9041.00	72.98	92.58	8844.23	32.00	531.16	27.18 N	531.02 E	531.72@	87.07	8.50
9072.00	76.68	91.80	8852.34	31.00	561.05	26.04 N	560.91 E	561.52@	87.34	12.18
9104.00	79.84	92.33	8858.85	32.00	592.35	24.91 N	592.22 E	592.74@	87.59	10.01
9136.00	82.04	92.06	8863.89	32.00	623.92	23.70 N	623.80 E	624.25@	87.82	6.93
9168.00	85.30	91.48	8867.41	32.00	655.70	22.72 N	655.58 E	655.97@	88.01	10.35
9199.00	87.23	91.89	8869.43	31.00	686.61	21.81 N	686.50 E	686.85@	88.18	6.36
9231.00	89.69	91.23	8870.29	32.00	718.58	20.94 N	718.47 E	718.78@	88.33	7.96
9327.00	92.07	90.94	8868.82	96.00	814.53	19.12 N	814.44 E	814.66@	88.65	2.50
9422.00	91.98	88.38	8865.46	95.00	909.47	19.69 N	909.37 E	909.58@	88.76	2.69
9517.00	91.63	87.69	8862.47	95.00	1004.38	22.94 N	1004.27 E	1004.53@	88.69	0.81
9613.00	90.84	88.85	8860.40	96.00	1100.32	25.84 N	1100.20 E	1100.50@	88.65	1.46
9707.00	89.52	88.37	8860.11	94.00	1194.31	28.12 N	1194.17 E	1194.50@	88.65	1.49
9803.00	87.85	88.77	8862.31	96.00	1290.26	30.52 N	1290.11 E	1290.47@	88.65	1.79
9899.00	89.16	87.81	8864.81	96.00	1386.19	33.38 N	1386.03 E	1386.43@	88.62	1.69
9994.00	88.90	87.56	8866.42	95.00	1481.12	37.22 N	1480.94 E	1481.41@	88.56	0.38
10089.00	88.29	88.84	8868.75	95.00	1576.06	40.20 N	1575.86 E	1576.37@	88.54	1.49
10185.00	87.49	88.63	8872.28	96.00	1671.98	42.32 N	1671.77 E	1672.31@	88.55	0.86
10280.00	86.88	90.29	8876.95	95.00	1766.86	43.21 N	1766.65 E	1767.18@	88.60	1.86
10375.00	87.49	90.61	8881.62	95.00	1861.74	42.47 N	1861.53 E	1862.01@	88.69	0.72
10471.00	88.46	90.02	8885.01	96.00	1957.67	41.94 N	1957.47 E	1957.92@	88.77	1.18
10566.00	87.93	90.65	8888.00	95.00	2052.62	41.38 N	2052.42 E	2052.84@	88.84	0.87
10661.00	88.90	90.27	8890.63	95.00	2147.57	40.62 N	2147.38 E	2147.76@	88.92	1.10
10757.00	87.41	91.83	8893.72	96.00	2243.49	38.86 N	2243.31 E	2243.64@	89.01	2.25
10852.00	88.64	91.08	8896.99	95.00	2338.38	36.45 N	2338.22 E	2338.50@	89.11	1.52
10948.00	89.69	90.62	8898.39	96.00	2434.35	35.03 N	2434.19 E	2434.45@	89.18	1.19
11043.00	90.84	90.20	8897.95	95.00	2529.34	34.35 N	2529.19 E	2529.42@	89.22	1.29
11137.00	90.40	89.88	8896.94	94.00	2623.33	34.28 N	2623.18 E	2623.41@	89.25	0.58

PathFinder Energy Services, Inc.

Survey Report

DEVON ENERGY
RIGEL 20 FEDERAL COM #2H
EDDY COUNTY, NM
RIG:MCVAY 10

Page 03/03

Measured Depth (ft)	Incl (deg)	Drift Dir. (deg)	TVD (ft)	Course Length (ft)	Vertical Section (ft)	TOTAL Rectangular Offsets (ft) (ft)		Closure Dist Dir (ft) (deg)		DLS (dg/100ft)
11230.00	90.04	91.10	8896.58	93.00	2716.32	33.49 N	2716.18 E	2716.38@	89.29	1.37
11322.00	91.45	90.53	8895.38	92.00	2808.29	32.18 N	2808.16 E	2808.34@	89.34	1.65
11416.00	89.52	90.90	8894.59	94.00	2902.27	31.01 N	2902.14 E	2902.31@	89.39	2.09
11510.00	89.16	90.81	8895.67	94.00	2996.24	29.61 N	2996.12 E	2996.27@	89.43	0.39
11603.00	90.13	90.88	8896.25	93.00	3089.22	28.23 N	3089.11 E	3089.24@	89.48	1.05
11719.00	90.40	90.81	8895.71	116.00	3205.20	26.52 N	3205.10 E	3205.21@	89.53	0.24
11813.00	87.85	90.61	8897.14	94.00	3299.16	25.36 N	3299.07 E	3299.17@	89.56	2.72
11907.00	88.02	90.57	8900.53	94.00	3393.09	24.39 N	3393.01 E	3393.09@	89.59	0.19
12001.00	88.20	90.40	8903.63	94.00	3487.03	23.60 N	3486.95 E	3487.03@	89.61	0.26
12096.00	88.11	90.00	8906.69	95.00	3581.98	23.26 N	3581.90 E	3581.98@	89.63	0.43
12191.00	89.25	89.76	8908.88	95.00	3676.95	23.46 N	3676.87 E	3676.95@	89.63	1.23
12284.00	89.16	89.23	8910.17	93.00	3769.94	24.28 N	3769.86 E	3769.94@	89.63	0.58
12378.00	89.78	88.63	8911.04	94.00	3863.93	26.04 N	3863.84 E	3863.93@	89.61	0.92
12471.00	90.84	89.22	8910.54	93.00	3956.91	27.78 N	3956.82 E	3956.92@	89.60	1.30
12565.00	90.92	88.98	8909.09	94.00	4050.90	29.26 N	4050.80 E	4050.90@	89.59	0.27
12659.00	91.01	89.02	8907.51	94.00	4144.88	30.90 N	4144.77 E	4144.88@	89.57	0.10
12752.00	91.10	88.48	8905.80	93.00	4237.85	32.93 N	4237.73 E	4237.86@	89.55	0.59
12845.00	91.10	88.08	8904.01	93.00	4330.80	35.72 N	4330.67 E	4330.82@	89.53	0.43
12938.00	91.01	88.00	8902.30	93.00	4423.75	38.90 N	4423.60 E	4423.77@	89.50	0.13
13032.00	91.19	87.56	8900.49	94.00	4517.68	42.54 N	4517.51 E	4517.71@	89.46	0.51
STRAIGHT LINE PROJECTION TO BIT @ 13117' MD.										
13117.00	91.19	87.56	8898.73	85.00	4602.60	46.16 N	4602.42 E	4602.65@	89.43	0.00



A Schlumberger Company

TIE-IN SURVEY INFORMATION SHEET**CLIENT INFORMATION**

CLIENT:	DEVON ENERGY		
LEASE / WELL No.:	RIGEL 20 FEDERAL COM	2H	
WELL LOCATION:	EDDY COUNTY		
COUNTY / STATE / COUNTRY:	EDDY COUNTY	NM	USA
RIG:	McVAY 10		
API WELL No:	30-015-39394		
JOB No:	700005143-WT-WT		
P.O. / AFE No.	158210		
DIRECTIONAL COMPANY:	PATHFINDER ENERGY SERVICES		

WELL SITE INFORMATION

TOTAL MAGNETIC CORRECTION (TMC):			
On Wall Plat:	7.459936	LWD Calculated:	7.451189
		Agreed Upon:	7.45
X =	675037 670000	Feet	Y = 599759.140000
			Feet
SITE LATITUDE:	32.648034	SITE LONGITUDE:	103.898945
GRID SYSTEM:	TRUE ☐ UTM ☒ LAMBERT ☐	ZONE: NEW MEXICO EAST NAD 83	
PROPOSED DRIFT DIRECTION:	89.68		
KELLY BUSHING ELEVATION:	20		
ALTITUDE:	3413.3	Feet	WATER DEPTH: N/A
			Feet

TIE-IN SURVEY

MEASURED DEPTH:	8234.77
DRIFT ANGLE:	0.1
DRIFT DIRECTION:	269.80
TRUE VERTICAL DEPTH:	8231.82
VERTICAL SECTION:	35.35
RECTANGULAR COORDINATE (N / S):	35.35
RECTANGULAR COORDINATE (E / W):	98.41
CLOSURE DISTANCE / DIRECTION:	
SURVEY CALCULATION METHOD:	AA ☐ MC ☒ RC ☐ BT ☐
SOURCE OF TIE-IN DATA (COMPANY):	VAUGHN ENERGY SERVICES
COPY OF TIE-IN SURVEY REPORT	☒ YES ☐ NO

WELL PLAN

KICKOFF DEPTH:	8291'	TOTAL DEPTH:	13357'
KICKOFF ANGLE:	0°	MAX ANGLE:	90

PES Engineers:

GEORGE SAKAS

**Signature of both field engineers required if applicable

SAUL CARRILLO

Directional Driller:

DATE: 18-Feb-2012



Company: Devon Energy
Lease/Well: Rigel 20 Fed Com/2H
Location: S20 T19S R31E
Rig Name: McVay 10
State/County: New Mexico/Eddy
Latitude: 32.65, Longitude: -103.90
GRID North is 0.23 Degrees East of True North
VS-Azi: 0.00 Degrees



FIELD COPY ONLY (NOT DEFINITIVE)

RKB : 20 feet

DRILLOG MS GYRO SURVEY CALCULATIONS

Filename: rigel20fedcom-01_ed.ut

Minimum Curvature Method

Report Date/Time: 2/19/2012 / 23:11

Vaughn Energy Services

Gardendale, Texas

817-741-3610

Ray Seago

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	TVD FT	+N/-S FT	+E/-W FT	Vertical Section FT	Closure Distance FT	Closure Direction Deg	Dogleg Severity Deg/100
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	****
178.29	0.38	84.61	178.29	0.05	0.58	0.05	0.58	84.61	0.21
271.97	0.50	88.24	271.97	0.10	1.29	0.10	1.30	85.75	0.13
365.65	0.52	79.29	365.64	0.19	2.11	0.19	2.12	84.94	0.09
459.33	1.17	72.93	459.31	0.55	3.45	0.55	3.49	80.98	0.71
553.01	1.95	81.37	552.96	1.07	5.94	1.07	6.04	79.81	0.87
646.69	2.41	80.71	646.57	1.63	9.46	1.63	9.60	80.25	0.49
740.37	2.04	80.04	740.18	2.23	13.04	2.23	13.23	80.29	0.40
834.05	1.65	76.19	833.81	2.84	15.99	2.84	16.24	79.93	0.44
927.73	1.83	60.88	927.45	3.89	18.60	3.89	19.01	78.19	0.53
1021.41	1.70	52.40	1021.08	5.47	21.01	5.47	21.71	75.42	0.31
1115.09	1.78	32.74	1114.72	7.54	22.90	7.54	24.11	71.78	0.64
1208.77	1.87	32.04	1208.35	10.06	24.50	10.06	26.49	67.67	0.10
1302.45	1.87	27.65	1301.98	12.72	26.03	12.72	28.97	63.96	0.15
1396.13	1.95	40.22	1395.61	15.29	27.77	15.29	31.70	61.16	0.45
1489.81	3.25	38.70	1489.19	18.59	30.46	18.59	35.68	58.61	1.38
1583.49	3.01	44.21	1582.73	22.42	33.83	22.42	40.59	56.47	0.41
1677.17	3.29	52.01	1676.27	25.84	37.67	25.84	45.68	55.55	0.55
1770.85	3.74	54.01	1769.77	29.29	42.26	29.29	51.42	55.28	0.49
1864.53	3.70	65.32	1863.26	32.35	47.48	32.35	57.45	55.73	0.78
1958.21	3.71	77.76	1956.74	34.25	53.18	34.25	63.26	57.22	0.86
2051.89	2.90	71.13	2050.27	35.66	58.38	35.66	68.41	58.59	0.96
2145.57	2.22	81.19	2143.85	36.70	62.42	36.70	72.41	59.54	0.86
2239.25	1.85	84.69	2237.48	37.12	65.72	37.12	75.48	60.54	0.41
2332.93	1.79	77.17	2331.11	37.58	68.66	37.58	78.27	61.30	0.26
2426.61	1.52	49.42	2424.75	38.72	71.03	38.72	80.90	61.40	0.89
2520.29	1.45	68.55	2518.40	39.96	73.08	39.96	83.30	61.33	0.53
2613.97	1.49	87.77	2612.05	40.45	75.41	40.45	85.57	61.79	0.53
2707.65	1.80	90.17	2705.69	40.49	78.10	40.49	87.97	62.60	0.33
2801.33	1.84	87.70	2799.32	40.55	81.06	40.55	90.64	63.43	0.09
2895.01	1.73	93.32	2892.96	40.52	83.98	40.52	93.24	64.24	0.22
2988.69	2.02	108.11	2986.59	39.93	86.95	39.93	95.68	65.34	0.60
3082.37	2.05	98.54	3080.21	39.17	90.18	39.17	98.32	66.52	0.36
3176.05	2.09	113.86	3173.83	38.23	93.39	38.23	100.91	67.74	0.59
3269.73	2.03	123.62	3267.45	36.62	96.33	36.62	103.06	69.19	0.38
3363.41	1.72	113.54	3361.08	35.14	99.00	35.14	105.05	70.46	0.48

Measured Depth FT	Incl Angle Deg	Drift Direction Deg	TVD FT	+N/-S FT	+E/-W FT	Vertical Section FT	Closure Distance FT	Closure Direction Deg	Dogleg Severity Deg/100
3457.09	1.49	120.88	3454.72	33.95	101.34	33.95	106.87	71.48	0.33
3550.77	1.21	112.22	3548.38	32.95	103.30	32.95	108.43	72.31	0.37
3644.45	0.67	104.57	3642.04	32.44	104.74	32.44	109.65	72.79	0.60
3738.13	1.11	115.40	3735.71	31.92	106.09	31.92	110.79	73.26	0.50
3831.81	1.06	128.02	3829.38	31.00	107.59	31.00	111.96	73.93	0.26
3925.49	1.09	117.13	3923.04	30.06	109.06	30.06	113.13	74.59	0.22
4019.17	0.92	161.28	4016.71	28.93	110.10	28.93	113.84	75.28	0.83
4112.85	0.64	153.32	4110.38	27.75	110.58	27.75	114.01	75.91	0.33
4206.53	0.60	174.87	4204.05	26.80	110.85	26.80	114.05	76.41	0.25
4300.21	0.48	163.81	4297.73	25.93	111.01	25.93	114.00	76.85	0.17
4393.89	0.53	184.26	4391.40	25.12	111.08	25.12	113.89	77.26	0.20
4487.57	0.57	149.56	4485.08	24.28	111.29	24.28	113.91	77.69	0.35
4581.25	0.74	131.51	4578.75	23.48	111.98	23.48	114.42	78.16	0.28
4674.93	0.53	159.83	4672.43	22.67	112.58	22.67	114.84	78.61	0.40
4768.61	0.42	156.16	4766.10	21.95	112.87	21.95	114.99	78.99	0.12
4862.29	0.55	178.30	4859.78	21.19	113.02	21.19	114.99	79.38	0.24
4955.97	0.32	157.30	4953.46	20.50	113.14	20.50	114.98	79.73	0.30
5049.65	0.17	122.04	5047.14	20.18	113.35	20.18	115.14	79.90	0.22
5143.33	0.34	101.02	5140.82	20.06	113.74	20.06	115.50	80.00	0.21
5237.01	0.66	90.55	5234.49	20.00	114.56	20.00	116.29	80.10	0.36
5330.69	1.46	71.04	5328.16	20.38	116.23	20.38	118.01	80.05	0.93
5424.37	1.23	47.27	5421.81	21.46	118.11	21.46	120.04	79.70	0.64
5518.05	1.36	29.77	5515.47	23.11	119.40	23.11	121.62	79.05	0.44
5611.73	1.60	22.69	5609.12	25.28	120.46	25.28	123.08	78.15	0.32
5705.41	1.57	6.14	5702.76	27.76	121.10	27.76	124.24	77.09	0.49
5799.09	1.36	7.86	5796.41	30.13	121.39	30.13	125.07	76.06	0.22
5892.77	1.38	356.28	5890.06	32.36	121.46	32.36	125.70	75.08	0.30
5986.45	1.12	343.20	5983.72	34.36	121.13	34.36	125.91	74.16	0.41
6080.13	1.19	357.03	6077.38	36.21	120.81	36.21	126.12	73.31	0.31
6173.81	0.72	351.87	6171.05	37.77	120.68	37.77	126.45	72.62	0.51
6267.49	0.39	350.55	6264.73	38.67	120.54	38.67	126.59	72.21	0.36
6361.17	0.32	338.48	6358.40	39.23	120.39	39.23	126.62	71.95	0.11
6454.85	0.27	196.18	6452.08	39.26	120.23	39.26	126.48	71.92	0.60
6548.53	0.54	244.44	6545.76	38.86	119.77	38.86	125.92	72.03	0.44
6642.21	0.63	257.92	6639.44	38.56	118.88	38.56	124.97	72.03	0.17
6735.89	0.86	284.19	6733.11	38.62	117.69	38.62	123.87	71.83	0.43
6829.57	1.08	269.44	6826.77	38.79	116.13	38.79	122.43	71.53	0.36
6923.25	1.19	256.17	6920.44	38.55	114.30	38.55	120.63	71.36	0.30
7016.93	1.01	262.11	7014.10	38.20	112.54	38.20	118.85	71.25	0.23
7110.61	0.70	272.23	7107.77	38.11	111.15	38.11	117.50	71.07	0.36
7204.29	0.42	288.77	7201.44	38.24	110.26	38.24	116.70	70.87	0.35
7297.97	0.59	281.45	7295.12	38.45	109.46	38.45	116.02	70.65	0.20
7391.65	0.82	268.20	7388.79	38.52	108.31	38.52	114.96	70.42	0.30
7485.33	0.61	242.44	7482.47	38.27	107.20	38.27	113.83	70.35	0.40
7579.01	1.20	251.97	7576.13	37.74	105.83	37.74	112.35	70.37	0.64
7672.69	1.45	247.03	7669.79	36.97	103.81	36.97	110.20	70.40	0.29
7766.37	1.47	257.65	7763.44	36.26	101.55	36.26	107.83	70.35	0.29
7860.05	0.44	245.78	7857.11	35.85	100.05	35.85	106.28	70.29	1.11
7953.73	0.31	229.47	7950.78	35.54	99.53	35.54	105.68	70.35	0.18
8047.41	0.29	268.08	8044.46	35.37	99.09	35.37	105.21	70.36	0.21
8141.09	0.22	268.50	8138.14	35.35	98.67	35.35	104.82	70.29	0.08
8234.77	0.10	269.80	8231.82	35.35	98.41	35.35	104.57	70.24	0.12

HORIZONTAL DISPLACEMENT IS
104.57 FEET AT 70.24 DEGREES

33
21
84
39
105.5



A Schlumberger Company

PathFinder Energy Services, Inc. Magnetic & Grid Calculations

Devon Energy
Rigel 20 Federal Com #2H
Eddy County, NM
Rig:McVay 10

Mon Jan 23 15:02:22 2012

Coordinates

Latitude: 32.648034 N (32 deg. 38 min. 52.9225 sec.)
Longitude: 103.898945 W (-103 deg. 53 min. 56.2007 sec.)
Elevation: 3433.30 feet.
Calculation Date: Jan/23/2012

20 -
3433.30
3413.3 hnd

Magnetic Calculations

Model: IGRF2010
Dip Angle: 60.5080 degrees
Total Magnetic Field: 0.48775 gauss
Magnetic Declination: 7.694282 degrees
Horizontal Intensity: 0.240119 gauss
To Convert a Magnetic Dir. to a TRUE North Dir. Add 7.694282 Degs

Transverse Mercator Grid Calculations NAD83

Grid System: Transverse Mercator: new mexico east
Ellipsoid: GRS80
X: 675037.6700 feet
Y: 599759.1400 feet
True to Grid: (convergence) -0.234346 degrees
Magnetic to Grid: 7.459936 degrees
To Convert a Magnetic Dir. to a GRID dir. Add 7.459936 Degs.

PathFinder Energy Services, Inc.

Magnetic & Grid Calculations

DEVON ENERGY
RIGEL 20 FEDERAL COM #2H
HACKBERRY

*Field
Calculation*

Sat Feb 18 17:06:20 2012

Coordinates

Latitude: 32.648034 N (32 deg. 38 min. 52.9225 sec.)
Longitude: 103.898945 W (-103 deg. 53 min. 56.2007 sec.)
Elevation: 3433.30 feet.
Calculation Date: Feb/18/2012

Magnetic Calculations

Model: IGRF2010
Dip Angle: 60.5063 degrees
Total Magnetic Field: 0.48768 gauss
Magnetic Declination: 7.685535 degrees
Horizontal Intensity: 0.240097 gauss
To Convert a Magnetic Dir. to a TRUE North Dir. Add 7.685535 Degr

Transverse Mercator Grid Calculations NAD83

Grid System: Transverse Mercator: new mexico east
Ellipsoid: GRS80
X: 675037.6700 feet
Y: 599759.1400 feet
True to Grid: (convergence) -0.234346 degrees
Magnetic to Grid: 7.451189 degrees
To Convert a Magnetic Dir. to a GRID dir. Add 7.451189 Degr.