

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD Artesia
Tresia

FORM APPROVED OMB NO 1004-0135 Expires July 31, 2010

Lease Serial No. NMNM048343

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
shandoned well. Hee form 2160-2 (APD) for such proposals

abandoned we	6 If Indian, Allottee	or Tribe Name				
SUBMIT IN TRI	PLICATE - Other instructio	ns on reverse side.	7 If Unit or CA/Agre	eement, Name and/or No		
I. Type of Well			8 Well Name and No			
Oil Well Gas Well Oth	ner		PIGLET 21 FEDI	ERAL 8		
2 Name of Operator OXY USA WTP LP	Contact JE E-Mail. JENNIFER_D	NNIFER A DUARTE UARTE@OXY COM	9 API Well No. 30-015-40669-	9 API Well No. 30-015-40669-00-X1		
3a. Address		b Phone No (include area code		r Exploratory		
HOUSTON, TX 77210		h. 713-513-6640	ARTESIA			
4. Location of Well (Footage, Sec., 7	, R, M, or Survey Description)		11. County or Parish,	and State		
Sec 21 T17S R28E NWNW 7	27FNL 462FWL		EDDY COUNT	Y, NM		
12. CHECK APPR	ROPRIATE BOX(ES) TO IN	NDICATE NATURE OF	NOTICE, REPORT, OR OTHE	ER DATA		
TYPE OF SUBMISSION	-	ТҮРЕ О	F ACTION			
Notice of Intent	☐ Acidize	Deepen	☐ Production (Start/Resume)	☐ Water Shut-Off		
-	☐ Alter Casing	Fracture Treat	Reclamation	☐ Well Integrity		
☐ Subsequent Report	Casing Repair	New Construction	Recomplete	Other Change to Original A		
☐ Final Abandonment Notice	Change Plans	Plug and Abandon	☐ Temporarily Abandon	Change to Original A PD		
	☐ Convert to Injection	□ Plug Back	☐ Water Disposal			
OXY USA WTP LIMITED PAR plans on the original APD Th 2012. Please see the attache further information, please fee RECEIVED NOV 0.7 2012	is was already approved by d documentation for your re-	Ed Fernandez via email o view If you have any que ne.	estions or need APPROT	2 2012 AND MANAGEMENT OFFICE		
14 I hereby certify that the foregoing is	true and correct		CAME			
	Electronic Submission #157 For OXY US	A WTP LP sent to the Car	ell Information System Isbad			
	itted to AFMSS for processing	by DEBORAH MCKINNEY	on 11/02/2012 (13DLM1482SE)			
Name (Printed/Typed) JENNIFER	R A DUARTE	Title REGUI	LATORY ANALYST	· · · · · · · · · · · · · · · · · · ·		
Signature (Electronic S	Submission)	Date 11/01/2	2012			
	THIS SPACE FOR	FEDERAL OR STATE	OFFICE USE			
Approved By EDWARD FERNAN	DEZ	TitlePETROLE	EUM ENGINEER	Date 11/02/2012		
Conditions of approval, if any, are attache certify that the applicant holds legal or equivalent would entitle the applicant to conduct the applicant the applicant the applicant the applicant to conduct the applicant	ntable title to those rights in the su	t warrant or bject lease Office Carlsba	nd			
Title 18 U.S.C Section 1001 and Title 43 States any false, fictitious or fraudulent	USC Section 1212, make it a critistatements or representations as to	me for any person knowingly an any matter within its jurisdiction	d willfully to make to any department on	or agency of the United		

OXY USA Inc Piglet 21 Federal 8 Sundry Information

OPERATOR NAME / NUMBER: OXY USA WTP LP

LEASE NAME / NUMBER: Piglet 21 Federal 8

STATE: NM COUNTY: Eddy

SURFACE LOCATION: 727' FNL & 462' FWL, **Sec** 21, T17S, **R**28E

C-102 PLAT APPROX GR ELEV: 3597'

EST KB ELEV: 3611' (14' KB)

1. SUMMARY OF CHANGES:

a. Based on historic wells drilled in this area, the surface and production cement volumes have been adjusted. This will allow us to cut down on the exceess cement having to be hauled off and exposed of.

b. We will only run the 100 sks of lead thixotropic cement if loses occur while driling the surface section.

2. CEMENT PROGRAM CHANGE:

Surface Interval

Interval	Amount sx	Ft of Fill	Туре	Gal/Sk	PPG	Ft ³ /sk	24 Hr Comp
Surface (TOC:	0' - 400')				•	•	
Lead: 0'-450' (165% Excess)	. 100	0' (Contingency Slurry if losses are present)	Premium Plus Cement: 10 lbm/sk Cal-Seal 60, 0.125 lbm/sk Poly-E-Flake, 10 lbm/sk Kol-Seal, I % Calcium Chloride - Flake	7.46	14.2	1.67	1290 psi
Tail: 0' - 450' (165% Excess)	300	450'	Premium Plus Cement: 1 % Calcium Chloride - Flake	6.36	14.8	1.34	1608 psi

Production Interval

Interval	Amount sx	Ft of Fill	Туре	Gal/Sk	PPG	Ft ³ /sk	24 Hr Comp
Production (To	OC: 0' - 5300')		•			
Lead: 0' - 3000' (120 % Excess)	600	3000'	Halliburton Light Premium Plus: 5% Salt, 3 lbm/sk Kol-Seal, 0.125 lb/sx Poly-E-Flake, 0.35% HR-800	9.69	12.9	1.87	660 psi
Tail: 3000' - 5300' (120 % Excess)	575	2300'	Premium Plus Cement: 0.5% Halad ®-344, 0.2% WellLife 734, 5 lbm/sk Microbond, 0.3% Econolite, 0.3% CFR-3	7.72	14.2	1.55	1914 psi