

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-24156
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. OG-784
7. Lease Name or Unit Agreement Name New Mexico Z State
8. Well Number 1
9. OGRID Number 013837
10. Pool name or Wildcat Millman; Yates-SR QN-GB-SA, East

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐ **RECEIVED**

2. Name of Operator
Mack Energy Corporation **MAY 18 2005**

3. Address of Operator
P. O. Box 960 Artesia, NM 88211-0960 **OOD-ARTESIA**

4. Well Location
Unit Letter A 660 feet from the North line and 660 feet from the East line
Section 12 Township 19S Range 28E NMPM County Eddy

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3378' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input checked="" type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	P AND A <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	MULTIPLE COMPL <input type="checkbox"/>	CASING/CEMENT JOB <input type="checkbox"/>	
OTHER: _____ <input type="checkbox"/>		OTHER: _____ <input type="checkbox"/>	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1. Notify OCD 24 hours prior to starting plugging operations.
2. Set CIBP @ 1714' w/ 35' cement cap above perfs @ 1814'.
3. Circ hole with mud gel.
4. Set 35 sx cement plug 50' above and below 9 5/8" csg from 462-362'. - WOC TAG
5. Set 10 sx surface plug.
6. Install dry hole marker.

If this work requires an
earthen pit, a permit must
be approved prior to
construction of the pit(s).

Notify OCD 24 hrs. prior to any work done

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐ a general permit ☐ or an (attached) alternative OCD-approved plan ☐


SIGNATURE Jerry W. Sherrell TITLE Production Clerk DATE 5/17/2005

Type or print name Jerry W. Sherrell E-mail address: jerrys@mackenergycorp.com Telephone No. (505)748-1288
For State Use Only

APPROVED BY: Phil Hawkins TITLE Field Inspector DATE 5/24/05
Conditions of Approval (if any):

MACK ENERGY CORPORATION
 NEW MEXICO Z STATE #1
 Sec 12 T19S R28E 660FNL 660FEL

BEFORE



9 5/8" 36# @ 412' C/w 250sks Circ

Perfs 1814'-2392'

CIBP 2550'w/35'cmt cap
 Perfs 2592-2632'

5 1/2" 14# @ 2992' C/w 1475sks Circ

AFTER



10sk plug surface

9 5/8" 36# @ 412' C/w 250sks Circ *wow TAG*

CIBP 1714' w/35'cmt cap
 Perfs 1814'-2392'

CIBP 2550'w/35'cmt cap
 Perfs 2592-2632'

5 1/2" 14# @ 2992' C/w 1475sks Circ

- 1 Notify OCD 24hrs of plugging
- 2 Set CIBP @ 1714' w/35'cmt cap above perfs at 1814" and circ hole with mud
- 3 Set 35 sk cmt plug 50' above and below csg 9 5/8" From 462'-362"
- 4 Set 10sk surface plug
- 5 Install dry hole marker