

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised June 10, 2003

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-005-63410
1. Type of Well: Oil Well ☐ Gas Well ☒ Other		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator Yates Petroleum Corporation		6. State Oil & Gas Lease No. VO-5657
3. Address of Operator 105 S. 4 th Street, Artesia, NM 88210		7. Lease Name or Unit Agreement Name Roulette AXR State
4. Well Location Unit Letter <u>E</u> : <u>1775</u> feet from the <u>North</u> line and <u>788</u> feet from the <u>West</u> line Section <u>8</u> Township <u>10S</u> Range <u>26E</u> NMPM <u>Chaves</u> County		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3779' GR		9. OGRID Number 025575
		10. Pool name or Wildcat Foor Ranch Wolfcamp/Pecos Slope Abo

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPLETION ☐	CASING TEST AND CEMENT JOB ☐	
OTHER: ☐		OTHER: Plugback, recomple and commingle well ☒	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

5/4/05 - Set CIBP at 5850' with 35' cement. Perforate Wolfcamp 5540'-5548' (48).
5/5/05 - Acidize Wolfcamp 5540'-5548' with 900g 7-1/2% acid and 72 balls.
5/6/05 - Set CIBP at 5500' with 35' cement. Perforate Wolfcamp 5080'-5090', 5174'-5184' with 44 holes.
5/9/05 - Acidize Wolfcamp 5080'-5184' with 2000g 20% IC acid and 66 balls.
5/11/05 - Perforate Abo 4482'-4488', 4499'-4517', 4582'-4588', 4600'-4602', 4640'-4644', 4682'-4693' and 4740'-4746' for a total of 60 holes. Set composite bridge plug at 5050'.
5/13/05 - Frac Abo 4482'-4746' with 113,500g 55Q CO2 foam and 250K 16/30 Brown.
6/7/05 - Drilled out composite at 5050' and pushed down to 5500'. Set packer at 4410'.

WELL IS NOW COMMINGLED WOLFCAMP AND ABO

DHC-3465

Foor Ranch Wolfcamp Oil-0% Gas-50%
Pecos Slope Abo Oil-0% Gas-50%

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE: Tina Huerta TITLE: Regulatory Compliance Supervisor DATE: June 13, 2005

Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471

(This space for State use)

APPROVED BY Jim W. Green TITLE District II Supervisor DATE JUN 18 2005

Conditions of approval, if any: