Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

OCD Artesia

FORM APPROVED

Expires: July	31, 201
OMB No. 10	04-013

5. Lease Serial No. NMLC - 054908

6. If Indian, Allottee or Tribe Name

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an
abandoned well. Use Form 3160-3 (APD) for such proposals

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.			NA			
SUBMI	T IN TRIPLICATE – Other instructions	on page 2.	7. If Unit of CA/Agreement, Name and/or No. NA			
1. Type of Well Oil Well Gas W	/ell		8. Well Name and No. Fair 18 Federal #2			
2. Name of Operator Fair Oil, Ltd.		9. API Well No. 30-015-40472				
3a. Address		o. (include area code) 27	1	10. Field and Pool or Exploratory Area Cedar Lake; Glorieta-Yeso		
4. Location of Well <i>(Footage, Sec., T.</i> 990' FNL & 330' FEL, Sec 18, T17S, R31E, NM	R.,M., or Survey Description) PM		11. Country or Parish, Eddy NM	11. Country or Parish, State Eddy NM		
12. CHEC	CK THE APPROPRIATE BOX(ES) TO IN	DICATE NATURE OF NO	TICE, REPORT OR OTHI	ER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION					
Notice of Intent	Alter Casing Fra	· -	roduction (Start/Resume)	☐ Water Shut-Off ☐ Well Integrity		
Subsequent Report		=	ecomplete emporarily Abandon	Other		
Final Abandonment Notice		· <u>=</u>	/ater Disposal			
Attach the Bond under which the variable following completion of the involvatesting has been completed. Final determined that the site is ready for Due to inablility to stop water flow in head syamatic is attached to add has been completed. Lead Slurry- 144 cu-ft, volume factor body Sodium Metasilicat + 5% body Tail Slurry - 90 cu-ft, volume factor Yield (cf/sack) 1.34, Mix Water (gps	n 8 5/8" casing @ 980', Fair plans to rur anger for 7" casing. Will cement 7" bac or of 2.15 = 70sks (35:65) Poz (Fly Ash) oc MPA-5 + 113.2% Fresh Water. Slurn of 1.34 = 70 sks Class C Cement + 2%	th No. on file with BLM/BIA multiple completion or reconfer all requirements, including 2605' of 7" 23#, P-110 upok to surface as follows: Class C Cement + 4% by weight (ppg) 12.5, Slurr bwoc Calcium Chloride +	Required subsequent reports and in a new intervaling reclamation, have been altra-flush casing with floopwood Bentonite II + 5% by Yield (cf/sack) 2.15, Mr. 56.4% Fresh Water. SI	orts must be filed within 30 days, a Form 3160-4 must be filed once completed and the operator has at collar and float shoe. New well owww Sodium Choloride + 2.5% ix Water (gps) 11.81.		
Joint Strength 223M#). DV tool set	~ 4500'. No change in the amount or p	RECEIVE DEC 1 9 2012 NMOCD ARTE	D	OCT 9 2012 Wesley Transport		
14. I hereby certify that the foregoing is t Rodney K. Thomson	rue and correct. Name (Printed/Typed)	Title Production Mana	ager	SUPERVISOR-EPS		
Signature Cody 1h		Date 10/09/2012				
	THIS SPACE FOR FED	ERAL OR STATE O	FFICE USE			
Approved by .		Title		Date		
	d. Approval of this notice does not warrant or title to those rights in the subject lease which thereon	r certify				

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false,

fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

