(April 2004)	UNITED STATES DEPARTMENT OF THE INTH	RIOR RECEIV	FORM APPROVED OM B No. 1004-0137 Expires: March 31, 2007
	SUREAU OF LAND MANAGEN NOTICES AND REPORT	1×10^{-1}	013 5 Lease Serial No. NMNM05039A
Do not use the abandoned we	nis form for proposals to drill ell. Use Form 3160-3 (APD)	i or to re-enter an for such Moodesalis.AR	TESIA ^{6.} If Indian, Allottee or Tribe Name
	IPLICATE- Other instruction	ons on reverse side.	7. If Unit or CA/Agreement, Name and/or NMNM071016X
1. Type of Well Oil Well Gas Well 2. Name of Operator BOPCO, L. P.			8. Well Name and No. PLU Ross Ranch 28-25-30 USA #
3a. Address	3b. F	Phone No. (include area code)	9. API Well No. 30-015-40765
P. O. Box 2760 Midland, TX ' 4. Location of Well <i>(Footage, Sec.,</i>		2-683-2277	10. Field and Pool, or Exploratory Area Corral Canyon Bone Spring, Sout
SHL: 150' FSL, 660' FWL, Se	c. 28, T25S, R30E, Lat: N32.094024, c. 28, T25S, R30E, Lat: N32.107825,		II. County or Parish, State Eddy
12. CHECK AI	PPROPRIATE BOX(ES) TO INDI	CATE NATURE OF NOT	CE, REPORT, OR OTHER DATA
TYPE OF SUBMISSION	(TYPE OF ACTI	ON
Notice of Intent Subsequent Report Final Abandonment Notice	Alter Casing Fra Casing Repair Ne Change Plans Plu	acture Treat Reclam	olete Cement operat arily Abandon
If the proposal is to deepen dire Attach the Bond under which the following completion of the inv	ectionally or recomplete horizontally, give the work will be performed or provide the E volved operations. If the operation results in nal Abandonment Notices shall be filed on	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of pletion in a new interval, a Form 3160-4 shall be filed
If the proposal is to deepen dire Attach the Bond under which th following completion of the inv testing has been completed. Fin determined that the site is ready BOPCO , L.P. respectfully Change the 5-1/2" , 17#, H approximately 5,000' to pr circulated a minimum of 5	ectionally or recomplete horizontally, give the work will be performed or provide the F volved operations. If the operation results in nal Abandonment Notices shall be filed on or final inspection.) requests the following changes for the CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw	subsurface locations and measure Bond No. on file with BLM/BIA. In a multiple completion or recom ly after all requirements, includin he above captioned well: g cement job from one stage are zones to increase the cha	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of pletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator b to two stage. The DV tool will be set at nce for a successful cement job. Cement will be additions of approval. Please see below for upda
If the proposal is to deepen dire Attach the Bond under which the following completion of the invi- testing has been completed. Find determined that the site is ready BOPCO , L.P. respectfully Change the 5-1/2" , 17#, H approximately 5,000' to pro- circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 65	ectionally or recomplete horizontally, give the work will be performed or provide the F volved operations. If the operation results in nal Abandonment Notices shall be filed on or final inspection.) requests the following changes for the CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom ly after all requirements, includin ne above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk)	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of pletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator b to two stage. The DV tool will be set at nce for a successful cement job. Cement will be additions of approval. Please see below for upda
If the proposal is to deepen dire Attach the Bond under which th following completion of the invite testing has been completed. Fir determined that the site is ready BOPCO , L.P. respectfully Change the 5-1/2", 17#, H approximately 5,000' to pr circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 6 1,100 sks Tail - 5	ectionally or recomplete horizontally, give a he work will be performed or provide the F volved operations. If the operation results in nal Abandonment Notices shall be filed on of or final inspection.) requests the following changes for the CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw 500' inside of the 8-5/8", 32#, J-55, L7 5:35 Class "H"Poz + additives (12.4 50:50 Class "H":Poz Cement + additives :50 Class "H":Poz Cement + additives	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom- ly after all requirements, includin the above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk) ives (14.5 ppg, 1.28 cu ft/sk) cu ft/sk) es (14.5 ppg, 1.28 cu ft/sk)	nce for a sucessful cement job. Cement will be aditions of approval. Please see below for upda
If the proposal is to deepen dire Attach the Bond under which th following completion of the invite testing has been completed. Fir determined that the site is ready BOPCO , L.P. respectfully Change the 5-1/2", 17#, H approximately 5,000' to pr circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 6 1,100 sks Tail - 5	ectionally or recomplete horizontally, give : he work will be performed or provide the F volved operations. If the operation results in nal Abandonment Notices shall be filed on of or final inspection.) requests the following changes for the CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw 500° inside of the 8-5/8", 32#, J-55, L7 5:35 Class "H"Poz + additives (12.4 50:50 Class "H":Poz Cement + additives :50 Class "H":Poz Cement + additives	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom ly after all requirements, includin the above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk) ives (14.5 ppg, 1.28 cu ft/sk) cu ft/sk) es (14.5 ppg, 1.28 cu ft/sk) d IOI IOCOID	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of pletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator l to two stage. The DV tool will be set at nce for a successful cement job. Cement will be additions of approval. Please see below for upda
If the proposal is to deepen dire Attach the Bond under which th following completion of the invi- testing has been completed. Fir determined that the site is ready BOPCO , L.P. respectfully Change the 5-1/2", 17#, H approximately 5,000' to pr circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 6 1,100 sks Tail - 5	ectionally or recomplete horizontally, give : he work will be performed or provide the F volved operations. If the operation results in nal Abandonment Notices shall be filed on of or final inspection.) requests the following changes for the CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw 500° inside of the 8-5/8", 32#, J-55, L7 5:35 Class "H"Poz + additives (12.4 50:50 Class "H":Poz Cement + additives :50 Class "H":Poz Cement + additives	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom- ly after all requirements, includin the above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk) ives (14.5 ppg, 1.28 cu ft/sk) cu ft/sk) es (14.5 ppg, 1.28 cu ft/sk)	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of pletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator l to two stage. The DV tool will be set at nce for a successful cement job. Cement will be additions of approval. Please see below for upda
If the proposal is to deepen dire Attach the Bond under which the following completion of the invi- testing has been completed. Find determined that the site is ready BOPCO, L.P. respectfully Change the 5-1/2", 17#, H approximately 5,000' to pre- circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 66 1,100 sks Tail - 50 Stage 2: 275 sks Lead - C 125 sks Tail - 50	ectionally or recomplete horizontally, give : he work will be performed or provide the H volved operations. If the operation results in nal Abandonment Notices shall be filed on 7 final inspection.) requests the following changes for th CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw 500' inside of the 8-5/8", 32#, J-55, L' 5:35 Class "H"Poz + additives (12.4 50:50 Class "H":Poz Cement + additive class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class TC" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class TC" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + addi	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom ly after all requirements, includin the above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk) ives (14.5 ppg, 1.28 cu ft/sk) cu ft/sk) es (14.5 ppg, 1.28 cu ft/sk) d fof record	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of pletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator l to two stage. The DV tool will be set at nee for a successful cement job. Cement will be additions of approval. Please see below for upda SEEE ATTACHED FOR SEEE ATTACHED FOR CONDITIONS OF 2013
If the proposal is to deepen dire Attach the Bond under which the following completion of the invi- testing has been completed. Fin- determined that the site is ready BOPCO, L.P. respectfully Change the 5-1/2", 17#, H approximately 5,000' to pro- circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 6 1,100 sks Tail - 5 Stage 2: 275 sks Lead - C 125 sks Tail - 50	ectionally or recomplete horizontally, give : he work will be performed or provide the H volved operations. If the operation results in nal Abandonment Notices shall be filed on 7 final inspection.) requests the following changes for th CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw 500' inside of the 8-5/8", 32#, J-55, L' 5:35 Class "H"Poz + additives (12.4 50:50 Class "H":Poz Cement + additive class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class TC" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class TC" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + addi	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom ly after all requirements, includin the above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk) ives (14.5 ppg, 1.28 cu ft/sk) cu ft/sk) es (14.5 ppg, 1.28 cu ft/sk) d for record	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 upletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator l to two stage. The DV tool will be set at nce for a successful cement job. Cement will be additions of approval. Please see below for upda SEEE ATTACHED FOR SEEE ATTACHED FOR CONDITIONS OF 2013
If the proposal is to deepen dire Attach the Bond under which the following completion of the invi- testing has been completed. Fin- determined that the site is ready BOPCO, L.P. respectfully Change the 5-1/2'', 17#, H approximately 5,000' to pr circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 6 1,100 sks Tail - 5 Stage 2: 275 sks Lead - C 125 sks Tail - 50	ectionally or recomplete horizontally, give : he work will be performed or provide the H volved operations. If the operation results in nal Abandonment Notices shall be filed on 7 final inspection.) requests the following changes for th CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw 500' inside of the 8-5/8", 32#, J-55, L' 5:35 Class "H"Poz + additives (12.4 50:50 Class "H":Poz Cement + additive class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class "C" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class TC" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + additive Class TC" + additives (12.4 ppg, 2.09 5:50 Class "H":Poz Cement + addi	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom ly after all requirements, includin the above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk) ives (14.5 ppg, 1.28 cu ft/sk) cu ft/sk) es (14.5 ppg, 1.28 cu ft/sk) Cl for record iOCD 107 3 Title Drilling Engin Date 1.2 /20 /12	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of opletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator l to two stage. The DV tool will be set at nee for a successful cement job. Cement will be additions of approval. Please see below for upda SEEE ATTACHED FOR SEEE ATTACHED FOR CONDITIONS OF 2013 eer
If the proposal is to deepen dire Attach the Bond under which the following completion of the invi- testing has been completed. Fin- determined that the site is ready BOPCO, L.P. respectfully Change the 5-1/2", 17#, H approximately 5,000' to pu- circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 66 1,100 sks Tail - 50 Stage 2: 275 sks Lead - C 125 sks Tail - 50 () 14. Ihereby certify that the fore Name (<i>Printed/Typed</i>) Christopher Gies Signature <u>Approved by</u> Conditions of approval, if any, are a	ectionally or recomplete horizontally, give : he work will be performed or provide the F volved operations. If the operation results in nal Abandonment Notices shall be filed on or final inspection.) requests the following changes for the CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw 500' inside of the 8-5/8", 32#, J-55, L7 5:35 Class "H"Poz + additives (12.4 50:50 Class "H":Poz Cement + additive class "C" + additives (12.4 ppg, 2.09 :50 Class "H":Poz Cement + additive CP-10 CP-10 THIS SPACE FOR FEDE attached. Approval of this notice does not or equitable title to those rights in the su	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom ly after all requirements, includin the above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk) ives (14.5 ppg, 1.28 cu ft/sk) cu ft/sk) es (14.5 ppg, 1.28 cu ft/sk) Cl fOF record Title Drilling Engin Date 1.2 /20 /12 ERAL OR STATE OF Title	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of opletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator l to two stage. The DV tool will be set at nee for a successful cement job. Cement will be additions of approval. Please see below for upda SEEE ATTACHED FOR SEEE ATTACHED FOR CONDITIONS OF 2013 eer
If the proposal is to deepen dire Attach the Bond under which the following completion of the invi- testing has been completed. Fin- determined that the site is ready BOPCO, L.P. respectfully Change the 5-1/2", 17#, H approximately 5,000' to pu- circulated a minimum of 5 cement volumes: Stage 1: 450 sks Lead - 66 1,100 sks Tail - 50 Stage 2: 275 sks Lead - C 125 sks Tail - 50 () 14. I hereby certify that the fore Name (<i>Printed/Typed</i>) Christopher Gies Signature <u>Approved by</u> Conditions of approval, if any, are a certify that the applicant holds legal which would entitle the applicant to Title 18 U.S.C. Section 1001 and Titke	ectionally or recomplete horizontally, give : he work will be performed or provide the F volved operations. If the operation results in nal Abandonment Notices shall be filed on or final inspection.) requests the following changes for the CP-110, LTC/BTC production casing rovide hydrostatic relief to the delaw 500' inside of the 8-5/8", 32#, J-55, L7 5:35 Class "H"Poz + additives (12.4 50:50 Class "H":Poz Cement + additive class "C" + additives (12.4 ppg, 2.09 :50 Class "H":Poz Cement + additive CP-10 CP-10 THIS SPACE FOR FEDE attached. Approval of this notice does not or equitable title to those rights in the su ponduct operations thereon.	subsurface locations and measure Bond No. on file with BLM/BIA. in a multiple completion or recom ly after all requirements, includin the above captioned well: g cement job from one stage are zones to increase the cha IC casing shoe as per the cor ppg, 2.19 cu ft/sk) ives (14.5 ppg, 1.28 cu ft/sk) cu ft/sk) es (14.5 ppg, 1.28 cu ft/sk) d for record for precord for any person knowingly and v	d and true vertical depths of all pertinent markers and a Required subsequent reports shall be filed within 30 of opletion in a new interval, a Form 3160-4 shall be filed g reclamation, have been completed, and the operator 1 to two stage. The DV tool will be set at nee for a successful cement job. Cement will be additions of approval. Please see below for upda SEE ATTACHED FOR SEE ATTACHED FOR CONDITIONS OF CONDITIONS OF CONDITIONS OF CONDITIONS OF DEG 2 1 2012

.

	(Instructions on		<u>ר ו</u>	
ł	unsurations on	nnoo		

Conditions of Approval

BOPCO, L.P. PLU Ross Ranch 28-25-30 USA #1H API 30-015-40765 T25S-R30E, Sec 28 December 21, 2012

1. The minimum required fill of cement behind the 5 1/2 inch production casing is:

a. First stage to DV tool:

Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job. Operator should have plans as to how they will achieve circulation on the next stage.

b. Second stage above DV tool:

Cement should tie-back at least 500 feet into previous casing string. Operator shall provide method of verification.

JAM 122112