

Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM

87505

Energy, Minerals and Natural Resources

Revised August 1, 2011

RECEIVED

JAN 15 2013

NMOCD ARTESIA

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.

30-015-39640

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Patton 5 Fee

8. Well Number 7H

9. OGRID Number

229137

10. Pool name or Wildcat

Atoka; Glorieta-Yeso 3250

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

COG Operating LLC

3. Address of Operator

One Concho Center - 600 W Illinois Ave Midland, TX 79701

4. Well Location

Unit Letter M : 982 feet from the SOUTH line and 330 feet from the WEST lineSection 5 Township 19S Range 26E NMPM County EDDY

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3363'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐

OTHER: Change Casing Program

☒

OTHER:

☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

COG proposes to drill an 11" hole to 1200' w/fresh water, run 8-5/8" 32# J-55 and cement to surface. Drill a 7-7/8" hole to 2410' MD and kick off and drill curve to 2930' TVD 3232' MD. Drill a 7-7/8" lateral to new BHL @ 2895' TVD 7314' MD. Run a 5 1/2" 17# L-80 casing to TD cement to surface with 800 sacks.

A revised directional plan is attached.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE Permitting Tech

DATE 01/11/2013

Type or print name Kelly J. Holly

E-mail address: kholly@concho.com

PHONE: 432-685-4384

For State Use Only

APPROVED BY:

TITLE

DATE

1/15/2013

Conditions of Approval (if any):