

Office

June 19, 2008

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

Energy, Minerals and Natural Resources

RECEIVED

FEB 11 2013

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

NMOCD ARTESIA Santa Fe, NM 87505

WELL API NO.

30-015-40488

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator

LIME ROCK RESOURCES II-A,L.P.

3. Address of Operator

c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401

7. Lease Name or Unit Agreement Name

EVEREST 14 N

8. Well Number #8

9. OGRID Number 277558

10. Pool name or Wildcat

Atoka, Glorieta-Yeso (3250)

4. Well Location

Unit Letter N : 990 feet from the SOUTH line and 2210 feet from the WEST line

Section 14 Township 18-S Range 26-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3319' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☐CASING/CEMENT JOB ☒OTHER: Spud & Casings ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spud well on 1/30/13. Drilled 12-1/4" hole to 440'. Landed 8-5/8" 24# J-55 csg @ 437'. Cmted w/435 sx (583 cf) "C" cmt w/2% Cacl2 & 0.125# CF. Circ 168 sx cmt to surface. On 1/31/13, PT 8-5/8" csg to 1500 psi for 30 min-OK.


Drilled 7-7/8" hole from 8-5/8" csg shoe to 4315' on 2/5/13. Ran open hole logs. On 2/6/13, landed 5-1/2" 17# J-55 csg @ 4315'. Cmted lead w/200sx (380 cf) 35/65 poz "C" cmt w/1/4#/sx CF, 0.30% CD-32, 5% salt, 5# LCM-1, 0.005# static free, & 0.15% R-3. Tailed w/700 sx (924 cf) "C" cmt w/0.25#/sx CF, 0.005# static free, 0.15% R-3. Circ 144 sx cmt to pit. Released drilling rig on 2/7/13. Plan to pressure test the 5-1/2" csg before completion operations.

Spud Date: 1/30/13

Drilling Rig Release Date: 2/7/13

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE Petroleum Engineer - Agent

DATE 2/8/13

Type or print name Mike Pippin

E-mail address: mike@pippinllc.com

PHONE: 505-327-4573

For State Use Only

APPROVED BY:



TITLE

D. S. H. Spiverson

DATE

2/14/13

Conditions of Approval (if any):

