

30-015-38663

WELL NAME: NASH 49
LOCATION: 510' FNL & 500' FEL, SEC 13, T 23S & R 29E
FORMATION:
SPUD DATE: 06/12/12
IP:

COUNTY/STATE: EDDY, NM
LEASE: NASH DRAW, BYCN
CURRENT STATS: ESP
COMPL DATE:
API No: 30-015-38663



17 1/2" HOLE
13-3/8" 48# H40, CSG @ 225'
CMT W/350 SX
CIRC TO SURF W/162 SX

PERF @ 710' SQZ'D W/200SX (7/4/12)
RE-SQZ (12/20/12)

12-1/4" HOLE

9-5/8" 38#, 4-55 CSG SET @ 3200'
CMT W/1250 SX
CIRC TO SURF W/209 SX

8-3/4" HOLE

7" 26# P-110, CSG SET @ 7206'
CMT 1ST STG W/900 SX
CMT 2ND STG W/200 SX
CIRC TO SURF W/34 SX

ELEV:
OL: 3001'
KB: 3018'

MD	MKA	TVD	CHG
0	0.00	0.0	
1,000	4.50	999.5	
2,000	3.02	6167.2 ROP	
3,000	10.50	6,312.7	
4,000	67.62	6,831.5	
5,000	47.42	6,863.1 STAGE 1	
6,000	87.15	6,910.3 PLUG	
7,000	64.99	6,912.7 STAGE 2	
8,000	69.96	6,915.8 PLUG	
9,000	69.90	6,917.2 STAGE 3	
10,000	87.58	6,950.3 PLUG	
11,000	89.00	6,953.5 STAGE 4	
12,000	89.00	6,969.0 PLUG	
13,000	89.69	6,969.3	
14,000	87.06	6,972.0 STAGE 4	
15,000	88.44	6,983.4	
16,000	88.99	6,986.1 PLUG	
17,000	87.05	6,985.4 STAGE 5	
18,000	82.91	7,013.0	
19,000	83.91	7,033.0 PLUG	
20,000	49.67	7,058.4 STAGE 6	
21,000	87.05	7,033.0	
22,000	86.08	7,035.2 PLUG	
23,000	82.14	7,056.7 STAGE 7	
24,000	82.14	7,056.0	

TUBING (12/27/12):
187 JTS 2-7/8" J55, 1 JT 2-7/8" J55, SN @
6083', 4 STAGE ESP PMP, ESP INTAKE
(TOP) @ 6172', SEAL ASSEMB. 3-3/8",
MOTOR @ 6200', DESANDER @ 6215', 1
JT 2-7/8" J55, DESANDER, 1 JT 2-7/8" J55
LANDED @ 6385'

MVD: 11,732'
TVD: 6984.7'
TD: 11,732'

PERF:
STG 1-11,650'
STG 2-11,217'-11,238', 11,445'-11,467'
STG 3-10,760'-10,782', 10,889'-11,011'
STG 4-10,077'-10,099', 10,305'-10,327', 10,533'-10,559'
STG 5-9393'-9415', 9521'-9543', 9849'-9871'
STG 6-8709'-8731', 8937'-8959', 9165'-9187'
STG 7-8029'-8047', 8253'-8275', 8481'-8503'
STG 8-7341'-7363', 7569'-7591', 7797'-7819'

CURVE F/6212'-6984.7'

6-1/8" OH FR/7214'-11,732'

4-1/2", 11.6#, P-110 LINER FR/6527'-11,713'

