	UNITED STATES DEPARTMENT OF THE INTEI BUREAU OF LAND MANAGEM	RIOR ENT	Artesia 5	OMB N Expires:	APPROVED O. 1004-0135 July 31, 2010
SUNDRY NOTICES AND REPORTS ON WELL Do not use this form for proposals to drill or to re-en			5	5. Lease Serial No. NMNM106678	
abandoned well. Use form 3160-3 (APD) for such proposals.			6	6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE - Other instructions on reverse side. 1. Type of Well Image: Contact: Contact: Contact: Contact: TROY M PETERSON YATES PETROLEUM CORPORATION€-Mail: tpeterson@yatespetroleum.com			7	 If Unit or CA/Agreement, Name and/or No. 8. Well Name and No. BOLIVAR BRD FEDERAL COM 1 9. API Well No. 30-015-40742-00-X1 	
			8		
			9		
		Phone No. (include area code 575-748-4211	s) I·	10. Field and Pool. or Exploratory UNDESIGNATED SULFATE DRAW: W.C.	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)			1	1. County or Parish,	and State
Sec 33 T24S R27E NESE 1		EDDY COUNTY,		Υ, NM	
12. CHECK AP	PROPRIATE BOX(ES) TO INI	DICATE NATURE OF	NOTIÇE, REP	ORT, OR OTHE	R DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
X Notice of Intent	□ Acidize	Deepen	Production	(Start/Resume)	UWater Shut-Off
Subsequent Report	□ Alter Casing	Fracture Treat	🗖 Reclamatio		U Well Integrity
	Casing Repair	■ New Construction	Recomplet	orarily Abandon Change to Original A PD	
□ Final Abandonment Notice	 Change Plans Convert to Injection 	Plug and Abandon Plug Back	U Temporari		
Attach the Bond under which the	work will be performed or provide the Bo	ubsurface locations and mease ond No. on file with BLM/BL	A. Required subset	al depths of all pertin quent reports shall be	ent markers and zones. filed within 30 days
Attach the Bond under which the v following completion of the invol- testing has been completed. Final determined that the site is ready for Yates Petroleum Corporation production string. DV/Stage Stage 1: Lead - 1400sx of F Stage 2: Lead - 360sx of 35 14.2) 5700'-1850' 25% exce	work will be performed or provide the Bo ved operations. If the operation results in Abandonment Notices shall be filed only or final inspection.) on respectfully requests a change e Packer tool will be placed at ap 2VL (YLD 1.41 WT 13) 12075'-57 5:65:6 PozC (YLD 2 WT 12.6), Ta	ubsurface locations and measure ond No. on file with BLM/BL a multiple completion or rec y after all requirements, include in the DV/Stage Packe prox. 5700'. Cement as 00' 35% excess ail - 345sx of 50:50 PozC	ured and true vertic A. Required subset completion in a new ding reclamation, h r placement on s follows: C (YLD 1.36 WT	al depths of all pertin quent reports shall be interval, a Form 316 ave been completed. the	ent markers and zones. filed within 30 days 0-4 shall be filed once and the operator has PTEC for record NMOCD 165 167 4/2/002 2013
Attach the Bond under which the v following completion of the invol- testing has been completed. Final determined that the site is ready for Yates Petroleum Corporation production string. DV/Stage Stage 1: Lead - 1400sx of F Stage 2: Lead - 360sx of 35 14.2) 5700'-1850' 25% exces Essentially Original COA on	work will be performed or provide the Bo ved operations. If the operation results in Abandonment Notices shall be filed only or final inspection.) on respectfully requests a change e Packer tool will be placed at ap PVL (YLD 1.41 WT 13) 12075'-57 i:65:6 PozC (YLD 2 WT 12.6), Ta ess sundry dated 02/20/2013 st g is true and correct. Electronic Submission #20290	ubsurface locations and measurface locations and measure ond No. on file with BLM/BL a multiple completion or rec y after all requirements, includ in the DV/Stage Packe prox. 5700'. Cement as 00' 35% excess ail - 345sx of 50:50 PozC till applies	ured and true vertic A. Required subsec- completion in a new ding reclamation, h r placement on s follows: C (YLD 1.36 WT C (YLD 1.36 WT) C (YLD 1.36 WT C (YLD 1.36 WT) C (YLD 1.36 WT C (YLD 1.36 WT) C (YLD	al depths of all pertin quent reports shall be interval, a Form 316 ave been completed. the ACCE RECEIN APR 01 NMOCD AF	ent markers and zones. filed within 30 days 0-4 shall be filed once and the operator has PPTECI FOT record NMOCD 165 4/2/007 2013 TESIA
Attach the Bond under which the v following completion of the invol- testing has been completed. Final determined that the site is ready for Yates Petroleum Corporation production string. DV/Stage Stage 1: Lead - 1400sx of F Stage 2: Lead - 360sx of 35 14.2) 5700'-1850' 25% exce Essentially Original COA on	work will be performed or provide the Bo ved operations. If the operation results in Abandonment Notices shall be filed only or final inspection.) on respectfully requests a change e Packer tool will be placed at ap PVL (YLD 1.41 WT 13) 12075'-57 5:65:6 PozC (YLD 2 WT 12.6), Ta ess sundry dated 02/20/2013 st g is true and correct. Electronic Submission #20290 For YATES PETROLEU	ubsurface locations and measure ond No. on file with BLM/BL n a multiple completion or rec y after all requirements, includ e in the DV/Stage Packe prox. 5700'. Cement as '00' 35% excess ail - 345sx of 50:50 PozC till applies	ured and true vertic A. Required subsec- completion in a new ding reclamation, h r placement on s follows: C (YLD 1.36 WT C (YLD 1.36 WT) C (YLD 1.36 WT C (YLD 1.36 WT) C (YLD 1.36 WT C (YLD 1.36 WT) C (YLD	al depths of all pertin quent reports shall be interval, a Form 316 ave been completed. the ACCE RECEN APR 01 a NMOCD AF	ent markers and zones. filed within 30 days 0-4 shall be filed once and the operator has PTECI for record NMOCD 165 4/2/002 2013 TESIA
Attach the Bond under which the v following completion of the invol- testing has been completed. Final determined that the site is ready for Yates Petroleum Corporation production string. DV/Stage Stage 1: Lead - 1400sx of F Stage 2: Lead - 360sx of 35 14.2) 5700'-1850' 25% exces Essentially Original COA on 14. Thereby certify that the foregoing Name(Printed/Typed) TROY M	work will be performed or provide the Bo ved operations. If the operation results in Abandonment Notices shall be filed only or final inspection.) on respectfully requests a change e Packer tool will be placed at ap PVL (YLD 1.41 WT 13) 12075'-57 5:65:6 PozC (YLD 2 WT 12.6), Ta ess sundry dated 02/20/2013 st g is true and correct. Electronic Submission #20290 For YATES PETROLEU committed to AFMSS for processin	ubsurface locations and measure ond No. on file with BLM/BL n a multiple completion or rec y after all requirements, includ e in the DV/Stage Packe prox. 5700'. Cement as '00' 35% excess ail - 345sx of 50:50 PozC till applies	ured and true vertic A. Required subsec- completion in a new ding reclamation, h r placement on 5 follows: C (YLD 1.36 WT C (YLD 1.36 WT ell Information S to the Carlsbad 03/28/2013 (13K PLANNER	al depths of all pertin quent reports shall be interval, a Form 316 ave been completed. the ACCE RECEN APR 01 a NMOCD AF	ent markers and zones. filed within 30 days 0-4 shall be filed once and the operator has PPTECI FOT record NMOCD 165 4/2/007 2013 TESIA
Attach the Bond under which the v following completion of the invol- testing has been completed. Final determined that the site is ready for Yates Petroleum Corporation production string. DV/Stage Stage 1: Lead - 1400sx of F Stage 2: Lead - 360sx of 35 14.2) 5700'-1850' 25% exce Essentially Original COA on 14. Thereby certify that the foregoing Name(Printed/Typed) TROY M	work will be performed or provide the Bo ved operations. If the operation results in Abandonment Notices shall be filed only or final inspection.) on respectfully requests a change e Packer tool will be placed at ap PVL (YLD 1.41 WT 13) 12075'-57 :65:6 PozC (YLD 2 WT 12.6), Ta ses sundry dated 02/20/2013 st Electronic Submission #20290 For YATES PETROLEU committed to AFMSS for processin M PETERSON ic Submission)	ubsurface locations and measure ond No. on file with BLM/BL a multiple completion or rec y after all requirements, includ in the DV/Stage Packe prox. 5700'. Cement as '00' 35% excess ail - 345sx of 50:50 PozC till applies by verified by the BLM We M CORPORATION, sent g by KURT SIMMONS on Title WELL	ured and true vertic A. Required subser- completion in a new ding reclamation, h r placement on a follows: C (YLD 1.36 WT C (YLD 1.36 W	al depths of all pertin quent reports shall be interval, a Form 316 ave been completed. the ACCE RECEN APR 01 MMOCD AF	ent markers and zones. filed within 30 days 0-4 shall be filed once and the operator has PTECI for record NMOCD 165 42013 TESTA
Attach the Bond under which the v following completion of the invol- testing has been completed. Final determined that the site is ready for Yates Petroleum Corporation production string. DV/Stage Stage 1: Lead - 1400sx of F Stage 2: Lead - 360sx of 35 14.2) 5700'-1850' 25% exce Essentially Original COA on 14. Thereby certify that the foregoing Name(Printed/Typed) TROY M	work will be performed or provide the Bo ved operations. If the operation results in Abandonment Notices shall be filed only or final inspection.) on respectfully requests a change e Packer tool will be placed at ap VL (YLD 1.41 WT 13) 12075'-57 :65:6 PozC (YLD 2 WT 12.6), Ta ess sundry dated 02/20/2013 st Electronic Submission #20290 For YATES PETROLEU committed to AFMSS for processin M PETERSON ic Submission) THIS SPACE FOR F	ubsurface locations and meast ond No. on file with BLM/BL n a multiple completion or rec y after all requirements, includ e in the DV/Stage Packe prox. 5700'. Cement as 00' 35% excess ail - 345sx of 50:50 PozO till applies by verified by the BLM We M CORPORATION, sent g by KURT SIMMONS on Title WELL Date 03/27/2 EDERAL OR STATE	ured and true vertic A. Required subser- completion in a new ding reclamation, h r placement on a follows: C (YLD 1.36 WT C (YLD 1.36 W	al depths of all pertin quent reports shall be interval, a Form 316 ave been completed. the ACCE RECEN APR 01 MMOCD AF	ent markers and zones. filed within 30 days 0-4 shall be filed once and the operator has PTECI for record NMOCD 165 42013 TESTA

** BLM REVISED ** BLM REVISED ** BLM REVISED ** BLM REVISED **