

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-015-41032
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator OXY USA Inc.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 50250 Midland, TX 79710		7. Lease Name or Unit Agreement Name Cedar Canyon 15
4. Well Location Unit Letter <u>M</u> : <u>170</u> feet from the <u>South</u> line and <u>360</u> feet from the <u>West</u> line Section <u>15</u> Township <u>24S</u> Range <u>29E</u> NMPM County <u>Eddy</u>		8. Well Number <u>2H</u>
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>2927' GL</u>		9. OGRID Number <u>16696</u>
		10. Pool name or Wildcat Pierce Crossing Bone Springs E.

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐


SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

2/28/13, drill 7-7/8" hole to 12960'M 8795'V 3/8/13. RIH w/ 5-1/2" 17# L80 LTC csg & set @ 12960', ACP @ 2638'. Cmt w/ 720sx (315bbl) H w/ additives 11.9ppg, 2.46 yield followed by 730sx (213bbl) H w/ additives 13.2ppg, 1.64 yield had partial returns while cementing, circ spacer to surf, but no cmt. Set ACP, pressure to 2800# hold for 5 min, OK. Pressure to 3400# hold for 5 min, OK. Pressure to 3800# hold for 5 min, ACP set. Test csg to 3975# for 5 min, confirm set. RD Rel Rig 3/11/13.



Spud Date:

2/23/13

Rig Release Date:

3/11/13

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

David Stewart

TITLE

Regulatory Advisor

DATE

3/28/13

Type or print name
For State Use Only

David Stewart

E-mail address: david_stewart@oxy.com

PHONE: 432-685-5717

APPROVED BY:

R. Dade

TITLE

Dr. H. Spewer

DATE

04/03/2013

Conditions of Approval (if any):