

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-40968
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Layla 35 OB Fee
8. Well Number 1H
9. OGRID Number 14744
10. Pool name or Wildcat Culebra Bluff; Bone Spring South 15011
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3021'

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs, NM 88241

4. Well Location

Unit Letter O : 150 feet from the South line and 1980 feet from the East line
Section 35 Township 23S Range 28E NMPM Eddy County

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

04/04/13..M1 & spud 17 1/2" hole. TD'd hole @ 519'. Ran 519' of 13 3/8" 48# H40 ST&C csg. Cemented with 560 sks Class C w/2% CaCl2 w/additives. Mixed @ 14.8 /g w/ 1.34 yd. Plug down @ 3:45 PM 04/05/13. Circ 50 sks cement to the pit. WOC 18 hrs. At 6:00 AM 04/06/13, tested BOPE & csg to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

Spud Date: 04/04/2013

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Jackie Lathan

TITLE Hobbs Regulatory

DATE 04/29/13

Type or print name Jackie Lathan

E-mail address: jlathan@mewbourne.com

PHONE: 575-393-5905

For State Use Only

APPROVED BY:

RDade

TITLE

Dist # Supervisor

DATE

4/30/2013

Conditions of Approval (if any):

aw