Submit 3 Copies To Appropriate District State of New Mex	kico Form C-103
Energy Minerals and Natur	al Resources June 19, 2008
1625 N. French Dr., Hobbs, NNT 888 PECEIVED District II	WELL API NO. 30-015-41119
1301 W. Grand Ave., Artesia, NM 88210 OIL CONSERVATION	DIVISION 5 Indicate True of Loope
District III MAY 14 2013 220 South St. France 1000 Rio Brazos Rd., Aztec, NN 87410	
1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, MMOCD ARTESIA 87505	6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLU DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR	
PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other	8. Well Number #5
2. Name of Operator	9. OGRID Number 277558
LIME ROCK RESOURCES II-A,L.P.	
3. Address of Operator c/o Mike Pippin LLC, 3104 N. Sullivan, Farmington, NM 87401	10. Pool name or Wildcat Red Lake, Glorieta-Yeso NE (96836)
4. Well Location	
Unit Letter <u>C</u> : <u>430</u> feet from the <u>NORTH</u> line and <u>2300</u> feet from the <u>WEST</u> line	
	nge 27-E NMPM Eddy County
11. Elevation (Show whether DR, 3590' GL	RKB, RT, GR, etc.)
12. Check Appropriate Box to Indicate Na	ture of Notice. Report or Other Data
NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK D PLUG AND ABANDON	
	COMMENCE DRILLING OPNS. P AND A
PULL OR ALTER CASING	CASING/CEMENT JOB
OTHER:	
	OTHER: Completion IXI
13. Describe proposed or completed operations. (Clearly state all p	OTHER: Completion
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion.	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt &	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40',
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion.	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65',
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop sa	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel.
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop s Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40',
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop s Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop s Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50 gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 2 3530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53',
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop s Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50 gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800'.	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 2 3530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes.
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 82' 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop st Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 56' gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800', Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 2 3530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes.
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop s Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50 gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800'.	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 23530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', . 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes. 24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop si Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50' gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800', Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 44'	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 2 3530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes. 24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked 9 3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35', 0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60',
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop si Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 56' gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800' Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 44' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 2 3530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes. 24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked 9 3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35', 0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60',
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop si Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 56 gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800', Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 40' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel.	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 2 3530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes. 24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked 9 3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35', 0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60', acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760#
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop si Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 56' gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800', Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 40' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel. On 4/16/13, MIRUSU. Drilled CBPs @ 3495', 3900' & 4195' & CO to Ran pump & rods. Released completion rig on 4/19/13.	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 2,3530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes. 24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked 9,3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35', 0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60', acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760# PBTD4805'. On 4/18/13, landed 2-7/8" 6.5# J-55 tbg @ 4721'.
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop st Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50' gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800' Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 44' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel. On 4/16/13, MIRUSU. Drilled CBPs @ 3495', 3900' & 4195' & CO to Ran pump & rods. Released completion rig on 4/19/13. Spud Date: 3/28/13 Drilling	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 23530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes. 24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked 9,3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35', 0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60', acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760# PBTD4805'. On 4/18/13, landed 2-7/8" 6.5# J-55 tbg @ 4721'. Rig Release Date: 4/3/13
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop si Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 56' gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800', Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 40' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel. On 4/16/13, MIRUSU. Drilled CBPs @ 3495', 3900' & 4195' & CO to Ran pump & rods. Released completion rig on 4/19/13.	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 23530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes. 24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked 9,3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35', 0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60', acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760# PBTD4805'. On 4/18/13, landed 2-7/8" 6.5# J-55 tbg @ 4721'. Rig Release Date: 4/3/13
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop si Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50 gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800', Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 40', 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel. On 4/16/13, MIRUSU. Drilled CBPs @ 3495', 3900' & 4195' & CO to Ran pump & rods. Released completion rig on 4/19/13. Spud Date: 3/28/13 Drilling I hereby certify that the information above is true and complete to the bes	ertinent details, and give pertinent dates, including estimated date e Completions: Attach wellbore diagram of proposed completion CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40', 5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65', eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13, and in X-linked gel. e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40', 0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000 4,744# 16/30 siber prop sand in X-linked gel. 23530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53', 10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes. 24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked 9,3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35', 0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60', acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760# PBTD4805'. On 4/18/13, landed 2-7/8" 6.5# J-55 tbg @ 4721'. Rig Release Date: 4/3/13
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 82 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop ss Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50' gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800', Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 44' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel. On 4/16/13, MIRUSU. Drilled CBPs @ 3495', 3900' & 4195' & CO to Ran pump & rods. Released completion rig on 4/19/13. Spud Date: 3/28/13 Drilling I hereby certify that the information above is true and complete to the bes SIGNATURE	ertinent details, and give pertinent dates, including estimated date         e Completions: Attach wellbore diagram of proposed completion         CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40',         5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65',         eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13,         and in X-linked gel.         e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40',         0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000         4,744# 16/30 siber prop sand in X-linked gel.         23530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53',         10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes.         24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked         9,3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35',         0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60',         acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760#         PBTD4805'. On 4/18/13, landed 2-7/8" 6.5# J-55 tbg @ 4721'.         Rig Release Date:       4/3/13         st of my knowledge and belief.         um Engineer - Agent       DATE5/10/13
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 8. 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop si Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middle 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50' gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800', Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 44' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel. On 4/16/13, MIRUSU. Drilled CBPs @ 3495', 3900' & 4195' & CO to Ran pump & rods. Released completion rig on 4/19/13. Spud Date: 3/28/13 Drilling I hereby certify that the information above is true and complete to the bes SIGNATURE	ertinent details, and give pertinent dates, including estimated date         e Completions: Attach wellbore diagram of proposed completion         CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40',         5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65',         eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13,         and in X-linked gel.         e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40',         0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000         4,744# 16/30 siber prop sand in X-linked gel.         0 3530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53',         10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes.         24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked         0 3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35',         0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60',         acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760#         PBTD4805'. On 4/18/13, landed 2-7/8'' 6.5# J-55 tbg @ 4721'.         Rig Release Date:       4/3/13         st of my knowledge and belief.         aum Engineer - Agent       DATE5/10/13
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 88', 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop s: Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middl- 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50 gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800' Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 44' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel. On 4/16/13, MIRUSU. Drilled CBPs @ 3495', 3900' & 4195' & CO to Ran pump & rods. Released completion rig on 4/19/13. Spud Date: 3/28/13 Drilling I hereby certify that the information above is true and complete to the bes SIGNATURE	ertinent details, and give pertinent dates, including estimated date         e Completions: Attach wellbore diagram of proposed completion         CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40',         5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65',         eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13,         and in X-linked gel.         e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40',         0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000         4,744# 16/30 siber prop sand in X-linked gel.         23530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53',         10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes.         24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked         23130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35',         0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60',         acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760#         PBTD4805'. On 4/18/13, landed 2-7/8" 6.5# J-55 tbg @ 4721'.         Rig Release Date:       4/3/13         st of my knowledge and belief.         um Engineer - Agent       DATE5/10/13         mike@pippinllc.com       PHONE: _505-327-4573
of starting any proposed work). SEE RULE 1103. For Multiple or recompletion. On 4/6/13, PT 5-1/2" csg to 5000 psi for 30 min-OK. Drilled out cmt & 48', 55', 60', 65', 70', 76', 87', 4306', 28', 33', 40', 55', 66', 75', 80', 88', 70', 78', 84', 95', 4508', 24', 54', 60' w/1-0.34" spf. Total 41 holes. Tr fraced lower Yeso w/89,449# 16/30 Brady & 11,659# 16/30 siber prop s: Set 5-1/2" CBP @ 4195'. PT csg & CBP to 4000 psi-OK. Perfed middl- 50', 60', 70', 90', 95', 4100', 05', 10', 15', 20', 25', 30', 35', 40', 45', 50 gal 7.5% HCL acid & 44 perf balls. Fraced w/54,111# 16/30 Brady & 14 Set 5-1/2" CBP @ 3900'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 67', 78', 85', 90', 94', 3700', 10', 36', 40', 53', 60', 72', 81', 93', 3800' Treated perfs w/2000 gal 7.5% HCL acid & 51 perf balls. Fraced w/89,1 gel. Set 5-1/2" CBP @ 3495'. PT csg to 4000 psi-OK. Perfed upper Yeso @ 40', 45', 50', 55', 68', 80', 85', 90', 95', 3300', 10', 15', 20', 25', 28', 44' 70' w/1-0.34" spf. Total 43 holes. Treated perfs w/2000 gal 7.5% HCL 16/30 siber prop sand in X-linked gel. On 4/16/13, MIRUSU. Drilled CBPs @ 3495', 3900' & 4195' & CO to Ran pump & rods. Released completion rig on 4/19/13. Spud Date: 3/28/13 Drilling I hereby certify that the information above is true and complete to the bes SIGNATURE	ertinent details, and give pertinent dates, including estimated date         e Completions: Attach wellbore diagram of proposed completion         CO to PBTD4805'. Perfed lower Yeso @ 4220', 25', 32', 40',         5', 90', 96', 4400', 05', 10', 15', 20', 25', 30', 50', 55', 60', 65',         eated w/2000 gal 7.5% HCL acid & 62 perf balls. On 4/15/13,         and in X-linked gel.         e Yeso @ 3930', 40', 50', 60', 70', 80', 90', 4000', 10', 30', 40',         0', 55', 60' w/1-0.34" spf. Total 29 holes. Treated perfs w/1000         4,744# 16/30 siber prop sand in X-linked gel.         23530', 55', 60', 65', 70', 75', 88', 98', 3614', 26', 36', 40', 53',         10', 20', 30', 40', 48', 56', w/1-0.34" spf. Total 34 holes.         24# 16/30 Brady & 11,741# 16/30 siber prop sand in X-linked         9,3130', 40', 50', 56', 67', 80', 90', 3200', 10', 20', 25', 30', 35',         0', 60', 65', 70', 77', 86', 95', 3405', 15', 20', 24', 33', 47', 60',         acid & 65 perf balls. Fraced w/80,375# 16/30 Brady & 22,760#         PBTD4805'. On 4/18/13, landed 2-7/8" 6.5# J-55 tbg @ 4721'.         Rig Release Date:       4/3/13         st of my knowledge and belief.         um Engineer - Agent       DATE5/10/13