Form 3160-5 (August 2007)

# UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135	
Expires: July 31, 2010	
5. Lease Serial No.	

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an
abandoned well. Use form 3160-3 (APD) for such proposals

NMNM0415461

abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on reverse side.					7. If Unit or CA/Agreement, Name and/or No.			
Type of Well     ☐ Gas Well					Well Name and No.     OLD INDIAN DRAW 11			
Name of Operator Contact: CAROL ADLER     CHESAPEAKE OPERATING INC E-Mail: carol.adler@chk.com					9. API Well No. 30-015-21844-00-S1			
3a. Address 3b. Phone No. (inc. Ph.: 817-556-5:				)	10. Field and Pool, or Exploratory			
OKLAHOMA CITY, OK 73154	-1821	INDIAN DRAW						
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)				11. County or Parish, and State				
Sec 19 T22S R28E NENE 330FNL 668FEL					EDDY COUNTY, NM			
12. CHECK APPR	ROPRIATE BOX(ES) TO	INDICATE	NATURE OF 1	NOTICE, RI	EPORT, OR OTHER	DATA		
TYPE OF SUBMISSION	TYPE OF ACTION							
☐ Notice of Intent	☐ Acidize ☐ Dee		epen Produc		ion (Start/Resume)	☐ Water Shut-Off		
_	☐ Alter Casing	☐ Fract	ure Treat	☐ Reclamation		■ Well Integrity		
☑ Subsequent Report	Subsequent Report ☐ Casing Repair ☐		Construction	□ Recomp	olete	☐ Other		
☐ Final Abandonment Notice	☐ Change Plans		and Abandon	☐ Temporarily Abandon				
	Convert to Injection		g Back		Disposal			
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)  CONFIDENTIAL  CHESAPEAKE RESPECTFULLY SUBMITS THE FINAL PLUG AND ABANDON FOR THE FOLLOWING:  OLD INDIAN DRAW UNIT 11  EDDY COUNTY, NEW MEXICO  4/2/2013 MOVE IN AND RIG UP PLUGGING EQUIPMENT START PLUGGING  MOVE IN AND RIG UP ALL PLUGGING EQUIPMENT - NDWH & NUBOP - TIH WITH 4.343 GAUGE RING TO 3200' - TIH WITH 5.5 CIBP AND SET AT 3195' - SDON  ACCEPTED TO ITECOMO AND A CONTROL OF THE START								
14. I hereby certify that the foregoing is	Electronic Submission #2	207680 verifie			n System			
For CHESAPEAKE OPERATING INC, sent to the Carlsback Committed to AFMSS for processing by KURT SIMMONS on 05/21/2013 (					•			
Name (Printed/Typed) CAROL ADLER			Title REGUI	_ATORY AN	ALYST II/AGENT			
Signature (Electronic	Submission)		Date 05/16/2	2013				
	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE U	SE			
Approved By ACCEPTED			JAMES A AMOS TitleSUPERVISOR EPS Date 06/			06/09/2013		
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			Office Carlsba	ıd				
Title 18 U.S.C. Section 1001 and Title 43 States any false, fictitious or fraudulent					ake to any department or	agency of th	e United	

## Additional data for EC transaction #207680 that would not fit on the form

#### 32. Additional remarks, continued

### 4/3/2013 CONTINUE PLUGGING

HELD PJSM - P/U PERF SUB & TIH WITH 98 1/2 JOINTS TBG TO 3195' - TAGGED 5.5 CIBP - CAP 5.5 CIBP WITH 25SKS CMT - (240') - DICPLACE 11.1 BBLS - LD 23 JOINTS - BOT IS 2498' SPOT 40 SKS CMT W/2%CAL. CLOR. (325') DISPLACE 8.1 BBLS - STAND BACK 26 STANDS & LD 25 JOINTS - WOC - R/U WIRELINE & TIH AND TAGG CMT @ 2168' - PERF. @ 1650' - P/U PKR & TIH TO 1295' - LOAD HOLE & SET PKR - PRESSURE TESTED TO 1500 PSI - CONTACTED BLM - ADVISED TO SPOT 25 SKS AT 1700' - REALEASED PKR TOOH P/U PERF SUB TIH W/53 JOINTS TO 1716' - SPOT 25 SKS CMT DISPLACE 5.1 BBLS - LD 20 JOINTS - SDON

## 4/4/2013 FINISH PLUGGING

HELD PJSM - R/U WIRELINE TIH AND TAG CMT PLUG @ 1471' - RD WIRELINE - STAND BACK 8 STANDS & LD 16 JOINTS - RU WIRELINE PERF @ 452' - RD WIRELINE - PU 5.5 PKR AND 2 JOINTS TO 60' - LOAD HOLE AND SET PKR - EST. INJ. RATE DOWN 5.5 X 10 3/4 CSG TO SURFACE - PUMP 200 SKS CMT DOWN 5 1/2" X 10 3/4" CSG TO SURFACE - DISPLACE 1/2 BBL - RELEASE PKR & LD 2 JOINTS - NDBOP - FILL 5 1/2" WELL BORE W/ 10 SKS CMT - CUT OFF WELLHEAD & ANCHORS - CLEAN LOCATION - INSTALL DRY HOLE MARKER - RD MOVE OFF PLUGGING EQUIPMENT - BLM (TERRY WILSON ON LOCATION FOR CMT JOB)

CHK PN 890666