Form 3160-5 (August 2007)

1.

OCD Artesia

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

Lease Serial No. NMNM2748

SUNDAT NOTICES AND REPORTS ON WELLS	
Do not use this form for proposals to drill or to re-enter an	n
abandoned well. Use form 3160-3 (APD) for such proposal	İs

6. If Indian, Allottee or Tribe Name

abandoned well. Use form 3160-3 (APD) for such proposals.									
SUBMIT IN TRIPLICATE - Other instructions on reverse side.						7. If Unit or CA/Agreement, Name and/or No.			
Type of Well					8. Well Name and No. GISSLER B 97				
Name of Operator BURNETT OIL COMPANY IN	GARVIS		9. API Well No. 30-015-41276-00-X1						
3a. Address 801 CHERRY STREET UNIT FORT WORTH, TX 76102-68	o. (include area code) 32-5108 Ext: 632		10. Field and Pool, or Exploratory LOCO HILLS GLORIETA-YESO						
4. Location of Well (Footage, Sec., T			11. County or Parish, and State						
Sec 11 T17S R30E SWSW 33 32.842534 N Lat, 103.948002	·		EDDY COUNTY, NM						
12. CHECK APPI	ROPRIATE BOX(ES) TO	INDICATI	E NATURE OF N	NOTICE, RI	EPORT, OR	OTHER	DATA		
TYPE OF SUBMISSION	TYPE OF ACTION								
□ Notice of Intent	Notice of Intent Alter Casing		epen Product		tion (Start/Resume)		■ Water Shut-Off		
			☐ Fracture Treat ☐		□ Reclamation		■ Well Integrity		
Subsequent Report	□ Casing Repair	□ Nev	w Construction	on Recomplete			Other		
☐ Final Abandonment Notice	☐ Change Plans	☐ Plu	g and Abandon Tempo		orarily Abandon		Production Start-up		
	☐ Convert to Injection		g Back		Disposal				
If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) 5/28/13 - TEST CSG TO 1500 PSI (GOOD). PBTD @ 6009'. 5/29/13 - PERF @ 5638' ,5646',5658' ,5666', 5672', 5702', 5707', 5725', 5735', 5754', 5774', 5796', 5808', 13 INT, 3 SPF, 39 HOLES, 0.42 EHD, 19 GRAM CHARGE, 34" PENETRATION. 5/30/13 - SPOT 250 GAL 15% NEFE ACID ACROSS PERFS, ACIDIZE W 2500 GAL 15% NEFE ACID & 78 BALL SEALERS. 5/31/13 -FRAC DN 7", 23#, J55 CSG W 546,504 GAL OF SLICKWATER, 19,652 100 MESH, 162,411# 40/70: RECEIVED PERF @ 5410', 5418', 5434', 5445', 5462', 5480', 5486', 5596', 5506', 5540', 5544', 5562', 3 SPF, 12 INT, 36 HOLES. ACCEPTED TO ACCEPTE									
14. I hereby certify that the foregoing is true and correct. Electronic Submission #211168 verified by the BLM Well Information System For BURNETT OIL COMPANY INC, sent to the Carlsbad Committed to AFMSS for processing by KURT SIMMONS on 06/20/2013 (13KMS6562SE) Name(Printed/Typed) LESLIE M GARVIS Title REGULATORY COORDINATOR									
Signature (Electronic S	Submission)	_	Date 06/19/20	013					
THIS SPACE FOR FEDERAL OR STATE OFFICE USE									
_Approved By ACCEPTED				JAMES A AMOS _{Title} SUPERVISOR EPS			Date 06/23/2013		
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to condu	iitable title to those rights in the		Office Carlsbac	<u> </u>					
Fitle 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false firstitions or fraudulent statements or representations as to any matter within its jurisdiction.									

Additional data for EC transaction #211168 that would not fit on the form

32. Additional remarks, continued

6/3/13 - SLICKWATER FRAC W 468,594 GAL SLICKWATER, 20,448# 100 MESH, 146,769# 40/70 SN.

6/5/13 - INSTALLED: 167 JTS 2 7/8" J55 TBG 5290', KB (9') 5299', SN 5300', ESP 5355', DESANDER 5359',2 JTS 2 7/8" J55 TBG 5423', INTAKE 5327'

6/9/13 - FIRST DAY OF PRODUCTION 06/08/13. 22 BO, 1251 BLW, 33 MCF, 792 BHP, 1714' FLAP, 17,145 BLWTR, 50# CSG, 300# TBG, 55 HZ.

6/19/13 - 24 HR Test - 136 BO, 467 BLW, 288 MCF, 233 BHP, 422' FLAP, 10,031 BLWTR, 50# CSG, 250# TBG, 54 HZ.