UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT DECEIVED

OCD Artesia

FORM APPROVED OMB NO. 1004-0135 Expires: July 31, 2010

SUNDRY Do not use the	5. Lease Serial No. NMLC029395A						
abandoned we	6. If Indian, Allottee of	or Tribe Name					
SUBMIT IN TRI	7. If Unit or CA/Agre	ement, Name and/or No.					
Type of Well Gas Well	8. Well Name and No. TURNER A 032						
Name of Operator LINN OPERATING INC		9. API Well No. 30-015-05230					
3a. Address 600 TRAVIS STREET, SUITE 5100 Ph: 281-84 HOUSTON, TX 77002			(include area code) 0-4000				
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description)			11. County or Parish,	and State	
Sec 18 T17S R31E Mer NMP 32.831808 N Lat, 103.905954	EL			EDDY COUNT	Υ, NM		
12. CHECK APPI	ROPRIATE BOX(ES) TO	DINDICATE	NATURE OF I	NOTICE, RI	EPORT, OR OTHE	R DATA	
TYPE OF SUBMISSION		TYPE OF ACTION					
■ Notice of Intent	☐ Acidize	🗖 Deep	en	☐ Product	ion (Start/Resume)	☐ Water Shut-Off	
_	☐ Alter Casing	☐ Frac	ure Treat	☐ Reclam.	ation	■ Well Integrity	
☐ Subsequent Report	□ Casing Repair	□ New	Construction	☐ Recomp	olete	Other	
☐ Final Abandonment Notice	☐ Change Plans	🔀 Plug	and Abandon	□ Tempor	arily Abandon		
	Convert to Injection	☐ Plug	Back	☐ Water D	Disposal		
13. Describe Proposed or Completed Ope If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final Ab- determined that the site is ready for fi	ally or recomplete horizontally, rk will be performed or provide to perations. If the operation re	give subsurface lette Bond No. on sults in a multiple	ocations and measurable with BLM/BIA	ired and true ve A. Required sul	ertical depths of all perting begunnt reports shall be	ient markers and zones. filed within 30 days	
PROPOSED P&A PROCEDURES:				CO	NDITIONS OF	APPROVAL	
1. MIRU PLUGGING UNIT. F	RIH W/ TBG. TAG CMT @	9 1665'. CIRC	MUD LADEN F	ELUID.	•		
2. S POT-30-SXS-CMT-@-13 0.	D'. WOC AND TAG	ertora	te@/5	350,5	'QZ emiti	to 1250.	
3. PERF 7" CSG @ 580". CIR	C CMT TO SURFACE IN	SIDE AND OU	JT W/ APPROX	160 SXS C	NAT.	ON PROCEDURE	
4. CUT OFF WELLHEAD, INSTALL DRY HOLE MARKER, RDMO. ATTACHED						ACHED	
CURRENT AND PROPOSED	WELLBORE DIAGRAMS	ATTACHED	- //	/	/ , D	1',	
At cut-off v	verify ent	to Sui	rt. all	ann	celus, F.	emecial	
cont may be	required,		scound (evel 1	Dry Hole Ma	Ker Required	
14. I hereby certify that the foregoing is	Electronic Submission #	221191 verified PERATING IN	by the BLM Wel	arisbad	•		
Name(Printed/Typed) TERRY B CALLAHAN			Title REG Co	OMPLIANCE	SPECIALIST III		
Signature (Electronic S	Submission)		Date 09/25/2	013	Accepted NM L	for record	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE							
Approved By James	a. amos		Title S/	305		Date/0-20-/	
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent hould entitle the applicant to conduct the applicant the applicant to conduct the applicant the applicant the applicant to conduct the applicant the ap	Office Cf	^O					

Well Frame:	Turner A #31	
	The state of the s	
ocation	Location: 18507A: 16507A1	w
ection!	F: 175 R: 31E Sec: 18	
loci:		
Ounty:	[ddy-	3
i/Local	,	\$
ald:	Fren Grayburg 1924 pan Devations:	7
L.	3701'	\$
F. B-G) Colo		3
wiley?		Z
czei-z Aez-di	Estal.	
-		
/72/1951	Soud 12-1/2" hole & 6/6 to 1955"; Set 7" cig @ 1,895" & emid in/ 100 sa emt. Set 5-1/2" cig at bottom, top	3
	Ø 1885', perferesed at pay intervals, no cost.	3
V14/19/1	1920-1965 shot with 25C gra. Kitro-ghearin	3
/17/1933	Well tested and produced 25 6GPD.	35 55
/10/1951	RiH w/ stg and set @ 1961'	\$
/78/1971	NOI filed to TA well (less than 3 0020)	à.
//78/1971 /5/1972 //29/1979	PON w/thg: Copped with with 2000s WOC valve. Well is TA'd. Held for extended potential Bradesheed was piped to sunface w/ a valve installed for pressure checks in accordance w/ GCD	\$
	Plug back w/ sand to \$815', Spot 20 sas cres, top of cmi plug (# 1605', Well is 14'd. Held for waterflood	8
/34/1994	pojenital	\$
		, i
		3
·		Š
		į.
		150
		š
		Ž
		3
		8
		1
		1
		100
		8.00
		8
		241
		NUCLEAR SANDE
		WC CO
		7
	ļ	, ,
		. :
		i
		İ

				Well Name:	further A #32
	Current	_		SP3 Np.:	10-012-02330
77	ofibore Diagra	9 1 D		ippd Date:	1/23/1953
213		1112		WED Update:	9/14/2013 R. Van Howe
Á		113		Hote Stra:	13-1/3*
		18		Suri Coc:	9-5/8", 384, 1-55
\$				Cement Sleed:	\$3 m
1		1118		Depth:	\$10"
3		1110		£10C	N/A
3 9		Zamman we were		Hole Mes:	y'
		11/2	9-5/8", 750	121.Sec	7*, 204
4		0	MI @ 513.		
3		8			***
3		Š		Coment Blead:	100 ses
9		į,		Betures:	
		ă		inc.	N/# .
8		8		L	
$(x_i,x_i)_{i=1}^{N}$			<u>Add on frequent less</u> 4/16/1953 Add on frequent less 4/16/1953 1,910-1,957	E,3201.E,957' shot with 150 gzs Phro-ghyearin	
West Action		in the second			Tything Decali
G		3		Idints	Description 2:3/5
ğ	i	18			
8		3		Phy Depth	
ŝ		8			
8		3		<u> </u>	And Detail (top to bottom)
- 3		8		Rods	Description
13		â			
15		3			
8		统			
8		搓		1	وندسته شريع والرسيب من وما في منطق والمنظوم بالتاليوف في في وقع ويواني المنظمة المنطقة والمنطقة والمنط
8	-	推			-
		1		Eumeina Moni	
3		8			
2	302335939	Æ	Spat cret w/ 30 cas		
		12			
3	134646351436363	ř.	Plagged with sand from	n 1935'-TD	
			7", 204 set@ 1015"		
ı		1		Hole Stre:	€*
		1		Pied Sin	5-1/37, 17x
		1		Capacity (bbt/ft):	1
				Cament Slynd: Retuins:	nen#
	\$and	1		TOC:	
				O-pih	1805'-1965'
-		1		1	
j			1,920,-1,924,	l	<u> </u>
		l		1	
			1.954'.1 057'		

TD: 1,965'

Open Hele from 1895'-1965'

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 East Greene Street Carlsbad, New Mexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>ninety (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

The rig used for the plugging procedure cannot be released and moved off without the prior approval of the authorized officer. Failure to do so may result in enforcement action.

- 2. <u>Notification:</u> Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The BOP must be installed and maintained as per API and manufacturer recommendations. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of **brine** water. Minimum nine (9) pounds per gallon.
- 5. <u>Cement Requirement</u>: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. Any plug that requires a tag will have a minimum WOC time of 4 hours.

In lieu of a cement plug across perforations in a cased hole (not for any other plugs), a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient. Before pumping or bailing cement on top of CIBP, tag will be required to verify depth. Based on depth, a tag of the cement may be deemed necessary.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The BLM is to be notified a minimum of 4 hours prior to the wellhead being cut off to verify that cement is to surface in the casing and all annuluses. Wellhead cut off shall commence within ten (10) calendar days of the well being plugged. If the cut off cannot be done by the 10th day, the BLM is to be contacted with justification to receive an extension for completing the cut off.

The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement, unless otherwise noted in COA (requirements will be attached). The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and three copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash</u>: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration will be required. See attached reclamation procedure.

Requirements for dry hole markers in Prairie Chicken Habitat <u>Well Identification Markers</u> Conditions of Approval (COA)

The BLM Carlsbad Field Office (CFO) Conditions of Approval (COA) have required that ground level dry hole markers be placed on wells within the Lesser Prairie Chicken habitat area. Onshore Order 2.III.G.10 allows for surface caps to be installed at the base of the cellar of a minimum of 3 feet below the restored ground level. Therefore, these markers shall be set a minimum of 3 feet below the restored ground level. All markers shall be identified by GPS coordinates.

The dry hole markers will be to the following specifications. The operator will construct the markers as follows:

- 1. A steel plate 1/4 inch thick shall be placed on the wellbore, welded in place and with a weep hole.
- 2. Aluminum data plates may be bolted to the steel plate with minimum ¼ inch bolts and locking nuts or self tapping fine threaded screws. A minimum of one in each corner is to be installed on each plate.
- 3. An 8 inch x 8 inch aluminum plate, which is 12 gauge or .080 sign material (1/8 inch aluminum plate may be used in place of the .080 plate) with the required information for that well stamped or engraved in a minimum 3/8 inch tall letter or number.
- 4. The following information will be stamped or engraved on the 8 inch X 8 inch aluminum plate in the following order.
 - a. First row: Operator's name
 - b. Second row: Well name and number
 - c. Third row: Legal location to include ¼ ¼, Section, Township, and range. If the legal location cannot be placed on one row it can be split into two rows with the ¼ ¼ (example: 1980 FNL 1980 FWL) being on the top row.
 - d. Fourth row: Lease Number and API number.
 - i. Example marker plate: (attached)

Notification to NMOCD of this marker type will be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a below ground level dry hole marker was installed and GPS coordinates recorded as required in the COAs from the BLM.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Reclamation Objectives and Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses. At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land and water are restored.

The long-term objective of final reclamation is to set the course for eventual ecosystem restoration, including the restoration of the natural vegetation community, hydrology, and wildlife habitats. In most cases this means returning the land to a condition approximating or equal to that which existed prior to the disturbance. The final goal of reclamation is to restore the character of the land and water to its predisturbance condition. The operator is generally not responsible for achieving full ecological restoration of the site. Instead, the operator must achieve the short-term stability, visual, hydrological, and productivity objectives of the surface management agency and take steps necessary to ensure that long-term objectives will be reached through natural processes.

To achieve these objectives, remove any and all contaminants, scrap/trash, equipment, pipelines and powerlines. Strip and remove caliche, contour the location to blend with the surrounding landscape, redistribute the native soils, provide erosion control as needed, rip and seed as specified in the original APD COA. This will apply to well pads, facilities, and access roads. Barricade access road at the starting point. If reserve pits have not reclaimed due to salts or other contaminants, submit a plan for approval, as to how you propose to provide adequate restoration of the pit area.

- The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of
 Operations must include adequate measures for stabilization and reclamation of disturbed lands.
 Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD
 process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). For final reclamation, the appropriate time for submittal would be when filing the Notice of Intent, or the Subsequent Report of Abandonment, Sundry Notices and Reports on Wells (Form 3160-5). Interim reclamation is to be completed within 6 months of well completion, and final reclamation is to be completed within 6 months of well abandonment.
- 3. The operator must file a Subsequent Report Plug and Abandonment (Form 3160-5) following the plugging of a well.
- 4. Previous instruction had you waiting for a BLM specialist to inspect the location and provide you with reclamation requirements. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with reclamation as per approved APD. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation

- equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 5. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 6. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met. If after two growing seasons the location and/or access roads are not showing the potential for successful revegetation, additional actions may be needed. When you feel the BLM objectives have been met submit a Final Abandonment Notice (FAN), Form 3160-5, stating that all reclamation requirements have been achieved and the location and/or access road is ready for a final abandonment inspection.
- 7. At this time the BLM specialist will inspect the location and/or access road. If the native soils and contour have been restored, and the revegetation is successful, the FAN will be approved, releasing the operator of any further liability of the location and/or access road. If the location and/or access road have not achieved the objective, you will be notified as to additional work needed or additional time being needed to achieve the objective.

If there are any questions, please feel free to contact any of the following specialists:

Inspection & Enforcement

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909, 575-361-2648 (Cell)

Mike Burton Environmental Protection Specialist 575-234-2226

Jeffery Robertson Natural Resource Specialist 575-234-2230

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Doug Hoag Civil Engineering Technician 575-234-5979

Linda Denniston
Environmental Protection Specialist
575-234-5974

Solomon Hughes Natural Resource Specialist 575-234-5951

Permitting

Cody Layton Natural Resource Specialist 575-234-5959

Trishia Bad Bear Natural Resource Specialist 575-393-3612

Todd Suter Surface Protection Specialist 575-234-5987

Tanner Nygren Natural Resource Specialist 575-234-5975

Amanda Lynch Natural Resource Specialist 575-234-5922

Legion Brumley Environmental Protection Specialist 575-234-5957

Realty, Compliance

Randy Pair Environmental Protection Specialist 575-234-6240