

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-41729
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Salt Draw 2 CN Fee
8. Well Number 2H
9. OGRID Number 14744
10. Pool name or Wildcat WC; Salt Draw; Wolfcamp (Gas) 97721

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other
2. Name of Operator Mewbourne Oil Company
3. Address of Operator PO Box 5270, Hobbs, NM 88241
4. Well Location Unit Letter C : 150 feet from the North line and 1670 feet from the West line Section 2 Township 25S Range 28E NMPM Eddy County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 2971'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒


OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

01/05/14...TD 12 1/4" hole. TD'd hole @ 2560'. Ran 2560' of 9 5/8" 36# J55 LT&C csg. Cemented with 600 sks BJ Lite Class "C" (35:65:6) w/additives. Mixed @ 12.5 #/g w/ 2.06 yd. Tail with 200 sks Class "C" w/additives. Mixed @ 14.8 #/g w/ 1.33 yd. Plug down @ 5:00 P.M. 01/05/14. Circ 191 sks to the pit. Tested BOPE to 5000# & Annular to 2500#. At 6:00 P.M. 01/06/14, tested csg to 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

Spud Date: 12/31/2013

Rig Release Date:



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 01/09/14

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: AS H. Spewison TITLE AS H. Spewison DATE 1/15/2014

Conditions of Approval (if any):