

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-015-41782

5. Indicate Type of Lease
STATE ☐ FEE ☒
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Yates Petroleum Corporation

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location

Unit Letter	A	:	250	feet from the	North	line and	660	feet from the	East	line
Unit Letter	A	:	330	feet from the	North	line and	660	feet from the	East	line
Section	23		Township	19S	Range	25E	NMPM	Eddy	County	
Section	14		Township	19S	Range	25E	NMPM	Eddy	County	

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,425' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: production casing ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/30/14 - Drilled to 2,180' KOP and continued drilling directional. Drilled to 3,048' and reduced hole to 8-1/2" and resumed drilling.
2/4/14 - Reached TD 8-1/2" hole to 7,480'.
2/5/14 - Set 5-1/2" 17# L-80 BT&C casing at 7,480'. Float collar set at 7,433'. Cemented with 450 sx TXI Litewt + 4 lb/sx B288 + 0.2% D013 + 3% D020 + 5 lb/sx D042 + 5% D044 + 0.2% D046 + 0.2% D065 + 0.125 lb/sx D130 + 0.02% D208 (yld 2.07, wt 12.00).
Tailed in with 800 sx TXI Litewt + 0.2% D046 + 0.5% D112 + 30% D151 + 1.5% D174 + 0.12% D208 (yld 1.82, wt 13.00). Circulated 185 sacks to surface. ND BOP.

Spud Date:

1/23/14

Rig Release Date:

2/6/14

RECEIVED

FEB 18 2014

NMOCD ARTESIA

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Laura Watts TITLE Regulatory Reporting Technician DATE February 14, 2014

Type or print name Laura Watts E-mail address: laura@yatespetroleum.com PHONE: 575-748-4272

For State Use Only

APPROVED BY: Dr. Dade TITLE District Supervisor DATE 2/19/14

Conditions of Approval (if any):