

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTFORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010**SUNDRY NOTICES AND REPORTS ON WELLS**
Do not use this form for proposals to drill or to re-enter and
Abandoned well. Use Form 3160-3 (APD) for such proposals**SUBMIT IN TRIPLICATE – Other instructions on page 2.**

5. Lease Serial No.

NMLC-029395B

6. If Indian, Allottee or Tribe Name

7. If Unit of CA/Agreement, Name and/or No.

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

8. Well Name and No.

LEE FEDERAL 73 <308720>

2. Name of Operator

APACHE CORPORATION <873>

9. API Well No.

30-015-41113

3. Address

**303 VETERANS AIRPARK LN, #3000
MIDLAND, TX 79705**

3b. Phone No. (include area Code)

432-818-1000 / 432-818-1168

10. Field and Pool or Exploratory Area

CEDAR LAKE; GLORIETA-YESO <96831>

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

UL 1, SEC 20, T17S, R31E, 1570' FSL & 465' FEL

11. County or Parish, State

EDDY COUNTY, NM

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION

- ☐
- Notice of Intent
-
- ☒
- Subsequent Report
-
- ☐
- Final Abandonment Notice

- ☐
- Acidize
-
- ☐
- Alter Casing
-
- ☐
- Casing Repair
-
- ☐
- Change Plans
-
- ☐
- Convert to Injection

- ☐
- Deepen
-
- ☐
- Fracture Treat
-
- ☐
- New Construction
-
- ☐
- Plug and Abandon
-
- ☐
- Plug Back

- ☐
- Production (Start/Resume)
-
- ☐
- Reclamation
-
- ☐
- Recomplete
-
- ☐
- Temporarily Abandon
-
- ☐
- Water Disposal

- ☐
- Water Shut-Off
-
- ☐
- Well Integrity
-
- ☒
- Other

**DRILLING OPS:
CASING & CEMENT
REPORT**

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directional or recompleat horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attached the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Bond No: **BLM-CO-1463****11/2/2013 SPUD****11/3/2013 Surface Csg 13 3/8, Hole 17.5", H-40, 48# set @ 371' Cmt with:**

LEAD: 200 sx Class C (14.4 wt 1.55 yld)

TAIL: 520 sx Class C (14.8 wt, 1.34 yld)

CIRC 224 SX To Surface.

WOC.

Surface Csg Pressure Test: 1200 PSI/30 min

REPORT CONTINUED ON PAGE 2.

ACCEPTED FOR RECORD

MAR 1 2014

BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICE

14. I hereby certify that the foregoing is true and correct.

Name (Printed/Typed)

MICHELLE COOPERTitle **DRILLING TECH**

Signature

*Michelle Cooper*Date **1/28/2014**CRD 3/11/14
Accepted for Record
NMLC**THIS SPACE FOR FEDERAL OR STATE OFFICE USE**

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

LEE, FEDERAL 73 - Csg & Cmt End of Well Sundry

11/6/2013 Drl F/3301' – T/3417' TD.

11/7/2013 Intermediate Csg 8 5/8, Hole 11", J-55, 32# SET @ 3417' Circ Hole

Lead: 650 sx Class C (12.5 wt, 2.13 yld)

Tail: 440 sx Class C (14.8 wt, 1.33 yld)
Circ 171 sx to surface.

Csg Pressure Test: 1200 PSI/30 min

11/12/2013 Drl F/6300' – T/6362' TD. Circ and Cond Hole. RU Schlumberger Loggers

11/13/2013 Production Csg 5.5, Hole 7.875, J-55, 17# set @ 6362' Cmt with:

Lead: 410 sx Class C (12.6 wt, 2.00 yld)

Tail: 690 sx Class C (14.2 wt, 1.31 yld)

Circ 185 sx to surface.

Prod Csg pressure test 2500 PSI/30 min-OK.

11/13/2013- RR