

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103

Revised August 1, 2011

**RECEIVED**

OIL CONSERVATION DIVISION

MAR 24 2014

220 South St. Francis Dr.  
Santa Fe, NM 87505**NMOC D ARTESIA**

WELL API NO.

30-015-41304

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil &amp; Gas Lease No.

7. Lease Name or Unit Agreement Name

San Lorenzo 9 OB Fee

8. Well Number 1H

9. OGRID Number

14744

10. Pool name or Wildcat

WC-015 S25281D; Wolfcamp (Gas) 97949

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other

2. Name of Operator

Mewbourne Oil Company

3. Address of Operator

PO Box 5270, Hobbs, New Mexico

4. Well Location

Unit Letter O : 200 feet from the South line and 2450 feet from the East lineSection 9 Township 25S Range 28E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

2972' GL

## 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

## NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐DOWNHOLE COMMINGLE ☐OTHER: ☐

## SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐COMMENCE DRILLING OPNS. ☐ P AND A ☐CASING/CEMENT JOB ☒OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

02/09/14...MI &amp; spud 17 1/2" hole. TD'd hole @ 435'. Ran 435' of 13 3/8" 48# H40 ST&amp;C csg. Cemented with 500 sks Class "C" w/2% CaCl2. Mixed @ 14.8 #/g w/ 1.35 yd. Circ 125 sks cement to pit. WOC 18 hrs. At 1:00 P.M. 02/11/14, tested csg &amp; BOPE to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

02/13/14...TD 12 1/4" hole at 2525'. Ran 2525' of 9 5/8" 36# J55 LT&amp;C csg. Cemented with 600 sks BJ Lite Class C (35:65:6) w/additives. Mixed @ 12.5 #/g w/ 2.07 yd. Tail w/200 sks Class C w/0.25% CaCl2. Mixed @ 14.8 #/g w/ 1.33 yd. Plug down @ 11:30 PM 02/13/14. Circulated 150 sks of cmt to the pit. Tested BOPE to 5000# &amp; annular to 2500#. At 6:00 P.M. 02/14/14, tested csg 1500# for 30 minutes, held OK. Drilled out with 8 3/4" bit.

Spud Date: 02/09/14

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 03/19/14Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE Asst. Reg. Sec. DATE 3/25/2014

Conditions of Approval (if any):