Form 3160-5 (August 2007)

UNITED STATES

OCD Artesia MAR 1 9 2014 |

FORM APPROVED

	EPARTMENT OF THE I		NMOCD	AD-	Expires	NO. 1004-0135 s: July 31, 2010	,
SUNDRY	UREAU OF LAND MANA NOTICES AND REPO is form for proposals to	RTS ON WI		AHIES	Expires Lease Serial No. NMNM38636		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use form 3160-3 (APD) for such proposals.					6. If Indian, Allottee	or Tribe Name	
SUBMIT IN TRI	PLICATE - Other instruc	ctions on rev	erse side.		7. If Unit or CA/Agr	eement, Name and/or No.	
Type of Well Gas Well ☐ Oth	ner .				8. Well Name and No AMOCO FEDER		
Name of Operator CIMAREX ENERGY CO OF COMMANDER	Contact: COLORA B@ ail: DEYLER@		S.COM		9. API Well No. 30-015-24826		
3a. Address 600 N. MARIENFELD, SUITE MIDLAND, TX 79701		Ph: 432-68	. (include area code) 7-3033) ,	10. Field and Pool, o BRUSHY DRA	r Exploratory W; DELAWARE	
4. Location of Well (Footage, Sec., T	., R., M., or Survey Description	1)			11. County or Parish	, and State	
Sec 27 T26S R29E Mer NMP	NENE 990FNL 330FEL	• *			EDDY COUNT	Y, NM	
12. СНЕСК АРРГ	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF 1	NOTICE, RE	EPORT, OR OTHE	ER DATA	
TYPE OF SUBMISSION			TYPE O	F ACTION			
■ Notice of Intent	☐ Acidize	□ Dee	pen	☐ Producti	ion (Start/Resume)	☐ Water Shut-Off	
_	☐ Alter Casing	☐ Frac	ture Treat	□ Reclama	ation	■ Well Integrity	
☐ Subsequent Report	□ Casing Repair	☐ Nev	Construction	□ Recomp	lete	☐ Other	
☐ Final Abandonment Notice	☐ Change Plans	🛛 Plug	and Abandon	☐ Tempora	arily Abandon		•
	☐ Convert to Injection	🗖 Plug	; Back	■ Water D	isposal		
13. Describe Proposed or Completed Ope If the proposal is to deepen directions Attach the Bond under which the wor following completion of the involved testing has been completed. Final At determined that the site is ready for fi	ally or recomplete horizontally, rk will be performed or provide l operations. If the operation re bandonment Notices shall be fil inal inspection.)	give subsurface the Bond No. or sults in a multipled only after all	locations and measu if file with BLM/BIA e completion or reco requirements, includ	red and true ve A. Required sub completion in a re	rtical depths of all perti- osequent reports shall be new interval, a Form 31 n, have been completed	inent markers and zones. e filed within 30 days 60-4 shall be filed once , and the operator has	
1) SET 5-1/2" CIBP @ 4,900; 2) PUMP 25 SXS.CMT. @ 4,0 3) PERF.X ATTEMPT TO SQ 4) PERF. X ATTEMPT TO SQ 5) PERF. X CIRC. TO SURF., 6) DIG OUT X CUT OFF WEL	096'-3,956'(T/C.C.) Z.105 SXS.CMT. @ 2,98 Z. 110 SXS.CMT. @ 562 FILLING ALL ANNULI, 2	6'-2,650'(T/DI 2'-250'(8-5/8"\$ 25 SXS.CMT	.WR.,B/SALT);V SHOE,T/SALT-A @ 63'-3'.		AIIA	ON PROCEDURE ACHED RKER	
DURING THIS PROCEDURE THE REQUIRED DISPOSAL,	WE PLAN TO USE THE PER OCD RULE 19.15.1	CLOSED-LC	OP SYSTEM W			1	
	المستجمع ومستواها والمتأثر المتارج ومراكب ومراكب			SEE A	TTACHED FO	OR The state of th	
<u> (2)</u>	cepted for record	PIOC		CONDI	ITIONS OF A	IPPROVAL	
14. I hereby certify that the foregoing is	# Electronic Submission # For CIMAREX ENE	RGY CO OF C	OLÓRADO, sent	to the Carlsb	aď	,	
Name (Printed/Typed) DAVID A I	Committed to AFMSS t EYLER	or processing	Title AGENT		2 014 () 	•	
Signature (Electronic S			Date 02/25/2				
	THIS SPACE FO	OR FEDERA	L OR STATE	OFFICE US	SE		
Approved By formus (h. Como		Title SE	15	-	3-/2-/- Date	/
Conditions of approval, if any, are attached certify that the applicant holds legal or equivalent would entitle the applicant to conductive would entitle the applicant to conductive the applicant to conduct the applicant the applicant to conduct the applicant the applica	litable title to those rights in the		Office CF	0	· · · · · · · · · · · · · · · · · · ·	,	
7							_

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.



8 5/8" 24# csg @ 512' Cmt w/300 sx, circ to surface

Estimated TOC @ 3420'

5-1/2" 15.5# K55 LTC csg @ 5096' Cmt w/350 sx, Est TOC @ 3420'

PBTD: 5061' TD: 5125'

Cimarex Energy Co. of Colorado Amoco Federal 5

API'30-015-24826 990' FNL & 330' FEL, Sec 27, T26S R29E Eddy County, NM GL:2878.4' KB; 2886' Spud: 4/8/84

API No. 30-015-24826

12 1/4" hole to 512'

Tubing Detail

KE Correction

Quantity	Description	Length	Setting Depth
	KP		0.00
141 :	2-7/8" N 80 8rd tbg	4553 GZ	4553.62
- 3	2-7:81 x 5-1/21 TAC	3.5	4556,52
14	2-7/8" N-60 8rd (bg	453.6	. 5016.12
1	API SN	1.1	5011 22
	,	·	5011.22

Rod Detail

Amoco Federal 5

KB Correct on

Quantity	Description	Length	[
1	1-4/4* PR	12 00	12.00
1	7/6" x 8" rad sub	5.00	26.00
51	7/8" (eds	1275,00	1295.00 =
129 .	3/4" rods	(3225,00	4520.00
12	7/8" roas	390.00	4820 00
1	7/8"x2" litt sub w/ on/off tool	2.00	4522.00

Delaware Perfs:

4944', 47', 50', 59', 61, 68', 70', 79', 81', 83', 88', 90', 5001', 3', 5', 7', 9', 13', 15', 17', 19', 21', 23', 25', 30', 31'

7 7/8" hole to TD 5125'

Cimarex Energy Co. of Colorado Amoco Federal 5 API 30-015-24826 990' FNL & 330' FEL, Sec 27, T26S R29E Eddy County, NM -GL:2878.4' KB: 2886' Spud: 4/8/84 PERF. X CIRC. 25 5X5. @ 63 - 3 . API No. 30-015-24826 PXA Rustle 310 FLUID 7/5alf 500 B/S-H 2675 8 5/8" 24# csg @ 512' ' Cmt w/300 sx, circ to surface 12 1/4" hole to 512' De1. 2850 PERF. X SQZ. 110 SXS. C- 562-250-796 brig FLUID PERF. X 502. 105 5x5.@2986-2650-111pxA FLUID Estimated TOC @ 3420' Pump 25 SXS. CMT. @ 4096 - 3956! Cherry Cyn 4026 Dump 25 5x5. @ 4900'- 4760! Delaware Perfs: Cherry Cyn Perfs. 4944', 47', 50', 59', 61, 68', 70', 79', 81', 83', 88', 90', 5001', 3', 5', 7', 9', 13', 15', 17', 19', 5-1/2" 15.5# K55 LTC csg @ 5096" 21', 23', 25', 30', 31' Cmt w/350 sx, Est TOC @ 3420' 7 7/8" hole to TD 5125' PBTD: 5061' TD: 5125'

DAE 02/20/14

BUREAU OF LAND MANAGEMENT Carlsbad Field Office 620 East Greene Street Carlsbad, New Wexico 88220 575-234-5972

Permanent Abandonment of Federal Wells Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within <u>nine(v (90)</u> days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

- 2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.
- 3. <u>Blowout Preventers</u>: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.
- 4. <u>Mud Requirement:</u> Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.
- 5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C" for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

- 6. <u>Dry Hole Marker</u>: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).
- 7. <u>Subsequent Plugging Reporting</u>: Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment; Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. **Show date well was plugged.**
- 8. <u>Trash:</u> All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office 620 E. Greene St. Carlsbad, New Mexico 88220-6292 www.blm.gov/nm



In Reply Refer To: 1310

Interim Reclamation Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses.

Interim reclamation consists of minimizing the footprint of disturbance by reclaiming all portions of the well site not needed for production operations. The portions of the cleared well site not needed for operational and safety purposes are recontoured to a final or intermediate contour that blends with the surrounding topography as much as possible. Sufficient level area remains for setup of a workover rig and to park equipment. Topsoil is respread over areas not needed for all-weather operations. Production facilities should be clustered to maximize the opportunity for interim reclamation. In order to inspect and operate the well or complete workover operations, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is repaired and reclaimed following use.

To reduce final reclamation costs; maintain healthy, biologically active topsoil; and to minimize habitat, visual, and forage loss during the life of the well, all salvaged topsoil should be spread over the area of interim reclamation, rather than stockpiled.

- 1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
- 2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). Interim reclamation is to be completed within 6 months of well completion.
- 3. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with interim reclamation as per approved APD or Sundry Notice. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
- 4. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
- 5. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos Supervisory Environmental Protection Specialist 575-234-5909 (Office), 575-361-2648 (Cell)

Linda Denniston Environmental Protection Specialist '575-234-5974

Jennifer Van Curen Environmental Protection Specialist 575-234-5905

Mike Burton
Environmental Protection Specialist
575-234-2226

Jeffery Robertson Natural Resource Specialist

Solomon Hughes Natural Resource Specialist 575-234-5951

Douglas Hoag Civil Engineering Technician 575-234-5979