Submit I Copy To Appropriate District State of New Mexico	Form C-103
Office  District 1 – (575) 393-6161  District 1 – (575) 748-1283  District 1 – (575) 748-1283	Revised July 18, 2013
1625 N. French Dr., Hobbs, NMC EVELVELV	WELL API NO.
811 S. First St. Artesia NM 88210. 20 20QIL CONSERVATION DIVISION	30-005-60909
District II - (575) 748-1283 811 S. First St., Artesia, NM 88210 District III - (505) 334-61 8 APR 2 8 2014 CONSERVATION DIVISION 1220 South St. Francis Dr.	5. Indicate Type of Lease
1000 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	STATE FEE
District IV – (505) 476-3460 ARTESIA Santa Fe, NM 87505 1220 S. St. Francis Dr., Santa Fe, NM 87505	6. State Oil & Gas Lease No.
87505	
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A	Ric
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	8. Well Number
1. Type of Well: Oil Well Gas Well Other P&A	2
2. Name of Operator	9. OGRID Number
Yates Petroleum Corporation	025575
3. Address of Operator	10. Pool name or Wildcat
105 South Fourth Street, Artesia, NM 88210	Pecos Slope; Abo
4. Well Location	
	660 feet from the West line
<del></del>	<del></del>
Section 29 Township 6S Range 25E	NMPM. Chaves County
11. Elevation (Show whether DR, RKB, RT, GR, etc.	2.) 建起头线效应量源
3,794' GR	
12. Check Appropriate Box to Indicate Nature of Notice	, Report or Other Data
	•
	BSEQUENT REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WO	RK
TEMPORARILY ABANDON	RILLING OPNS.□ P AND A 🛛
PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEME	NT JOB 🔲
DOWNHOLE COMMINGLE	
CLOSED-LOOP SYSTEM	
OTHER: OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, a	
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple C	ompletions: Attach wellbore diagram of
proposed completion or recompletion.	
A/OO/AA NHI DOD	
4/20/14 – NU BOP.	1.60111 to 1.0 to 1.05 1.7600.
4/21/14 – RIH with GR/JB to 3,430', set a 4-1/2" CIBP at 3,426'. Tagged CIBP and pum	ped 60 bbls salt gel. Spotted 25 sacks "C" Neat
on CIBP. Perf'd at 1,850'. Pumped 25 sacks Class "C" Neat. Broke circulation. Displace	
4/20/14 Taggod alice at 1 600? Double at 1 246? Double 25 and Class (C2) Next Di-	
	splaced to 1,246'. WOC
4/23/14 - Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp	splaced to 1,246'. WOC
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP.	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.
4/23/14 - Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP.	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP.	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar.	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar.	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar.	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar.   Spud Date:  Rig Release Date:	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.  ELL IS PLUGGED AND ABANDONED.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar.   Spud Date:  Rig Release Date:	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.  ELL IS PLUGGED AND ABANDONED.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar.   Spud Date:  Rig Release Date:	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.  ELL IS PLUGGED AND ABANDONED.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar. Spud Date:  Rig Release Date:	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.  ELL IS PLUGGED AND ABANDONED.  ge and belief.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar. When the same part of the same	splaced to 1,246'. WOC laced to 750'. WOC 4 hours. Tagged at 730'.  ELL IS PLUGGED AND ABANDONED.  ge and belief.
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar. When the same part of the second process of the sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cem	ge and belief.  Technician DATE April 28, 2014
A/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar.   Spud Date:  Rig Release Date:  I hereby certify that the information above is true and complete to the best of my knowled  SIGNATURE  TITLE Regulatory Reporting  Type or print name  Laura Watts  E-mail address: laura@yatespetrole	ge and belief.  Technician DATE April 28, 2014
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar. When the same part of the second process of the sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 850'. Pumped 25 sacks cem	ge and belief.  Technician DATE April 28, 2014
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar. Wellhead. Installed dry hole m	ge and belief.  Technician DATE April 28, 2014  Lum.com PHONE: 575-748-4272
4/23/14 – Tagged plug at 1,224'. Perf'd 4 holes at 850'. Pumped 25 sacks cement. Disp Perf'd 4 holes at 60'. Pumped 20 sacks and circulated to surface. ND BOP. 4/25/14 – Dug out cellar and cutoff wellhead. Installed dry hole marker. Filled cellar.   Spud Date:  Rig Release Date:  I hereby certify that the information above is true and complete to the best of my knowled SIGNATURE  TITLE Regulatory Reporting  Type or print name  Laura Watts  E-mail address: laura@yatespetrole	ge and belief.  Technician DATE April 28, 2014

\$50BMit Subsequent C-103

Approved for plugging of well bore only.
I lability under bond is retained pending receipt of C-103 (Subsequent Report of Well Plugging) which may be found at OCD Web Page under Forms, www.cmnrd.state.nm.us/ocd.