Submit 1 Copy To Appropriate District RECEINES State of New Mexico Office District 1 – (575) 393-6161 1625 N. French Dr., Hobbs, NM 88240 ADD 2014	Form C-103 Revised August 1, 2011
1625 N. French Dr., Hobbs, NM 88240 District II - (575) 748-1283 APR 3 0 2014 DISTRICT PROPERTY ATTION DIVISION	WELL API NO. 30-015-10102
OLL GERN GOLD STREET STREET	5. Indicate Type of Lease
District III – (505) 334-6178 NMOCD ARTE 220 South St. Francis Dr. 1000 Rio Brazos Rd., Aztec, NM. 87410 Santa Fe, NM 87505	STATE S FEE S
District IV - (505) 476-3460 Santa Fe, INIVI 87303 1220 S. St. Francis Dr., Santa Fe, NM 87505	6. State Oil & Gas Lease No. NM-7075
SUNDRY NOTICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	PAN AM STATE
1. Type of Well: Oil Well Gas Well Other	8. Well Number 001
2. Name of Operator	9. OGRID Number
Alamo Permian Resources. LLC 3. Address of Operator	274841 10. Pool name or Wildcat
415 W. Wall Street, Suite 500, Midland, TX 79701	EMPIRE; YATES-SR, EAST
4. Well Location	
Unit Letter I : 2310 feet from the S line and 330 feet from the	E line .
Section 28 Township 17S Range 28E NMPM	County EDDY
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	of the second se
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐ TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS.☐ P AND A ☐	
TEMPORARILY ABANDON	_
DOWNHOLE COMMINGLE	
OTHER: OTHER:	RETURN TO PRODUCTION
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.	
$\frac{04/22/14}{MIRU Aztec Rig \#528. Unhung head. LD polish rod \& liner. POOH w/(1) 2'x5/8" rod sub, (30) 5/8" rods, (1) 8'x1-1/4" pump w/6" gas anchor. ND WH, NU BOP (8-1/4" flange). PU 1 jt tbg, tag btm w/25 jts 2-3/8" tbg. Close BOP. Plan on testing tbg on 4/23/14. Tag btm @ 790.37'.$	
4/23/14	
Open BOP. Had zero pressure on well. Rig up TBG testing. RIH w/8' muleshoe (open ended), (1) 6' x 2 3/8 slotted sub. (1) 2 3/8 sn (25 joints) 2 3/8 tbg. testing all TBG 5000 psi below slips. SN @ 790.37, EOT @ 804.47.ND BOP, NU well head, RIH w/6" gas anchor, (1) 8' x 1 1/4 pump, (30) 5/8 rods, (1) 2' x 5/8 rod sub; Pick up polish rod and liner. hung head on, hooked up pump truck, loaded tubing, pressured up tubing. Hooked up to back side, flush back side with 8 bbls fresh water and paraffin disbursement. Left well on 20% auto,	
pumping to battery.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE TITLE Regulatory Affairs Coordinator DATE 04/24/2014	
Type or print name	
BU COLA DE SOULCE SINU	
APPROVED BY // DATE O/J//Y Conditions of Approval (if any):	