| (August 2007)<br>DEPARTMENT OF THE INTERIOR<br>BUREAU OF LAND MANAGEMENT<br>SUNDRY NOTICES AND REPORTS ON WELLS<br>Do not use this form for proposals to drill or to re-enter an   |   | E  | OMB NO. 1004-0135<br>Expires: July 31. 2010<br>5. Lease Serial No.<br>NMNM048343   |  |  |
|--|---|--|--|--|--|
|  |   | NMNM04   |  |  |  |
| abandoned we   | II. Use form 3160-3 (APD  | )) for such proposals.   | 6. If Indian, A  | llottee or Tribe Name  |  |
| SUBMIT IN TRIPLICATE - Other instructions on reverse side.  1. Type of Well  SOI! Well Gas Well Other  |   | 7. If Unit or C.   | 7. If Unit or CA/Agreement, Name and/or No.  |  |  |
|  |   | · · · · · · · · · · · · · · · · · · ·  | 8. Well Name and No.<br>ARTESIA YESO FEDERAL UNIT 19   |  |  |
| 2. Name of Operator<br>OXY USA WTP LP  | Contact: J<br>E-Mail: jennifer_dua  | IENNIFER A DUARTE  | 9. API Well N<br>30-015-4  |  |  |
| 3a. Address<br>PO BOX 4294<br>HOUSTON TX 77210   |   | 3b. Phone No. (include area code<br>Ph: 713-513-6640   | ) 10. Field and I<br>ARTESIA   | Pool, or Exploratory   |  |
| HOUSTON, TX 77210         4. Location of Well (Footage, Sec., T., R., M., or Survey Description)   |   |  | 11. County or  | 11. County or Parish, and State  |  |
| Sec 21 T17S R28E SENW 18   | 330FNL 1590FWL  |  | EDDY CC  | DUNTY, NM  |  |
| 12. CHECK APP  | ROPRIATE BOX(ES) TO   | INDICATE NATURE OF   | NOTICE, REPORT, OR (   | OTHER DATA   |  |
| TYPE OF SUBMISSION   |   | ΤΥΡΕ Ο   | F ACTION   | ·····  |  |
| Notice of Intent   | <ul> <li>Acidize</li> <li>Alter Casing</li> </ul>   | <ul> <li>Deepen</li> <li>Fracture Treat</li> </ul>   | <ul> <li>Production (Start/Resu</li> <li>Reclamation</li> </ul>  | me) 🔲 Water Shut-Ofl   |  |
| Subsequent Report  | Casing Repair   | New Construction   | Recomplete   | 🛛 Other<br>Drilling Operation  |  |
| Final Abandonment Notice   | <ul> <li>Change Plans</li> <li>Convert to Injection</li> </ul>  | Plug and Abandon Plug Back   | <ul> <li>Temporarily Abandon</li> <li>Water Disposal</li> </ul>  | , so a second  |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURFA<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST  | d operations. If the operation rest<br>bandonment Notices shall be filed<br>final inspection.)<br>ACE HOLE. TD HOLE @ 3<br>00 SX 1.34 YLD CEMENT.   | ults in a multiple completion or rec<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED   | ompletion in a new interval, a Fo<br>ling reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.   | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>95?.<br>4G 7.875?                    |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURF/<br>04/10/14 ? CEMENT WITH 20  | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ (<br>00 SX 1.34 YLD CEMENT,<br>FED SURFACE CASING T<br>)?. BEGIN RUNNING 5.5?<br>NG 5.5? L80 17# PRODUC  | ults in a multiple completion or rec<br>d only after all requirements, inclu<br>395?, RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>CTION CASING TO 4900?. (   | ompletion in a new interval, a Fo<br>ling reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.   | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>05?.<br>JG 7.875?                    |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURF/<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST<br>PRODUCTION HOLE.<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN   | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ (<br>00 SX 1.34 YLD CEMENT,<br>FED SURFACE CASING T<br>)?. BEGIN RUNNING 5.5?<br>NG 5.5? L80 17# PRODUC  | ults in a multiple completion or rec<br>d only after all requirements, inclu<br>395?, RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>CTION CASING TO 4900?. (   | ompletion in a new interval, a Fo<br>ling reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.   | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>95?.<br>NG 7.875?<br>v<br>. 2.48 YLD |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURF/<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST<br>PRODUCTION HOLE.<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN   | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ (<br>00 SX 1.34 YLD CEMENT,<br>FED SURFACE CASING T<br>)?. BEGIN RUNNING 5.5?<br>NG 5.5? L80 17# PRODUC  | ults in a multiple completion or rec<br>d only after all requirements, inclu<br>395?, RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>CTION CASING TO 4900?. (   | SURFACE CASING TO 39<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.<br>EMENTED WITH 800 SX  | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>95?.<br>NG 7.875?<br>•<br>• 2.48 YLD |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURF/<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST<br>PRODUCTION HOLE.<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN   | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ 3<br>00 SX 1.34 YLD CEMENT.<br>TED SURFACE CASING T<br>PROBURFACE CASING T<br>)?. BEGIN RUNNING 5.5?<br>NG 5.5? L80 17# PRODUC<br>JALTED 92SX TO SURFAC  | ults in a multiple completion or rec<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>CTION CASING TO 4900?. (<br>CE. RELEASED RIG.  | ompletion in a new interval, a Following reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.<br>CEMENTED WITH 800 SX<br>CEMENTED WITH 800 SX<br>CEMENTED WITH 800 SX<br>MOCD  | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>95?.<br>NG 7.875?<br>•<br>• 2.48 YLD |  |
| following completion of the involvec<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURFA<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST<br>PRODUCTION HOLE.<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN<br>CEMENT. TOC = 0?; CIRCU   | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ 3<br>00 SX 1.34 YLD CEMENT.<br>TED SURFACE CASING T<br>PROBUTING 5.5?<br>NG 5.5? L80 17# PRODUC<br>IALTED 92SX TO SURFAC<br>Strue and correct.<br>Electronic Submission #2<br>For OXY 1  | ults in a multiple completion or rec<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>CTION CASING TO 4900?. (<br>CE. RELEASED RIG.<br>49154 verified by the BLM We<br>USA WTP LP, sent to the Car   | ompletion in a new interval, a Following reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.<br>CEMENTED WITH 800 SX<br>CEMENTED WITH 800 SX<br>CEMENTED WITH 800 SX<br>MOCD  | pleted, and the operator has<br>95?.<br>NG 7.875?<br>4<br>2.48 YLD                                     |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURFA<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? CEMENT WITH 20<br>04/11/14 ? TD WELL @ 4900<br>04/14/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN<br>CEMENT. TOC = 0?; CIRCU  | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ 3<br>00 SX 1.34 YLD CEMENT.<br>TED SURFACE CASING T<br>PROBUTING 5.5?<br>NG 5.5? L80 17# PRODUC<br>IALTED 92SX TO SURFAC<br>Strue and correct.<br>Electronic Submission #2<br>For OXY 1  | ults in a multiple completion or rec<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>CTION CASING TO 4900?. (<br>CE. RELEASED RIG.<br>49154 verified by the BLM We<br>USA WTP LP, sent to the Car   | ompletion in a new interval, a Foling reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.<br>EMENTED WITH 800 SX<br>Copied for Focor<br>NMOCD<br>STD 6/26/19<br>Il Information System<br>Isbad  | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>05?.<br>NG 7.875?<br>. 2.48 YLD      |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURFA<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST<br>PRODUCTION HOLE.<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN<br>CEMENT. TOC = 0?; CIRCU   | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ 3<br>00 SX 1.34 YLD CEMENT.<br>TED SURFACE CASING T<br>PROBURFACE CASING T<br>PROBURFACE CASING T<br>PROBURFACE CASING 5.5?<br>NG 5.5? L80 17# PRODUC<br>IALTED 92SX TO SURFAC<br>Submission #2<br>Submission)   | ults in a multiple completion or red<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>TION CASING TO 4900?. (<br>CE. RELEASED RIG.   | ompletion in a new interval, a Folling reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.<br>CEMENTED WITH 800 SX<br>CEPTED for for for for<br>NMOCD<br>SUD 6/26/19<br>Il Information System<br>Isbad                                      | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>05?.<br>NG 7.875?<br>. 2.48 YLD      |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURFA<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST<br>PRODUCTION HOLE.<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN<br>CEMENT. TOC = 0?; CIRCU  | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ 3<br>00 SX 1.34 YLD CEMENT.<br>TED SURFACE CASING T<br>PROBURFACE CASING T<br>PROBURFACE CASING T<br>PROBURFACE CASING 5.5?<br>NG 5.5? L80 17# PRODUC<br>IALTED 92SX TO SURFAC<br>Submission #2<br>Submission)   | ults in a multiple completion or red<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>TION CASING TO 4900?. (<br>CE. RELEASED RIG.<br>49154 verified by the BLM We<br>USA WTP LP, sent to the Car<br>Title REGU<br>Date 06/10//<br>R FEDERAL OR STATE        | ompletion in a new interval, a Folling reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.<br>CEMENTED WITH 800 SX<br>CEPTED for for for for<br>NMOCD<br>SUD 6/26/19<br>Il Information System<br>Isbad                                      | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>95?.<br>NG 7.875?<br>•<br>• 2.48 YLD |  |
| following completion of the involvec<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURFA<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST<br>PRODUCTION HOLE.<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN<br>CEMENT. TOC = 0?; CIRCU<br>14. Thereby certify that the foregoing is<br>Name ( <i>Printed/Typed</i> ) JENNIFE<br>Signature (Electronic :<br>   | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ 3<br>00 SX 1.34 YLD CEMENT.<br>FED SURFACE CASING T<br>PROBURFACE CASING T<br>PRODUC<br>IALTED 92SX TO SURFAC<br>s true and correct.<br>Electronic Submission #2<br>For OXY I<br>R A DUARTE<br>Submission)<br>THIS SPACE FO  | alts in a multiple completion or red<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>TION CASING TO 4900?. (<br>CE. RELEASED RIG.<br>49154 verified by the BLM We<br>USA WTP LP, sent to the Car<br>Title REGU<br>Date 06/10//<br>R FEDERAL OR STATE        | ompletion in a new interval, a Foling reclamation, have been com<br>SURFACE CASING TO 39<br>29SX TO SURFACE.<br>D TEST. BEGAN DRILLIN<br>SING.<br>EMENTED WITH 800 SX<br>CODIECT FOR FOR FOR<br>NMOCD<br>SPD 6/26/19<br>Il Information System<br>Isbad<br>ATORY SPECIALIST<br>2014<br>OFFICE USE | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>05?.<br>.2.48 YLD<br>d               |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURFA<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? CEMENT WITH 20<br>04/11/14 ? PRESSURE TEST<br>PRODUCTION HOLE.<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN<br>CEMENT. TOC = 0?; CIRCU   | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ 3<br>00 SX 1.34 YLD CEMENT.<br>TED SURFACE CASING T<br>PROBURFACE CASING T<br>PRODUC<br>IALTED 92SX TO SURFAC<br>Submission #2<br>For OXY I<br>R A DUARTE<br>Submission)<br>THIS SPACE FO  | alts in a multiple completion or red<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>. TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>CTION CASING TO 4900?. C<br>CE. RELEASED RIG.<br>49154 verified by the BLM We<br>USA WTP LP, sent to the Car<br>Title REGU<br>Date 06/10//<br>R FEDERAL OR STATE<br> | SURFACE CASING TO 39         SURFACE CASING TO 39         29SX TO SURFACE.         D TEST. BEGAN DRILLIN         SING.         EMENTED WITH 800 SX   | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>05?.<br>.2.48 YLD<br>d               |  |
| following completion of the involved<br>testing has been completed. Final Al<br>determined that the site is ready for f<br>AYFU #19 - Amended<br>04/09/14 ? SPUD 11? SURFA<br>04/10/14 ? CEMENT WITH 20<br>04/11/14 ? CEMENT WITH 20<br>04/13/14 ? TD WELL @ 4900<br>04/14/14 ? FINISHIN RUNNIN<br>CEMENT. TOC = 0?; CIRCU<br>14. 1 hereby certify that the foregoing is<br>Name ( <i>Printed/Typed</i> ) JENNIFE<br>Signature (Electronic :<br>Signature (Electronic :<br>Conditions of approval, if any, are attache<br>certify that the applicant holds legal or eq<br>which would entitle the applicant to cond<br>Title 18 U.S.C. Section 1001 and Title 43<br>States any false, fictitious or fraudulent | d operations. If the operation rest<br>bandonment Notices shall be file<br>final inspection.)<br>ACE HOLE. TD HOLE @ 0<br>00 SX 1.34 YLD CEMENT.<br>FED SURFACE CASING T<br>PROBURFACE CASING T<br>PRODUC<br>IALTED 92SX TO SURFAC<br>Submission #2<br>For OXY I<br>R A DUARTE<br>Submission)<br>THIS SPACE FO<br>ed. Approval of this notice does a<br>putable title to those rights in the<br>uct operations thereon. | alts in a multiple completion or red<br>d only after all requirements, inclu<br>395?. RUN 8.625? J55 24#<br>. TOC = 0?; CIRCULATED<br>O 2065 PSI-30 MIN = GOO<br>L80 17# PRODUCTION CA<br>CTION CASING TO 4900?. C<br>CE. RELEASED RIG.<br>49154 verified by the BLM We<br>USA WTP LP, sent to the Car<br>Title REGU<br>Date 06/10//<br>R FEDERAL OR STATE<br> | and scanned  | rrm 3160-4 shall be filed once<br>pleted, and the operator has<br>05?.<br>.2.48 YLD<br>d               |  |

·