

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-015-41594
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Cedar Canyon 15
8. Well Number 3H
9. OGRID Number 16696
10. Pool name or Wildcat Pierce Crossing Bone Spring, E.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
OXY USA Inc.

3. Address of Operator  
P.O. Box 50250 Midland, TX 79710

4. Well Location  
Unit Letter L : 1888 feet from the South line and 700 feet from the West line  
Section 15 Township 24S Range 29E NMPM County Elly

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
2925.8 GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☒ P AND A ☐  
CASING/CEMENT JOB ☒  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Spud 14-3/4" hole 6/15/14, drill to 390' 6/15/14. RIH & set 11-3/4" 47# J-55 BTC csg @ 390', pump 20bbl FW spacer, then cmt w/ 250sx (74bbl) PPC w/ additives 14.2ppg 1.67 yield followed by 300sx (71bbl) PPC w/ additives 14.8ppg 1.34 yield, had full returns, circ 168sx (50bbl) cmt to surface. WOC. Install WH, test to 800#, RU BOP, test @ 250# low 5000# high. 6/17/14, RIH & tag cmt @ 344', test csg to 2150# for 30 min, test passed, drill new formation to 400', perform FIT test to 87psi, EMW=9.8ppg, pressure fell to 0# in 6 min. Decision made to drill ahead.

6/17/14 drill 10-5/8" hole to 3130', 6/18/14. RIH & set 8-5/8" 32# J55 LTC csg @ 3125', pump 20bbl FW spacer then cmt w/ 660sx (221bbl) Light PPC w/ additives 12.9ppg 1.88 yield followed by 230sx (54bbl) PPC w/ additives 14.8ppg 1.33 yield, had full returns, circ 113sx (38bbl) cmt to surface, WOC. Install Cameron pack-off bushing, test to 2000# for 15min, good test. 6/20/14, RIH & tag cmt @ 3070', circ hole, pressure test csg to 2750# for 30 min, tested good. Drill new formation to 3140', perform FIT test to 500#, EMW=12.2ppg, good test.

NM OIL CONSERVATION  
ARTESIA DISTRICT

Spud Date:

6/15/14

Rig Release Date:

JUN 30 2014

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

RECEIVED

SIGNATURE David Stewart TITLE Sr. Regulatory Advisor DATE 6/25/14

Type or print name David Stewart E-mail address: david\_stewart@oxy.com PHONE: 432-685-5717

For State Use Only

APPROVED BY: David Stewart TITLE Sr. Regulatory Advisor DATE 7-2-14

Conditions of Approval (if any):