

Submit 1 Copy To Appropriate District Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-015-40482
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Leavitt 13C
8. Well Number #1
9. OGRID Number 277558
10. Pool name or Wildcat Red Lake, Glorieta-Yeso (51120)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
LIME ROCK RESOURCES II-A, L.P.

3. Address of Operator
1111 Bagby Street, Suite 4600 Houston, Tx 77379

4. Well Location
Unit Letter C : 330 feet from the North line and 2310 feet from the West line
Section 13 Township 18-S Range 26-E NMPM Eddy County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,290.6' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☒
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER Change TD to 4,700' ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Lime Rock would like to change the TD to 4,700' in order to get the entire Tubbs section. The 5-1/2" csg will also be lengthened. The cmt behind the 5-1/2" casing will be increased proportionally, so cmt will circulate to surface.

NM OIL CONSERVATION
ARTESIA DISTRICT

AUG 28 2014

RECEIVED

Spud Date:

Drilling Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Spencer Cox TITLE Production Engineer DATE 8/28/14

Type or print name Spencer Cox E-mail address: scox@limerockresources.com PHONE: 713-292-9528

For State Use Only

APPROVED BY: T.C. Shepard TITLE "Geologist" DATE 8-28-2014

Conditions of Approval (if any):