

OCD Artesia
NM OIL CONSERVATION
ARTESIA DISTRICTFORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

14-562

TOS
92274**UNORTHODOX
LOCATION**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SEP 22 2014

APPLICATION FOR PERMIT TO DRILL OR REENTER**RECEIVED**

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input checked="" type="checkbox"/> REENTER		5. Lease Serial No. NMNM111412
1b. Type of Well: <input type="checkbox"/> Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name
2. Name of Operator COG Operating LLC.		7. If Unit or CA Agreement, Name and No.
3a. Address 2208 West Main Street Artesia, NM 88210		8. Lease Name and Well No. Quien Sabe 25 Federal #2H
3b. Phone No. (include area code) 575-748-6940		9. API Well No. 30-015-42662
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface 190' FNL & 1650' FEL Unit Letter B (NWNE) SHL Sec 25-T24S-R27E At proposed prod. Zone 660' FSL & 1980' FEL Unit Letter O (SWSE) BHL Sec 25-T24S-R27E		10. Field and Pool or Exploratory Wildcat, Workcamp
14. Distance in miles and direction from nearest town or post office* Approximately 4 miles from Malaga		11. Sec., T.R.M. or Blk and Survey or Area Sec. 25 - T24S - R27E
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. Unit line, if any) 190'	16. No. of acres in lease 320	17. Spacing Unit dedicated to this well 320
18. Distance from location* to nearest well, drilling, completed, applied for, on this lease, ft. SHL: 1050' BHL: 4640'	19. Proposed Depth TVD: 8,980' MD: 13,309'	20. BLM/BIA Bond No. on file NMB000740 & NMB00215
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3113.1' GL	22. Approximate date work will start* 10/1/2014	23. Estimated duration 30 days

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- | | |
|---|--|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the authorized officer. |

25. Signature <i>Mayte Reyes</i>	Name (Printed/Typed) Mayte Reyes	Date 8-6-14
Title Regulatory Analyst		
Approved by (Signature) Steve Caffey	Name (Printed/Typed)	Date SEP 17 2014
Title FIELD MANAGER		
Office CARLSBAD FIELD OFFICE		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)


Carlsbad Controlled Water Basin

Approval Subject to General Requirements
& Special Stipulations AttachedSEE ATTACHED FOR
CONDITIONS OF APPROVAL

Surface Use Plan
COG Operating LLC
Quien Sabé 25 Federal #2H
SHL: 190' FNL & 1650' FEL UL B
Section 25, T24S, R27E
BHL: 660' FSL & 1980' FEL UL O
Section 25, T24S, R27E
Eddy County, New Mexico

OPERATOR CERTIFICATION

I hereby certify that I, or persons under my direct supervision, have inspected the drill site and access road proposed herein; that I am familiar with the conditions that presently exist; that I have full knowledge of State and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or COG Operating LLC, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements. Executed this 6th day of August, 2014.

Signed:  _____

Printed Name: Melanie J. Parker

Position: Regulatory Coordinator

Address: 2208 W. Main Street, Artesia, NM 88210

Telephone: (575) 748-6940

Field Representative (if not above signatory): Rand French

E-mail: mparker@concho.com

DISTRICT I
1625 N. FRENCH DR., HOBBS, NM 88240
Phone: (575) 393-6181 Fax: (575) 393-0720

DISTRICT II
811 S. FIRST ST., ARTESIA, NM 88210
Phone: (575) 748-1283 Fax: (575) 748-0720

DISTRICT III
1000 RIO BRAZOS RD., AZTEC, NM 87410
Phone: (505) 334-6178 Fax: (505) 334-6170

DISTRICT IV
1220 S. ST. FRANCIS DR., SANTA FE, NM 87505
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico
Energy, Minerals & Natural Resources Department
OIL CONSERVATION DIVISION
1220 SOUTH ST. FRANCIS DR.
Santa Fe, New Mexico 87505

Form C-102
Revised August 1, 2011
Submit one copy to appropriate
District Office

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number 30-015-	42662	Pool Code 85780	Pool Name Sulphate Draw Wildcat ; Wolfcamp (GAS)
Property Code 40004	Property Name QUIEN SABE 25 FEDERAL		Well Number 2H
OGRID No. 229137	Operator Name COG OPERATING, LLC		Elevation 3113.1

Surface Location

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
B	25	24-S	27-E		190	NORTH	1650	EAST	EDDY


Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
0	25	24-S	27-E		660	SOUTH	1980	EAST	EDDY
Dedicated Acres 320	Joint or Infill	Consolidation Code	Order No.						

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

<p>Y=434888.4 N X=558682.0 E</p> <p>NAD 27 SURFACE LOCATION Y=434722.4 N X=559698.2 E LAT.=32.195022° N LONG.=104.140346° W</p> <p>NAD 27 PROPOSED BOTTOM HOLE LOCATION Y=430249.9 N X=559379.2 E LAT.=32.182728° N LONG.=104.141403° W</p> <p>Y=429573.9 N X=558689.1 E</p>	<p>190' S.L.</p> <p>1650'</p> <p>GRID AZ. = 184°04'47" HORZ. DIST. = 4,483.9'</p> <p>660'</p> <p>1980'</p> <p>Y=429604.6 N X=560024.8 E</p>	<p>OPERATOR CERTIFICATION</p> <p>I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the Division.</p> <p><i>Melanie J Parker</i> 8/6/14 Signature Date Melanie J Parker Printed Name mparker@concho.com E-mail Address</p> <p>SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</p> <p>JANUARY 6, 2014 Date of Survey</p> <p>Signature & Seal of Professional Surveyor</p> <p><i>Chad L. Harcrow</i> 6/13/14 Certificate No. CHAD HARCROW 17777 W.O. # 14-497 DRAWN BY: SP</p>
--	---	---


SECTION 25, TOWNSHIP 24 SOUTH, RANGE 27 EAST, N.M.P.M.,
EDDY COUNTY NEW MEXICO



ALL FEATURES ARE EXISTING UNLESS OTHERWISE NOTED

DIRECTIONS TO LOCATION

FROM THE INTERSECTION OF CR #720 (BLACKRIVER VILLAGE RD) AND CR #774 (ROADRUNNER RD) GO APPROX. 2.4 MILES SOUTHWEST ALONG ROADRUNNER RD TO THE EXISTING QUINE SABE 25 FED #1H WELL; THEN GO TO WEST SIDE OF PAD AND PROPOSED WELL IS APPROX. 910 FEET WEST.




HARCROW SURVEYING, LLC
2314 W. MAIN ST, ARTESIA, N.M. 88210
PH: (575) 513-2570 FAX: (575) 746-2158
chad_harcrow77@yahoo.com



COG OPERATING, LLC		
QUIEN SABE 25 FED #2H WELL LOCATED 190 FEET FROM THE NORTH LINE AND 1650 FEET FROM THE EAST LINE OF SECTION 25, TOWNSHIP 24 SOUTH, RANGE 27 EAST, N.M.P.M., EDDY COUNTY, NEW MEXICO		
SURVEY DATE: 01/06/2014	PAGE: 1 OF 1	
DRAFTING DATE: 01/09/2014		
APPROVED BY: CH	DRAWN BY: SP	FILE: 14-05

EXHIBIT 2



LEGEND


- WELL
- WELLPAD
- EXISTING ROAD
- PROPOSED ROAD

WELL NAME: QUIEN SABA 25 FED #2H

SEC: 25 TWP: 24 S. RGE: 27 E. ELEVATION: 3113.1'

STATE: NEW MEXICO COUNTY: EDDY 190' FNL & 1650' FEL

W.O. # 14-05 LEASE: QUIEN SABA 25 FED SURVEY: N.M.P.M



LOCATION MAP TOPO 1/9/2014 SP



COG OPERATING, LLC

HARCROW SURVEYING, LLC
1107 WATSON, ARTESIA N.M. 88210
PH: (575) 313-2570 FAX: (575) 746-2158
chad_harcrow77@yahoo.com





LEGEND

- WELL
- WELLPAD
- EXISTING ROAD
- PROPOSED ROAD

WELL NAME: QUIEN SABE 25 FED #2H

SEC: 25 TWP: 24 S. RGE: 27 E. ELEVATION: 3113.1'

STATE: NEW MEXICO COUNTY: EDDY 190' FNL & 1650' FEL

W.O. # 14-05 LEASE: QUIEN SABE 25 FED SURVEY: N.M.P.M

0 2,500 FEET

0 0.05 0.1 0.2 Miles 1 IN = 1,000 FT

ACCESS ROAD MAP - IMAGERY 1/9/2014 SP




CONCHO





COG OPERATING, LLC



HARCROW SURVEYING, LLC
1107 WATSON, ARTESIA N.M. 88210
PH: (575) 513-2570 FAX: (575) 746-2158
chad_harcrow77@yahoo.com





LEGEND

-  WELL
-  WELLPAD
-  EXISTING ROAD
-  PROPOSED ROAD

WELL NAME: QUIEN SABE 25 FED #2H			
SEC: 25	TWP: 24 S.	RGE: 27 E.	ELEVATION: 3113.1'
STATE: NEW MEXICO		COUNTY: EDDY	190' FNL & 1650' FEL
W.O. # 14-05	LEASE: QUIEN SABE 25 FED		SURVEY: N.M.P.M
			
			
VICINITY MAP		1/9/2014	SP



CONCHO

COG OPERATING, LLC



HARCROW SURVEYING, LLC
 1107 WATSON, ARTESIA N.M. 88210
 PH: (575) 513-2570 FAX: (575) 746-2158
 chad_harcrow77@yahoo.com

13

18

17

24

19

20

FLOWLINE
TOTAL LENGTH: 1121'


1186'

1027'

84'

PROPOSED WELL
QUIEN SABE 25
FED #2H

EXISTING WELL
QUIEN SABE 25
FED #1H



DATA FOR "WELLS WITHIN 1 MI." HAS BEEN TAKEN FROM THE NEW MEXICO EMNRD WEBSITE. THE DATA HAS BEEN UPDATED THROUGH APRIL 2013.

LEGEND


- WELL
- BOTTOMHOLE
- WELLS WITHIN 1 MI.
- 1 MI. BUFFER

QUIEN SABE 25 FED #2H

SEC: 25 TWP: 24 S. RGE: 27 E. ELEVATION: 3113.1'

STATE: NEW MEXICO COUNTY: EDDY 190' FNL & 1650' FEL

W.O. # 14-497 LEASE: QUIEN SABE 25 FED SURVEY: N.M.P.M



1 MILE MAP

06/12/2014

SP.

CONCHO
COG OPERATING, LLC



HARCROW SURVEYING, LLC.
2314 W. MAIN ST, ARTESIA, NM 88210
PH: (575) 513-2570 FAX: (575) 746-2158
chad_harcrow77@yahoo.com

COG Operating LLC, Quien Sabe 25 Federal 2H

1. Geologic Formations

TVD of target	8980'	Pilot hole depth	N/A
MD at TD:	13,309'	Deepest expected fresh water:	200'

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
Quaternary Fill	Surface	Water	
Rustler	732	Water	
Top of Salt	797	Salt	
Lamar	2442		
Delaware Group	2482	Oil/Gas	
Bone Spring	5905	Oil/Gas	
Wolfcamp	8808	Oil/Gas	
Upper Wolfcamp	8980	Target Zone	

*H2S, water flows, loss of circulation, abnormal pressures, etc.

2. Casing Program

See COA

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0	775 ⁴⁰⁰	13.375"	54.5	J55	STC	3.08	2.33	12.17
12.25"	0	2475 ²³⁷⁵	9.625"	36	J55	LTC	1.57	0.82	5.08
8.75"	0	13,309	5.5"	17	HCP110	LTC	2.01	2.50	2.91
BLM Minimum Safety Factor							1.125	1.0	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
- BLM standard formulas where used on all SF calculations.
- Assumed 9.1 ppg MW equivalent pore pressure from 9-5/8" shoe to deepest TVD in wellbore. This is justified by field data in the area that shows upper section of Wolfcamp having normal pressure gradient. See attachment.
- Explanation for SF's below BLM's minimum standards:
 - 9-5/8" Burst SF @ 0.82 – used BLM's frac gradient scenario to qualify.
 $3520 \text{ psi}/2475' = 1.44 > 0.7$

COG Operating LLC, Quien Sabe 25 Federal 2H

	Y. or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification. See assumptions above table.	N
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program

Csg	# sx	Density ppg	Yield ft ³ /sx	H ₂ O gal/sx	500# Comp. Strength (hours)	Slurry Description
Sfc	300	13.5	1.75	9.2	13	Lead: Class C + 4% Gel + 2% CaCl ₂
	250	14.8	1.34	6.4	6	Tail: Class C + 2% CaCl ₂
Intrmd	500	13.5	1.75	9.2	15	Lead: Class C + 4% Gel
	250	14.8	1.34	6.4	6	Tail: Class C + 2% CaCl ₂
Prod	550	11.9	2.5	14.1	72	Lead: 50:50:10 H Blend (FR, Retarder, FL adds as necessary)
	1300	14.4	1.25	5.7	17	Tail: 50:50:2 H Blend (FR, Retarder, FL adds as necessary)

See
COA

Casing String	TOC	% Excess
Surface	0'	50% on OH volumes
Intermediate	0'	35% on OH volumes
Production	0'	35% on OH volumes

4. Pressure Control Equipment

N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
---	--

BOP installed and tested before drilling which hole?	Size?	System Rated WP	Type	✓	Tested to:
12-1/4"	13-5/8"	2M	Annular	X	50% of working pressure
			Blind Ram		WP
			Pipe Ram		
			Double Ram		
			Other*		
8-3/4"	11"	5M	Annular	X	50% testing pressure
			Blind Ram	X	WP
			Pipe Ram	X	
			Double Ram		
			Other*		

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

Y	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
N	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
	Are anchors required by manufacturer?
N	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. See attached schematic & Description.

5. Mud Program

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	Surf. shoe	FW Gel	8.6-8.8	28-34	N/C
Surf csg	Int shoe	Saturated Brine	10.0-10.2	28-34	N/C
Int shoe	TD	Cut Brine	8.5-9.3	28-34	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	Pason PVT
---	-----------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
X	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
Resistivity	
Density	
CBL	
Mud log	
PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	4250 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe:

No abnormal drilling conditions are expected to occur.

Hydrogen Sulfide (H₂S) monitors will be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

	H ₂ S is present
X	H ₂ S Contingency Plan Attached

8. Other Facets of Operation

Is this a walking operation? No

Will be pre-setting casing? No

Attachments:

- BOP & Choke Schematics (2M sent previously)
- Directional Plan
- Rig plat (sent previously)
- H2S Contingency Plan (including H2S schematic) (sent previously)
- Offset bit record showing normal pressure gradient in upper Wolfcamp section.

COG Operating LLC



Well: Quien Sabe 25 Federal Well 2H
 Site: Quien Sabe 25 Federal
 Project: Eddy County, New Mexico
 Design: rev1
 Rig: Patriot 2

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	Vsect	Annotation
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	8502.54	0.00	0.00	8502.54	0.00	0.00	0.00	0.00	0.00	KOP Begin 12"/100' build
3	8544.21	5.00	204.43	8544.15	-1.65	-0.75	12.00	204.43	1.70	
4	9252.54	90.00	204.43	8980.00	-434.72	-197.47	12.00	0.00	447.66	Begin 4"/100' turn
5	9866.08	90.00	179.89	8980.00	-1029.92	-325.71	4.00	-90.00	1050.48	Begin 90.00° lateral
6	13308.67	90.00	179.89	8980.00	-4472.50	-319.00	0.00	0.00	4483.86	PBHL/TD


Surface Location: RKB=3113.1+17 @ 3130.10usft (Patriot 2)
 US State Plane 1927 (Exact solution)
 New Mexico East 3001

Northing: 434722.40 Easting: 559698.20 Latitude: 32.19502169 Longitude: -104.14034576
 Total Correction (M => G) To convert a Magnetic Direction to a Grid Direction, Add 7.41°



Azimuths to Grid North
 True North: -0.10°
 Magnetic North: 7.41°

Magnetic Field
 Strength: 48271.1snT
 Dip Angle: 60.00°
 Date: 2/18/2014
 Model: IGRF2010





COG Operating LLC

Eddy County, New Mexico

Quien Sabe 25 Federal

Quien Sabe 25 Federal Well 2H

Original Hole

SHL: 190 FNL 1650 FEL

BHL: 660 FSL 1980 FEL

Plan: rev1

Standard_report

16 July, 2014



Standard_report

Company:	COG Operating LLC	Local Co-ordinate Reference:	Well Quien Sabe 25 Federal Well 2H
Project:	Eddy County, New Mexico	TVD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Site:	Quien Sabe 25 Federal	MD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Well:	Quien Sabe 25 Federal Well 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	rev1	Database:	EDM 5000.1 Ddatabase

Project:	Eddy County, New Mexico		
Map System:	US State Plane 1927 (Exact solution)	System Datum:	Mean Sea Level
Geo Datum:	NAD 1927 (NADCON CONUS)		
Map Zone:	New Mexico East 3001		

Site:		Quien Sabe 25 Federal									
Site Position:		Northing:		434,747.60 usft		Latitude:		32.19508574			
From:		Map		Easting:		560,748.20 usft		Longitude:		-104.13695128	
Position Uncertainty:		0.00 usft		Slot Radius:		13-3/16 "		Grid Convergence:		0.10 °	

Well	Quien Sabe 25 Federal Well 2H, Surf Loc: 190 FNL 1650 FEL Sect 25					
Well Position	+N/-S	0.00 usft	Northing:	434,722.40 usft	Latitude:	32.19502169
	+E/-W	0.00 usft	Easting:	559,698.20 usft	Longitude:	-104.14034576
Position Uncertainty		0.00 usft	Wellhead Elevation:	usft	Ground Level:	3,113.10 usft

Wellbore	Original Hole				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	2/18/2014	7.52	60.00	48,271

Design	rev1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(usft)	(usft)	(usft)	(°)
	0.00	0.00	0.00	184.08

Survey Tool Program		Date 7/16/2014		
From (usft)	To (usft)	Survey (Wellbore)	Tool Name	Description
0.00	13,308.50	rev1 (Original Hole)	MWD	MWD - Standard



Standard_report

Company:	COG Operating LLC	Local Co-ordinate Reference:	Well Quien Sabe 25 Federal Well 2H
Project:	Eddy County, New Mexico	TVD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Site:	Quien Sabe 25 Federal	MD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Well:	Quien Sabe 25 Federal Well 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	rev1	Database:	EDM 5000.1 Ddatabase

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	DLeg (°/100ft)	V. Sec (usft)	Northing (usft)	Easting (usft)	
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
1,900.00	0.00	0.00	1,900.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,100.00	0.00	0.00	2,100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,200.00	0.00	0.00	2,200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,300.00	0.00	0.00	2,300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,400.00	0.00	0.00	2,400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,500.00	0.00	0.00	2,500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,600.00	0.00	0.00	2,600.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	



Standard_report

Company:	COG Operating LLC	Local Co-ordinate Reference:	Well Quien Sabe 25 Federal Well 2H
Project:	Eddy County, New Mexico	TVD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Site:	Quien Sabe 25 Federal	MD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Well:	Quien Sabe 25 Federal Well 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	rev1	Database:	EDM 5000.1 Ddatabase

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	DLeg (°/100ft)	V. Sec (usft)	Northing (usft)	Easting (usft)	
2,700.00	0.00	0.00	2,700.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,800.00	0.00	0.00	2,800.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
2,900.00	0.00	0.00	2,900.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,000.00	0.00	0.00	3,000.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,100.00	0.00	0.00	3,100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,200.00	0.00	0.00	3,200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,300.00	0.00	0.00	3,300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,400.00	0.00	0.00	3,400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,500.00	0.00	0.00	3,500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,600.00	0.00	0.00	3,600.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,700.00	0.00	0.00	3,700.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,800.00	0.00	0.00	3,800.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
3,900.00	0.00	0.00	3,900.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,000.00	0.00	0.00	4,000.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,100.00	0.00	0.00	4,100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,200.00	0.00	0.00	4,200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,300.00	0.00	0.00	4,300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,400.00	0.00	0.00	4,400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,500.00	0.00	0.00	4,500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,600.00	0.00	0.00	4,600.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,700.00	0.00	0.00	4,700.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,800.00	0.00	0.00	4,800.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
4,900.00	0.00	0.00	4,900.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
5,000.00	0.00	0.00	5,000.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
5,100.00	0.00	0.00	5,100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
5,200.00	0.00	0.00	5,200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
5,300.00	0.00	0.00	5,300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	



Standard_report

Company:	COG Operating LLC	Local Co-ordinate Reference:	Well Quien Sabe 25 Federal Well 2H
Project:	Eddy County, New Mexico	TVD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Site:	Quien Sabe 25 Federal	MD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Well:	Quien Sabe 25 Federal Well 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	rev1	Database:	EDM 5000.1 Database

Planned Survey									
MD (usft)	Inc (%)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	DLeg (°/100ft)	V. Sec (usft)	Northing (usft)	Easting (usft)
5,400.00	0.00	0.00	5,400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
5,500.00	0.00	0.00	5,500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
5,600.00	0.00	0.00	5,600.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
5,700.00	0.00	0.00	5,700.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
5,800.00	0.00	0.00	5,800.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
5,900.00	0.00	0.00	5,900.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,000.00	0.00	0.00	6,000.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,100.00	0.00	0.00	6,100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,200.00	0.00	0.00	6,200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,300.00	0.00	0.00	6,300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,400.00	0.00	0.00	6,400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,500.00	0.00	0.00	6,500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,600.00	0.00	0.00	6,600.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,700.00	0.00	0.00	6,700.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,800.00	0.00	0.00	6,800.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
6,900.00	0.00	0.00	6,900.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,000.00	0.00	0.00	7,000.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,100.00	0.00	0.00	7,100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,200.00	0.00	0.00	7,200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,300.00	0.00	0.00	7,300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,400.00	0.00	0.00	7,400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,500.00	0.00	0.00	7,500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,600.00	0.00	0.00	7,600.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,700.00	0.00	0.00	7,700.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,800.00	0.00	0.00	7,800.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
7,900.00	0.00	0.00	7,900.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20
8,000.00	0.00	0.00	8,000.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20



Standard_report

Company:	COG Operating LLC	Local Co-ordinate Reference:	Well Quien Sabe.25 Federal Well 2H
Project:	Eddy County, New Mexico	TVD Reference:	RKB=3113.1+17 @ 3130.10usft.(Patriot 2)
Site:	Quien Sabe 25 Federal	MD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Well:	Quien Sabe.25 Federal Well 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	rev1	Database:	EDM:5000.1 Ddatabase:

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	DLeg (°/100ft)	V. Sec (usft)	Northing (usft)	Easting (usft)	
8,100.00	0.00	0.00	8,100.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
8,200.00	0.00	0.00	8,200.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
8,300.00	0.00	0.00	8,300.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
8,400.00	0.00	0.00	8,400.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
8,500.00	0.00	0.00	8,500.00	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
8,502.54	0.00	0.00	8,502.54	0.00	0.00	0.00	0.00	434,722.40	559,698.20	
KOP Begin 12°/100' build										
8,544.21	5.00	204.43	8,544.15	-1.65	-0.75	12.00	1.70	434,720.75	559,697.45	
8,600.00	11.70	204.43	8,599.32	-9.02	-4.10	12.00	9.29	434,713.38	559,694.10	
8,700.00	23.70	204.43	8,694.42	-36.65	-16.65	12.00	37.74	434,685.75	559,681.55	
8,800.00	35.70	204.43	8,781.13	-81.67	-37.10	12.00	84.10	434,640.73	559,661.10	
8,900.00	47.70	204.43	8,855.66	-142.12	-64.56	12.00	146.35	434,580.28	559,633.64	
9,000.00	59.70	204.43	8,914.76	-215.36	-97.83	12.00	221.77	434,507.04	559,600.37	
9,100.00	71.70	204.43	8,955.84	-298.18	-135.45	12.00	307.07	434,424.22	559,562.75	
9,200.00	83.70	204.43	8,977.12	-386.98	-175.78	12.00	398.50	434,335.42	559,522.42	
9,252.54	90.00	204.43	8,980.00	-434.72	-197.47	12.00	447.66	434,287.68	559,500.73	
Begin 4°/100' turn										
9,300.00	90.00	202.53	8,980.00	-478.24	-216.38	4.00	492.43	434,244.16	559,481.82	
9,400.00	90.00	198.53	8,980.00	-571.87	-251.44	4.00	588.31	434,150.53	559,446.76	
9,500.00	90.00	194.53	8,980.00	-667.72	-279.89	4.00	685.94	434,054.68	559,418.31	
9,600.00	90.00	190.53	8,980.00	-765.32	-301.59	4.00	784.84	433,957.08	559,396.61	
9,700.00	90.00	186.53	8,980.00	-864.19	-316.42	4.00	884.51	433,858.21	559,381.78	
9,800.00	90.00	182.53	8,980.00	-963.86	-324.32	4.00	984.49	433,758.54	559,373.88	
9,866.08	90.00	179.89	8,980.00	-1,029.92	-325.71	4.00	1,050.48	433,692.48	559,372.49	
Begin 90.00° lateral										
9,900.00	90.00	179.89	8,980.00	-1,063.84	-325.65	0.00	1,084.31	433,658.56	559,372.55	
10,000.00	90.00	179.89	8,980.00	-1,163.84	-325.45	0.00	1,184.04	433,558.56	559,372.75	



Standard_report

Company:	COG Operating LLC	Local Co-ordinate Reference:	Well Quien Sabe 25 Federal Well 2H
Project:	Eddy County, New Mexico	TVD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Site:	Quien Sabe 25 Federal	MD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Well:	Quien Sabe 25 Federal Well 2H.	North Reference:	Grid
Wellbore:	Original Hole.	Survey Calculation Method:	Minimum Curvature
Design:	rev1	Database:	EDM 5000.1 Ddatabase

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	DLeg (°/100ft)	V. Sec (usft)	Northing (usft)	Easting (usft)	
10,100.00	90.00	179.89	8,980.00	-1,263.84	-325.26	0.00	1,283.78	433,458.56	559,372.94	
10,200.00	90.00	179.89	8,980.00	-1,363.84	-325.06	0.00	1,383.51	433,358.56	559,373.14	
10,300.00	90.00	179.89	8,980.00	-1,463.84	-324.87	0.00	1,483.24	433,258.56	559,373.33	
10,400.00	90.00	179.89	8,980.00	-1,563.84	-324.67	0.00	1,582.97	433,158.56	559,373.53	
10,500.00	90.00	179.89	8,980.00	-1,663.84	-324.48	0.00	1,682.71	433,058.56	559,373.72	
10,600.00	90.00	179.89	8,980.00	-1,763.84	-324.28	0.00	1,782.44	432,958.56	559,373.92	
10,700.00	90.00	179.89	8,980.00	-1,863.84	-324.09	0.00	1,882.17	432,858.56	559,374.11	
10,800.00	90.00	179.89	8,980.00	-1,963.84	-323.89	0.00	1,981.90	432,758.56	559,374.31	
10,900.00	90.00	179.89	8,980.00	-2,063.84	-323.70	0.00	2,081.64	432,658.56	559,374.50	
11,000.00	90.00	179.89	8,980.00	-2,163.84	-323.50	0.00	2,181.37	432,558.56	559,374.70	
11,100.00	90.00	179.89	8,980.00	-2,263.84	-323.31	0.00	2,281.10	432,458.56	559,374.89	
11,200.00	90.00	179.89	8,980.00	-2,363.84	-323.11	0.00	2,380.83	432,358.56	559,375.09	
11,300.00	90.00	179.89	8,980.00	-2,463.84	-322.92	0.00	2,480.57	432,258.56	559,375.28	
11,400.00	90.00	179.89	8,980.00	-2,563.84	-322.72	0.00	2,580.30	432,158.56	559,375.48	
11,500.00	90.00	179.89	8,980.00	-2,663.84	-322.53	0.00	2,680.03	432,058.56	559,375.67	
11,600.00	90.00	179.89	8,980.00	-2,763.83	-322.33	0.00	2,779.76	431,958.57	559,375.87	
11,700.00	90.00	179.89	8,980.00	-2,863.83	-322.14	0.00	2,879.50	431,858.57	559,376.06	
11,800.00	90.00	179.89	8,980.00	-2,963.83	-321.94	0.00	2,979.23	431,758.57	559,376.26	
11,900.00	90.00	179.89	8,980.00	-3,063.83	-321.75	0.00	3,078.96	431,658.57	559,376.45	
12,000.00	90.00	179.89	8,980.00	-3,163.83	-321.55	0.00	3,178.69	431,558.57	559,376.65	
12,100.00	90.00	179.89	8,980.00	-3,263.83	-321.36	0.00	3,278.43	431,458.57	559,376.84	
12,200.00	90.00	179.89	8,980.00	-3,363.83	-321.16	0.00	3,378.16	431,358.57	559,377.04	
12,300.00	90.00	179.89	8,980.00	-3,463.83	-320.97	0.00	3,477.89	431,258.57	559,377.23	
12,400.00	90.00	179.89	8,980.00	-3,563.83	-320.77	0.00	3,577.62	431,158.57	559,377.43	
12,500.00	90.00	179.89	8,980.00	-3,663.83	-320.58	0.00	3,677.36	431,058.57	559,377.62	
12,600.00	90.00	179.89	8,980.00	-3,763.83	-320.38	0.00	3,777.09	430,958.57	559,377.82	
12,700.00	90.00	179.89	8,980.00	-3,863.83	-320.19	0.00	3,876.82	430,858.57	559,378.01	



Standard_report

Company:	COG Operating LLC	Local Co-ordinate Reference:	Well Quien Sabe 25 Federal Well-2H
Project:	Eddy County, New Mexico	TVD Reference:	RKB=3113.1+17. @ 3130.10usft (Patriot 2)
Site:	Quien Sabe 25 Federal	MD Reference:	RKB=3113.1+17 @ 3130.10usft (Patriot 2)
Well:	Quien Sabe 25 Federal Well 2H	North Reference:	Grid
Wellbore:	Original Hole	Survey Calculation Method:	Minimum Curvature
Design:	rev1	Database:	EDM 5000.1 Ddatabase

Planned Survey										
MD (usft)	Inc (°)	Azi (azimuth) (°)	TVD (usft)	N/S (usft)	E/W (usft)	DLeg (°/100ft)	V. Sec (usft)	Northing (usft)	Easting (usft)	
12,800.00	90.00	179.89	8,980.00	-3,963.83	-319.99	0.00	3,976.55	430,758.57	559,378.21	
12,900.00	90.00	179.89	8,980.00	-4,063.83	-319.80	0.00	4,076.29	430,658.57	559,378.40	
13,000.00	90.00	179.89	8,980.00	-4,163.83	-319.60	0.00	4,176.02	430,558.57	559,378.60	
13,100.00	90.00	179.89	8,980.00	-4,263.83	-319.41	0.00	4,275.75	430,458.57	559,378.79	
13,200.00	90.00	179.89	8,980.00	-4,363.83	-319.21	0.00	4,375.48	430,358.57	559,378.99	
13,300.00	90.00	179.89	8,980.00	-4,463.83	-319.02	0.00	4,475.22	430,258.57	559,379.18	
13,308.67	90.00	179.89	8,980.00	-4,472.50	-319.00	0.00	4,483.86	430,249.90	559,379.20	
PBHL/TD										

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment	
		+N/-S (usft)	+E/-W (usft)		
8,502.54	8,502.54	0.00	0.00	KOP Begin 12°/100' build	
9,252.54	8,980.00	-434.72	-197.47	Begin 4°/100' turn	
9,866.08	8,980.00	-1,029.92	-325.71	Begin 90.00° lateral	
13,308.67	8,980.00	-4,472.50	-319.00	PBHL/TD	



LATITUDE/LONGITUDE	API WELL NO.	FILE NUMBER
+32.1843/-104.121	30-015---	Z1TM7J

COUNTY/PARISH/OFFSHORE/STATE EDDY, NEW MEXICO	FIELD / AREA	DIRECTIONS Higby hole road	SPUD DATE 01/02/2008	TD DATE 02/18/2008	STATUS COMPLETE
WELL NAME / NUMBER Dakota federal 30 / 1	OPERATOR EOG RESOURCES, INC.	OPERATOR REPRESENTATIVE William Henderson /			
CONTRACTOR PERMIAN DRILLING COMPANY	RIG 3	CONTRACTOR REPRESENTATIVE JC Terry /	DRAWWORKS National 80		
SALESMAN RUTLEDGE, JEREMY	TURNKEY / OTHER /	PUMP 1 / LINER Emsco D-1000 / 0	PUMP 2 / LINER Emsco D-1000 / 0	SOLIDS CONTROL SYSTEM TYPE / DRILLING FLUIDS PROVIDER CLOSE /	
DRILLING TYPE / DIRECTIONAL DRILLING SERVICE PROVIDER VERTICAL /	WORK TYPE DAYWORK	SURVEY	ABSTRACT	SECT. COORD.	S-T-R 30 - 24S - 28E BLOCK

NO.	SIZE (in)	MFG	BIT TYPE	NOZZLES	SERIAL NO.	MEASURED DEPTH OUT	DISTANCE (ft)	HRS	ROP (ft/hr)	ACCUM DRLG HRS	WT (klbf)	TOTAL (rpm)	VERT DEV OUT (deg)	P.P. (psi)	FLOW (USgal/min)	MUD (ppg) / DULL GRADING										
																WT I	FV O	PV DC	YP L	FL B/S	TYPE G	SLDS ODC	DATE RP			
1	17.5	HCC	GTX-CS1	3X15	6053461	312 674	232 594	5 19.5	46.4 30.5	5 19.5	20-20 20-20	95-95 70-70	1.5 1.5	800 450	240 240	8.4 8.4	36 36					W W	01/02/2008 01/03/2008			
						spot pill on bottom and circulate, LD ss and rmr, run 13 3/8 casing, 01-03-2008 cement casing 01-04-2008 nipple up BOP and test, pick up BHA and TIH. 01-05-2008											1	1	WT	A	E	I	NO	TD		
2	12.25	HCC	GX-28	3X15	5082173	1130 1613 2177	456 939 1503	20.75 43.5 65.5	22 21.6 22.9	40.25 63 85	25-25 42-42 12-18	60-60 68-68 60-60	0.75 1.25 1.75	1700 1900 1900	310 310 310	10 10 10	29 29 29					B B B	01/06/2008 01/07/2008 01/08/2008			
						formation is salt and anhy.																				
						2470	1796	83.25	21.6	102.75	35-35	60-60	1.68	1950	310	10	29					B	01/09/2008			
						pump sweep and circulate, TOH LD (18) 8"dc, rmr, and ss, 01-09-2008. finish laying down BHA, rig up and run casing, run 59jts of 9 5/8 40# J-55 casing to 2478', and cement 01-10-2008 cement with 750sx 50/50 POZ (lead) and 250sx Calss "C" 10/0 S1 (tail) circulate excess to the reserve. 01-10-2008 Nipple up BOP 01-10-2008.																				
bha=bit, bs, (2) 8"dc, 3pt, 8"dc, 3pt, ss, (15) 8"dc, xo, (12) 6"dc, TBHA=972.97															3	3	WT	A	E	I	BT	TD				
3	8.75	SMITH	F37HY	3X16	PG2579	3065 3935	595 1465	12.75 35.25	46.7 41.6	115.5 138	20-40 45-45	58-58 58-58	1.03 1	1700 1800	482 482	8.4 8.4	28 28					W W	01/11/2008 01/12/2008			
						formation 20% shale & 80% sand.																				
						4669	2199	63	34.9	165.75	45-45	58-58	0.76	2200	482	8.4	29					W	01/13/2008			
						4848	2378	70.5	33.7	173.25	45-50	51-51	1	2100	482	8.4	28					W	01/14/2008			
						5758	3288	99.75	33	202.5	50-50	52-52	0.14	2250	482	8.4	29					W	01/15/2008			
						6421	3951	123	32.1	225.75	55-55	52-52	0.62	2150	482	8.4	29					W	01/16/2008			
						6959	4489	140.25	32	243	55-55	52-52	0.64	2250	482	8.4	29					W	01/17/2008			
						formation at 6680' was 50/50 limestone and shale.																				
bha=bit, rmr, tri collar, rmr, (24) 6.25" dc, jars, (3) 6.25" dc, xo, TBHA= 912.25															3	4	BT	H	E	I	WT	HR				
4	8.75	SMITH	F37HY	3X16	PB2579	7468 8035 8527 8685	509 1076 1568 1726	12.25 40.25 63.75 71.25	41.6 26.7 24.6 24.2	255.25 283.25 306.75 314.25	50-50 55-55 55-55 55-55	57-57 50-50 50-50 50-50	0.19 1.02 1.02 0.71	2000 1650 1650 1750	360 360 360 360	8.5 8.5 8.5 9.1	29 29 29 32					W W W W	01/18/2008 01/19/2008 01/20/2008 01/21/2008			
						formation is 60% shale, 30% limestone, and 10% sand.																				
						9395	2436	110.25	22.1	353.25	55-55	50-50	0.71	1800	360	9.1	32					W	01/22/2008			
						9500	2541	118.25	21.5	361.25	55-55	50-50	0.71	1875	360	9.1	32					W	01/23/2008			
						circulate and pump sweep, rig up logging tools and log well. 01-23-2008 pick up bit and sub, TIH and circulate, rig up Bill Rodgers and LDDP. 01-24-2008 rig up cementers and cement well. 01-25-2008 circulate, and cement with 850sx 50/50 POZ (lead) and tail with 200sx Class "C" + 2% CaCl. 01-26-2008 nipple up and test BOP 01-27-2008 and 01-28-2008																				
bha=bit, rmr, tricollar, rmr, (24) 6"dc, jars, (3) 6.25" dc, xo, TBHA=912.25															5	4	BT	N	E	I	WT	TD				

Continued Next Page

Continued Next Page



New Mexico Office of the State Engineer

Water Column/Average Depth to Water

(A CLW##### in the
POD suffix indicates the
POD has been replaced
& no longer serves a
water right file.)

(R=POD has
been replaced,
O=orphaned,
C=the file is
closed)

(quarters are 1=NW 2=NE 3=SW 4=SE)

(quarters are smallest to largest) (NAD83 UTM in meters)

(In feet)

POD	Sub	Q	Q	Q	Sec	Tws	Rng	X	Y	Depth	Depth	Water
POD Number	Code	basin	County	64	16	4	Sec	Tws	Rng		Well	Water Column
C 01721	C	ED		1	25	24S	27E	580271	3562033*		170	

Average Depth to Water: --

Minimum Depth: --

Maximum Depth: --

Record Count: 1

PLSS Search:

Section(s): 25

Township: 24S

Range: 27E

*UTM location was derived from PLSS - see Help

The data is furnished by the NMOSE/ISC and is accepted by the recipient with the expressed understanding that the OSE/ISC make no warranties, expressed or implied, concerning the accuracy, completeness, reliability, usability, or suitability for any particular purpose of the data.



New Mexico Office of the State Engineer

Water Column/Average Depth to Water

(A CLW##### in the
POD suffix indicates the
POD has been replaced
& no longer serves a
water right file.)

(R=POD has
been replaced,
O=orphaned,
C=the file is
closed)

(quarters are 1=NW 2=NE 3=SW 4=SE)

(quarters are smallest to largest)

(NAD83 UTM in meters)

(In feet)

POD Number	POD Sub- Code	basin	County	Q 64	Q 16	Q 4	Sec	Tws	Rng	X	Y	Depth Well	Depth Water	Water Column
C 00342	C	C	ED	4	1	13	24S	27E		580432	3565080*	2565		
C 00347			ED	1	1	13	24S	27E		580010	3565479*	60	30	30
C 00364	C	C	ED	1	2	09	24S	27E		575997	3567043*	2270		
C 00516			ED	1	3	4	08	24S	27E	574288	3565901*	105	36	69
C 00516 CLW201016	O		ED	1	3	4	08	24S	27E	574288	3565901*	62		
C 00516 CLW308590	O		ED	1	3	4	08	24S	27E	574288	3565901*	105	36	69
C 00516 POD6			ED	1	4	3	08	24S	27E	573885	3565895*	78	17	61
C 00516 S	C		ED	1	3	4	08	24S	27E	574288	3565901	50	17	33
C 00631	C		ED	3	3	4	08	24S	27E	574288	3565701*	50	24	26
C 00683	C		ED	4	3	08	24S	27E		573986	3565796*	50	17	33
C 00821	C		ED	3	2	09	24S	27E		575996	3566635*	97	50	47
C 00850	C		ED	2	3	09	24S	27E		575595	3566223*	108	35	73
C 00929	C		ED	3	3	18	24S	27E		572013	3564159*	54	33	21
C 01169	C		ED	1	4	3	18	24S	27E	572282	3564261*	55	35	20
C 01187	C		ED	4	3	08	24S	27E		573986	3565796*	108	17	91
C 01366			ED	4	08		24S	27E		574590	3566003*	60	35	25
C 01452	C		ED			22	24S	27E		577435	3563175*	95	70	25
C 01721	C		ED	1	25		24S	27E		580271	3562033*	170		
C 01841	C		ED	1	29		24S	27E		573806	3561953*	150		
C 01943	C		ED	1	13		24S	27E		580221	3565275*	30	25	5
C 02976	C		ED	4	2	3	12	24S	27E	580519	3566195*	57	27	30
C 03037	C		ED	4	3	4	12	24S	27E	580930	3565795*	116	25	91
C 03145	C		ED	3	1	4	13	24S	27E	580749	3564579*	103	40	63
C 03147	C		ED	3	3	3	12	24S	27E	579885	3565715	140		
C 03260 POD1	C		ED	3	3	3	12	24S	27E	579995	3565935	80	56	24
C 03260 POD2	O	C	ED	1	3	3	12	24S	27E	580100	3565984	80	56	24

*UTM location was derived from PLSS - see Help

(A CLW##### in the
POD suffix indicates the
POD has been replaced
& no longer serves a
water right file.)

(R=POD has
been replaced,
O=orphaned,
C=the file is
closed)

(quarters are 1=NW 2=NE 3=SW 4=SE)

(quarters are smallest to largest)

(NAD83 UTM in meters)

(In feet)

POD Number	POD Sub-Code	basin	County	Q 64	Q 16	Q 4	Sec	Tws	Rng	X	Y	Depth Well	Depth Water	Water Column
C 03489 POD1	C	ED		2	4	3	08	24S	27E	574153	3565939	200		
C 03490 POD1	C	ED		3	4	3	08	24S	27E	573812	3565709	140	23	117
C 03560 POD1	C	ED		2	3	3	18	24S	27E	572009	3564150	68	28	40

Average Depth to Water: 33 feet

Minimum Depth: 17 feet

Maximum Depth: 70 feet

Record Count: 29


PLSS Search:

Township: 24S


Range: 27E

The data is furnished by the NMOSE/ISC and is accepted by the recipient with the expressed understanding that the OSE/ISC make no warranties, expressed or implied, concerning the accuracy, completeness, reliability, usability, or suitability for any particular purpose of the data.


2,000 psi BOP Schematic




5,000 psi BOP Schematic



2M Choke Manifold Equipment



5M Choke Manifold Equipment



COG Operating LLC

Rig Plat & Closed Loop Equipment Diagram

Well pad will be 340' X 340'
with cellar in center of pad





Exhibit 1

"I further certify that COG will comply with Rule 19.15.17
NMAC by using a Closed Loop System."

COG Operating LLC
H₂S Equipment Schematic
Terrain: Shinnery sand hills.

Well pad will be 340' X 340'
with cellar in center of pad

Location Entry
Condition Sign



COG OPERATING LLC
HYDROGEN SULFIDE DRILLING OPERATIONS PLAN

1. HYDROGEN SULFIDE TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

- a. The hazards and characteristics of hydrogen sulfide (H₂S).
- b. The proper use and maintenance of personal protective equipment and life support systems.
- c. The proper use of H₂S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
- d. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

- a. The effects of H₂S on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
- b. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
- c. The contents and requirements of the H₂S Drilling Operations Plan and the Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H₂S zone (within 3 days or 500 feet) and weekly H₂S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H₂S Drilling Operations Plan and the Public Protection Plan. This plan shall be available at the well site. All personnel will be required to carry documentation that they have received the proper training.

2. H₂S SAFETY EQUIPMENT AND SYSTEMS

Note: All H₂S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H₂S. If H₂S greater than 100 ppm is encountered in the gas stream we will shut in and install H₂S equipment.

- a. Well Control Equipment:
 - Flare line.
 - Choke manifold with remotely operated choke.
 - Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit.
 - Auxiliary equipment to include: annular preventer, mud-gas separator, rotating head.

- b. Protective equipment for essential personnel:
Mark II Surviveair 30-minute units located in the dog house and at briefing areas.
- c. H2S detection and monitoring equipment:
2 - portable H2S monitor positioned on location for best coverage and response. These units have warning lights and audible sirens when H2S levels of 20 ppm are reached.
- d. Visual warning systems:
Caution/Danger signs shall be posted on roads providing direct access to location. Signs will be painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used, when appropriate. See example attached.
- e. Mud Program:
The mud program has been designed to minimize the volume of H2S circulated to the surface.
- f. Metallurgy:
All drill strings, casings, tubing, wellhead, blowout preventers, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H2S service.
- g. Communication:
Company vehicles equipped with cellular telephone.

COG OPERATING LLC has conducted a review to determine if an H2S contingency plan is required for the above referenced well. We were able to conclude that any potential hazardous volume would be minimal. H2S concentrations of wells in this area from surface to TD are low enough; therefore, we do not believe that an H2S contingency plan is necessary.

W A R N I N G

**YOU ARE ENTERING AN H₂S AREA
AUTHORIZED PERSONNEL ONLY**

- 1. BEARDS OR CONTACT LENSES NOT ALLOWED***
- 2. HARD HATS REQUIRED***
- 3. SMOKING IN DESIGNATED AREAS ONLY***
- 4. BE WIND CONSCIOUS AT ALL TIMES***
- 5. CK WITH COG OPERATING LLC FOREMAN AT MAIN OFFICE***

COG OPERATING LLC

1-575-748-6940

EMERGENCY CALL LIST

	<u>OFFICE</u>	<u>MOBILE</u>
COG OPERATING LLC OFFICE	575-748-6940	
SHERYL BAKER	575-748-6940	432-934-1873
KENT GREENWAY	575-746-2010	432-557-1694
SETH WILD	432-683-7443	432-528-3633
WALTER ROYE	575-748-6940	432-934-1886

EMERGENCY RESPONSE NUMBERS

	<u>OFFICE</u>
STATE POLICE	575-748-9718
EDDY COUNTY SHERIFF	575-746-2701
EMERGENCY MEDICAL SERVICES (AMBULANCE)	911 or 575-746-2701
EDDY COUNTY EMERGENCY MANAGEMENT (HARRY BURGESS)	575-887-9511
STATE EMERGENCY RESPONSE CENTER (SERC)	575-476-9620
CARLSBAD POLICE DEPARTMENT	575-885-2111
CARLSBAD FIRE DEPARTMENT	575-885-3125
NEW MEXICO OIL CONSERVATION DIVISION	575-748-1283
INDIAN FIRE & SAFETY	800-530-8693
HALLIBURTON SERVICES	800-844-8451




COG Operating LLC
2208 West Main
Artesia, NM 88210

Production Facility Layout

Quien Sabe 25 Federal #2H
Section 25 - T24S - R27E

Exhibit 3



Surface Use & Operating Plan

Quien Sabe 25 Federal #2H

- Surface Tenant: Hayhurst-Rook Family Educational Trust, 518 Orchard, Carlsbad, NM 88220
- New Road: 1186'
- Flow Line: On well pad.
- Facilities: Will be constructed on well pad – see Exhibit 3

- **Well Site Information**
 - V Door: East
 - Topsoil: South
 - Interim Reclamation: South and West

Notes

Onsite: On-site was done by Tanner Nygren (BLM); Rand French (COG) on January 28, 2014.

SURFACE USE AND OPERATING PLAN

1. Existing & Proposed Access Roads

- A. The well site survey and elevation plat for the proposed well is attached with this application. It was staked by Harcrow Surveying, Artesia, NM.
- B. All roads to the location are shown on the Location Verification Map Exhibit 2. The existing lease roads are illustrated and are adequate for travel during drilling and production operations. Upgrading existing roads prior to drilling the well will be done where necessary. The road route to the well site is depicted in Exhibit #2. The road shown in Exhibit #2 will be used to access the well.
- C. Directions to location: See 600 x 600 plat
- D. Routine grading and maintenance of existing roads will be conducted as necessary to maintain their condition as long as any operations continue on this lease. Roads will be maintained according to specifications in section 2 of this Surface Use and Operating Plan.

2. Proposed Access Road:

The Location Verification Map shows that 1186' of new access road will be required for this location. If any road is required it will be constructed as follows:

The maximum width of the running surface will be 14'. The road will be crowned, ditched and constructed of 6" rolled and compacted caliche. Ditches will be at 3:1 slope and 4 feet wide. Water will be diverted where necessary to avoid ponding, prevent erosion, maintain good drainage, and to be consistent with local drainage patterns.

- A. The average grade will be less than 1%.
- B. No turnouts are planned.
- C. No culvert, cattleguard, gates, low water crossings or fence cuts are necessary.
- D. Surfacing material will consist of native caliche. Caliche will be obtained from the actual well site if available. If not available onsite, caliche will be hauled from the nearest BLM approved caliche pit.

3. Location of Existing Well:

The One-Mile Radius Map shows existing wells within a one-mile radius of surface hole location and the bottom hole location.

4. Location of Existing and/or Proposed Facilities:

- A. COG Operating LLC does not operate an oil production facility on this lease.
- B. If the well is productive, contemplated facilities will be as follows:
 - 1) A tank battery and facilities will be constructed as shown Exhibit 3.
 - 2) The tank battery and facilities including all flow lines and piping will be installed according to API specifications.
 - 3) Any additional caliche will be obtained from the actual well site. If caliche does not exist or is not plentiful from the well site, the caliche will be hauled from a BLM approved caliche pit. Any additional construction materials will be purchased from contractors.
 - 4) It will be necessary to run electric power if this well is productive. Power will be provided by Xcel Energy and they will submit a separate plan and ROW for service to the well location.
 - 5) If the well is productive, rehabilitation plans will include the following:
 - The original topsoil from the well site will be returned to the location, and the site will be re-contoured as close as possible to the original site.

5. Location and Type of Water Supply:

The well will be drilled with combination brine and fresh water mud system as outlined in the drilling program. The water will be obtained from commercial water stations in the area and hauled to location by transport truck over the existing and proposed access roads shown in Exhibit #2. If a commercial fresh water source is nearby, fast line may be laid along existing road ROW's and fresh water pumped to the well. No water well will be drilled on the location.

6. Source of Construction Materials and Location "Turn-Over" Procedure:

Obtaining caliche: One primary way of obtaining caliche to build locations and roads will be by "turning over" the location. This means, caliche will be obtained from the actual well site. A caliche permit will be obtained from BLM prior to obtaining caliche. 2400 cubic yards is the maximum amount of caliche needed for pad and roads. Amount will vary for each pad. The procedure below has been approved by BLM personnel:

- A. The top 6 inches of topsoil is pushed off and stockpiled along the side of the location.
- B. An approximate 160' X 160' area is used within the proposed well site to remove caliche.
- C. Subsoil is removed and stockpiled within the surveyed well pad.
- D. When caliche is found, material will be stock piled within the pad site to build the location and road.
- E. Then subsoil is pushed back in the hole and caliche is spread accordingly across entire location and road.
- F. Once well is drilled, the stock piled top soil will be used for interim reclamation and spread along areas where caliche is picked up and the location size is reduced.
- G. Neither caliche, nor subsoil will be stock piled outside of the well pad. Topsoil will be stockpiled along the edge of the pad as depicted in the Well Site Layout or survey plat.

In the event that no caliche is found onsite, caliche will be hauled in from a BLM approved caliche pit or other established mineral pit. A BLM mineral material permit will be acquired prior to obtaining any mineral material from BLM pits or land.

7. Methods of Handling Water Disposal:

- A. The well will be drilled utilizing a closed loop mud system. Drill cuttings will be held in roll-off style mud boxes and taken to an NMOCD approved disposal site.
- B. Drilling fluids will be contained in steel mud pits.
- C. Water produced from the well during completion will be held temporarily in steel tanks and then taken to an NMOCD approved commercial disposal facility.

- D. Garbage and trash produced during drilling or completion operations will be collected in a trash bin and hauled to an approved landfill. No toxic waste or hazardous chemicals will be produced by this operation.
- E. Human waste and grey water will need to be properly contained and disposed of. Proper disposal and elimination of waste and grey water may include but are not limited to portable septic systems and/or portable waste gathering systems (i.e. portable toilets).
- F. After the rig is moved out and the well is either completed or abandoned, all waste materials will be cleaned up within 30 days. In the event of a dry hole only a dry hole marker will remain.

8. Ancillary Facilities:

No airstrip, campsite or other facilities will be built as a result of the operation on this well.

9. Well Site Layout:

- A. The drill pad layout, with elevations staked by Harcrow Surveying, is shown in the Elevation Plat. Dimensions of the pad and pits are shown on the Rig Layout. V door direction is East. Topsoil, if available, will be stockpiled per BLM specifications. Because the pad is almost level no major cuts will be required.
- B. The Rig Layout Closed-Loop exhibit shows the proposed orientation of closed loop system and access road. No permanent living facilities are planned, but a temporary foreman/toolpusher's trailer will be on location during the drilling operations.

10. Plans for Restoration of the Surface:

- A. Interim Reclamation will take place after the well has been completed. The pad will be downsized by reclaiming the areas not needed for production operations. The portions of the pad that are not needed for production operations will be re-contoured to its original state as much as possible. The caliche that is removed will be reused to either build another pad site or for road repairs within the lease. The stockpiled topsoil will then be spread out reclaimed area and reseeded with a BLM approved seed mixture. In the event that the well must be worked over or maintained, it may be necessary to drive, park, and/or operate machinery on reclaimed land. This area will be repaired or reclaimed after work is complete.

- B. Final Reclamation: Upon plugging and abandoning the well all caliche for well pad and lease road will be removed and surface will be recountoured to reflect its surroundings as much as possible. Caliche will be recycled for road repair or reused for another well pad within the lease. If any topsoil remains, it will be spread out and the area will be re-seeded with a BLM approved mixture and re-vegetated as per BLM orders.

11. Surface Ownership:

- A. The surface is owned by the U.S. Government and is administered by the Bureau of Land Management. The surface is multiple uses with the primary uses of the region for grazing of livestock and the production of oil and gas.
- B. The surface tenant is Hayhurst-Rook Family Educational Trust, 518 Orchard, Carlsbad, NM 88220.
- C. The proposed road routes and surface location will be restored as directed by the BLM.

12. Other Information:

- A. The area around the well site is grassland and the topsoil is sandy. The vegetation is moderately sparse with native prairie grasses, some mesquite and shinnery oak. No wildlife was observed but it is likely that mule deer, rabbits, coyotes and rodents traverse the area.
- B. There is no permanent or live water in the immediate area.
- C. There are no dwellings within 2 miles of this location.
- D. If needed, a Cultural Resources Examination is being prepared by Boone Arch Services of NM, LLC., 2030 North Canal, Carlsbad, New Mexico, 88220, phone # 575-885-1352 and the results will be forwarded to your office in the near future. Otherwise, **COG will be participating in the Permian Basin MOA Program.**

13. Bond Coverage:

Bond Coverage is Statewide Bonds # NMB000740 and NMB000215

Surface Use Plan
COG Operating LLC
Quien Sabe 25 Federal #2H
SHL: 190' FNL & 1650' FEL UL B
Section 25, T24S, R27E
BHL: 660' FSL & 1980' FEL UL O
Section 25, T24S, R27E
Eddy County, New Mexico

14. Lessee's and Operator's Representative:

The COG Operating LLC representative responsible for assuring compliance with the surface use plan is as follows:

Sheryl Baker
Drilling Superintendent
COG Operating LLC
2208 West Main Street
Artesia, NM 88210
Phone (575) 748-6940 (office)
(432) 934-1873 (cell)

Ray Peterson
Drilling Manager
COG Operating LLC
One Concho Center
600 W Illinois Ave
Midland, TX 79701
Phone (432) 685-4304 (office)
(432) 818-2254 (business)

PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	COG Operating, LLC
LEASE NO.:	NMNM-111412
WELL NAME & NO.:	Quien Sabe 25 Federal 2H
SURFACE HOLE FOOTAGE:	0190' FNL & 1650' FEL
BOTTOM HOLE FOOTAGE:	0660' FSL & 1980' FEL
LOCATION:	Section 25, T. 24 S., R 27 E., NMPM
COUNTY:	Eddy County, New Mexico

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

- ☐ **General Provisions**
- ☐ **Permit Expiration**
- ☐ **Archaeology, Paleontology, and Historical Sites**
- ☐ **Noxious Weeds**
- ☒ **Special Requirements**
 - Berm Well Pad
 - Erosion Control
- ☐ **Construction**
 - Notification
 - Topsoil
 - Closed Loop System
 - Federal Mineral Material Pits
 - Well Pads
 - Roads
- ☐ **Road Section Diagram**
- ☒ **Drilling**
 - Cement Requirements
 - Medium Cave/Karst
 - Logging Requirements
 - Waste Material and Fluids
- ☒ **Production (Post Drilling)**
 - Well Structures & Facilities
 - Pipelines
- ☐ **Interim Reclamation**
- ☐ **Final Abandonment & Reclamation**

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

V. SPECIAL REQUIREMENT(S)

1. Berming of the Well Pad

The entire perimeter of the well pad will be bermed to prevent oil, salt, and other chemical contaminants from leaving the well pad.

- The compacted berm shall be constructed at a minimum of 12 inches high with impermeable mineral material (e.g. caliche).
- No water flow from the uphill side(s) of the pad shall be allowed to enter the well pad.
- The topsoil stockpile shall be located outside the bermed well pad.
- Topsoil, either from the well pad or surrounding area, shall not be used to construct the berm.
- No storm drains, tubing or openings shall be placed in the berm.
- If fluid collects within the bermed area, the fluid must be vacuumed into a safe container and disposed of properly at a state approved facility.
- The integrity of the berm shall be maintained around the surfaced pad throughout the life of the well and around the downsized pad after interim reclamation has been completed.
- Any access road entering the well pad shall be constructed so that the integrity of the berm height surrounding the well pad is not compromised. (Any access road crossing the berm cannot be lower than the berm height.)

2. Erosion

Any water erosion that may occur due to the construction of the well pad during the life of the well will be quickly corrected and proper measures will be taken to prevent future erosion.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS**Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts


Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill out sloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

$$400 \text{ foot road with } 4\% \text{ road slope: } \frac{400'}{4\%} + 100' = 200' \text{ lead-off ditch interval}$$

Cattleguards

An appropriately sized cattleguard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattleguards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.

Construction Steps

1. Salvage topsoil
2. Construct road

3. Redistribute topsoil
4. Revegetate slopes




Figure 1. Cross-sections and plans for typical road sections representative of BLM resource or FS local and higher-class roads.

VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ **Eddy County**

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

1. **Although Hydrogen Sulfide has not been reported in the area, it is always a potential hazard. Operator has stated that they will have monitoring equipment in place prior to drilling out of the surface shoe. If Hydrogen Sulfide is encountered, report measured amounts and formations to the BLM.**
2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. **If the drilling rig is removed without approval – an Incident of Non-Compliance will be written and will be a “Major” violation.**
3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
4. **The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The top and bottom of Salt are to be recorded on the Completion Report.**

B. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.).

The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) time prior to drilling out for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater for all casing strings. DURING THIS WOC TIME, NO DRILL PIPE, ETC. SHALL BE RUN IN THE HOLE. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. IF OPERATOR DOES NOT HAVE THE WELL SPECIFIC CEMENT DETAILS ONSITE PRIOR TO PUMPING THE CEMENT FOR EACH CASING STRING, THE WOC WILL BE 30 HOURS. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Medium Cave/Karst

Possibility of water flows in the Castile and Salado.

Possibility of lost circulation in the Salado and Delaware.

Abnormal Pressures may be encountered in the Wolfcamp.

- 1. The 13-3/8 inch surface casing shall be set at approximately 400 feet and cemented to the surface. If salt is encountered, set casing at least 25 feet above the salt.**
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.**
 - b. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.**
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.**
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.**

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing, which shall be set at approximately 2375 feet (basal anhydrite of the Castile formation) is:

☒ Cement to surface. If cement does not circulate see B.1.a, c-d above. **Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst.**

Formation below the 9-5/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

Centralizers required on horizontal leg, must be type for horizontal service and a minimum of one every other joint.

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:

☒ Cement to surface. If cement does not circulate, contact the appropriate BLM office. **Excess calculates to negative 12% - Additional cement will be required.**

4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **2000 (2M) psi (Installing a 2M annular)**.
 - a. **For surface casing only:** If the BOP/BOPE is to be tested against casing, the wait on cement (WOC) time for that casing is to be met (see WOC statement at start of casing section). Independent service company required.

3. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the 9-5/8 intermediate casing shoe shall be **5000 (5M) psi. 5M system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.**
4. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
 - b. The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer**. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (18 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
 - c. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
 - d. The results of the test shall be reported to the appropriate BLM office.
 - e. All tests are required to be recorded on a calibrated test chart. **A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.**
 - f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

E. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

JAM 091714

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the

largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, **Shale Green** from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

STANDARD STIPULATIONS FOR SURFACE INSTALLED PIPELINES

A copy of the application (Grant, Sundry Notice, APD) and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.
2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 et seq. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.
3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, et seq. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, et seq.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to activity of the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. The holder shall be liable for damage or injury to the United States to the extent provided by 43 CFR Sec. 2883.1-4. The holder shall be held to a standard of strict liability for damage or injury to the United States resulting from pipe rupture, fire, or spills caused or substantially aggravated by any of the following within the right-of-way or permit area:

- a. Activities of the holder including, but not limited to construction, operation, maintenance, and termination of the facility.
- b. Activities of other parties including, but not limited to:
 - (1) Land clearing.
 - (2) Earth-disturbing and earth-moving work.
 - (3) Blasting.
 - (4) Vandalism and sabotage.
- c. Acts of God.

The maximum limitation for such strict liability damages shall not exceed one million dollars (\$1,000,000) for any one event, and any liability in excess of such amount shall be determined by the ordinary rules of negligence of the jurisdiction in which the damage or injury occurred.

This section shall not impose strict liability for damage or injury resulting primarily from an act of war or from the negligent acts or omissions of the United States.

5. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil, salt water, or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil, salt water, or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any responsibility as provided herein.

6. All construction and maintenance activity will be confined to the authorized right-of-way width of 20 feet. If the pipeline route follows an existing road or buried pipeline right-of-way, the surface pipeline must be installed no farther than 10 feet from the edge of the road or buried pipeline right-of-way. If existing surface pipelines prevent this distance, the proposed surface pipeline must be installed immediately adjacent to the outer surface pipeline. All construction and maintenance activity will be confined to existing roads or right-of-ways.

7. No blading or clearing of any vegetation will be allowed unless approved in writing by the Authorized Officer.

8. The holder shall install the pipeline on the surface in such a manner that will minimize suspension of the pipeline across low areas in the terrain: In hummocky or dune areas, the pipeline will be "snaked" around hummocks and dunes rather than suspended across these features.

9. The pipeline shall be buried with a minimum of 24 inches under all roads, "two-tracks," and trails. Burial of the pipe will continue for 20 feet on each side of each crossing. The condition of the road, upon completion of construction, shall be returned to at least its former state with no bumps or dips remaining in the road surface.

10. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. Excluding the pipe, all above-ground structures not subject to safety requirement shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2; designated by the Rocky Mountain Five State Interagency Committee.

13. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. Signs will be maintained in a legible condition for the life of the pipeline.

14. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway.

15. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the authorized officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the authorized officer. An evaluation of the discovery will be made by the authorized officer to determine appropriate cultural or scientific values. The holder will

be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the authorized officer after consulting with the holder.

16. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, powerline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

17. Surface pipelines must be less than or equal to 4 inches and a working pressure below 125-psi.

IX. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

X. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Seed Mixture 1, for Loamy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be no primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law(s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (small/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

<u>Species</u>	<u>lb/acre</u>
Plains lovegrass (<i>Eragrostis intermedia</i>)	0.5
Sand dropseed (<i>Sporobolus cryptandrus</i>)	1.0
Sideoats grama (<i>Bouteloua curtipendula</i>)	5.0
Plains bristlegrass (<i>Setaria macrostachya</i>)	2.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed