## Form 3160-5 (April 2004)

## UNITED STATES

FORM APPROVED

DEPARTMENT OF THE INTERIOR					Expires: March 31, 2007			
BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160 - 3 (APD) for such proposals.						5. Lease Serial Nb. NM-0557370  6. If Indian, Allottee or Tribe Name		
1. Type of Well ☐ ☐ Gas Well ☐ ☐ Other						8. Well Name and No.		
2. Name of Operator Lime Rock Resources A-II, L.P.						Eagle 26 P Federal #4  9. API Well No.		
3a Address 1111 Bagby Street, Suite 4600.	o. (include area 526	code)	30-015-	30-015-39360  10. Field and Pool, or Exploratory Area				
4. Location of Well (Footage, Sec.,				Red La	Red Lake; Glorieta-Yeso NE			
330' FSL and 530' FEL, Sec. 26-T17S-R27E					_	11 County or Parish, State		
	· · · · · · · · · · · · · · · · · · ·		·	<u>:</u>	Eddy C	ounty, New Mexico	<del></del>	
	PPROPRIATE BOX(ES) TO	INDICATE			REPORT, OR	OTHER DATA		
TYPE OF SUBMISSION	TYPE OF ACTION							
✓ Notice of Intent	☐ Acidize ☐ Alter Casing ☐ Casing Repair	Deepen Fracture Tn New Const		Production ( Reclamation Recomplete	Start/Resume)	Water Shut-Off Well Integrity Other Lost Circula	ation	
Change Plans Plug and Abandon				Temporarily Abandon		during drilling and		
Final Abandonment Notice Convert to Injection Plug Back				Water Dispos	al	intent to mitigate09		
testing has been completed. Fi determined that the site is read 09-17-2011 - On the morr after verbal 12-1/4" bit, 13-3/8", 48# cement the c	ning of 9-17-2011, the company approval from Mr. Wesley In and ream the surface hole with H-40 Grade, STC surface piperement to surface using 100 sx 2% calcium chloride. Lime Ring and cementing it in place.	y lost circulation gram at 08:15: h a 17-1/2" bit be, setting the cof Thixotropic cock intends to	on at 75' while a.m. 9-17-201 to 185'. Once taking at 180'. H cement, 19 provide at le	e drilling the 1, intends to e the hole is r . After the ca 50 sx of Class	12-1/4" surface drill the 12-1/4" eamed to depth, sing is set at 180 C cement with	hole. Lime Rock Reson hole to 185' MD. Pull the company intends to 0', the company intends cello flake, and 150 sx of M representatives prio	or has urces, the o run to of Class C	
Verka	approx 1	1. 10	///	, '/		RE	CEIVED	
14. I hereby certify that the fore Name (Printed/Typed)	going is true and correct	1						
Robert S. (Sid) A	Ashworth		Title Produc	ction Enginee	r		7	
Signature Seri (1	shwar		Date		10/05/20TDF	ROVED		
	THIS SPACE FOR	FEDERAL	OR STAT	E OFFIC	E ÚSÈ			
Approved by  Conditions of approval, if any, are certify that the applicant holds legal which would entitle the applicant to	l or equitable title to those rights i				SEB	ate 6 2014  EY W. INGRAM		

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to Pany department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)