			· ·	
Submit 1 Copy To Appropriate District Office	State of New Me	exico	Form C-	103
<u>District I</u> - (575) 393-6161	Energy, Minerals and Natu	ural Resources	Revised July 18, 2 WELL API NO.	2013
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283			30-015-28164	
District III - (505) 743-1283OIL CONSERVATION DIVISION811 S. First St., Artesia, NM 882101220 South St. Francis Dr.		5. Indicate Type of Lease		
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, NM 8		STATE FEE	
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM	Santa Fe, Nivi S	1505	6. State Oil & Gas Lease No.	
87505 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other SWD			7. Lease Name or Unit Agreement Nan	ne
			Lakewood Farms SWD 18	
			8. Well Number	
2. Name of Operator COG Operating LLC			9. OGRID Number 229137	
3. Address of Operator			10. Pool name or Wildcat	
One Concho Center, 600 W Illinois Ave, Midland, TX 79701			SWD;Devonian	
4. Well Location	(() foot from the North	11	(() fact from the West line	
Unit Letter <u>D</u> : Section 18	<u>660</u> feet from the <u>North</u> Township 19S	line and <sup>·</sup> Range 26E	<u>660</u> feet from the <u>West</u> line NMPM County Eddy	
	11. Elevation (Show whether DR			
	33	85	A DETERMINENT OF A DETERMINENT	
12. Check Ap	propriate Box to Indicate N	Nature of Notice	, Report or Other Data	
NOTICE OF INT		SUE	BSEQUENT REPORT OF:	
		REMEDIAL WO		
	CHANGE PLANS	CASING/CEMEN		
CLOSED-LOOP SYSTEM	·		<u>_</u>	
OTHER: Change SWD interval to C		OTHER:	nd give pertinent dates, including estimated	
	(). SEE RULE 19.15.7.14 NMA		ompletions: Attach wellbore diagram of	1 date
COG Operating LLC respectful completion. (Canyon interval 77		om a Devonian	SWD completion to a Canyon SWI	)
Test 0.5/92	- 'n and waarend an aleast			
Test 9-5/8" casing to 500 psi ag Finish drilling out cement plug				
Wash down to plug at 8,950' an	· · · · ·			
Set 500' cement plug so we can				
Re-test 9-5/8 to 500 psi.	8			
Run 7" 26# HCL-80 csg and set				
Cement to surface. Run CBL on	7".			
(Communicated issues with Ra	ndy Dade on 1/22/15)			
•	<u> </u>			
Spud Date:	Rig Release D	ate:		
		L		
I hereby certify that the information ab	ove is true and complete to the h	pest of my knowled	ge and helief	
V.C.			-	
SIGNATURE	TITLE_Lead	Regulatory Analys	tDATE_ <u>1/23/15</u>	
Type or print name <u>Kanicia Castillo</u> For State Use Only	E-mail address: <u>kcasti</u>	illo@concho.com_	PHONE: <u>432-685-4332</u>	
	de Dec	Rinn	uch lab-	_
APPROVED BY: Conditions of Approval (if any):	ject until 500	a gran	<u>/S/1</u>	
	int in a	Dennit :	Approved	
Do Not In	ject until 500	permin 15		