UNITED STATES Expert Oblice 1.004 DEPARTMENT OF THE INTERIOR R-111-POTASE APPLICATION FOR PERMIT TO DRILL OR REENTER Case State No. Is. Type of work: DRULL Is. Address p.O. Box SQ250 Show Thome Num (where were code) Mailand, TX. 79710 432-685-5717 Code Canyon Bone Spring Code Canyon Bone Spring A starface 150 FNL 2000 FVA. NEWN(C) Sec 34 T232S R25E A starface 150 FNL 2000 FVA. NEWN(C) Sec 34 T232S R25E A starface from proposed 1507 Iso Diasec from proposed 1507 Iso Diasec from proposed 685° Bordenard file, minime, if any 1507 Iso Diasec from proposed 685	Yorm 3160-3 (March 2012)	3			Operator		FORM OMB	APPROVED
DEPARTMENT OF THE INTERIOR R-111-POTASIE NumMagazza BUREAU OF LAND MANAGEMENT APPLICATION FOR PERMIT TO DRILL OR REENTER International Colspan="2">International Colspan="2" International Colspan="2" International Colspan="2" International Colspan="2" International Colspan="2" International Colspan="2" International Colspan="2" Internaternatin Colspan="2" International Cols		UNI	ITED STATES		operator	Sobà	Expires	October 31, 2014
APPLICATION FOR PERMIT TO DRILL OR REENTER 1a. Type of work: DIRLL REENTER 1 If Units Alloster or Tribe Name and 1a. Type of work: DIRLL REENTER ATS / U.A 714 I. Units of CA Agreement, Name and 1b. Type of work: DIRLL REENTER ATS / U.A 714 I. Units of CA Agreement, Name and 1b. Type of work: DIRLL REENTER ATS / U.A 714 I. Units of CA Agreement, Name and 2. Name of Openiar OXY USA Inc. (1698) 30-015 4.3 9-400 3b. Address problems of XY USA Inc. (1698) 30-015 4.4 9-400 3b. Address problems of XY USA Inc. (1698) 10.015 4.4 9-400 3b. Address problems of XY USA Inc. (1698) 10.015 4.4 9-400 4. Location of Well (Reper Instantion Control Network Work of Mark State Problems Nation Control Network Work State Nation Natin Nation Natin Nation Nation Nation Nation Nation Natin		DEPARTME	NT OF THE I	NTERIOR	R-111-1	POTASI	NMNMQB6024	
Ia. Type of wark: DRILL REENTER ATS - 14 97 b Ib. Type of wark: DBRILL REENTER ATS - 14 97 b Ib. Type of wark: DBR with Das well Dots Standard Standar	APPLI	CATION FOR I	PERMIT TO (DRILL OR	REENTER		6. If Indian, Allotee	e or Tribe Name
H15, Tupe of Well: Oil Well: Gas Well: Other Isingle Zune Multiple Zune S. Cases Name and Well No. 2. Name of Operator QXY USA Inc. (16896) 9. API Well Na. 30-015: 44.9,4.20 3. Address p.O. Box 50250 Jb. Phone Na. (incluse are order) 10. Field and Body of Exploratory Dedar Campon Bone Spring 4. Location of Well (Roor Ication clearly and in accordance with any Sum repursences Y A surface 150 FNL 2000 FVL NEMW(C) Sac 34 T235 R29E 14. Destance from proposed* I.S. Exploratory Sac 34 T235 R29E I.S. Exploratory 14. Destance from proposed* 150' 1440 ac 16 Sac 34 T235 R29E I.S. Exploratory 15. Distance from proposed* 150' 1440 ac 160 ac 160 ac 18 Proposed Depth 20. EUMPIA Bond Na. on file 21.: Elevations (Mow whether DF, KDB, RT, GL, etc.) 22. Approximate date work will start* 23. Estimated duation 35 days 32. A Surface Use Plan if the location is on National Forest System Lands, the SUP Dave If the location is on National Forest System Lands, the SUP Dave If the location is on National Forest System Lands, the SUP Dave If the location is on National Forest System Lands, the SUP Dave If the location is on National Forest System Lands, the BLM 9. Application and/or plans as may be required I BLM 25. Sign	la. Type of work: 🔽 D	RILL		R	× 11 07/0		7 If Unit or CA Agn	rement, Name and No.
2. Name of Operator OXY USA Inc. (16696) 9. API Well Na 30-015. 4/2 Q=2.0 3a. Address P.O. Box 50250 Midland, TX 78710 3b. Phone Na (neched area code) 10. Field and Pool, or Exploratory Ceder Canyon Bone Spring (4. Locstion of Well (Report Location clearly and in accordance vill any Sour repurements 1) 11. Sec. T. R. M. or Bilk and Survey or Atsurface 150 FNL 2000 FWL NENVU(C) A surface 150 FNL 2000 FWL NENVU(C) Sec 34 T23S R2SE 11. Distance from proposed for indicand riter with line, if any) 150' 14. Distance from proposed for control on carest ing, unit line, if any) 150' 15. Distance from proposed for control of unit line, if any) 16. No of acres in lease 17. Spacing Unit dedicated to this well for control well, diffice, completed, applied for, on this lease, fit. 150' 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 22. Approximate date work will start ⁴ SUPO must be filed with the requirements of Onshore Oil and Gas Order No. I, must be attached to this form: 23. Estimated duration 3327.1' GR 23. Signature Name (Printed Typeed) David Stewart Date 71/ LB[23. Signature Name (Printed Typeed) David Stewart Date 71/ LB[23. Signature Name (Printed Typeed) David Stewart David Stewart@oxy. com Date 71/ LB[23. Signature Name (Printed Typeed) Date 71/ LB[Date 71/ LB[i wei) 🗍 Gas Weil	Other	FT Sine		pie Zone	8. Lease Name and Cypress 34 Federa	Well No. al #11H (2047
3L. Address P.O. Box 50250 Midland, TX 79710 3b. Phone No. (include area cody 432.685.5717 10. Field and Pool, or Exploratory Codar Canyon Bone Spring 4. Location of Well (Report location clearly and in accordance with any Sone repursions.) At surface 150 FNL 2000 FWL. NENWICD At proposed prot. Zone 180 FSL 1979 FWL SESW(N) 11. Sec., T. R. M. or Bilk and Survey or Sec 34 T23S R29E 14. Distance in miles and direction from nearest lown or post office* 6 miles nontheast from Loving, NM 15. Size (The Number of Sec. 1979 FWL SESW(N) 13. Size (The Number of Sec. 1979 FWL SESW(N) 15. Distance in miles and direction from nearest lown or post office* 6 miles nontheast from Loving, NM 16. No. of acres in lease 17. Spacing Unit dedicated to this well 160 ac 13. Siz (Ada to nearest in operation to nearest property or lease line, if any) 1440 ac 160 ac 14. Distance from opposed Loridon* 10. Reposed Dopth sepplied for, on this less, fit. 19. Proposed Depth 8859' 13524'M 20. ELMBIA Bond Na on file NMB000B62 ESB000226 21. Elevation (Show whether DF, KDB, RT, GL, etc.) 32. A Drifting Plan. 22. Approximate date work will start* 32. A Attachments 21. Estimated duration 35 days 23. A Surface Use Filen (if the location is on National Forst System Lands, the SUPO must be filen with the appropriate Forest Service Office). 4. Mane (Printed Typed) David Stewart Box(d, stewart@oxy.com 25. Signature Name (Printed Typed) David Stewart Date 1/16. 25. Signature Name (Printed Typed) David Stewa	2. Name of Operator OXY	USA Inc.		<u> </u>	(16696)		9. API Well Na 30-015- 429-	<u></u> 20
4. Location of Well (Report Jecation clearly and in accordance with any Sure requirements y At surface 150 FNL 2000 FWL NENW(C) At proposed prod. zone 180 FSL 1979 FWL SESW(N) 11. Sec., T. M. or Bilk and Survey or. Sec. 34 T23S R29E 14. Distance in miles and direction from nearest lown or post office" 12. County or Parish Bottom to rearest direction from nearest lown or post office" 13. Sin MM 15. Distance from proposed* Incluion to rearest direction from nearest lown or post office" 16. No. of acres in lease 17. Spacing Unit dedicated to this well tocation to nearest direction from proposed location* to nearest well, drilling, completed, espiled for, on this tess, ft. 19. Proposed Depth 8557 20. BLM/BIA Bond Na. on file NMB000862 20. BLM/BIA Bond Na. on file NMB000862 20. BLM/BIA Bond Na. on file NMB000862 21. "Elevations (Show whether DF, KDB, RT, GL, etc.) 3027.1' GR 22. Approximate date work will start* 22. Approximate date work will start* 23. Signature 23. Estimated duration 35 days 24. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be file with the appropriate Forest Service Office). 4 Bond to cover the operations unless covered by an existing bond on the 20 above). 25. Signature Mam (Printed Typed) Date T/1 (E) 26. Signature Name (Printed Typed) Date LSUM 27. Defiling Plan Signature Name (Printed Typed) Date LSUM 28. Signature Name (Printed Typed) Date LSUM </td <td>3a. Address P.O. Box 502 Midland TX</td> <td>250</td> <td>1</td> <td>3b. Phone No. 432-685-57</td> <td>(include area code) 17</td> <td></td> <td>10. Field and Pool, or Cedar Canyon Bor</td> <td>Exploratory</td>	3a. Address P.O. Box 502 Midland TX	250	1	3b. Phone No. 432-685-57	(include area code) 17		10. Field and Pool, or Cedar Canyon Bor	Exploratory
At surface 130 FNL 2000 FWL NERVICID Sec 34 T23S R29E At proposed prod. zone 180 FSL 1379 FWL SESW(N) 12. County or Parish 13. Sit Because from proposed* 12. County or Parish 13. Sit Sec 34 T23S R29E 13. Sit 14. Distance from proposed* 13. Sit Index on the set first, the property or lease first, the property	4. Location of Well (Report 1	location clearly and in	accordance with any	State requiremen	us. 9		11. Sec., T. R. M. or B	Blk and Survey or Area
14. Distance in miles and direction from nearest lown or post office* 12. County or Parish Eddy 13. Sin MM 15. Distance from proposed* 16. No. of acres in lease 17. Spacing Unit Ideicated to this well tool to acrest in the eddy of the eddy 18. Distance from proposed location* 19. Proposed Depth 20. BL/MBIA Bond No. on file NM 16. Distance from proposed location* 19. Proposed Depth 20. BL/MBIA Bond No. on file NBD000862 ESB000226 21 Elevations (Show whether DF, KDB, RT, GL, etc.) 22. Approximate date work will start* 23. Estimated duration 23. Estimated duration 2. A triachments 74. A triachments 74. A triachments 74. A triachments 7. Nelling Plan. 14. Subtract for proposal by a registered surveyor. 4. Bond to cover the operations unless covered by an existing bond on a SUPO must be filed with the appropriate Forest Service Office. 4. Bond to cover the operations and/or plans as may be required to BLM. 25. Signature Name (Printed Typed) Date 71. (B) 71. The For Marce Stary of the subject tease while work would entitle the applicant of the subject tease work would entitle the applicant of the proposal does office. 5. Operator certification 25. Signature Name (Printed Typed) Date 71. (B) 71. tele Stary office	At surface 150 FNL 20 At proposed prod. zone 1	80 FSL 1979 FWL	SESW(N)				Sec 34 T23S	R29E
15. Distance from proposed* property or tease line, ft. (Also to nearest drig. unit line, if any) 150° 16. No. of acres in lease 1440 ac 17. Spacing Unit dedicated to this well 160 ac 18. Distance from proposed location* to nearest well, dulling, completed, applied for, on this lease, ft. 19. Proposed Depth 885° 20. BLM/BIA Bond Na. on file NMB0000862 ESB000226 21.* Elevations (Show whether DF, KDB, RT, GL, etc.) 3027.1' GR 22. Approximate date work will start* 23. Estimated duration 35 days 24. Attachments The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. I, must be attached to this form: 35. days 1. Well plat certified by a registered surveyor. 4. Bond to cover the operations unless covered by an existing bond on liem 20 above). 2. Signature 4. Bond to cover the operations and/or plans as may be required I BLM. 2. Signature Name (Printed Typed) David Stewart Date 11. (B[16. Fe Age) 7. Title Fe Age CE o Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant conduct operations shere. Date 11. (B[16. Fe Age] 16. Fe Age] Name (Printed Typed) David Stewart Date 11. (B[16. File USC. Section 1001 and Tide 43 USC. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the Us States any fasks,	14. Distance in miles and direct 6 miles northeast I	tion from nearest town from Loving, NM	or post office*	·			12. County or Parish Eddy	13. State NM
(Also to nearest ang. unit me, it any) 10.0 me 18. Distance from proposed location* 19. Proposed Depth applied for, on this lease, ft. 695' 21. Elevations (Show whether DF, KDB, RT, GL, etc.) 22. Approximate date work will start* 23. Estimated duration 3027.1' GR 24. Attachments 24. Attachments 24. Attachments 25. Signature 24. Attachments 26. Signature 4. Bond to cover the operations unless covered by an existing bond on liten 20 above). 25. Signature Name (Printed Typed) 26. Signature Date 71.1'Ele Sr. Regulatory Advisor Approval does not warrant or certify that the applicant holds legator requirable title to those rights in the subject lease which would entitle the applicant holds legator equitable title to those rights in the subject lease which would entitle the applicant holds legator equitable title to those rights in the subject lease which would entitle the applicant holds legator equitable title to those rights in the subject lease which would entitle the applicant holds legator equitable title to those rights and willfully to make to any department or agency of the Us Sute sum frage. Find that the applicant holds legator equitable title to those rights in the subject lease which would entitle the applicant holds legator equitable title to those rights in the subject lease which would entitle the applicant holds legator equitable title to those rights and willfully to make to any department or agency of the Us Sute sum frage. F	15. Distance from proposed* location to nearest property or lease line, it.	150		16. No. of acr 1440 e	es in lease	17, Spacin 160 -	g Unit dedicated to this t	well
12 Distance Initial projects of the initial properties of the initial propertis of the initial propert	(Also to nearest drig, unit li	ine, if any)		19 Proposed F	Jenth	20 BI M/F	IA Bond No. on file	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3027,1' GR 22. Approximate date work will star* 02/10/2015 23. Estimated duration 35 days 24. Attachments 24. Attachments 7. Well plat certified by a registered surveyor. 24. Attachments be attached to this form: 1. Well plat certified by a registered surveyor. 4. Bond to cover the operations unless covered by an existing bond on ltem 20 above). 25. Signature 4. Bond to cover the operations unless covered by an existing bond on ltem 20 above). 25. Signature Name (Printed Typed) David Stewart 7. Title Sr. Regulatory Advisor 6. Supproved by approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant conduct operations thereon. Date 7. Title FC MAA 7. Title IB USC. Section 1000 and Tide 43 USC. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the Us States any fake, ficilitous or fraududent statements or representations as to any matter within its jurisdiction.	to nearest well, drilling, con applied for, on this lease, ft.	npleted, 895	•	8859V 135	524'M	NMB000	862 ESB000226	
24. Attachments The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, must be attached to this form: 1. Well plat certified by a registered surveyor. 4. Bond to cover the operations unless covered by an existing bond on Item 20 above). 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). 4. Bond to cover the operations unless covered by an existing bond on Item 20 above). 25. Signature 4. Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). 5. Operator certification 25. Signature Name (Printed Typed) Date 71 (18) Title Sr. Regulatory Advisor david_stewart@oxy.com Approved by domany Name (Printed Typed) Date If (18) Title For March Conditions approval does not warrant or certify that the applicant holds legalor equitable title to those rights in the subject lease which would entitle the applicant holds legalor equitable title to those rights in the subject lease which would entitle the applicant conduct operations of approval, if any, are stached. Title B USC. Section 1001 and Tide 43 USC. Section 1212, make it a crime for any person knowingly and willfolly to make to any departmen	212 Elevations (Show whether 3027.1' GR	DF, KDB, RT, GL, e	etc.)	22. Approxima	ite date work will sta	r1 ^{\$}	23. Estimated duration	n
The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, must be attached to this form: 1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). 25. Signature 4 25. Signature 4 26. Approved by Starge Machiner 71.168			1	02/10/2015			35 days	
David Stewart Title Sr. Repulatory Advisor david_stewart@oxy.com Approved by Approved Name (Printed Typed) Title State and the subject lease which would entitle the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant conduct operations thereon. Conditions of approval, if any, are attached. Title IS US.C. Section 1001 and Title 43 US.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the Unstates any false, fictilious or fraudulent statements or representations as to any matter within its jurisdiction.	The following, completed in acco 1. Well plat certified by a registr 2. A Deilling Plan	ordance with the requi	rements of Onshore	02/10/2015 24. Attach Oil and Gas O	ments rder No. I, must be a 4 Bond to cover th ltem 20 above).	itached to this	35 days form: s unless covered by an	existing bond on file (see
Interest Sr. Repulatory Advisor david_stewart@oxy.com Approved by segment (Interest Stewart) Date Date Approved by segment (Interest Stewart) Date Date Title St. George MacDonell Date For Mark Office C For Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant conduct operations thereon. Conditions of approval, if any, are attached. Title 18 US.C. Section 1001 and Title 43 US.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the Us States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Attachement or agency of the Us States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	The following, completed in acco 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the I SUPO must be filed with the	ordance with the requi lered surveyor. location is on Nations appropriate Forest Se	rements of Onshore at Forest System La rvice Office).	02/10/2015 24. Attach Oil and Gas Or ands, the	ments rder No. I, must be al 4 Bond to cover th Item 20 above). 5. Operator certific 6. Such other site BLM. Trinted Timeda	tached to this are operation ation specific info	35 days form: s unless covered by an mation and/or plans as	existing bond on file (see may be required by the
Approved by proved by pro	The following, completed in acco 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the I SUPO must be filed with the 25. Signature	ordance with the requi lered surveyor. location is on Nations appropriate Forest Se	rements of Onshore at Forest System La rvice Office).	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S	ments der No. 1, must be a 4 Bond to cover th Item 20 above). 5 Operator certific 6 Such other site BLM. rinted Typed) towart	itached to this ne operation ation specific info	35 days form: s unless covered by an mation and/or plans as	existing bond on file (see may be required by the Date -1118(14
File Office For March CFo Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Tide 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the Us States any false, fictilious or fraudulent statements or representations as to any matter within its jurisdiction.	The following, completed in accord 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the USUPO must be filed with the 25. Signature Title Sr. Regulatory Adviso	ordance with the requi tered surveyor. location is on Nations e appropriate Forest Se	rements of Onshore at Forest System La invice Office).	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S	ments rder No. I, must be al 4 Bond to cover th Item 20 above). 5. Operator certific 6. Such other site BLM. rinted Typed) towart david_ster	tached to this ne operation ation specific infor wart@oxy.	35 days form: s unless covered by an mation and/or plans as	existing bond on file (see may be required by the Date -1 (B (14
Application approval does not warrant or certify that the applicant holds legal or equitable title to those tights in the subject lease which would entitle the applicant conduct operations thereon. Conditions of approval, if any, are attached. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the Us States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.	The following, completed in accu- 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the I SUPO must be filed with the 25. Signature Title Sr. Repulatory Adviso Approved by Asproven	ordance with the requi tered surveyor. location is on Nations appropriate Forest Se	rements of Onshore at Forest System La rvice Office).	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P	ments rder No. I, must be al 4 Band to cover the ltem 20 above). 5. Operator certific 6. Such other site : BLM. rinted Typed) itewart david_ster rinted Typed) /s/George	tached to this a operation ation specific infor wart@oxy.	35 days form: s unless covered by an mation and/or plans as com	existing bond on file (see may be required by the Date $-1(18(14))$ Date $-16/15$
Title 18 U.S.C. Section 1001 and Tide 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the Un States any false, fictilious or fraudulent statements or representations as to any matter within its jurisdiction.	The following, completed in acc. 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the I SUPO must be filed with the 25. Signature Title Sr. Regulatory Adviso Approved by Samaan Marine Title For Marine	ordance with the requi	rements of Onshore at Forest System La rvice Office).	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P David S	ments rder No. I, must be a 4 Bond to cover th ltem 20 above). 5. Operator certific 6. Such other site: BLM. rinted Typed) towart david_ster rinted Typed; /S/George CFo	tached to this ation specific infor wart@oxy.	35 days form: s unless covered by an mation and/or plans as corn	existing bond on file (see may be required by the Date 71(18(14 Date 16/15
	The following, completed in acc. 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the I SUPO must be filed with the 25. Signature Title Sr. Reputatory Adviso Approved by Approven Title For Market Application approval does not we conduct operations thereon. Conditions of approval, if any, a	ordance with the requi lered surveyor. location is on Nations appropriate Forest Se	rements of Onshore at Forest System La rvice Office). he applicant holds t	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P Office legal or equitab	ments rder No. I, must be al 4 Bond to cover th Item 20 above). 5. Operator certific 6. Such other site: BLM. rinted Typed) towart david_ster rinted Typed) /S/George CFo le title to those right	tached to this ation specific infor wart@oxy. ViacDor s in the subject	35 days form: s unless covered by an mation and/or plans as com	existing bond on file (see may be required by the Date -1(18(14)) Date 1/16/15 ntitle the applicant to
(Continued on page 2) *(Instructions on pa	The following, completed in acci 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the I SUPO must be filed with the 25. Signature Title Sr. Repulatory Adviso Approved by Strangery Title For Market Application approval does not w conduct operations thereon. Conditions of approval, if any, as Title BUSC. Section 1001 and To States any false, ficilitious or frauc	ordance with the requi lered surveyor. location is on Nations appropriate Forest Se arrant or certify that the re attached. Tide 43 U.S.C. Section I dulent statements or re	rements of Onshore at Forest System La rvice Office). he applicant holds to 1212, make it a crim epresentations as to e	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P David S Name (P David S Continue legal or equitab the for any personal any matter with	ments rder No. I, must be al 4 Bond to cover the Item 20 above). 5. Operator certific 6. Such other site BLM. rinted Typedy itewart crimed Typedy /S/George CFo le title to those right on knowingly and win its jurisdiction.	tached to this at operation ation specific infor wart@oxy. ViacDor s in the subji	35 days form: s unless covered by an mation and/or plans as com nell ct lease which would en	existing bond on file (see may be required by the Date $-1(18(14))$ Date $1/16/15$ ntitle the applicant to r agency of the United
SEE ATTACHED FOR APPROVAL SUBJECT TO	The following, completed in acci 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the i SUPO must be filed with the 25. Signature Title Sr. Repulatory Adviso Approved by Support Title For Application approval does not we conduct operations thereon. Conditions of approval, if any, a Title B U.S.C. Section 1001 and Tr States any false, fictitious or frauce (Continued on page 2)	ordance with the requi tered surveyor. location is on Nationa appropriate Forest Se or arrant or certify that the re attached. Tide 43 U.S.C. Section I dulent statements or re	rements of Onshore al Forest System La rvice Office). he applicant holds to 1212, make it a crim epresentations as to e	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P David S Name (P David S Office legal or equitab the for any personal any matter with	ments rder No. I, must be al 4 Bond to cover the ltem 20 above). 5. Operator certific 6. Such other site: BLM. Printed Typed) towart CFo le title to those right on knowingly and win its jurisdiction.	tached to this ne operation ation specific infor wart@oxy. VacDor s in the subjection illfully to ma	35 days form: s unless covered by an mation and/or plans as com nell set lease which would en ke to any department or *(Instr	existing bond on file (see may be required by the Date $-1(18(14))$ Date $16/15$ ntitle the applicant to r agency of the United ructions on page 2)
CONDITIONS OF APPROVAL GENERAL REQUIREMENTS AND	The following, completed in acci 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the I SUPO must be filed with the 25. Signature Title Sr. Repulatory Adviso Approved by Support Title For Market Application approval does not we conduct operations thereon. Conditions of approval, if any, and Title BUSC. Section 1001 and The States any false, ficilitious or frauditions of approval (Continued on page 2) SEE ATTACHI	ordance with the requi tered surveyor. location is on Nations appropriate Forest Se arrant or certify that the reatrached. Tide 43 U.S.C. Section I dutent statements or re ED FOR	rements of Onshore at Forest System La rvice Office). he applicant holds to 1212, make it a crim epresentations as to o	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P David S Name (P David S Name (P David S Name (P David S Name (P) David S David S	ments rder No. I, must be al 4 Band to cover th Item 20 above). 5. Operator certific 6. Such other site : BLM. rinted Typed) itewart david_ster rinted Typed) /s/George I CFo le title to those right on knowingly and w in its jurisdiction.	tached to this a operation ation specific infor wart@oxy. ViacDor s in the subje illfully to ma	35 days form: s unless covered by an mation and/or plans as com nell set lease which would en ke to any department or *(Instr SUBJECT TO	existing bond on file (see may be required by the Date $-1(18(14))$ Date $16/15$ ntitle the applicant to r agency of the United ructions on page 2)
Attached	The following, completed in acc. 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the I SUPO must be filed with the 25. Signature Title Sr. Repulatory Adviso Approved by Standary Title For Market Application approval does not w conduct operations thereon. Conditions of approval, if any, as Title BUSC. Section 1001 and T States any false, fictitious or frauc (Continued on page 2) SEE ATTACHI CONDITIONS	ordance with the requi lered surveyor. location is on Nation: appropriate Forest Se arrant or certify that the re attached. Tide 43 U.S.C. Section I dulent statements or re ED FOR OF APPRO.	rements of Onshore at Forest System La rvice Office). he applicant holds to 1212, make it a crim epresentations as to d	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P David S Name (P David S Name (P David S Name (P David S Name (P David S Name (P) David S	ments rder No. I, must be al 4 Bond to cover the ltem 20 above). 5. Operator certific 6. Such other site: BLM. rinted Typedy itewart crimed Typedy /s/George I cro le title to those right on knowingly and with its jurisdiction. APPR GENE OPER	tached to this at operation ation specific infor wart@oxy. ViacDor s in the subject illfully to ma OVAL S RAL R	35 days form: s unless covered by an mation and/or plans as com nell ectlease which would en ke to any department or *(Instr SUBJECT TO EQUIREMEN DI-11-ATION+O	existing bond on file (see may be required by the Date $-1 (B 14)$ Date $16/15$ ntille the applicant to r agency of the United ructions on page 2)
Rule 5.9 prior to transporting/selling	The following, completed in acc. 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the i SUPO must be filed with the 25. Signature Title Sr. Reputatory Adviso Approved by Structure Title For Market Application approval does not we conduct operations thereon. Conditions of approval, if any, a Title 18 U.S.C. Section 1001 and Ti States any false, fictitious or fraut (Continued on page 2) SEE ATTACHI CONDITIONS	ordance with the requi lered surveyor. location is on Nation: appropriate Forest Se arrant or certify that the re attached. Tide 43 U.S.C. Section I dutent statements or re ED FOR OF APPRO	rements of Onshore al Forest System La rvice Office). he applicant holds I 1212, make it a crim epresentations as to e	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P David S Name (P David S Office legal or equitab the for any person any matter with	ments rder No. I, must be al 4 Bond to cover the ltem 20 above). 5. Operator certific 6. Such other site: BLM. rinted Typedy itewart CFo le title to those right on knowingly and win its jurisdiction. APPR GENE SPEC ATTAC	tached to this at operation ation specific infor wart@oxy. MacDor s in the subject illfully to ma OVAL S RAL R ALST CHED	35 days form: s unless covered by an mation and/or plans as com nell set lease which would en ke to any department or *(Instr SUBJECT TO EQUIREMEN PULATIONS	existing bond on file (see may be required by the Date $-1 (B 14)$ Date $16/15$ ntille the applicant to r agency of the United ructions on page 2)
product. X AD	The following, completed in acci 1. Well plat certified by a regist 2. A Drilling Plan. 3. A Surface Use Plan (if the i SUPO must be filed with the 25. Signature Title Sr. Repulatory Adviso Approved by Strong Mark Title For Mark Application approval does not we conduct operations thereon. Conditions of approval, if any, a Title 18 U.S.C. Section 1001 and Tr States any false, fictilious or fraut (Continued on page 2) SEE ATTACHI CONDITIONS Must be in Rule 5.9 p	ordance with the requi tered surveyor. location is on Nationa appropriate Forest Se rarrant or certify that the re attached. Tide 43 U.S.C. Section I dulent statements or re ED FOR OF APPRO. n compliance prior to transp	rements of Onshore al Forest System La rvice Office). he applicant holds I 1212, make it a crim epresentations as to d VAL with NMOCI orting/selling	02/10/2015 24. Attach Oil and Gas Or ands, the Name (P David S Name (P David S Office legal or equitab the for any personany matter with Define the second seco	ments rder No. I, must be al 4 Bond to cover the ltem 20 above). 5. Operator certific 6. Such other site: BLM. rinted Typedy itewart CFS le title to those right on knowingly and win its jurisdiction. APPR GENE SPEC ATTA(tached to this at operation ation specific infor wart@oxy. MacDon s in the subject illfully to ma OVAL S RAL R AL=ST CHED	35 days form: s unless covered by an mation and/or plans as com nell set lease which would en ke to any department or *(Instr SUBJECT TO EQUIREMEN PULATIONS	existing bond on file (see may be required by the Date $-1(18(14))$ Date $16/15$ ntitle the applicant to r agency of the United ructions on page 2)

OPERATOR CERTIFICATION

I hereby cartify that I, or someone under my direct supervision, have inspected the drill site and access route proposed herein; that I am familiar with the conditions that presently exist; that I have full knowledge of State and Federal laws applicable to this operation; that the statements made in this APD package are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed in conformity with this APD package and the terms and conditions under which it is approved. I also certify that I, or the company I represent, am responsible for the operations conducted under this application. These statements are subject to the provisions of 18 U.S.C. 1001 for the filing of false statements. Executed this <u>UST</u> day of <u>True</u>, 2014.

Name:Jeff Gartland
Position:Reservoir Management Team Leader
Address:5 Greenway Plaza, Suite 110, Houston, TX 77046
Telephone:713-552-8567
E-mail: (optional):jeff_gartland@oxy.com
Company:Occidental Permian LP / OXY USA Inc / OXY USA WTP LP
Field Representative (if not above signatory):Dusty Weaver
Address (If different from above): _P.O. Box 50250 Midland, TX 79710
Telephone (if different from above):432-685-5723
E-mail (if different from above):calvin_weaver@oxy.com

Confer 1. (DD) N. America De, Meinte, Ned DECKS Finner (JTD) 200-4161 Fine (JTD) 200-4163 Finet (J 1113 Fine St, Anerek, Ned BELLO Finet (JT) Finet (JTD) 740-720 JTD) B. B. Persen De, Sam Fe, Ned FROM JTD) B. B. Persen De, Sam Fe, Ned FROM JTD) B. B. Persen De, Sam Fe, Ned FROM JTD) J. B. Persen De, Sam Fe, Ned FROM JTD) J. B. Persen De, Sam Fe, Ned FROM JTD) J. B. Persen De, Sam Fe, Ned FROM JTD) J. B. Persen De, Sam Fe, Ned FROM JTD) J. B. Persen De, Sam Fe, Ned FROM JTD) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. B. Persen De, Sam Fe, Ned FROM JED) J. JED J. JED J. JED) J

c.??..

1.52 6 3

and the second second

State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSER VATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-102 Revised August 1, 2011 Submit one copy to appropriate District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT												<u></u>	
	AP	I Needo			3	taal Code	T	· ·		Pool Name	1		· · · · · · · · · · · · · · · · · · ·
30-0	25-	42	420		<u></u>	520			edar (au	yon (sove	Spr	ing
Prop Rou	any Code I 7 A	0											Vell Nutaber 11 Li
	PITI NG	0	·		(CIPRESS	Chanter Menter Reported						
1 11	et.					ΟΥΥ	IIS I	INC				3	097 1'
	974					- Chri		antion		·			UR 7.1
UL or lot po	Section	Ta	mahla	·	Rana	رسم و	Lot Ka	Feet Gom the	Nanth/Santh line	Feet from the	Enst/W	ent ling	Capaty
C	34	29	SOUTH	29	EAST.	Ň.M.P.M		150'	NORTH	2000'	NES.	7	EDDY
	1-1												
ITT or bet on			con a b fer	BO	uom H	OLE LOCAL	On II I	MITCHENT I	North Surtac	C Erest Group day 1	E	wet Hones I	(hereite)
	94	20 20 20	SU11111	90	FAST	NNDN	TOS INC	180°		1070'	Enter We		FOR
a set al	34		3001 <u>A</u> ,		BADI, 1	N. 2. 5'. E.	<u>×.</u>	100	SUUIA	19/8	WE5		
Dedicated	Acres	Joist	or laft)	Coasolid	ulos Codo	Order No.	م هيريه الرود						1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 - 1995 -
160		LN				<u> </u>						<u> </u>	
No allowa	ble wil	l be as	signed to	this con	pletion	until all inter	ests ha	ve been cons	solidated or a 1	on-standard	unit has b	een appr	oved by the
division.				a particular and a			* .						
	an a	<u></u>	AUTO	NUN CX	anne ann ann ann ann ann ann ann ann ann			i i					1792/147
	20	00'	N		l I	C CUREACE I	OC A DOM	!			- ANI DA C		11049
	19	89'	6 9	march	Y 3	NEW MENO	DEALDIN DEAST	11		I have by son	i des de la factoria	des anticient,	lents to train could
				11	A.S	7-4614 1-610							(=14=43
8 2				1.0	ê Vî	LAT N 32	2680371	r []		arguntation (ater and a ver	tter hand or i	entranal sciences
				i je se						terrat is the	had balang ti	propried lase	en lak konste er
			1 JF5L	53		·		1		देव र रहेते छ।	dill dis sull at e	të kazingan	
			<u> </u>		<u>x</u> 4		- ,	_'			- (fann) e cainen -	le sodig lat	
		21.214		·	8 3 Y	<u>) ist a constant of</u>	· · · · · · · · · · · · · · · · · · ·	_1			tig Grassad er	o caspelory p	anday order
			§	Į.		TOP PI	DEF.						TETET AND
	1999 av 199		8 3	\$		NAD 16 Y=4612	27 42.8	1		le:	<u>Z</u>		
		ļ		2		X=8109 LAT.: N 32.1	675623 _	. [1			1.	L-C.	
F		Í		2	603	LONG: W 103	9742193	<u> </u>		Vinite -	staular	t se	Kez-Dew.
		ļ	§ 2 §	8	<u> </u>			ł		dewid	_staw	-100	ky.com
		[<u> </u>	<u> </u>	<u>s</u>		_ ~	_1		B-coll Addres	,		
		Ę		ài								· · ·	
		È		8 5				1		SLRV	SYOR COL	STRADO	N .
				\$ ₹	<u> </u>	BOTTON	ERF.	יר		I brain a	See S	V LAR	and an alter
		È		7 5	8 53 I	NEW MEDICO NAO 18	EAST	1.1					
		Ę		81 0	828	Y=46662 X=01105	18			and to fe	a si	Gen Po	
				ৰা <u>চ</u> মান্দ	s ×s	LONG.; W 103	148873 9740934	1			31 (9)	3076	161
					8 8)	[-1			doval.	end a	
		2	- 8	과[**	·		-,		- market	18		ø/
			<u>; </u>		₹ /]=		in the second			A Straten of		W swa	
			3		¥ ŠA			- - /					
			3	1		BOTTOM HOLE	LOCATION	41				<i>A</i>	
•		3	3	1/1	¥ 81	NAD 192	27 7 01	1.		PT	n	1 1	ali
¢	1980	<u>Ľ Ř</u>	<u> </u>	\mathcal{L}		LATL N 37.79	76 138007	11		den	9616	loc K	7/10/2018
g	1979	<u> </u>	11111		<u> </u>	LONG: W TOLS	740890	11		Continue)	₽ 5 4	15	079
		8	100 180's	alingthe	<u> </u>						HON	130919WL-	-a (Her. A) AND
-					•								التقتقية ويتشاده

مهود میشود. موجود است از میشود از می

(March 2012)		50	UCD Arte	310	OMB N Expires (No. 1004-0137 October 31, 2014
<i>r</i>	DEPARTMENT OF THE	es E interioi	R R-111-PO	ГАSH	5. Lease Serial No.	
	BUREAU OF LAND MA	ANAGEMEN	T R REENTER		6. If Indian, Allotee	e or Tribe Name
la. Type of work: 🚺 DRIL	L REEN	ITER A	15-14-976		7. If Unit or CA Agree	eement, Name and No.
lb. Type of Well: 🚺 Oil We	ell Gas Well Other	\checkmark	Single Zone 🔲 Multip	le Zone	8. Lease Name and Cypress 34 Federa	Well No. al #11H
2. Name of Operator OXY US	A Inc.		16696		9. API Well No. 30-015-	12920
3a. Address P.O. Box 50250 Midland, TX 79	710	3b. Phone 1 432-685-	No. (include area code) 5717		10. Field and Pool, or Cedar Canvon Bor	Exploratory ne Spring
4. Location of Well (Report local	tion clearly and in accordance with	any State requir	ements.*)		11. Sec., T. R. M. or B	Blk. and Survey or Area
At surface 150 FNL 2000	FWL NENW(C)				Sec 34 T23S	8 R29E
14. Distance in miles and direction	from nearest town or post office*	·			12. County or Parish	13. State
6 miles northeast from	n Loving, NM	16 No of	aaraa in laasa	17 Spacin	Eddy	NM well
location to nearest property or lease line, ft. (Also to nearest drig. unit line,	150' . if any)	14	40 ac	160 a	ac	weit
 Distance from proposed location to nearest well, drilling, complet applied for on this lease ft 	n* ^{eted,} 895'	19. Propos 8859'V	sed Depth 13524'M	20. BLM/F NMB000	BIA Bond No. on file D862 ESB000226	· · · ·
21. Elevations (Show whether DF	F, KDB, RT, GL, etc.)	22 Appro	ximate date work will star	t*	23. Estimated duratio	on
	1, <u>1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1</u>	24 Arr	achments		55 days	
The following completed in accord	ance with the requirements of Ons	hore Oil and Ge	s Order No.1. must be at	tached to thi	s fo r m:	
 A Driting Plan. A Surface Use Plan (if the loc. SUPO must be filed with the ap 25. Signature 	ation is on National Forest Syste propriate Forest Service Office).	m Lands, the	5. Operator certific 6. Such other site BLM. e (Printed Typed)	ation specific info	ormation and/or plans as	S may be required by t
Title	4	Dav	id Stewart			(18(1)
Sr. Regulatory Advisor			david_ste	wart@oxy	.com	
Approved by (Signature)	ge MacDonell	Nam	e (Printed Typed)			DateJAN 16
Title FIEL	MANAGER	Offi	CARLS	BAD FIF		
Application approval does not war	rant or certify that the applicant he	olds legal or eq	uitable title to those right	ts in the sub	ject lease which would e	entitle the applicant to
Conditions of approval, if any, are	attached.				APPROVAL	FOR TWO Y
Title 18 U.S.C. Section 1001 and Title	e 43 U.S.C. Section 1212, make it a lent statements or representations	crime for any as to any matter	person knowingly and w within its jurisdiction.	villfully to m	ake to any department of	or agency of the Unite
States any false, fictitious or fraudu			<u> </u>		*(Inst	tructions on page
States any false, fictitious or fraudu (Continued on page 2)						۳۸
(Continued on page 2)			APP	ROVA	L'ONRIEULI	10
(Continued on page 2)	TACHED		APP GEN	ROVA	REDITIREM	ENTS AND
(Continued on page 2) States any false, fictitious or fraudu (Continued on page 2)	TACHED FOR		APP GEN SPF	ROVA IERAL	REQUIREMI	ENTS AND
States any false, fictitious or fraudu (Continued on page 2) SEE AT CONDIT	TACHED FOR LIONS-OF-APPRO	VAT	APP GEN SPE	ROVA IERAL CIAL S ACHFI	REQUIREMI	ENTS AND
States any false, fictitious or fraudu (Continued on page 2) SEE AT CONDIT	TACHED FOR LIONS-OF-APPRO	VAL	APP GEN SPE ATT	ROVA IERAL CIAL S ACHEI	REQUIREMI	ENTS AND
States any false, fictitious or fraudu (Continued on page 2) SEE AT CONDIT NM OIL CONSER ARTESIA DISTRI	TACHED FOR LIONS-OF-APPRO VATION	VAL	APP GEN SPE ATT	ROVA IERAL CIAL S ACHEI	REQUIREMI STIPULATION	ENTS AND NS r basin

District 1 1625 N. French Dr., Hobbs, NM 88240 Phone: (375) 393-6161 Fax: (375) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone: (375) 748-1282 Fax: (375) 748-9720 District III 1000 Rio Branst Road, Atte., NM 87410 Phone: (505) 347-6178 Fax: (505) 334-6170 District IV 1220 S. St. Francis Dr., Sama Fe, NM 87505 Phone: (505) 476-3460 Fax: (505) 476-3462

.

•

4

State of New Mexico Energy, Minerals & Natural Resources Department OIL CONSERVATION DIVISION 1220 South St. Francis Dr. Santa Fe, NM 87505 Form C-102 Revised August 1, 2011 Submit one copy to appropriate District Office

AMENDED REPORT

	WELL LOCATION AND ACREAGE DEDICATION PLAT												
[API	Number		L	Pool Code		Pool Name						
30-c	x <u>5</u> -	42420		ווי	520		(e	2 Law Can	yon	Bove	Spring		
Ргоде	rty Code	\sim				Property	v Name				Well Number		
CYPRESS "34" FEDERAL											11H		
OGRID No. Operator Name												Elevation	
Neberle OXY USA INC.										3	027.1'		
Surface Location													
UL or lot no.	Section	Township		Ran	ge	Lot Ida	Feet from the	North/South line	Feet from the	East/W	est line	County	
c	34	23 SOUTH	29	EAST,	N. M. P. M.		150'	NORTH	2000'	WES	Т	EDDY	
L	<u>I</u> k		B	ottom I	Hole Locat	ion If I	Different I	From Surfac	e	- h o			
UL or lot no.	Section	Township		Ran	ge	Lot Idn	Feet from the	North/South line	Feet from the	East/W	est line	County	
N	34	23 SOUTH	29	EAST,	N. M. P. M.		180'	SOUTH	1979'	WES	ST .	EDDY	
Dedicated	Acres	Joint or Infill	Consol	idation Coo	e Order No.		1	t		1		L	
160		N											

No allowable will be assigned to this completion until all interests have been consolidated or a non-standard unit has been approved by the division.

	Cuuri 150 200 Country	OPERATOR CERTIFICATION
2000' 1999'	SURFACE LOCA NEW MEXICO E NAD 1927 Y=461422.6 LONG: W 103.974	10N I hereby certify that the information contained herein is true and ST 11 I hereby certify that the information contained herein is true and complete to the best of my hum-ledge and belief, and that this organization either owns a working interest or unleased mineral (interest in the land including the proposed bottom hole boration or has a right to drill this well at this location persuant to a contract with me owner of much a mineral in the land in under the including interest or unleased mineral
· · · · · · · · · · · · · · · · · · ·	TOP PERF. TOP PERF. - NEW MEXICO EL NAD 1927 Y=461242.6 X=610999.2 LT.: N 32.2675 LONG: W 103.974 00 10 10 10 10 10 10 10 10 10	ST
	BOTTOM PERI BOTTOM PERI BOTTOM PERI NEW MEXICO EA NAD 1927 Y=456621.0 Y=456621.0 Y=456621.0 X=611053.6 LAT:: N 32.2548 LONG: W 103.974	SURVEYOR CENTIFICATION I hereby certify physicily well conservation on this plat was plotted for free all the status surveys made by new uparty supervision and that the same is surging correct to the set of models of SCHARMBER 19, 20135 Date of Stress
<u>1980'</u> 1979'	BOTTOM HOLE LOC NEW MEXICO EA NAD 1927 Y=4564510 X=611055.60 LAT.: N 32.25433 LONG:: W 103.974	Signature and Store Professional Sub-store Store Professional Sub-store Store Series (Mark 1/10/2014 Certificate Namer 15079 Woff 130919WL-0 (Rev. A) (KA)



`Â'

LOCATION VERIFICATION MAP



UM-Directions

VICINITY MAP

ì

•



PROPOSED ROAD AND GO EAST FOR 42.0 FEET TO LOCATION.

Cypress 34 Federal #11H - 1 Mile AOR



Cypress 34 Federal - 9 Section Aerial







Flow live Route Map

OXY USA Inc Cypress 34 Federal #11H APD Drilling Data

OPERATOR NAME / NUMBER: OXY USA INC 16696 Federal Lease No. S-NMNM086024 LEASE NAME / NUMBER: Cypress 34 Federal 11H **COUNTY: Eddy** STATE: NM POOL NAME/NUMBER: Cedar Canyon Bone Spring 11520 SURFACE LOCATION: 150 FNL 2000 FWL NENW(C) Sec 34 T23S R29E SL: LAT: 32.2680571N LONG:103.9742245W X:610997.1 Y:461422.6 NAD: 27 PENETRATION POINT: 330 FNL 1999 FWL NENW(C) Sec 34 T23S R29E SL: LAT: 32.2675623N LONG:103.9742195W X:610999.2 Y:461242.6 NAD: 27 **BOTTOM PERFORATION:** 350 FSL 1980 FWL SESW(N) Sec 34 T23S R29E SL: LAT: 32.2548573N LONG:103.9740934W X:611053.6 Y:456621.0 NAD: 27 BOTTOM HOLE LOCATION: 180 FSL 1979 FWL SESW(N) Sec 34 T23S R29E SL: LAT: 32.2543900N LONG:103.970890W X:611055.6 Y:456451.01 NAD: 27 APPROX GR ELEV: 3027.1' EST KB ELEV: 3051.1' (24' KB) **GEOLOGIC NAME OF SURFACE FORMATION** 1.

a. Permian

2. ESTIMATED TOPS OF GEOLOGICAL MARKERS & DEPTHS OF ANTICIPATED FRESH WATER, OIL OR GAS

Formation	TVD - RKB	Expected Fluids
T. Rustler	206	-
T. Salt	430	
B. Salt	1442	
T. Delaware / Lamar	3089	
T. Bell Canyon	3121	Form Water
T. Cherry Canyon	3777	Oil/Gas
T. Brushy Canyon	5129	Oil/Gas
T. BSPG 1 st	6790	Oil/Gas
T. BSPG 2 nd	7861	Oil/Gas
Target BSPG 2 nd Sand	8859	Oil/Gas
T. BSPG 3 ^{ra}	8897	Oil/Gas

• Fresh water may be present above the Rustler formation. Surface casing will be set below the top of the Rustler to protect any possible fresh water.

LATERAL GREATEST PROJECTED TD: <u>13524' MD / 8859' TVD</u> OBJECTIVE: <u>2nd Bone Spring</u>

3. CASING PROGRAM (ALL NEW CASING)

New Surface Casing ran in a 14.75" hole filled with 8.50 ppg mud

Hole Size (in)	Interval (ft)	OD (in)	Wt (ppf)	Grade	Conn	ID (in)	Tension (klb)	Burst (psi)	Collapse (psi)	Burst SF	Coll SF	Ten SF
14.75	0-300	11.75	47	J55	BTC	11	737	3070	1510	1.43	5.69	6.62

New Intermediate Casing ran in a 10.625" hole filled with 10.2 ppg mud

Hole Size (in)	Interval (ft)	OD (in)	Wt (ppf)	Grade	Conn	ID (in)	Tension (klb)	Burst (psi)	Collapse (psi)	Burst SF	Coll SF	Ten SF
10.625	0-3100	8.625	32	J55	LTC	7.921*	503	3928	2533	1.30	2.46	2.27
	3000											

New Production Casing ran in a 7.875" hole filled with 9.2 ppg mud

		. 0										
Hole Size	Interval	OD	Wt	Crada	Conn	ID	Tension	Burst	Collapse	Burst	Coll	Ten
(in)	(ft)	(in)	(ppf)	Grade	Conn	(in)	(klb)	(psi)	(psi)	SF	SF	SF
7.875	0-13524	5.500	17	L80	BTC	4.892	397	7738	6285	1.22	1.49	1.73

*SPECIAL DRIFT TO 7.875"

Casing Design Assumptions:

Burst Loads

CSG Test (Surface)

- Internal: Displacement fluid + 70% CSG Burst rating
- External: Pore Pressure from section TD to surface
- CSG Test (Intermediate)
 - Internal: Displacement fluid + 70% CSG Burst rating
 - External: Pore Pressure from the Intermediate hole TD to Surface CSG shoe and MW of the drilling mud that was in the hole when the CSG was run to surface
- CSG Test (Production)
 - Internal: Displacement fluid + <u>80%</u> CSG Burst rating
 - External: Pore Pressure from the well TD the Intermediate CSG shoe and MW of the drilling mud that was in the hole when the CSG was run to surface

Gas Kick (Surface/Intermediate)

- Internal: Gas Kick based on Pore Pressure or Fracture Gradient @ CSG shoe with a gas 0.115psi/ft Gas gradient to surface while drilling the next hole section (e.g. Gas Kick while drilling the production hole section is a burst load used to design the intermediate CSG)
- External: Pore Pressure from section TD to previous CSG shoe and MW of the drilling mud that was in the hole when the CSG was run to surface

Stimulation (Production)

- Internal: Displacement fluid + Max Frac treating pressure (not to exceed 80% CSG Burst rating)
- External: Pore Pressure from the well TD to the Intermediate CSG shoe and 8.5 ppg MWE to surface

Collapse Loads

Lost Circulation (Surface/Intermediate)

• Internal: Losses experienced while drilling the next hole section (e.g. losses while drilling the production hole section are used as a collapse load to design the intermediate CSG). After losses there will be a column of mud inside the CSG with an equivalent weight to the Pore Pressure of the lost circulation zone

• External: MW of the drilling mud that was in the hole when the CSG was run

- Cementing (Surface/Intermediate/Production)
 - Internal: Displacement Fluid
 - External: Cement Slurries to TOC, MW to surface

Full Evacuation (Production)

- Internal: Atmospheric Pressure
- External: MW of the drilling mud that was in the hole when the CSG was run

Tension Loads

Running CSG (Surface/Intermediate/Production)

• Axial load of the buoyant weight of the string plus either 100 klb over-pull or string weight in air, whichever is less Green Cement (Surface/Intermediate/Production)

• Axial load of the buoyant weight of the string plus the cement plug bump pressure (Final displacement pressure + 500 psi)

Burst, Collapse and Tensile SF are calculated using Landmark's Stress Check (Casing Design) software.

4. CEMENT PROGRAM:

Surface Interval

Interval	Amount sx	Ft of Fill	Туре	Gal/Sk	PPG	Ft ³ /sk	24 Hr Comp
0' – 300' (165% Excess)	260	300	Premium Plus cement with 2 % Calcium Chloride - Flake (Accelerator)	6.39	14.8	1.35	1726

Intermediate Interval

Interval	Amount sx	Ft of Fill	Туре	Gal/Sk	PPG	Ft ³ /sk	24 Hr Comp
Lead: 0' – 2600' (165% Excess)	750	2600	Halliburton Light Premium Plus Cement with 5% Salt (Accelerator), 0.4% HR-800 (Retarder)	9.84	12.9	1.85	771
Tail: 2600' – 3100' (165% Excess)	210	500	Premium Plus cement	6.34	14.8	1.33	1779

Production Casing

Interval	Amount sx	Ft of Fill	Туре	Gal/Sk	PPG	Ft ³ /sk	24 Hr Comp
Lead: 0' - 8100' (100% Excess)	680	8100	TUNED LIGHT (TM) SYSTEM 0.80% HR-601, 3 lbm/sk Kol-Seal, 0.125 lbm/sk Poly-E-Flake	16.16	9.76	3.46	788
Tail: 8100' – 13524' (40% Excess)	810	5424	Super H Cement, 0.1% HR-800, 0.5% Halad R-344, 0.3% CFR-3, 2 lbm Kol-Seal, 3 lbm Salt	8.45	13.2	1.65	701
			DV TOOL SET AT 3200'	·		·	

DV Tool will be used for contingency. If returns are not lost during primary cementing operation, DV cancellation plug will be run and 2nd stage cancelled. Contingency recipe for 2nd stage as follows:

Stage 2 Lead: 0' – 2600' (10% Excess)	250	2600	Halliburton Light Premium Plus cement with 3 lbm/sk Salt	11.39	12.4	2.05	450 (500 psi in 29 hrs)
Stage 2 Tail: 2600' – 3200' (50% Excess)	100	600	94 lbm/sk Premium Plus Cement	6.34	14.8	1.33	1849

Cement Additives: Calcium Chloride, Salt (Accelerator); Halad R=344 (Low Fluid Loss Control); CER-3 (Dispersant); HR-601, HR-800 (Retarder); Kol-Seal, Poly-E-Flake (Lost Circulation Additive)

The volumes indicated above may be revised depending on caliper measurement.

5. DIRECTIONAL PLAN

Please see attached directional plan

6. PRESSURE CONTROL EQUIPMENT

Surface: <u>0' - 300'</u> None.

Intermediate and Production: <u>300' MD/TVD – 13524' MD / 8859' TVD</u>. Intermediate and Production hole will be drilled with a 13-5/8" 10M three ram stack with a 5M annular preventer and a 5M Choke Manifold.

a. All BOP's and associated equipment will be tested in accordance with Onshore Order #2

(250/5000 psi on rams for 10 minutes each and 250/3500 psi for 10 minutes for annular preventer, equal to 70% of working pressure) with a third party BOP testing service before drilling out the surface casing shoe. A Multibowl wellhead system will be used in this well therefore the BOPE test will cover the test requirements for the Intermediate and Production sections.

5le 70A

- **b.** The Surface and Intermediate casings strings will be tested to 70% of their burst rating for 30 minutes. This will also test the seals of the lock down pins that hold the pack-off in place in the Multibowl wellhead system.
- c. Pipe rams will be function tested every 24 hours and blind rams will be tested each time the drill pipe is out of the hole. These functional tests will be documented on the daily driller's log. A 2" kill line and 3" choke line will be accommodated on the drilling spool below the ram-type BOP.
- **d.** The BOPE test will be repeated within 21 days of the original test, on the first trip, if drilling the intermediate or production section takes more time than planned.
- e. Other accessory BOP equipment will include a floor safety valve, choke lines, and choke manifold having a 5000 psi working pressure rating and tested to 5000 psi.
- f. The Operator also requests a variance to connect the BOP choke outlet to the choke manifold using a co-flex hose manufactured by Contitech Rubber Industrial KFT. It is a 3" ID x 35' flexible hose with a 10,000 psi working pressure. It has been tested to 15,000 psi and is built to API Spec 16C. Once the flex line is installed it will be tied down with safety clamps (certifications attached).
- g. BOP & Choke manifold diagrams attached.

Depth	Mud Wt ppg	Vis Sec	Fluid Loss	Type System
0'-300'	8.5	28 - 38	NC	Fresh Water / Spud Mud
300'-3100' 3000	10.2	28 - 32	NC	NaCl Brine
3,100' - 8100'	9.0	28 – 34	NC	Cut Brine / Sweeps
8100' - 13524'	9.2	32 - 40	< 20	Cut Brine/Starch

7. MUD PROGRAM:

<u>Remarks</u>: Pump high viscosity sweeps as needed for hole cleaning. The mud system will be monitored visually/manually as well as with an electronic PVT. The necessary mud products for additional weight and fluid loss control will be on location at all times. Appropriately weighted mud will be used to isolate potential gas, oil, and water zones until such time as casing can be cemented into place for zonal isolation.

8. CLOSED LOOP SYSTEM

A closed loop system will be utilized, consisting of above ground steel tanks and haul-off bins. Liquids, drilling fluids and cuttings will be disposed of at an approved facility.

9. AUXILIARY WELL CONTROL AND MONITORING EQUIPMENT

a. A full opening drill pipe stabbing valve having the appropriate connections will be on the rig floor unobstructed and readily accessible at all times.

10. POTENTIAL HAZARDS

- a. H2S detection equipment will be in operation after drilling out the surface casing shoe until the production casing has been cemented. Breathing equipment will be on location from drilling out the surface shoe until production casing is cemented. If H2S is encountered the operator will comply with Onshore Order #6 and report to BLM.
- -b:--No-abnormal-temperatures-or-pressures-are-anticipated.--The-highest-anticipated-pressure gradient is **0.46 psi/ft.** Maximum anticipated bottom hole pressure is **between 4100 and 4200 psi.**
- c. All personnel will be familiar with all aspects of safe operation of equipment being used to drill this well. Adequate flare lines will be installed off the mud/gas separator where gas may be flared safely.

11. ANTICIPATED STARTING DATE AND DURATION OF OPERATIONS

Road and location construction will begin after the BLM has approved the APD. Anticipated spud date will be as soon as possible after BLM approval and as soon as a rig will be available. Move in operations and drilling is expected to take 35 days. If production casing is run, then an additional 30 days will be needed to complete the well and construct surface facilities and/or lay flow lines in order to place well on production.

12. WIRELINE LOGGING / MUD LOGGING / LWD

- a. Wireline logging: None
- b. Mud loggers to be rigged up from surface casing shoe to TD
- c. Acquire GR while drilling, from KOP to TD

COMPANY PERSONNEL:

<u>Name</u>	Title	Office Phone	Mobile Phone
Linsay Earle	Drilling Engineer	(713)350-4921	(832) 596-5507
Sebastian Millan	Drilling Engineer Supervisor	(713)350-4950	(832) 528-3268
Roger Allen	Drilling Superintendent	(713)215-7617	(281) 682-3919
Oscar Quintero	Drilling Manager	(713)985-6343	(713) 689-4946

SPACING UNITS:

The following wells are in the Cedar Canyon Bone Spring Pool.

1. Cypress 34 Federal #1H - 30-015-35053 - TVD-7915' - Units P-O-N-M - 1st Bone Spring

2. Cypress 34 Federal #2H - 30-015-35413 - TVD-7964' - Units F-G-H - 1st Bone Spring

3. Cypress 34 Federal #3H - 30-015-35692 - TVD-7949' - Units K-J-I - 1st Bone Spring

4. Cypress 34 Federal #4H - 30-015-35742 - TVD 7920' - Units D-E-L - 1st Bone Spring

5. Cypress 34 Federal #5 – 30-015-35693 – TVD 7924' – Units C-B-A – 1st Bone Spring

6. Cypress 34 Federal #8H - 30-015-39430 - TVD 8910' - Units O-J-G-B - 2nd Bone Spring

7. Cypress 34 Federal #9H - 30-015-42088 - TVD-8999' - Units P-I-H-A - 2nd Bone Spring

8. Cypress 34 Federal #10H – 30-015-Pending – TVD-8849' Units D-E-L-M – 2nd Bone Spring

9. Cypress 34 Federal #11H - 30-015-Pending - TVD-8859' - Units C-F-K-N - 2nd Bone Spring



.

.



Scientific Drilling, Int'l Planning Report

Database. Company: Project: Site: Well: Wellbore: Design:	EDM 500 OXY Eddy Cou Cypress Vellbore Design#2	01 Single User Dt unty, New Mexico 34 Fed 11H 34 Fed 11H #1		Local Co-o TVD: Refere MD: Refere North: Refe Survey Ca	rdinate, Reference nce: rence: culation:Method:	Well Cyp KB @ 30 KB @ 30 Grid Minimur	ress 34 Fed 11H 51.10usft 51:10usft Curvature	
Project	Eddy Cou	nty, New Mexico, N	ew Mexico,					isine in the second
Map System: Geo Datum: Map Zone:	US State PI NAD 1927 (New Mexico	ane 1927 (Exact so NADCON CONUS DEast 3001	olution))	System Dati	ım:	Mean Sea	_evel	
Site	Cypress 3	4 Fed 11H					an la sub a fan an a	الم
Site Position: From: Position Uncertainty	Map y:	0.00 usft	Northing: Easting: Slot Radius:	461,4 610,9	22.60 usft Latiti 197.10 usft Long 13-3/16 "Grid	ude: jitude: Convergence:		32° 16' 5.005 N 103° 58' 27.208 W 0.19 °
Well	Cypress 34	4 Fed 11H		allende Kalansen ander alle en en streffen en er beseter er beseter er en streffen er er beseter er beseter er	ander own warden an an an ander ander an	an a	ىرىرىيىتىرى ، سەھلارىمىيا يەكىمىز مەرمىيى. مەد يېچىرىي مەرمىيە مەرمىيە ئايمىر	an in a second
Well Position	+N/-\$	0.00 usft	Northing:		461,422.60 usft	Latitude:	,	32° 16' 5.005 N
	+E/-W	0.00 usft	Easting:		610,997.10 usft	Longitude:		103° 58' 27.208 W
Position Uncertainty	/	0.00 usft	Wellhead Eleva	ation:	0.00 usft	Ground Lev	el:	3,027.10 usft
Wellbore Magnetics	Wellbore	#1 Name	Sample Date	Declinăt	on	DipAngle	Field	Strength nTi
Leader Street	<u> </u>	IGRF2010	10/31/2013	the start to de	7.48	60	0.10	48,364
Design Audit Notes:	Design#2			5.22.1.20.20.20.20.00.00.00.00.00.00.00.00.00.				
Version:			Phase:	PROTOTYPE	Tie On D	epth:	0.00	
Vertical Section:		Depth Fi (u	om (TVD) sft)	+N/-S (usft)	+E/-W (usft)		Direction	
hanna ann an an an an an ann an an an an	للأستلام وللس ستست	0	00	0.00	0.00	<u>ales S.F. in S.F.H.</u>	179.33	
Plan Sections								
Measured Depth Incl (usft)	ination.A	zimuth · · · · Dept ((usn ((usn	al. h	+E/₌₩ (usft) ≻	Dögleg B Rate R //100usft); (*/10	ulld Túrn kate 00usft) (*/100us	TFO. (°)	Target
0.00	0.00	0.00	0.00 0.00	0.00	0.00	0.00	0.00 0.00	
8,142.90	0.00	0.00 8,14	2.90 0.00	0.00	0.00	0.00	0.00 0.00	
9,267.90	90.00	179.33 8,85	9.10 -716.15 9.10 -716.01	8.43	8.00	8.00	0.00 179.33	
13,523.64	90.00	179.33 8,85	59.10 -4,971.59	58.50	0.00	0.00	0.00 0.00 0.00 0.00	U34F 11H LIP

2-50



Scientific Drilling, Int'l Planning Report

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Vveil Cypress 34 Fed 11H
Company:	OXY	IVD Reference:	KB @ 3051.10usft
Project:	Eddy County, New Mexico	MD Reference:	KB @ 3051.10usft
Site:	Cypress 34 Fed 11H	North Reference:	Grid
Well:	Cypress 34 Fed 11H	Survey Calculation Method	Minimum Curvature
Wellbore:	Wellbore #1	and the second	· · · · · · · · · · · · · · · · · · ·
Design:	Design#2		יין איז
	ער היה איז	na ne san banda na mana na manana ana na mana kan mana kan mana kan mana ka manana ka manana kan mana kan mana Na mana banda na mana na manana manana kan na manakamana sa mana kan manana kan manana kan mana kan sa mana sa m	аларыны у талар алар каларынан жайдан улар жара арылар арылар тарар калар калар калар калар калар жана калар к Калар калар калар калар калар калар калар калар калар калар тара калар калар калар калар калар калар калар калар

Planned Survey

Flameu	Juivey	and a superior and a Superior and a superior and a superior Superior and a superior			۲۰۰۰ میں				مىر ئىل سىرىدىنى ئىن ئىلىيى بىر (يىن بىر ئىل سىرىدىنى ئىن ئىل بىر (يىن	
	Measured Depth	Inclination	Azimuth	Vertical Depth	+N/-S	, +E/-W	Section	Dogleg Rate	Rate	Rate
	(usft)	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(°/100usft)	(°/100usft)	(°/100usft)
	0.00	0.00	0.00	0.00	0.00	0.00	0.00	Ó.00	0.00	0.00
	100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
	200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
	300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
	400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
	500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
	600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	0.00	0.00
	700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
	800.00	0.00	0.00	800,00	0.00	0.00	0.00	0.00	0.00	0.00
	900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	0.00	0.00
	1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
	1,100,00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
	1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
	1,300.00	0.00	0.00	1.300.00	0.00	0.00	0.00	0.00	0.00	0.00
	1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
	1 500 00	0.00	0.00	1 500 00	0.00	0.00	0.00	0.00	0.00	0.00
	1,000.00	0.00	0.00	1,000.00	0.00	0.00 0.00	0.00	0.00	0.00	0.00
	1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
	1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00	0.00	0.00
	1,800.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
	1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,100.00	0.00	0.00	2,100.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,200.00	0.00	0.00	2,200.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,300.00	0.00	0.00	2,300.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,400.00	0.00	0.00	2,400.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,500.00	0.00	0.00	2,500.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,600.00	0.00	0.00	2,600.00	0.00	0.00	· 0.00	0.00	0.00	0.00
	2,700.00	0.00	0.00	2,700.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,800.00	0.00	0.00	2,800.00	0.00	0.00	0.00	0.00	0.00	0.00
	2,900.00	0.00	0.00	2,900.00	0.00	0.00	.0.00	0.00	0.00	0.00
	3,000.00	0.00	0.00 .	3,000.00		0:00 -			0:00	0:00
	3,100.00	0.00	0.00	3,100.00	0.00	0.00	0.00	0.00	0.00	0.00
	3,200.00	0,00	0.00	3,200,00	0.00	0.00	0.00	0.00	0.00	0.00
	3,300.00	0.00	0.00	3,300.00	0.00	0.00	0.00	0.00	0.00	0.00
	3,400.00	0.00	0.00	3,400.00	0.00	0.00	0.00	0.00	0.00	0.00
	3 500 00	0.00	0.00	3.500.00	0.00	0 00	0 00	0.00	0.00	0.00
	3,600.00	0.00	0.00	3,600.00	0.00	0.00	0.00	0.00	0.00	0.00
	3,700.00	0.00	0.00	3,700.00	0.00	0.00	0.00	0.00	0.00	0.00
	3,800.00	0.00	0.00	3,800.00	0.00	0.00	0.00	0.00	0.00	0.00
	3,900.00	0.00	0.00	3,900.00	0.00	0.00	0.00	0.00	0.00	0.00
	4 000 00	0.00	0.00	4 000 00	0.00	0.00	0.00	0.00	0.00	0.00
	4,100.00	0.00	0.00	4 100 00	0.00	0.00	0.00	0.00	0.00	0.00
	4,200,00	0.00	0.00	4,200,00	0.00	0.00	0.00	0.00	0.00	0.00
	1,200.00	0.00	0.00	4 300 00	0.00	0.00	0.00	0.00	0.00	0.00
	4 300 00	0.00	0.00	4,000.00	0.00	0.00	0.00	0.00	0.00	0.00
	4,300.00 4,400.00	0.00	0.00	4,400.00						
	4,300.00 4,400.00	0.00	0.00	4,400.00	0.00	0.00	0.00	0.00	0.00	0.00
	4,300.00 4,400.00 4,500.00	0.00	0.00	4,400.00	0.00	0.00	0.00	0.00	0.00	0.00
	4,300.00 4,400.00 4,500.00 4,600.00	0.00 0.00 0.00	0.00 0.00 0.00	4,400.00 4,500.00 4,600.00	0.00	0.00	0.00	0.00	0.00	0.00 0.00
	4,300.00 4,400.00 4,500.00 4,600.00 4,700.00 4,800.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	4,400.00 4,500.00 4,600.00 4,700.00 4,800.00	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00	0.00 0.00 0.00
Logen Cure dian - Sinn	4,300.00 4,400.00 4,500.00 4,600.00 4,700.00 4,800.00 4,900.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00	4,400.00 4,500.00 4,600.00 4,700.00 4,800.00 4,900.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00
en general de la comp	4,300.00 4,400.00 4,500.00 4,600.00 4,700.00 4,800.00 4,900.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00	4,400.00 4,500.00 4,600.00 4,700.00 4,800.00 4,900.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00
	4,300.00 4,400.00 4,500.00 4,600.00 4,700.00 4,800.00 4,900.00 5,000.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	4,400.00 4,500.00 4,600.00 4,700.00 4,800.00 4,900.00 5,000.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00
	4,300.00 4,400.00 4,500.00 4,600.00 4,700.00 4,800.00 4,900.00 5,000.00 5,100.00 5,200.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00	4,400.00 4,500.00 4,600.00 4,700.00 4,800.00 4,900.00 5,000.00 5,100.00 5,200.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00

96-3



Scientific Drilling, Int'l

96-4

Planning Report

	and the set of the set							1	and a state state of the state	al and a second s
Database:	EDM 5000.1 Sing	le User Db		i i	.ocal C	o-ordinate Re	ference:	Well Cypre	ss 34 Fed 11H	
Company:	OXY			1.	IVD Re	fèrence:		ົ້- 🕴 KB @ 3051	.10usft	
Project:	Eddy County, Ne	w Mexico		ļ.	ND Ref	erence:		KB @ 3051	.1Óusft	
Site:	Cypress 34 Fed	I1H		Ì	North R	eference:	•	Grid		
Well:	Cypress 34 Fed	I1H] (Survey	Calculation N	lethod:	😣 Minimum C	urvature	
Wellbore:	Wellbore #1			l						
Design:	Design#2			1			· · · ·	· .]	Antipation and the standard and his second state	r, anter a mon transferitarita e t. ver e fragmentala de ancara
Planned Sundy			an a		1.000.000.000.0000 			and a substant of the second se	۵. (۱۹۹۳) - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰ - ۲۰۰۰	n de service de la construction de La construction de la construction d La construction de la construction d
Fiamed Ourvey	net gange burger, nor he − net er net - per n		ng na na di ana mana sa a si ana. Ta		 ,	a. waa aayayaaday ahaan aya			، ويستعدي المسالية المراجعة المسيحينية المسيحية المسيحية المسالية المسيحة المسيحية المسيحية المسيحية المسيحية ا المستحدية المسيحية المسيحية المسيحية المسيحية المسيحية المسيحية المسيحة المسيحة المسيحية المسيحية المسيحية المسي	anna maganan na nafarinanse an
Measured			Vertical	·.			Vertical	Dogleg	Build	Turn
Depth (usft)	Inclination / (°)	vzimuth (°)	Depth (usft)	+N/-S (usft)		+E/-W (usft)	Section (usft)	Rate , (°/100usft)	Rate (°/100usft)	Rate (°/100usft)
5.400.00	0.00	0.00	5,400.00		.00	0.00	0.00	0.00	0.00	0.00

5,400.00	0.00	0.00	5,400.00	0.00	0.00	0.00	0.00	0.00	0.00
5 500 00	0.00	0.00	5 500 00	0.00	0.00	0.00	0.00	0.00	0.00
5,600,00	0.00	0.00	5,600,00	0.00	0.00	0.00	0.00	0.00	0.00
5,000.00	0.00	0.00	5,000.00	0.00	0.00	0.00	0.00	0.00	0,00
5,700.00	0.00	0.00	5,700.00	0.00	0.00	0.00	0.00	0.00	0.00
5,800.00	0.00	0.00	5,600.00	0.00	0.00	0.00	0.00	0.00	0.00
5,900.00	0.00	0.00	5,900.00	0,00	0.00	0.00	0.00	0.00	0.00
6,000.00	0.00	0.00	6,000.00	0.00	0.00	0.00	0.00	0.00	0.00
6,100.00	0.00	0.00	6,100.00	0.00	0.00	0.00	0.00	0.00	0.00
6,200.00	0.00	0.00	6,200.00	0.00	0.00	0.00	0.00	0.00	0.00
6,300.00	0.00	0.00	6,300.00	0.00	0.00	0.00	0.00	0.00	0.00
6,400.00	0.00	0.00	6,400.00	0.00	0.00	0.00	0.00	0.00	0.00
6,500.00	0.00	0.00	6,500.00	0.00	0.00	0.00	0.00	0.00	0.00
6.600.00	0.00	0.00	6,600,00	0.00	0.00	0.00	0.00	0.00	0.00
6 700 00	0.00	0.00	6 700.00	0.00	0.00	0.00	0.00	0.00	0.00
6,100.00	0.00	0.00	6,800,00	0.00	0.00	0.00	0.00	0.00	0.00
6,000,00	0.00	0.00	6,000,00	0.00	0.00	0.00	0.00	0.00	0.00
0,000.00	0,00	0.00	0,000.00	0,00		0.00	0.00	0.00	0.00
7,000.00	0.00	0.00	7,000.00	0.00	0.00	0.00	0.00	0.00	0.00
7,100.00	0.00	0.00	7,100.00	0.00	0.00	0.00	0.00	0.00	0.00
7,200.00	0.00	0.00	7,200.00	0.00	0.00	0.00	0.00	0.00	0.00
7,300.00	0.00	0.00	7,300.00	0.00	0.00	0.00	0.00	0.00	0.00
7,400.00	0.00	0.00	7,400.00	0.00	0.00	0.00	0.00	0.00	0.00
7,500.00	0.00	0.00	7,500.00	0.00	0.00	0.00	0.00	0.00	0.00
7,600.00	0.00	0.00	7,600.00	0.00	0.00	0.00	0.00	0.00	0.00
7,700.00	0.00	0.00	7,700.00	0.00	0.00	0.00	0.00	0.00	0.00
7 800 00	0.00	0.00	7 800 00	0.00	0.00	0.00	0.00	0.00	0.00
7 900 00	0.00	0.00	7 900 00	0.00	0.00	0.00	0.00	0.00	0.00
7,500.00	0.00	0.00	7,300.00	0.00	0.00	0.00	0.00	0.00	0.00
8,000.00	0.00	0.00	8,000.00	0.00	0.00	0.00	0.00	0.00	0.00
8,100.00	0.00	0.00	8,100.00	0.00	0.00	0.00	0.00	0.00	0.00
8,142.90	0.00	0.00	8,142.90	0.00	0.00	0.00	0,00	0.00	0.00
8,200.00	4.57	179.33	8,199.94	-2.27	0.03	2.27	8.00	8.00	0.00
8,300:00	12:57	. 179.33	8,298.74	-17.16	0:20	17:16			
8,400.00	20.57	179.33	8,394.51	-45.65	0.54	45.65	8.00	8.00	0.00
8,500.00	28.57	179,33	8,485.39	-87.19	1.03	87.20	8.00	8.00	0.00
8,600.00	36.57	179.33	8,569.59	-140.97	1.66	140,98	8.00	8.00	0.00
8,700.00	44,57	179.33	8,645.50	-205.95	2.42	205.96	8.00	8.00	0.00
8,800.00	52.57	179.33	8,711.62	-280.86	3.30	280.88	8.00	8.00	0.00
8,900,00	60.57	179.33	8,766.67	-364 24	4 29	364 26	8.00	8.00	0.00
			-,				0.00	0.00	0.00
9.000.00	68 57	179 33	8.809.58	-454 47	5 35	454 50	8 00	8 00	0.00
9,000.00 9.100.00	68.57 76.57	179.33 179.33	8,809.58 8,839.51	-454.47 -549 79	5.35 6.47	454.50 549.83	8.00 8.00	8.00	0.00
9,000.00 9,100.00 9,200.00	68.57 76.57 84 57	179.33 179.33 179.33	8,809.58 8,839.51 8,855.88	-454.47 -549.79 -648.35	5.35 6.47 7.63	454.50 549.83 648.40	8.00 8.00 8.00	8.00 8.00 8.00	0.00
9,000.00 9,100.00 9,200.00 9,267.90	68,57 76.57 84.57 90.00	179.33 179.33 179.33 179.33	8,809.58 8,839.51 8,855.88 8,859.10	-454.47 -549.79 -648.35 -716.15	5.35 6.47 7.63 8.43	454.50 549.83 648.40 716.20	8.00 8.00 8.00 8.00	8.00 8.00 8.00 8.00	0.00 0.00 0.00 0.00
9,000.00 9,100.00 9,200.00 9,267.90	68.57 76.57 84.57 90.00	179.33 179.33 179.33 179.33	8,809.58 8,839.51 8,855.88 8,859.10	-454.47 -549.79 -648.35 -716.15	5.35 6.47 7.63 8.43	454.50 549.83 648.40 716.20	8.00 8.00 8.00 8.00	8.00 8.00 8.00 8.00	0.00 0.00 0.00 0.00
9,000.00 9,100.00 9,200.00 9,267.90 9,300.00	68.57 76.57 84.57 90.00 90.00	179.33 179.33 179.33 179.33 179.33	8,809.58 8,839.51 8,855.88 8,859.10 8,859.10	-454.47 -549.79 -648.35 -716.15 -748.24	5.35 6.47 7.63 8.43 8.80	454.50 549.83 648.40 716.20 748.29	8.00 8.00 8.00 8.00 0.00	8.00 8.00 8.00 8.00 0.00	0.00 0.00 0.00 0.00
9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00	68.57 76.57 84.57 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33	8,809.58 8,839.51 8,855.88 8,859.10 8,859.10 8,859.10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24	5.35 6.47 7.63 8.43 8.80 9.98	454.50 549.83 648.40 716.20 748.29 848.29	8.00 8.00 8.00 8.00 0.00 0.00	8.00 8.00 8.00 8.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00
9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809.58 8,839.51 8,855.88 8,859.10 8,859.10 8,859.10 8,859.10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23	5.35 6.47 7.63 8.43 8.80 9.98 11.16	454.50 549.83 648.40 716.20 748.29 848.29 948.29	8.00 8.00 8.00 8.00 0.00 0.00 0.00	8.00 8.00 8.00 8.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00
9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00 9,600.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33	454.50 549.83 648.40 716.20 748.29 848.29 948.29 1,048.29	8.00 8.00 8.00 8.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00
9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00 9,600.00 9,700.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22 -1,148.22	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33 13.51	454.50 549.83 648.40 716.20 748.29 848.29 948.29 1,048.29 1,148.29	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0
9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00 9,600.00 9,700.00 9,800.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22 -1,148.22 -1,248.21	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33 13.51 14.69	454.50 549.83 648.40 716.20 748.29 848.29 948.29 1,048.29 1,148.29 1,248.29	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0
9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00 9,600.00 9,700.00 9,800.00 9,900.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22 -1,148.22 -1,248.21 -1,348.20	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33 13.51 14.69 15.86	454.50 549.83 648.40 716.20 748.29 848.29 948.29 1,048.29 1,148.29 1,248.29 1,348.29	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0
9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00 9,600.00 9,700.00 9,800.00 9,900.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22 -1,148.22 -1,248.21 -1,348.20 -1,448.19	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33 13.51 14.69 15.86 17.04	454.50 549.83 648.40 716.20 748.29 848.29 948.29 1,048.29 1,148.29 1,248.29 1,348.29 1,348.29	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.0
 9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00 9,600.00 9,600.00 9,700.00 9,800.00 9,800.00 9,900.00 10,000.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22 -1,148.22 -1,248.21 -1,348.20 -1,448.19	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33 13.51 14.69 15.86 17.04 18.22	454.50 549.83 648.40 716.20 748.29 848.29 1,048.29 1,048.29 1,348.29 1,348.29 1,348.29 1,548.29	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00
 9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00 9,600.00 9,600.00 9,700.00 9,800.00 9,800.00 10,000.00 10,100.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22 -1,148.22 -1,248.21 -1,348.20 -1,548.19 -1,548.18	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33 13.51 14.69 15.86 15.86 17.04 18.22 19.39	454.50 549.83 648.40 716.20 748.29 848.29 1,048.29 1,048.29 1,148.29 1,348.29 1,348.29 1,548.29 1,548.29 1,648.29	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00
 9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,400.00 9,500.00 9,600.00 9,600.00 9,700.00 9,800.00 10,000.00 10,000.00 10,200.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22 -1,148.22 -1,248.21 -1,348.20 -1,548.19 -1,648.18 -1,648.18	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33 13.51 14.69 15.86 17.04 18.22 19.39 20.57	454.50 549.83 648.40 716.20 748.29 848.29 948.29 1,048.29 1,048.29 1,248.29 1,248.29 1,448.29 1,548.29 1,648.29 1,648.29	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00 0.00
 9,000.00 9,100.00 9,200.00 9,267.90 9,300.00 9,500.00 9,500.00 9,600.00 9,700.00 9,800.00 9,900.00 10,000.00 10,100.00 10,200.00 10,300.00 10,400.00	68.57 76.57 84.57 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00 90.00	179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33 179.33	8,809,58 8,839,51 8,855,88 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10 8,859,10	-454.47 -549.79 -648.35 -716.15 -748.24 -848.24 -948.23 -1,048.22 -1,148.22 -1,248.21 -1,348.20 -1,548.19 -1,548.19 -1,548.18 -1,748.17 -1,848.17	5.35 6.47 7.63 8.43 8.80 9.98 11.16 12.33 13.51 14.69 15.86 17.04 18.22 19.39 20.57 21.75	454.50 549.83 648.40 716.20 748.29 948.29 948.29 1,048.29 1,148.29 1,248.29 1,348.29 1,548.29 1,548.29 1,648.29 1,748.29 1,748.29	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	8.00 8.00 8.00 0.00 0.00 0.00 0.00 0.00	0.00 0.00

OXT V	Permian
	the second s

•

Scientific Drilling, Int'l Planning Report

Database: Company: Project: Site: Well::	EDM 5000-1 Sin OXY Eddý County, Ne Cypress 34 Fed Cypress 34 Fed	gle User Db w Mexico 11H 11H		Loĉal (TVD R MD Re North I Survey	Co-ordinate Ref eference: ference: Reference: Calculation Me	erênçe:	Well Cypress 34 KB @ 3051,10u KB @ 3051.10u Grid Minimum Curva	4 Fed 11H sft sft ture	
Wellbore:	Wellbore #1								
Design:	{ Design#2				- Martin Barris State	A STR. WALL BEE	ใ มาลารมากการกระการกับ เลราะรัฐการกุล	leve water constantion at the sec	nanto anno companio accontecemento darro a M
Planned Survey		and and a second se			an a	fander biere fan fan de fange yn bryn		مريد مايند مريد المريد العربي المريد الم المريد المريد	100000000000000000000000000000000000000
Measured,			Vertical			Vertical	Dogleg.	Build	Turn
(usff)	Inclination	Azimuth	(usft)	+N/-S	+E/-W	Section	(%/100usft)	(100usff)	V100usft)
					in and			Y CONTRACTOR	
10,600.00	90.00	179.33	8,859.10	-2,048.15	24.10	2,048.29	0.00	0.00	0.00
10,700.00	50.00	170.00	0,000.10	-2,140.13	23.20	2,140.25	0.00	0.00	0.00
10,800.00	90.00	179.33	8,859.10	-2,248.14	26.45	2,248.29	0.00	0.00	0.00
11 000 00	90.00	179.33	8 859 10	-2,348.13	27.03	2,340.29	0.00	0.00	0.00
11,100.00	90.00	179.33	8 859 10	-2 548 12	29.98	2,548,29	0.00	0.00	0.00
11,200.00	90.00	179.33	8,859.10	-2,648.11	31.16	2,648.29	0.00	0.00	0.00
11 300 00	00.00	170 32	8 850 10	2 7/8 10	22.24	2 749 20	0.00	0.00	0.00
11 400 00	90.00	179.33	8 859 10	-2,740.10 -2 848 10	32,34 33,51	2,140.29 2 848 20	0.00	0.00	0.00
11,500,00	90.00	179.33	8 859 10	-2 948 09	34 69	2,948,29	0.00	0.00	0.00
11,600.00	90.00	179.33	8,859,10	-3,048.08	35.87	3.048.29	0.00	0.00	0.00
11,700.00	90.00	179.33	8,859.10	-3,148.08	37.04	3,148.29	0.00	0.00	0,00
11 800 00	90.00	179.33	8 859 10	-3 248 07	38.22	3 248 29	0.00	0.00	0.00
11,900.00	90.00	179.33	8 859 10	-3 348 06	39.40	3 348 29	0.00	0.00	0.00
12.000.00	90.00	179.33	8.859.10	-3,448.06	40.57	3 448 29	0.00	0.00	0.00
12,100.00	90.00	179.33	8,859.10	-3,548.05	41.75	3,548.29	0.00	0.00	0.00
12,200.00	90.00	179.33	8,859.10	-3,648.04	42.93	3,648.29	0.00	0.00	0.00
12 300 00	90.00	179 33	8 859 10	-3 748 04	44 10	3 748 29	0.00	0.00	0.00
12,400.00	90,00	179.33	8,859,10	-3.848.03	45.28	3.848.29	0.00	0.00	0.00
12,500.00	90.00	179.33	8,859,10	-3.948.02	46.46	3,948,29	0.00	0.00	0.00
12,600,00	90.00	179,33	8,859,10	-4.048.01	47.63	4.048.29	0.00	0.00	0.00
12,700.00	90.00	179.33	8,859.10	-4,148.01	48.81	4,148.29	0.00	0.00	0.00
12 800 00	90.00	179.33	8 859 10	-4 248 00	49 99	4 248 29	0.00	0.00	0.00
12,900.00	90.00	179.33	8,859,10	-4 347 99	51 16	4 348 29	0.00	0.00	0.00
13.000.00	90.00	179.33	8,859,10	-4.447.99	52 34	4 448 29	0.00	0.00	0.00
13,100.00	90.00	179.33	8,859.10	-4,547.98	53.52	4,548,29	0.00	0.00	0.00
13,200.00	90.00	179.33	8,859.10	-4,647.97	54.69	4,648.29	0.00	0.00	0.00
13 300 00	90.00	179.33	8 859 10	-4 747 97	55.87	4 748 29	0.00	0.00	0.00
13 353 64	90.00	179.33	8 859 10	-4 801 60	56.50	4,740.23	0.00	0.00	0.00
13,400.00	90.00	179.33	8,859,10	-4.847.96	57.05	4.848.29	0.00	0.00	0.00
13,500.00	90.00	179.33	8,859.10	-4,947:95	58:22~		0:00	0:00	0:00
13,523.64	90.00	179.33	8,859.10	-4,971.59	58.50	4,971.93	0.00	0.00	0.00
Design Targets		والاجريد ويحدث ويحدث والمراجع	Nothernooper and the formation	an a	1991		1	والمحافظة المتعادة المراجع	- In the state of the
Target Nāme - hit/miss target	Dip Angle D	ip Dir: T	VD. +N/-S	+E/-W	Northing	Fasi	lino		
Shape	(°) 11	(°)	sft)	(usft)	(usft)	(us	ft)	A CARACTER STATE	
		and and an a start of the second	and the second		2.5			atitude	
C34F 11H PP - plan misses target - Point	0.00 center by 0.02ust	0.00 8,6 ft at 8661.98u	517.70 -180 sft MD (8617.71	0.00 2.7 TVD, -180.00 M	10 461,24 N, 2.12 E)	2.60 61	0,999.20 32	2° 16' 3.224 N	103° 58' 27.190 W
C34F 11H LTP - plan hits target cer - Point	0.00 hter	0.00 8,8	59.10 -4,801	.60 56.5	50 456,62	21.00 61	1,053.60 32°	15' 17.486 N	103° 58' 26.737 W
C34F BHL - plan hits target cer - Point	0.00 nter	0.00 8,8	59.10 -4,971	.59 58.5	50 456,45	1.01 61	1,055.60 32°	15' 15.804 N	103° 58' 26.720 W

DP-5









6-N)

CM-3



Choke Manifold - Gas Separator (Top View)





4

.

Oxy Single Centrifuge Closed Loop System - New Mexico Flex III May 28, 2013 170' PONSTORI PARTS HOUSE HPU/ACCUMULATOR SKID TOOL BOX CABIN BOP TRANSPORT SKID DRILLERS DWWKS SKID DRILL LINE STORAGE SPOOL END OF BOGEY GUIDE TEDUBE **H** MAST IN HORIZONTAL POSITION ۵ หน่าง τ, <u>ç vzil</u> DRILL FLOO DRILL FLOOR UTILITY BOOM 0'-0 x11 -0" RATOR HOUSE INK D x11 --0 1 57.73 Ę £ CHOKE MANIFOLD 38'-7"x12'-0" WATER TANK ŧ FUTUR PUMP ł IR:P L ĩC 7 Ô 4 n Hi D VOLUNE TANKS 27-0'x8'-0" LUBESTER PUNP PARTS HOUSE ᅄ I 15 Roll off bins - for waste solids 戦闘 ्म ४४ Single dentrifuge 110' Waste tank 10.5 -8.5 ł 2.2 l l 180' 230'

CL-1

CL-2





Fluid Technology

Quality Document

QUALITY	Y CONT	ROL CERTIF	ICATE		CERT. I	N°:	746	
PURCHASER: Ph	oenix Bea	ttie Co.			P.O. Nº:	: 00	02491	
CONTITECH ORDER Nº: 41	2638	HOSE TYPE	: 3"	D	Ch	oke and Kill	I Hose	
HOSE SERIAL Nº: 52	2777	NOMINAL /	ACTUAL L	ENGTH:		10,67 m	······	
W.P. 68,96 MPa 1000	00 psi	T.P. 103,4	1 MPa	15000) psi	Duration:	60 ~	min.
Pressure test with water at ambient temperature	See	attachmer	nt. (1 pa	ige)				
[↑] 10 mm = 10 Min. → 10 mm = 25 MPa								-
10 mm = 10 Min. → 10 mm = 25 MPa		COL	IPLINGS					-
10 mm = 10 Min. → 10 mm = 25 MPa Type	5	COL Berial Nº	IPLINGS	Q	uality		Heat N°	
↑ 10 mm = 10 Min. → 10 mm = 25 MPa Type 3° coupling with	917	COL 3erial № 913	IPLINGS	Q	uelity 4130		Heat N° T7998A	-
↑ 10 mm = 10 Min. → 10 mm = 25 MPa Type 3° coupling with 4 1/16° Flange end	917	COL Berlal Nº 913	IPLINGS	Q AISI AISI	uelity 4130 4130		Heat N° T7998A 26984	
↑ 10 mm = 10 Min. → 10 mm = 25 MPa Type 3° coupling with 4 1/16° Flange end INFOCHIP INSTALLED I metal parts are flawless	917	COL Berial Nº 913	IPLINGS	Q AISI AISI	uelity 4130 4130	Af Tem	Heat N° T7998A 26984 PI Spec 16 perature ra	C te:"B"
↑ 10 mm = 10 Min. → 10 mm = 25 MPa Type 3° coupling with 4 1/16° Flange end INFOCHIP INSTALLED II metal parts are flawless /E CERTIFY THAT THE ABOVE HO RESSURE TESTED AS ABOVE WITH 10 mm = 25 MPa 10 mm = 25 MPa 11 metal parts are flawless 12 metal parts are flawless 12 metal parts are flawless 13 metal parts are flawless 14 metal parts are flawless 15 metal parts are flawless 16 metal parts are flawless 17 metal parts are flawless 18 metal parts are flawless 19 metal parts are flawless 19 metal parts are flawless 10 me	917 95E HAS BEE	COL Berial Nº 913 EN MANUFACI	URED IN A	Q AISI AISI	uelity 4130 4130 NCE WIT	AF Tem	Heat N° T7998A 26984 PI Spec 16 perature ra	C te:"B" ER AND
↑ 10 mm = 10 Min. → 10 mm = 25 MPa Type 3° coupling with 4 1/16° Flange end INFOCHIP INSTALLED II metal parts are flawless /E CERTIFY THAT THE ABOVE HC RESSURE TESTED AS ABOVE WIT ate: Inst	917 95E HAS BEE TH SATISFAC	COL Berlal N° 913 913 EN MANUFACT	TURED IN A	Q AISI AISI ACCORDA	uelity 4130 4130 NCE WIT	AF Tem TH THE TERMS Tech Rubber	Heat N° T7998A 26984 PI Spec 16 perature ra	C te:"B" ER AND

Coflex Hose Certification

Page: 1/1



🗢 PHOENIX Beattie

Form No 100/12

Phoenix Beattie Corp 11535 Brittmoore Park Drive Houston, TX 77041 Tel: (832) 327-0141 Fas: (832) 327-0146 E-sail mail@phoenixbeattie.com www.phoenixbeattie.com

Delivery Note

Customer Order Number	370-369-001	Delivery Note Number	003078	Page	1	
Customer Order Number 370-369-001 Customer / Invoice Address HELMERICH & PAYNE INT'L DRILLING CO 1437 SOUTH BOULDER TULSA, OK 74119		Delivery / Address HELMERICH & PAYNE IDC ATTN: JOE STEPHENSON - RI 13609 INDUSTRIAL ROAD HOUSTON, TX 77015	G 370			

Customer Acc No	Phoenix Beattie Contract Manager	Phoenix Beattie Reference	Date	
ноі	JJL.	006330	05/23/2008	

,				Qty To Follow	
1	HP10CK3A-35-4F1	1	. 1	0	
	3° 10K 16C C&K HOSE x 35ft OAL CW 4.1/16" API SPEC FLANGE E/				
	End 1: 4.1/16" 10Kps1 API Spec 6A Type 6BX Flange				
	End 2: 4.1/16" 10Kpsi API Spec 6A Type 6BX Flange				
{	c/w BX155 Standard ring groove at each end		i l		
	Suitable for H2S Service				
	Working pressure: 10,000psi				
	Test pressure: 15,000psi				
-	Standard: API 16C Full specification				
ľ	Armor Guarding: Included			1	
	Fire Rating: Not Included				
- {	femperature rating: -20 Deg C to +100 Deg C				
2 3	SECK3-HPF3	1		0	
1	LIFTING & SAFETY EQUIPMENT TO SUIT HP10CK3-35-F1	1 1			
i i	2 x 160mm ID Safety Clamps				
2	2 x 244mm ID Lifting Collars & element C's				
2	2 x 7ft Stainless Steel wire rope 3/4" OD				
4	4 x 7.75t Shackles				
3 5	SC725-200CS	1	1	0	
s	SAFETY CLAMP 200MM 7.25T C/S GALVANISED				

Continued...

All goods remain the property of Phoenix Beattle until paid for in full. Any damage or shortage on this delivery must be advised within 5 days. Returns may be subject to a handling charge.

🗢 PHOENIX Beattie

Phoenix Beattie Corp 11535 Brittmoore Park Drive Houston, TX 77041 Tel: (832) 327-0141 Fax: (832) 327-0148 E-mail mail@phoenixbeattie.com

Delivery Note

Customer Order Number	370-369-001	Delivery Note Number	003078	Page	2
Customer Order Number 370-369-001 Customer / Invoice Address HELMERICH & PAYNE INT'L DRILLING CO 1437 SOUTH BOULDER TULSA, OK 74119		Delivery / Address HELMERICH & PAYNE IDC ATTN: JOE STEPHENSON - RI 13609 INDUSTRIAL ROAD HOUSTON, TX 77015	G 370		

Customer Acc'No	Phoenix Beattie Contract Manager	Phoenix Beattle Reference	Date	
K01	JJL	006330	05/23/2008	

ltern No	Beattie Part Number / Description	Qty Ordered	Qty Sent	Qty To Follow
4	SC725-132CS SAFETY CLAMP 132MM 7.25T C/S GALVANIZED C/W BOLTS	1	1	0
5	OOCERT-HYDRO HYDROSTATIC PRESSURE TEST CERTIFICATE	1	1	0
6	OOCERT-LOAD LOAD TEST CERTIFICATES	1	. 1	D
 7	OOFREIGHT INBOUND / OUTBOUND FREIGHT PRE-PAY & ADD TO FINAL INVOICE NOTE: MATERIAL MUST BE ACCOMPANIED BY PAPERWORK INCLUDING THE PURCHASE-ORDER,-RIG-NUMBER TO ENSURE PROPER PAYMENT			0
		AND		
	Phoenix Beattle Inspection Signature :		Wie	
	Received In Good Condition : Signature			
 den gen som state i vikel til for live for	Print Name	San a di San a daga daga seria daga s	Y	مر می از می مرکز این می از می

Date

All goods remain the property of Phosnix Beattle until paid for in full. Any damage or shortage on this delivery must be advised within 5 days. Returns may be subject to a handling charge.

	Material Identification Certificate									
PA No 006	3330 Client HE	LMERICH & PA	YNE INT'L DRILLING	COent	Ref 37	70-369-001			Page	1
Part No	Description	Material Desc	Material Spec	Qty	WO No	Batch No	Test Cert No	Bin No	Drg No	Issue No
HP10CK3A-35-4F1	3" 10K 16C C&K HOSE × 357 OAL		1	1	2491	52777/H884		WATER		
SECK3-HPF3	LIFTING & SAFETY EQUIPMENT TO		<u></u>	1	2440	002440		N/STK		1
SC725-200C5	SAFETY CLAMP 200MH 7.25T	CARBON STEEL		1	2519	H665		22C		
SC725-132CS	SAFETY CLAHP 132HH 7.25T	CARBON STEEL		1	2242	8139		22		İ
ļ				ļ						·
	+		·	·					·	ļ
				<u> </u>	<u> </u>					
4				 	{				<u> </u>	[
				<u> </u>		+				••••••••••
										}
			<u></u>							
				<u> </u>		+	<u> </u>			
1			······				1			
1			1	1	1	1				f
					1			 		
								1		
1	<u>.</u>									
I				ļ	L	L				
		ļ	1	I	L	·	ļ	L		
<u> </u>		l	L.I				L	L	<u> </u>	
		<u> </u>	<u> </u>	<u> </u>	·			l	 	- <u> </u>
4		· · · · · · · · · · · · · · · · · · ·		4			·	<u> </u>	· · · · · · · · · · · · · · · · · · ·	·
<u>↓</u>			L	- {			 	Į		+
ļ4	<u></u>	·					+	+		+
		<u> </u>	<u>.</u>	+		+	·	<u> </u>	·	·+
ļ					+	·			· [··	
L(<u> </u>						.L	

We hereby certify that these goods have been inspected by our Quality Management System, and to the best of our knowledge are found to conform to relevant industry standards within the requirements of the purchase order as issued to Phoenix Beattle Corporation.

Coflex Hose Certification

Coflex Hose Certification



Fluid Technology

Quality Document

FH-6

CERTIFICATE OF CONFORMITY

: CONTITECH RUBBER INDUSTRIAL KFT. Supplier Equipment: 6 pcs. Choke and Kill Hose with installed couplings 3" x 10,67 m WP: 10000 psi Type: Supplier File Number : 412638 **Date of Shipment** : April. 2008 Phoenix Beattie Co. Customer Customer P.o. : 002491 **Referenced Standards** / Codes / Specifications : API Spec 16 C Serial No.: 52754,52755,52776,52777,52778,52782

STATEMENT OF CONFORMITY

We hereby certify that the above items/equipment supplied by us are in conformity with the terms, conditions and specifications of the above. Purchaser Order and that these items/equipment were fabricated inspected and tested in accordance with the referenced standards, codes and specifications and meet the relevant acceptance criteria and design requirements.

COUNTRY OF ORIGIN HUNGARY/EU

Signed Position: Q.C. Manager

ontiTech Rubber Industrial Kit. Quality Control Dept. (1)

Date: 04. April. 2008




H25-1

Permian Drilling Hydrogen Sulfide Drilling Operations Plan Cypress 34 Fed #11H

Open drill site. No homes or buildings are near the proposed location.

1. Escape

Personnel shall escape upwind of wellbore in the event of an emergency gas release. Escape can take place through the lease road on the WEST side of the location. Personnel need to move to a safe distance and block the entrance to location. If the primary route is not an option due to the wind direction, then a secondary egress route should be taken.

H25-2





Permian Drilling Hydrogen Sulfide Drilling Operations Plan New Mexico

<u>Scope</u>

This contingency plan establishes guidelines for the public, all company employees, and contract employees who's work activities may involve exposure to hydrogen sulfide (H2S) gas.

While drilling this well, it is possible to encounter H2S bearing formations. At all times, the first barrier to control H2S emissions will be the drilling fluid, which will have a density high enough to control influx.

<u>Objective</u>

- Provide an immediate and predetermined response plan to any condition when H2S is detected. All H2S detections in excess of 10 parts per million (ppm)
 concentration are considered an Emergency.
 - 2. Prevent any and all accidents, and prevent the uncontrolled release of hydrogen sulfide into the atmosphere.
 - 3. Provide proper evacuation procedures to cope with emergencies.
 - 4. Provide immediate and adequate medical attention should an injury occur.

H25-4

Discussion

Implementation:	This plan with all details is to be fully implemented before drilling to <u>commence</u> .	
Emergency response Procedure:	This section outlines the conditions and denotes steps to be taken in the event of an emergency.	
Emergency equipment Procedure:	This section outlines the safety and emergency equipment that will be required for the drilling of this well.	
Training provisions:	This section outlines the training provisions that must be adhered to prior to drilling.	
Drilling emergency call lists:	Included are the telephone numbers of all persons to be contacted should an emergency exist.	
Briefing:	This section deals with the briefing of all people involved in the drilling operation.	
Public safety:	Public safety personnel will be made aware of any potential evacuation and any additional support needed.	
Check lists:	Status check lists and procedural check lists have been included to insure adherence to the plan.	
General information:	A general information section has been included to supply support information.	

Hydrogen Sulfide Training

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on the well:

- 1. The hazards and characteristics of H2S.
- 2. Proper use and maintenance of personal protective equipment and life support systems.
- 3. H2S detection.
- 4. Proper use of H2S detectors, alarms, warning systems, briefing areas, evacuation procedures and prevailing winds.
- 5. Proper techniques for first aid and rescue procedures.
- 6. Physical effects of hydrogen sulfide on the human body.
- 7. Toxicity of hydrogen sulfide and sulfur dioxide.
- 8. Use of SCBA and supplied air equipment.
- 9. First aid and artificial respiration.
- 10. Emergency rescue.

In addition, supervisory personnel will be trained in the following areas:

- 1. The effects of H2S on metal components. If high tensile strength tubular is to be used, personnel will be trained in their special maintenance requirements.
- 2. Corrective action and shut-in procedures when drilling a well, blowout prevention and well control procedures.
- 3. The contents and requirements of the H2S Drilling Operations Plan.

H2S training refresher must have been taken within one year prior to drilling the well. Specifics on the well to be drilled will be discussed during the pre-spud meeting. H2S and well control (choke) drills will be performed while drilling the well, at least on a weekly basis. This plan shall be available in the well site. All personnel will be required to carry the documentation proving that the H2S training has been taken.

Service company and visiting personnel

- A. Each service company that will be on this well will be notified if the zone contains H2S.
- B. Each service company must provide for the training and equipment of their employees before they arrive at the well site.
 - Each-service-company will be expected to attend a well site briefing

Emergency Equipment Requirements

1. <u>Well control equipment</u>

The well shall have hydraulic BOP equipment for the anticipated pressures. Equipment is to be tested on installation and follow Oxy Well Control standard, as well as BLM Onshore Order #2.

Special control equipment:

- A. Hydraulic BOP equipment with remote control on ground. Remotely operated choke.
- B. Rotating head
- C. Gas buster equipment shall be installed before drilling out of surface pipe.

2. <u>Protective equipment for personnel</u>

- A. Four (4) 30-minute positive pressure air packs (2 at each briefing area) on location.
- B. Adequate fire extinguishers shall be located at strategic locations.
- C. Radio / cell telephone communication will be available at the rig.
 - Rig floor and trailers.
 - Vehicle.

3. <u>Hydrogen sulfide sensors and alarms</u>

- A. -H2S sensor with alarms will be located on the rig floor, at the bell nipple, and at the flow line. These monitors will be set to alarm at 10 ppm with strobe light, and audible alarm.
- B. Hand operated detectors with tubes.
- C. ^[]H2S monitor tester (to be provided by contract Safety Company.)
- D. There shall be one combustible gas detector on location at all times.

4. <u>Visual Warning Systems</u>

A. One sign located at each location entrance with the following language:

Caution – potential poison gas Hydrogen sulfide No admittance without authorization

Wind sock – wind streamers:

- A. One 36" (in length) wind sock located at protection center, at height visible from rig floor.
- B. One 36" (in length) wind sock located at height visible from pit areas.

Condition flags

A. One each condition flag to be displayed to denote conditions.

green – normal conditions yellow – potential danger red – danger, H2S present

B. Condition flag shall be posted at each location sign entrance.

5. <u>Mud Program</u>

The mud program is designed to minimize the risk of having H2S and other formation fluids at surface. Proper mud weight and safe drilling practices will be applied. H2S scavengers will be used to minimize the hazards while drilling. Below is a summary of the drilling program.

Mud inspection devices:

Garrett gas train or hatch tester for inspection of sulfide concentration in mud system.

Metallurgy

6.

- A. Drill string, casing, tubing, wellhead, blowbut preventers, drilling spools or adapters, kill lines, choke manifold, lines and valves shall be suitable for the H2S service.
- B. All the elastomers, packing, seals and ring gaskets shall be suitable for H2S service.
- 7. <u>Well Testing</u>

No drill stem test will be performed on this well.

8. <u>Evacuation plan</u>

Evacuation routes should be established prior to well spud for each well and discussed with all rig personnel.

- 9. <u>Designated area</u>
 - A. Parking and visitor area: all vehicles are to be parked at a predetermined safe distance from the wellhead.
 - B. There will be a designated smoking area.
 - C. Two briefing areas on either side of the location at the maximum allowable distance from the well bore so they offset prevailing winds perpendicularly, or at a 45-degree angle if wind direction tends to shift in the area.

Emergency procedures

- A. In the event of any evidence of H2S level above 10 ppm, take the following steps:
 - 1. The Driller will pick up off bottom, shut down the pumps, slow down the pipe rotation.
 - 2. Secure and don escape breathing equipment, report to the upwind designated safe briefing / muster area.
 - 3. All personnel on location will be accounted for and emergency search should begin for any missing, the Buddy System will be implemented.
 - 4. Order non-essential personnel to leave the well site, order all essential personnel out of the danger zone and upwind to the nearest designated safe briefing / muster area.
 - 5. Entrance to the location will be secured to a higher level than our usual "Meet and Greet" requirement, and the proper condition flag will be displayed at the entrance to the location.
 - 6. Take steps to determine if the H2S level can be corrected or suppressed and, if so, proceed as required.
- B. If uncontrollable conditions occur:
 - Take steps to protect and/or remove any public in the down-wind area from the rig – partial evacuation and isolation. Notify necessary public safety personnel and appropriate regulatory entities (i.e. BLM) of the situation.

- 2. Remove all personnel to the nearest upwind designated safe briefing / muster area or off location.
- 3. Notify public safety personnel of safe briefing / muster area.
- 4. An assigned crew member will blockade the entrance to the location. No unauthorized personnel will be allowed entry to the location.
- 5. Proceed with best plan (at the time) to regain control of the well. Maintain tight security and safety procedures.
- C. Responsibility:
 - 1. Designated personnel.
 - a. Shall be responsible for the total implementation of this plan.
 - b. Shall be in complete command during any emergency.
 - c. Shall designate a back-up.

All personnel:	1. 2. 3. 4.	On alarm, don escape unit and report to the nearest upwind designated safe briefing / muster area upw Check status of personnel (buddy system). Secure breathing equipment. Await orders from supervisor.
Drill site manager:	1	Don escape unit if necessary and report to nearest upwind designated safe briefing / muster area.
	3	Coordinate-preparations-of-individuals to return to point of release with tool pusher and driller (using the buddy system). Determine H2S concentrations. Assess situation and take control measures.
Tool pusher:	1. 2. 3. 4.	Don escape unit Report to up nearest upwind designated safe briefing / muster area. Coordinate preparation of individuals to return to point of release with tool pusher drill site manager (using the buddy system). Determine H2S concentration. Assess situation and take control measures.
Driller:	1.	Don escape unit, shut down pumps, continue

	2. 3. 4. 5. 6.	rotating DP. Check monitor for point of release. Report to nearest upwind designated safe briefing / muster area. Check status of personnel (in an attempt to rescue, use the buddy system). Assigns least essential person to notify Drill Site Manager and tool pusher by quickest means in case of their absence. Assumes the responsibilities of the Drill Site Manager and tool pusher until they arrive should they be absent.
Derrick man Floor man #1 Floor man #2	1.	Will remain in briefing / muster area until instructed by supervisor.
Mud engineer:	1. 2.	Report to nearest upwind designated safe briefing / muster area. When instructed, begin check of mud for ph and H2S level. (Garett gas train.)
Safety personnel:	1.	Mask up and check status of all personnel and secure operations as instructed by drill site manager.

<u>Taking a kick</u>

When taking a kick during an H2S emergency, all personnel will follow standard Well control procedures after reporting to briefing area and masking up.

محمد معمد دید ادر او چام ای

Open-hole logging

All unnecessary personnel off floor. Drill Site Manager and safety personnel should monitor condition, advise status and determine need for use of air equipment.

Running casing or plugging

Following the same "tripping" procedure as above. Drill Site Manager and safety personnel should determine if all personnel have access to protective equipment.

Ignition procedures

The decision to ignite the well is the responsibility of the operator (Oxy Drilling Management). The decision should be made only as a last resort and in a situation where it is clear that:

- 1. Human life and property are endangered.
- 2. There is no hope controlling the blowout under the prevailing conditions at the well.

Instructions for igniting the well

- 1. Two people are required for the actual igniting operation. They must wear self-contained breathing units and have a safety rope attached. One man (tool pusher or safety engineer) will check the atmosphere for explosive gases with the gas monitor. The other man is responsible for igniting the well.
- 2. Primary method to ignite: 25 mm flare gun with range of approximately 500 feet.
- 3. Ignite upwind and do not approach any closer than is warranted.
- 4. Select the ignition site best for protection, and which offers an easy escape route.
- 5. Before firing, check for presence of combustible gas.
- 6. After lighting, continue emergency action and procedure as before.
- 7. All unassigned personnel will remain in briefing area until instructed by supervisor or directed by the Drill Site Manager.

<u>Remember</u>: After well is ignited, burning hydrogen sulfide will convert to sulfur dioxide, which is also highly toxic. **<u>Do not assume the area is safe after the well is ignited.</u>**

Status check list

H25-12

Note: All items on this list must be completed before drilling to production casing point.

- 1. H2S sign at location entrance.
- 2. Two (2) wind socks located as required.
- 3. Four (4) 30-minute positive pressure air packs (2 at each Briefing area) on location for all rig personnel and mud loggers.
- 4. Air packs inspected and ready for use.
- 5. Cascade system and hose line hook-up as needed.
- 6. Cascade system for refilling air bottles as needed.
- 7. Condition flag on location and ready for use.
- 8. H2S detection system hooked up and tested.
- 9. H2S alarm system hooked up and tested.
- 10. Hand operated H2S detector with tubes on location.
- 11. 1 - 100' length of nylon rope on location.
- All rig crew and supervisors trained as required. 12.
- ___13. All outside service-contractors advised of potential H2S-hazard on well.
 - 14. No smoking sign posted and a designated smoking area identified.
- 15. Calibration of all H2S equipment shall be noted on the IADC report.

Checked by:_____ Date:

Procedural check list during H2S events

Perform each tour:

- 1. Check fire extinguishers to see that they have the proper charge.
- 2. Check breathing equipment to ensure that it in proper working order.
- 3. Make sure all the H2S detection system is operative.

Perform each week:

- 1. Check each piece of breathing equipment to make sure that demand or forced air regulator is working. This requires that the bottle be opened and the mask assembly be put on tight enough so that when you inhale, you receive air or feel air flow.
- 2. BOP skills (well control drills).
- 3. Check supply pressure on BOP accumulator stand by source.
- 4. Check breathing equipment mask assembly to see that straps are loosened and turned back, ready to put on.
- 5. Check pressure on breathing equipment air bottles to make sure they are charged to full volume. (Air quality checked for proper air grade "D" before bringing to location)
- 6. Confirm pressure on all supply-air bottles-
- 7. Perform breathing equipment drills with on-site personnel.
- 8. Check the following supplies for availability.
 - A. Emergency telephone list.
 - B. Hand operated H2S detectors and tubes.

General evacuation plan

- 1. When the company approved supervisor (Drill Site Manager, consultant, rig pusher, or driller) determines the H2S gas cannot be limited to the well location and the public will be involved, he will activate the evacuation plan.
- 2. Drill Site Manager or designee will notify local government agency that a hazardous condition exists and evacuation needs to be implemented.
- 3. Company or contractor safety personnel that have been trained in the use of H2S detection equipment and self-contained breathing equipment will monitor H2S concentrations, wind directions, and area of exposure. They will delineate the outer perimeter of the hazardous gas area. Extension to the evacuation area will be determined from information gathered.
- 4. Law enforcement personnel (state police, police dept., fire dept., and sheriff's dept.) Will be called to aid in setting up and maintaining road blocks. Also, they will aid in evacuation of the public if necessary.

5. After the discharge of gas has been controlled, company safety personnel will determine when the area is safe for re-entry.

<u>Important:</u> Law enforcement personnel will not be asked to come into a contaminated area. Their assistance will be limited to uncontaminated areas. Constant radio contact will be maintained with them.

Emergency actions

H2S-15

<u>Well blowout – if emergency</u>

- 1. Evacuate all personnel to "Safe Briefing / Muster Areas" or off location if needed.
- 2. If sour gas evacuate rig personnel.
- 3. If sour gas evacuate public within 3000 ft radius of exposure.
- 4. Don SCBA and shut well in if possible using the buddy system.
- 5. Notify Drilling Superintendent and call 911 for emergency help (fire dept and ambulance) if needed.
- 6. Implement the Blowout Contingency Plan, and Drilling Emergency Action Plan.
- 6. Give first aid as needed.

Person down location/facility

- 1. If immediately possible, contact 911. Give location and wait for confirmation.
- 2. Don SCBA and perform rescue operation using buddy system.

Toxic effects of hydrogen sulfide

Hydrogen sulfide is extremely toxic. The acceptable ceiling concentration for eight-hour exposure is 10 ppm, which is .001% by volume. Hydrogen sulfide is heavier than air (specific gravity -1.192) and colorless. It forms an explosive mixture with air between 4.3 and 46.0 percent by volume. Hydrogen sulfide is almost as toxic as hydrogen cyanide and is between five and six times more toxic than carbon monoxide. Toxicity data for hydrogen sulfide and various other gases are compared in table i. Physical effects at various hydrogen sulfide exposure levels are shown in table ii.

Table i

Toxicity of various gases

Common name	Chemical formula	Specific gravity (sc=1)	Threshold limit (1)	Hazardous limit (2)	Lethal concentration (3)
Hydrogen Cyanide	Hen	0.94	10 ppm	150 ppm/hr	300 ppm
Hydrogen Sulfide	H2S	1.18	10 ppm	250 ppm/hr	600 ppm
Sulfur Dioxide	So2	2.21	5 ppm	· – ,	1000 ppm
Chlorine	Cl2	2.45	l ppm	4 ppm/hr	1000 ppm
Carbon Monoxide	Со	0.97	50 ppm	400 ppm/hr	· 1000 ppm
Carbon Dioxide	Co2	1.52	5000 ppm	5%	10%
Methane	Ch4	0.55	90,000 ppm	Combustible	above 5% in air

1) threshold limit – concentration at which it is believed that all workers may be repeatedly exposed day after day without adverse effects.

2) hazardous limit – concentration that will cause death with short-term exposure.

3) lethal concentration – concentration that will cause death with short-term exposure.

Toxic effects of hydrogen sulfide

Table ii <u>Physical effects of hydrogen sulfide</u>

Perce	<u>ent-(%)Ppm</u>	Concentration Grains	Physical effects
0.	001 <10	<u>100 std. Ft3*</u> 00.65	Obvious and unpleasant odor.

0.002	10	01.30	Safe for 8 hours of exposure.
0.010	100	06.48	Kill smell in $3 - 15$ minutes. May sting eyes and throat
0.020	200	12.96	Kills smell shortly; stings eyes and throat.
0.050	500	32.96	Dizziness; breathing ceases in a few minutes; needs prompt artificial respiration.
0.070	700	45.36	Unconscious quickly; death will result if not rescued promptly.
0.100	1000	64.30	Unconscious at once; followed by death within minutes.

*at 15.00 psia and 60'f.

Use of self-contained breathing equipment (SCBA)

- 1. Written procedures shall be prepared covering safe use of SCBA's in dangerous atmosphere, which might be encountered in normal operations or in emergencies. Personnel shall be familiar with these procedures and the available SCBA.
- 2 SCBA's shall be inspected frequently at random to insure that they are properly used, cleaned, and maintained.
- 3. Anyone who may use the SCBA's shall be trained in how to insure proper facepiece to face seal. They shall wear SCBA's in normal air and then wear them in a test atmosphere. (note: such items as facial hair {beard or sideburns} and eyeglasses will not allow proper seal.) Anyone that may be reasonably expected to wear SCBA's should have these items removed before entering a toxic atmosphere. A special mask must be obtained for anyone who must wear eyeglasses or contact lenses.
- 4. Maintenance and care of SCBA's:
 - a. A program for maintenance and care of SCBA's shall include the following:
 - 1. Inspection for defects, including leak checks.
 - 2. Cleaning and disinfecting.
 - 3. Repair.
 - 4. Storage.
 - b. Inspection, self-contained breathing apparatus for emergency use shall be inspected monthly.
 - 1. Fully charged cylinders.
 - 2. Regulator and warning device operation.
 - 3. Condition of face piece and connections.
 - 4. Rubber parts shall be maintained to keep them pliable and prevent deterioration.
 - c. Routinely used SCBA's shall be collected, cleaned and disinfected as frequently as necessary to insure proper protection is provided.
- 5. Persons assigned tasks that requires use of self-contained breathing equipment shall be certified physically fit (medically cleared) for breathing equipment usage at least annually.
- 6. SCBA's should be worn when:
 - A. Any employee works near the top or on top of any tank unless test reveals less than 10 ppm of H2S.

- B. When breaking out any line where H2S can reasonably be expected.
- C. When sampling air in areas to determine if toxic concentrations of H2S exists.
- D. When working in areas where over 10 ppm H2S has been detected.
- E. At any time there is a doubt as to the H2S level in the area to be entered.

Rescue First aid for H2S poisoning

Do not panic!

Remain calm – think!

- 1. Don SCBA breathing equipment.
- 2. Remove victim(s) utilizing buddy system to fresh air as quickly as possible. (go up-wind from source or at right angle to the wind. Not down wind.)
- 3. Briefly apply chest pressure arm lift method of artificial respiration to clean the victim's lungs and to avoid inhaling any toxic gas directly from the victim's lungs.
- 4. Provide for prompt transportation to the hospital, and continue giving artificial respiration if needed.
- 5. Hospital(s) or-medical facilities-need-to-be informed, before-hand, of the possibility of H2S gas poisoning no matter how remote the possibility is.
- 6. Notify emergency room personnel that the victim(s) has been exposed to H2S gas.

Besides basic first aid, everyone on location should have a good working knowledge of artificial respiration.

Revised CM 6/27/2012





SURFACE USE PLAN OF OPERATIONS

Operator Name/Number:	OXY USA Inc.	16696
Lease Name/Number:	Cypress 34 Federal #11H	
Pool Name/Number:	Cedar Canyon Bone Spring	11520
Surface Location:	150 FNL 2000 FWL NENW(C) Sec 34 T23S R29E	Federal Lease No NMNM086024
Bottom Hole Location:	180 FSL 1979 FWL SESW(N) Sec 34 T23S R29E	

1. Existing Roads

- a. A copy of a USGS "Remuda Basin, NM" quadrangle map is attached showing the proposed location. The well location is spotted on this map, which shows the existing road system.
- b. The well was staked by Terry J. Asel, Certificate No. 15079 on 9/19/13, certified 9/25/13.
- c. Directions to Location: From the intersection of SH 128 and SH 31, go east on SH 128 for 4.5 miles. Turn south on CR 793 and go 4.1 miles. Turn west on lease road for 3.5 miles. Turn south for 1.2 miles, turn left on proposed road and go east for 42' to location.

2. New or Reconstructed Access Roads:

- a. A new access road will be built. The road will run approximately 42' east from an existing road.
- b. The maximum width of the road will be 15'. It will be crowned and made up of 6" of rolled and compacted caliche. Water will be deflected, as necessary, to avoid accumulation and prevent surface erosion.
- c. Surface material will be native caliche. This material will be obtained from a BLM approved pit nearest in proximity to the location. The average grade will be approximately 1%.
- d. No cattle guards, grates or fence cuts will be required. No turnouts are planned.
- e. Blade, water & repair existing caliche road(s) as needed.

3. Location of Existing Wells:

Existing wells within a one mile radius of the proposed well are shown on attached plat.

4. Location of Existing and/or Proposed Production Facilities.

- a. All permanent, lasting more than 6 months, above ground structures including but not limited to pumpjacks, storage tanks, pipeline risers, meter housing, etc. that are not subject to safety requirements will be painted a non-reflective paint color that blends in with the surrounding landscape. The paint-color-will be one of the colors from the BLM Standard Environmental Colors chart selected by the BLM authorized officer.
- b. In the event the well is found productive, the Goodnight 27 Federal central tank battery would be utilized and the necessary production equipment will be installed and will be stategically placed to allow for maximum interim reclamation of the well site. See proposed Production Facilities Layout diagram.
- c. A flowline to transport production will be installed from the proposed well to an existing production facility and will adhere to API Standards, see attached for detail and route.
- d. Electric line information is not available at this time. If necessary will be applied for by sundry notice or BLM right of way at a later date and will follow a route approved by the BLM.
- e. If plans change regarding the production facility or other infrastructure, a sundry notice or right of way will be submitted prior to installation or construction.

5. Location and types of Water Supply.

This well will be drilled using a combination of water mud systems. It will be obtained from commercial water stations in the area and will be hauled to location by transport truck using existing and proposed roads.

6. Construction Materials:

Primary

All caliche utilized for the drilling pad and proposed access road will be obtained from an existing BLM/State/Fee approved pit or from prevailing deposits found on the location. Will use BLM recommended extra caliche from other locations close by for roads, if available.

Secondary

The secondary way of obtaining caliche to build locations and roads will be by "turning over" the location. This means, caliche will be obtained from the actual well site. A caliche permit will be obtained from BLM prior to pushing up any caliche. 2400 cubic yards is max amount of caliche needed for pad and roads. Amount will vary for each pad. The procedure below has been approved by BLM personnel:

- A. The top 6" of topsoil is pushed off and stockpiled along the side of the location.
- B. An approximate 120' X 120' area is used within the proposed well site to remove caliche.
- C. Subsoil is removed and piled along side the 120' X 120' are within the pad site.
- D. When caliche is found, material will be stocked piled within the pad site to build the location and road.
- E. Then subsoil is pushed back in the hole and caliche is spread accordingly across entire location and road.
- F. Once well is drilled the stock piled top soil will be used for interim reclamation and spread along areas where caliche is picked up and the location size is reduced. Neither caliche nor subsoil will be stock piled outside of the well pad. Topsoil will be stockpiled along the edge of the pad as depicted in attached plat.

7. Methods of Handling Waste Material:

- a. The well will be drilled utilizing a closed loop system. Drill cuttings will be properly contained in steel tanks and taken to an NMOCD approved disposal facility.
- b. Drilling fluids and produced oil and water from the well during completion operations will be stored safely in closed containers and disposed of properly in an NMOCD approved disposal facility.
- c. Garbage and trash produced during drilling and completion operations will be collected in trash containers and disposed of properly at a state approved site. All trash on and around the well site will be collected for disposal.
- d. All human waste and grey water from drilling and completion operations will be properly contained and disposed of properly at a disposal facility.
- e. After drilling and completion operations, trash, chemicals, salts, frac sand and other waste material will be removed and disposed of properly at a disposal site.

8. Ancillary Facilities: None needed

9. Well Site Layout

- a. The proposed drilling pad to be built was staked and surveyed by a professional surveyor. The attached survey plat of the well site depicts the drilling pad layout as staked.
- b. The proposed well site layout with dimensions of the pad layout and equipment location.

 V-Door West
 CL Tanks

 South
 Pad 280' X 410'

10. Plans for Surface Reclamation:

Within 90 days of cessation of drilling and completion operations, all equipment not necessary for production operations will be removed. The location will be cleaned of all trash and junk to assure the well site is left as aesthetically pleasing as reasonably possible.

Interim Reclamation (well pad)

- a. Interim reclamation will be performed on the well site after the well is drilled and completed. See attached for the location and dimensions of the planned interim reclamation for the well site.
- b. The well location and surrounding areas will be cleared of, and maintained free of, all materials, trash, and equipment not required for production.

- c. In areas planned for interim reclamation, all the surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads.
- d. The areas planned for interim reclamation will then be recontoured to the original contour if feasible, or if not feasible, to an interim contour that blends with the surrounding topography as much as possible. Where applicable, the fill material of the well pad will be backfilled into the cut to bring the area back to the original contour. The interim cut and fill slopes prior to re-seeding will not be steeper than a 3:1 ratio, unless the adjacent native topography is steeper. Note: Constructed slopes may be much steeper during drilling, but will be recontoured to the above ratios during interim reclamation.
- e. Topsoil will be evenly respread and aggressively revegetated over the entire disturbed area not needed for all-weather operations including cuts & fills. To seed the area, the proper BLM seed mixture, free of noxious weeds, will be used. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites.
- f. Proper erosion control methods will be used on the area to control erosion, runoff and siltation of the surrounding area.
- g. The interim reclamation will be monitored periodically to ensure that vegetation has reestablished and that erosion and invasive/noxious weeds are controlled.

Final Reclamation (well pad, buried pipelines, etc.)

- a. Prior to final reclamation procedures, the well pad, road, and surrounding area will be cleared of material, trash, and equipment.
- b. All surfacing material will be removed and returned to the original mineral pit or recycled to repair or build roads and well pads.
- c. All disturbed areas, including roads, pipelines, pads, production facilities, and interim reclaimed areas will be recontoured to the contour existing prior to initial construction or a contour that blends indistinguishably with the surrounding landscape. Topsoil that was spread over the interim reclamation areas will be stockpiled prior to recontouring. The topsoil will be redistributed evenly over the entire disturbed site to ensure successful revegetation.
- d. After all the disturbed areas have been properly prepared, the areas will be seeded with the proper BLM seed mixture, free of noxious weeds. Final seedbed preparation will consist of contour cultivating to a depth of 4 to 6 inches within 24 hours prior to seeding, dozer tracking, or other imprinting in order to break the soil crust and create seed germination micro-sites.
- e. Proper erosion control methods will be used on the entire area to control erosion, runoff and siltation of the surrounding area.
- f. All unused equipment and structures including pipelines, electric line poles, tanks, etc. that serviced the well will be removed.
- g. All reclaimed areas will be monitored periodically to ensure that revegetation occurs, that the area is not redisturbed, and that erosion and invasive/noxious weeds are controlled.

11. Surface Ownership

The surface is owned by the U.S. Government and is administered by the BLM. The surface is multiple use with the primary uses of the region for the grazing of livestock and the production of oil and gas. The surface is leased to: 4T&K Cross Cattle Co., 1073 Marathon Rd., Carlsbad, NM 88220 They will be notified of our intention to drill prior to any activity.

12. Other Information

- a. The vegetation cover is generally sparse consisting of mesquite, yucca, shinnery oak, sandsage and perennial. native range grass. The topsoil is sandy in nature. Wildlife in the area is also sparse consisting of deer, coyotes, rabbits, rodents, reptiles, dove and quail.
- b. There is no permanent or live water in the general proximity of the location.
- c. There are no dwellings within 1 miles of the proposed well site.
- d. Cultural Resources Examination this well is located in the Permian Basin PA.

Pad + 1/4 mile road	\$1,552.00		\$0.20/ft over 1/4 mile	\$0.00	\$1,552.00
Pipeline - up to 1mile	\$1,433.00	1212'	\$299 per 1/4 mile	\$0.00	\$1,433.00
Total	\$2,985.00			\$0.00	\$2,985.00

e. Notice of this application was mailed to the following: None within 1 mile of surface location

13. Bond Coverage:

Bond Coverage is Individual-NMB000862, Nationwide-ESB00226

Operators Representatives:

The OXY Permian representatives responsible for ensuring compliance of the surface use plan are listed below.

Don Kendrick			
Production Coordinator			
1502 West Commerce Dr.			
Carlsbad, NM 88220			
Office Phone: 575-628-4132			
Cellular: 575-602-1484			

Roger Allen Drilling Superintendent P.O. Box 4294 Houston, TX 77210 Office Phone: 713-215-7617 Cellular: 281-682-3919

Sebastian Millan Drilling Engineering Supervisor P.O. Box 4294 Houston, TX 77210 Office Phone: 713-350-4950 Cellular:832-528-3268 Charles Wagner Manager Field Operations 1502 West Commerce Dr. Carlsbad, NM 88220 Office Phone: 575-628-4151 Cellular: 575-725-8306

Calvin (Dusty) Weaver Operation Specialist P.O. Box 50250 Midland, TX 79710 Office Phone: 432-685-5723 Cellular: 806-893-3067

Linsay Earle Drilling Engineer P.O. Box 4294 Houston, TX 77210 Office Phone: 713-350-4921 Cellular: 832-596-5507

Oxy U.S.A Inc.

New Mexico Staking Form

Date Staked:	9-19-13
Lease/Well Name:	Cypress 34 Fed # 11 H
Legal Description:	150 FNL 2000 FWL Sec. 34 T235 R295
Latitude:	32.16'05.45"
Longitude:	103.58' 28.97"
Move Information:2	O'EAST
County:	
Surface Owner/Tenant:	BLM
Nearest Residence:	miles?
Nearest Water Well:	
V-Door:	West
Road Description:	Road into NW corner from WesT
New Road:	/00
Upgrade Existing Road:	
Interim Reclamation:	50' SOUTH SO'EAST 20' NONTH 10'West
Source of Caliche:	
Top Soil:	EAST
Onsite Date Performed:	9-19-13
Onsite Attendees:	Legion Brumley-BLM JIMWILSON-Dry TErry Asel- Asel Survey
Special Notes:	

		APD Tracking # :
Storen i Seren i mare provinse provinse (Seren 2011) an i mare i mare i mare i mare i seren seren i seren a fr	Well-Site Evaluation Field	Form
Operator Name:	Well Name	gpress 34 Jed# 11 []
SHL: Section <u>34</u> , T. <u>J3</u> S. R.	29_E. Footage 150_F_N	L & Jerso FWL
Well Type: Horizontal Ve	ertical Oil Gas Other	NOS/APD Received? NOS APD
Surface Management Agency (SMA)): BLM FEE STATE Other	SMA Contacted? Yes No
Operator Representative/ Contact N	Name: ():150~	Phone
BLM Onsite Representatives	bin ly	Date <u>9-19-2013</u>
and a construction of the second s	n na fan de f I	and and a summing the second
Description & Topography: (cut & fill	, etc.)_Flat	
;=;=;=;=;=;	<u></u>	
	· · · · · · · · · · · · · · · · · · ·	
Soils: (reseeding stips, etc.) <u>Cook</u>	, Sonds	
Cave Area:		
Hydrogeology: (playas, floodplain, dr	ainages, erosive soils, plant indicators,	etc.)
Wildlife: (habitat, LPC, SDL, etc.)		
Range Improvements: (fences, etc.)	· · · · · · · · · · · · · · · · · · ·	
<u>Well Infrastructure</u> /		1, 5, 4
V-Door Direction: Topsoil: _	Cest	
Pad Size: $\underline{20 \times 410}$		
Road Route:		176
Prod. Facility Placement:		180 0. 230 3
Interim Rec: $NSEW$		
Other: Ocd will colord wh	a djacant branche of	110
but will be reaching.	¥	
Evaluation: (Moved?)		
	}	10

PECOS DISTRICT CONDITIONS OF APPROVAL

OPERATOR'S NAME:	OXY USA Inc	
LEASE NO.:	NM86024	
WELL NAME & NO.:	11H-Cypress 34 Federal	
SURFACE HOLE FOOTAGE:	150'/N & 20000'/W	
BOTTOM HOLE FOOTAGE	180'/S & 1979'/W	
LOCATION:	Section 34, T. 23 S., R. 29 E., NMPM	
COUNTY:	Eddy County, New Mexico	
		+

TABLE OF CONTENTS

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

General Provisions
Permit Expiration
Archaeology, Paleontology, and Historical Sites
Noxious Weeds
Construction
Notification
Topsoil
Closed Loop System
Federal Mineral Material Pits
Well Pads
Roads
Road Section Diagram
⊠ Drilling
R-111-P potash
H2S requirements
Cave/Karst Requirements
Logging requirements
Waste Material and Fluids
Production (Post Drilling)
Well Structures & Facilities
Pipelines
Interim Reclamation
Final Abandonment & Reclamation

I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

II. PERMIT EXPIRATION

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

0

IV. NOXIOUS WEEDS

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

VI. CONSTRUCTION

A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

C. CLOSED LOOP SYSTEM

Tanks are required for drilling operations: No Pits.

The operator shall properly dispose of drilling contents at an authorized disposal site.

D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation. The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

F. EXCLOSURE FENCING (CELLARS & PITS)

Exclosure Fencing

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

G. ON LEASE ACCESS ROADS

Road Width

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

Ditching

Ditching shall be required on both sides of the road.

Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall conform to Figure 1; cross section and plans for typical road construction.

Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outsloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

Cross Section of a Typical Lead-off Ditch



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

400 foot road with 4% road slope: $\underline{400'}_{4\%}$ + 100' = 200' lead-off ditch interval

Cattleguards

An appropriately sized cattleguard sufficient to carry out the project shall be installed and maintained at fence/road crossings. Any existing cattleguards on the access road route shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguards that are in place and are utilized during lease operations.

Fence Requirement

Where entry is granted across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting. The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fences.

Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.





VII. DRILLING

A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (575) 361-2822

- 1. Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.
- Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. If the drilling rig is removed without approval an Incident of Non-Compliance will be written and will be a "Major" violation.
- 3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
- 4. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

B. CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) time prior to drilling out for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater for all casing strings. DURING THIS WOC TIME, NO DRILL PIPE, ETC. SHALL BE RUN IN THE HOLE. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. IF OPERATOR DOES NOT HAVE THE WELL SPECIFIC CEMENT DETAILS ONSITE PRIOR TO PUMPING THE CEMENT FOR EACH CASING STRING, THE WOC WILL BE 30 HOURS. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

R-111-P potash Medium cave/karst Possible water flows in Castile and Salado. Posible lost circulation in Rustler, Salado and Delaware.

- 1. The **11** 3/4 inch surface casing shall be set at approximately **300** feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface. If salt is encountered, the operator shall set the casing **25**' above the salt.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
- d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Formation below the 11-3/4" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe and the mud weight for the bottom of the hole. Report results to BLM office.

2. The minimum required fill of cement behind the 8-5/8 inch intermediate casing, which shall be set in the basal anhydrite of the Castile formation at approximately 3000', is:

Cement to surface. If cement does not circulate see B.1.a, c-d above. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst and potash.

Formation below the 8-5/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight for the bottom of the hole. Report results to BLM office.

3. The minimum required fill of cement behind the 5-1/2 inch production casing is:

a. First stage to DV tool:

Cement to circulate. If cement does not circulate, contact the appropriate BLM office before proceeding with second stage cement job. Operator should have plans as to how they will achieve circulation on the next stage.

Operator has proposed a contingency DV tool at 3200'. If operator circulates cement on the first stage, operator is approved run the DV tool cancellation plug and cancel the second stage of the proposed cement plan. If cement does not circulate, operator will proceed with the second stage.

a. Second stage above DV tool:

Cement to surface. If cement does not circulate, contact the appropriate BLM office. Additional cement may be required – excess calculates to 14%.

- 4. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
- 5. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

C. PRESSURE CONTROL

- 1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
- 2. Variance approved to use flex line from BOP to choke manifold. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor. If the BLM inspector questions the straightness of the hose, a BLM engineer will be contacted and will review in the field or via picture supplied by inspector to determine if changes are required (operator shall expect delays if this occurs).
- 3. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 5000 (5M) psi. 5M system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.

- 4. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time.
 - b. The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer**.
 - c. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
 - d. The results of the test shall be reported to the appropriate BLM office.
 - e. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
 - f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.

D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

E. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

CRW 011515

VIII. PRODUCTION (POST DRILLING)

A. WELL STRUCTURES & FACILITIES

Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

Exclosure Netting (Open-top Tanks)

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

Open-Vent Exhaust Stack Exclosures

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

Containment Structures

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the

largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

Painting Requirement

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, <u>Shale Green</u> from the BLM Standard Environmental Color Chart (CC-001: June 2008).

B. PIPELINES

STANDARD STIPULATIONS FOR SURFACE INSTALLED PIPELINES

A copy of the application (Grant, Sundry Notice, APD) and attachments, including stipulations, survey plat and/or map, will be on location during construction. BLM personnel may request to you a copy of your permit during construction to ensure compliance with all stipulations.

Holder agrees to comply with the following stipulations to the satisfaction of the Authorized Officer:

1. The holder shall indemnify the United States against any liability for damage to life or property arising from the occupancy or use of public lands under this grant.

2. The holder shall comply with all applicable Federal laws and regulations existing or hereafter enacted or promulgated. In any event, the holder shall comply with the Toxic Substances Control Act of 1976 as amended, 15 USC 2601 <u>et seq</u>. (1982) with regards to any toxic substances that are used, generated by or stored on the right-of-way or on facilities authorized under this right-of-way grant. (See 40 CFR, Part 702-799 and especially, provisions on polychlorinated biphenyls, 40 CFR 761.1-761.193.) Additionally, any release of toxic substances (leaks, spills, etc.) in excess of the reportable quantity established by 40 CFR, Part 117 shall be reported as required by the Comprehensive Environmental Response, Compensation, and Liability Act, section 102b. A copy of any report required or requested by any Federal agency or State government as a result of a reportable release or spill of any toxic substances shall be furnished to the authorized officer concurrent with the filing of the reports to the involved Federal agency or State government.

3. The holder agrees to indemnify the United States against any liability arising from the release of any hazardous substance or hazardous waste (as these terms are defined in the Comprehensive Environmental Response, Compensation and Liability Act of 1980, 42 U.S.C. 9601, <u>et seq</u>. or the Resource Conservation and Recovery Act, 42 U.S.C. 6901, <u>et seq</u>.) on the Right-of-Way (unless the release or threatened release is wholly unrelated to activity of the Right-of-Way holder's activity on the Right-of-Way), or resulting from the activity of the Right-of-Way holder on the Right-of-Way. This agreement applies without regard to whether a release is caused by the holder, its agent, or unrelated third parties.

4. The holder shall be liable for damage or injury to the United States to the extent provided by 43 CFR Sec. 2883.1-4. The holder shall be held to a standard of strict liability for damage or injury to the United States resulting from pipe rupture, fire, or spills caused or substantially aggravated by any of the following within the right-of-way or permit area:

- a. Activities of the holder including, but not limited to construction, operation, maintenance, and termination of the facility.
- b. Activities of other parties including, but not limited to:
 - (1) Land clearing.
 - (2) Earth-disturbing and earth-moving work.
 - , (3) Blasting.
 - (4) Vandalism and sabotage.
- c. Acts of God.

The maximum limitation for such strict liability damages shall not exceed one million dollars (\$1,000,000) for any one event, and any liability in excess of such amount shall be determined by the ordinary rules of negligence of the jurisdiction in which the damage or injury occurred.

This section shall not impose strict liability for damage or injury resulting primarily from an act of war or from the negligent acts or omissions of the United States.

5. If, during any phase of the construction, operation, maintenance, or termination of the pipeline, any oil, salt water, or other pollutant should be discharged from the pipeline system, impacting Federal lands, the control and total removal, disposal, and cleaning up of such oil, salt water, or other pollutant, wherever found, shall be the responsibility of the holder, regardless of fault. Upon failure of the holder to control, dispose of, or clean up such discharge on or affecting Federal lands, or to repair all damages resulting therefrom, on the Federal lands, the Authorized Officer may take such measures as he deems necessary to control and clean up the discharge and restore the area, including, where appropriate, the aquatic environment and fish and wildlife habitats, at the full expense of the holder. Such action by the Authorized Officer shall not relieve the holder of any responsibility as provided herein.

6. All construction and maintenance activity will be confined to the authorized right-ofway width of 20 feet. If the pipeline route follows an existing road or buried pipeline right-of-way, the surface pipeline must be installed no farther than 10 feet from the edge of the road or buried pipeline right-of-way. If existing surface pipelines prevent this distance, the proposed surface pipeline must be installed immediately adjacent to the outer surface pipeline. All construction and maintenance activity will be confined to existing roads or right-of-ways.

7. No blading or clearing of any vegetation will be allowed unless approved in writing by the Authorized Officer.

8. The holder shall install the pipeline on the surface in such a manner that will minimize suspension of the pipeline across low areas in the terrain. In hummocky of duney areas, the pipeline will be "snaked" around hummocks and dunes rather then suspended across these features.

9. The pipeline shall be buried with a minimum of <u>24</u> inches under all roads, "two-tracks," and trails. Burial of the pipe will continue for 20 feet on each side of each crossing. The condition of the road, upon completion of construction, shall be returned to at least its former state with no bumps or dips remaining in the road surface.

10. The holder shall minimize disturbance to existing fences and other improvements on public lands. The holder is required to promptly repair improvements to at least their former state. Functional use of these improvements will be maintained at all times. The holder will contact the owner of any improvements prior to disturbing them. When necessary to pass through a fence line, the fence shall be braced on both sides of the passageway prior to cutting of the fence. No permanent gates will be allowed unless approved by the Authorized Officer.

11. In those areas where erosion control structures are required to stabilize soil conditions, the holder will install such structures as are suitable for the specific soil conditions being encountered and which are in accordance with sound resource management practices.

12. Excluding the pipe, all above-ground structures not subject to safety requirement shall be painted by the holder to blend with the natural color of the landscape. The paint used shall be a color which simulates "Standard Environmental Colors" – **Shale Green**, Munsell Soil Color No. 5Y 4/2; designated by the Rocky Mountain Five State Interagency Committee.

13. The pipeline will be identified by signs at the point of origin and completion of the right-of-way and at all road crossings. At a minimum, signs will state the holder's name, BLM serial number, and the product being transported. Signs will be maintained in a legible condition for the life of the pipeline.

14. The holder shall not use the pipeline route as a road for purposes other than routine maintenance as determined necessary by the Authorized Officer in consultation with the holder. The holder will take whatever steps are necessary to ensure that the pipeline route is not used as a roadway.

15. Any cultural and/or paleontological resource (historic or prehistoric site or object) discovered by the holder, or any person working on his behalf, on public or Federal land shall be immediately reported to the authorized officer. Holder shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the authorized officer. An evaluation of the discovery will be made by the authorized officer to determine appropriate cultural or scientific values. The holder will

be responsible for the cost of evaluation and any decision as to proper mitigation measures will be made by the authorized officer after consulting with the holder.

16. The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, powerline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

17. Surface pipelines must be less than or equal to 4 inches and a working pressure below 125 psi.

IX. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

X. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well.

Seed Mixture 2, for Sandy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)* per acre. There shall be <u>no</u> primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed* per acre:

Species	l <u>b/acre</u>
Sand dropseed (Sporobolus cryptandrus)	1.0
Sand love grass (Eragrostis trichodes)	1.0
Plains bristlegrass (Setaria macrostachya)	2.0

*Pounds of pure live seed:

Pounds of seed x percent purity x percent germination = pounds pure live seed