

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0137
Expires: July 31, 2010

SUNDRY NOTICES AND REPORTS ON WELLS
*Do not use this form for proposals to drill or to re-enter and
Abandoned well. Use Form 3160-3 (APD) for such proposals*

SUBMIT IN TRIPLICATE - Other instructions on page 2.

| | | |
|--|--|---|
| 1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other | | 5. Lease Serial No. NMLC-029395A |
| 2. Name of Operator APACHE CORPORATION <873> | | 6. If Indian, Allottee or Tribe Name |
| 3. Address 303 VETERANS AIRPARK LN, #3000 MIDLAND, TX 79705 | 3b. Phone No. (include area Code) 432-818-1000 / 432-818-1943 | 7. If Unit of CA/Agreement, Name and/or No. |
| 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) UL A, SEC 19, T 17 S, R 31 E, 905' ENL & 935' FEL | | 8. Well Name and No. TONY FEDERAL 55 <308738> |
| 12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA | | 9. API Well No. 30-015-41319 |
| TYPE OF SUBMISSION | | 10. Field and Pool or Exploratory Area CEDAR LAKE; GLORIETA-YESO <96831> |
| TYPE OF ACTION | | 11. County or Parish, State EDDY COUNTY, NM |

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Acidize ☐ Deepen ☐ Production (Start/Resume)
☐ Alter Casing ☐ Fracture Treat ☐ Reclamation
☐ Casing Repair ☐ New Construction ☐ Recomplete
☐ Change Plans ☐ Plug and Abandon ☐ Temporarily Abandon
☐ Convert to Injection ☐ Plug Back ☐ Water Disposal

- ☐ Water Shut-Off
☐ Well Integrity
☒ Other
DRILLING OPS: CASING
& CEMENT REPORT

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directional or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attached the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.

Bond No: BLM-CO-1463

11/21/2014 SPUD;

11/21 DRLG SURFACE 91' -355' TD; NOTIFIED BLM OF CSG & CMT

SURFACE CSG 13.375" HOLE 17.5", H40, 48# CSG SET 355'; FC @ 318'; RAN 5 CENTRALIZERS;

CMT: LEAD: 200 SX; (CL C, 14.40 PPG, 1.65 YLD)

TAIL: 500 SX; (CL C, 14.80 PPG, 1.34 YLD)

CIRC 323 SX;

NM OIL CONSERVATION
ARTESIA DISTRICT

FEB 16 2015

SURFACE CSG PRESSURE TEST 2000 PSI/30 MIN - OK

RECEIVED

REPORT CONTINUED ON PAGE 2.

| | | |
|--|---------------------------------------|---|
| 14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) SHATARA BROWN | | Accepted for record W.D. NMACD 2/18/15 |
| Signature <i>Shatara Brown</i> | Title DRILLING TECH Date 2/16/2015 | |

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

| | | |
|---|--------|------|
| Approved by | Title | Date |
| Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. | Office | |

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212; make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FEB 16 2015

RECEIVED

TONY FEDERAL 55 End of Well Sundry

11/22-11/25 DRILL CEMENT AND FLOAT;TAGGED CEMENT @ 280'; DRLG F/308'-T/490'; START INTERMEDIATE HOLE; DRLG F/490' - T/3500' TD

11/26 INTERMEDIATE CSG 8.625" HOLE 11", J55, 32# CSG SET 3500'; FC @ 3460'; RAN 27 CENTRALIZERS;
LEAD: 1000 SX; (CL C, 12.9 PPG, 1.92 YLD)
TAIL: 350 SX; (CL C, 14.8 PPG, 1.32 YLD)
CIRC 140 SX

INTERMEDIATE CSG PRESSURE TEST 2000 PSI/ 30 MIN- OK

11/26-11/29 WOC CMT; DRILL CEMENT & SHOE TRACK F/ 3500'- T/ 4003'; TAG PLUG @ 3468'; TAG FC @ 3458'; TAG SHOE @ 3500'; DRLG F/ 4003'-4816'; START PRODUCTION HOLE; DRLG F/4816'-T/6400' TD;
NOTIFIED BLM OF CSG & CMT

11/29 RU & LOG; NOTIFIED BLM RUN CSG & CMT

11/30 PRODUCTION CSG 5.5"; HOLE 7.625", J55, 17# CSG SET 6400'; FC @ 6356'; RAN 54 CENTRALIZERS
LEAD: 450 SX; (CL H, 12.6 PPG, 2.05 YLD)
TAIL: 475 SX; (CL H, 14.2 PPG, 1.37 YLD)
CIRC 191 SX
PRODUCTION CSG PRESSURE TEST 2500 PSI/ 30 MIN- OK

RD 2/17/15
Accepted for record
NMOCD

11/30/2014 RIG RELEASED