FEB 13 2015 OCD Artesia

Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERRECEIVED BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB No. 1004-0137 Expires: July 31, 2010

5. Lease Serial No. NMLC-029426B

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter and Abandoned well. Use Form 3160-3 (APD) for such proposals					6. If Indian,	Allottee or	Гribe Name			
SUBMIT IN TRIPLICATE – Other instructions on page 2.					7. If Unit of CA/Agreement, Name and/or No.					
1. Type of Well ⊠ Oil Well □				DERAL 19H <308711>						
2. Name of Operator APACHE CORPORATION <873>					9. API Well No. 30-015-41909					
3. Address 303 VETERANS AIRPARK LN, #3000 MIDLAND, TX 79705		3b. Phone No. (include area Code)			10. Field and Pool or Exploratory Area					
		432-818-1000 / 432-818-1168			FREN; GLORIETA-YESO <26770>					
4. Location of Well (Footage, Sec.,	vey Description)			11. County or Parish, State						
LOT I, SEC 10, T17S, R31E, 2280'			EDDY COUNTY, NM							
12. CHECK THE APPROPRIATE BOX(ES) TO INDICA				CATE NATURE OF NOTICE, REPORT OR OTHER DATA						
TYPE OF SUBMISSION TYPE OF ACTI					N					
□ Notice of Intent □ Acidize □ Alter Casing □ Casing Repair □ Change Plans □ Convert to Inject		New Cor	Facture Treat Reclam New Construction Recomp			DRILLING OPS: CASI y Abandon & CEMENT REPORT			<u></u>	
If the proposal is to deepen directional Attached the Bond under which the wo following completion of the involved o testing has been completed. Final Abar determined that the site is ready for final Bond No: BLM-CO-1463 2/13/2014 NOTIFIED JOSE V	rk will be performed o perations. If the opera ndonment Notices mus al inspection. 2/13/2014 SPUD	r provide the Bond N tion results in a mult t be filed only after a	Io. on file with iple completion all requirements	BLM/BIA. Req n or recompletion s, including recla	uired subsequer i in a new interv mation, have be	nt reports must by val, a Form 3160 een completed a	pe filed within 30 0-4 must be filed and the operator h	days once as		
2/13/2014 NOTIFIED JOSE WITH BLM OF SPUD; DRILLING SRUFACE 51' TO 105'; DRILLING NOTIFIED SHERIL WITH BLM OF CASING & CEMENT JOB					7 103 10 073	, 1011 17 1011	13.373 CAGIIVO	,		
2/14/2014 <u>SURFACE CSG 13.375, HOLE 17.5, H-40, 48# SET 675'; FC @ 634'</u> ; RAN 8 CENTRAL					ZERS; WOC					
CMT WITH: LEAI	D 730 SX, CLASS C (14.8 WT, 1.34 YLD));							
ON ALL FOUR SII	•						ŕ) TAG		
CMT WITH: 62 SF	KS CLASS C ; MIXED) @ 14.8 PPG ; YIEI	LD @ 1.34 CF/	SK ; 15 BBLS S	LY; CIRC 41 S	X TO SURFAC	Œ			
SURFACE CSG PR	RESSURE TEST: 1200	PSI/30 MIN –OK		RE	PORT CONT	INUED ON PA	GE 2.			
14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)						CEPTED	FOR REC	ORD		
MICHELLE CO	OOPER /		Title DF	RILLING TECH					┞	
Signature / while	Coases			7/2014		FEB_1	0 2015		H	
	THIS SP	ACE FOR FEDER	AL OR STAT	E OFFICE USE		Less.	rshda	11	L	
Approved by			Title		В	UREAU OF LAI CARLOBAD	ND MANAGEME FIELD OFFICE	NT.		
Conditions of approval, if any, are attached. or certify that the applicant holds legal or equ lease which would entitle the applicant to cor	uitable title to those rig	hts in the subject	Office							

Title 18 U>S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

CROW FEDERAL 19H - Csg & Cmt End of Well Sundry

2/17/2014 DRILL 2955'-3500' TD; CONTACTED ON CALL W/ BLM GAVE 4 HRS NOTICE TO RUN CSG & CMT; CIRC

INTERMEDIATE CSG 8.625, HOLE 11", J55, 32#, SET @ 3500' FC 3454; 28 CENTRALIZERS; CIRC FOR CMT

CMT: 780 SX CLASS C 12.9 WT, 1.92 YLD

490 SX CLASS C 14.8 WT, 1.33 YLD

CIRC 248 SX

INTERMEDIATE CSG PRESSURE TEST 1200 PSI/ 30 MIN-OK

2/25/2014 DRILL 9659'-9813'; TD MD 9813 TD TVD 5339.1 MIRU SCHLUMBERGER WL & LOGGED OPEN HOLE

2/27/2014 PRODUCTION CSG 5.5, HOLE 7.875, L80, 17# SET @ 9813' FC 6375.8; 30 CENTRALIZERS; CIRC

> CMT: 380 SX CLASS C 12.6 WT, 2.6 YLD. 1150 SX CLASS C 14.2 WT, 1.31 YLD

CIRC 66 SX; PRODUCTION CSG PRESSURE TEST 2500 PSI/ 30 MIN- OK

2/28/2014 RIG RELEASED