NM OIL CONSERVATION ARTESIA DISTRICT			
Form 3160-5 (August 2007) UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT RECEIVED		Expires: July 31, 2010	
		5. Lease Serial No. NMLC-029548A	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to re-enter and Abandoned well. Use Form 3160-3 (APD) for such proposals		6. If Indian, Allottee or Tribe Name	
SUBMIT IN TRIPLICATE – Other instructions on page 2.		7. If Unit of CA/Agreement, Name and/or No.	
1. Type of Well Gas Well Other		8. Well Name and No. COFFEE FEDERAL #18 <308710>	
2. Name of Operator APACHE CORPORATION <873>		9. API Well No. 30-015-42400	
3. Address 3b. Phone No. (include area Code)		10. Field and Pool or Exploratory Area	
303 VETERANS AIRPARK LN, #3000 MIDLAND, TX 79705 432-818	-1117 / 432-818-1198	CEDAR LAKE; GLORIETA-YESO <96831>	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		11. County or Parish, State	
LOT 2, SEC 18, T17S, R31E, 1900' FNL & 1010' FWL		EDDY COUNTY, NM	
12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA			
TYPE OF SUBMISSION TYPE OF ACTION			
 Notice of Intent Acidize Acidize Acidize Acidize Acidize Casing Repair Subsequent Report Alter Casing Casing Repair Final Abandonment Notice Acidize Convert to Injection Plug and Abandon Plug Back 13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directional or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attached the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection. Bord No: BLM-CO-1463 8/25/2014 – SPUD 8/25/2014 – SP3 3 psi 24 hr – 1205 psi Circ 143 sx cmt to surf Surf Csg pressure test: 1200 psi/30 min - OK 			
REPORT CONTINUED ON PAGE 2.			
14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed) VICKI BROWN	Title DRILLING TEC		ED FOR RECORD
Nighin 174 Bag 8.			
	Date 11/6/2014	FF	<u>B 2 5 2015</u>
THIS SPACE FOR FEDERAL OR STATE OFFICE USE Image: Comparison of the second			
Title		CARLS	BAD FIELD OFFICE
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.			
Title 18 U>S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.			
(Instructions on page 2)			

Coffee Federal #18 - Csg & Cmt End of Well Sundry

8/30/2014 - 8-5/8" Intermediate, 11" Hole, #32, J-55 csg set @ 3518' Cmt with:

<u>8/31/2014 - Lead</u>: 950 sx (35:65) Poz C w/ 6% Bentonite + 5% Salt (12.4wt, 2.1 yld, 11.16 gal/sk) Compressive Strengths: **12 hr** – 589 psi **24 hr** – 947 psi

Tail:250 sx Class C(14.8 wt, 1.34 yld, 6.31 gal/sk)Compressive Strengths:12 hr - 813 psi24 hr - 1205 psiCirc 61 sx cmt to surfIntermediate casing pressure test:2000 psi/30 min - OK

9/3/2014 - DRL F/6320' - T/6412' TD. RU SCHLUMBERGER LOGGERS.

9/4/2014 - 5-1/2" Production, 7/875" Hole, #17, J-55 csg set @ 6412' Cmt with:

Lead: 430 sx (35:65) Poz C w/ 5% Salt + 6% Bentonite (12.4 wt, 2.1 yld, 11.64 gal/sk) Compressive Strengths: 12 hr - 589 psi 24 hr - 947 psi

 Tail: 540 sx (50:50) Poz C w/ 5% Salt + 2% Bentonite
 (14.2 wt, 1.28 yld, 5.89 gal/sk)

 Compressive Strengths:
 12 hr – 1379 psi
 24 psi – 2332 psi
 Circ 101 sx cmt to surf

 Production Casing Pressure Test:
 2500 psi/30 min - OK

9/4/2014 - RR

t