Form 3160-5 (March 2012)							FORM APPROVED OMB No. 1004-0137 Expires: October 31, 2014 5. Lease Serial No. NM 58815, NM 113407 & NM 130858	
SUNDRY NOTICES AND REPORTS ON WELLS IVED Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.						6. If Indian, Allottee or Tribe Name N/A		
SUBMIT IN TRIPLICATE – Other instructions on page 2.						7. If Unit of CA/Agreement, Name and/or No. N/A		
I. Type of Well Gas Well Other						8. Well Name and No. PARKWAY 19-18 FEDERAL COM #1H		
2. Name of Operator NADEL AND GUSSMAN PERMIAN, LLC.						9. API Well No. 30-015-42545		
3a. Address 3b. Phone No. (incl 601 N. MARIENFELD, SUITE 508 MIDLAND, TX 79701 (432) 682-442					le)	10. Field and Pool or Exploratory Area TURKEY TRACK; BONE SPRING		
4. Location of Well (Footage, Sec., T.R., M., or Survey Description) 150 FSL, 330 FWL, SEC. 19, T-19-S, R-30-E						11. County or Parish, State EDDY, NM		
	12. CHECI	THE APPROPRIATE BO	K(ES) TO IND	ICATE NATURE	E OF NOTI	CE, REPORT OR OTHER	R DATA	
TYPE OF SU	TYPE OF SUBMISSION TYPE OF ACTIO							
Notice of Inter	t	Acidize	Deepo	en ure Treat	=	luction (Start/Resume) lamation	Water Shut-Ot [*] Well Integrity	
Subsequent Re	port	Casing Repair		Construction	_	omplete porarily Abandon	SURF & INT CSG	
Final Abandonment Notice		Change Plans	Plug	and Abandon Back	_	er Disposal		
 following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements. including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) 9/6/2014: SPUD 9/8/2014: SURFACE CASING - DRILL 26" HOLE TO 427'. RUN 427' OF 20" 94# J-55 CASING. CEMENT WITH 935 SACKS CLASS C. CIRCULATED 280 SACKS TO PIT. DISPLACED W/ 137 BBLS FRESH WATER, BUMPED PLUG, FLOATS HELD, FULL RETURNS. TESTED CSG TO 750 PSI, HELD GOOD 9/12/2014: IST INTERMEDIATE - DRILL 17.5" HOLE TO 1759'. RUN 40 JTS OF 13-38" 54.5# J-55 STC CASING TO 1759'. CEMENT WITH LEAD 750 SACKS CLASS C 35/65, 12.6 PPG, 1.9 YIELD. TAIL WITH 415 SACKS CLASS C, 14.8 PPG 1.34 YIELD. BUMP PLUG, FLOATS HELD FULL RETURNS. CIRCULATED 280 SACKS TO PIT. TESTED CASING TO 1000 PSI FOR 30 MINS. HELD GOOD 9/18/2014: 2ND INTERMEDIATE - DRILL 12.55" HOLE TO 3545'. RUN 3545' OF 9-5/8" 36# J-55 CASING. 1ST STAGE CEMENT WITH LEAD 520 SACKS CLASS C 35/65, 12.8 PPG, 1.9 YIELD. TAILD WITH 190 SACKS CLASS C, 14.8 PPG, 1.33 YIELD, NO RETURNS, BUMPED PLUG, EXTERNAL CASING PACKER SET @ 180'; DV TOOL SET @ 1877' AND DROPPED BOMB DID NOT CIRCULATE CEMENT FROM DV TOOL. 2ND STAGE CEMENT WITH LEAD 340 SACKS CLASS C, 12.8 PPG, 1.89 YIELD. TAIL WITH 210 SACKS CLASS C, 14.8 PPG, 1.33 YIELD. CIRCULATED 75 SACKS TO SURFACE. BUMPED PLUG WITH 1500 PSI, FLOAT HELD. TESTED CSG TO 1000 PSI, HELP GOOD 14. 1 hereby certify that the foregoing is true and correct. Name (<i>Printed/Typed</i>) SARAH PRESLEY 								
14. 1 hereby certify th	at the foregoing is tru	ie and correct. Name (Printed)	-			TACCEPTE		
SARAH PRESLEY				Title REGULA				
Signature Savanpus Da					ate 10/07/2014			
0		THIS SPACE F	OR FEDE	RAL OR ST	ATE OF	FICE USE BURE	AU OF LAND HARD CITED	
Approved by								
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify					Tide Date Office			
fictitious or fraudulent	statements or repres	I.S.C. Section 1212, make it a c entations as to any matter with			nd willfully	to make to any department of	or agency of the United States any false,	
(Instructions on page 2	!)							