Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office May 27, 2004 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30-015-34144 District II OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease District III 1220 South St. Francis Dr. STATE 🖂 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 V-2480 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH Marathon AGI State PROPOSALS.) 8. Well Number 1. Type of Well: Oil Well Gas Well **RECEIVED** 2-H 2. Name of Operator 9. OGRID Number OCT 27 2005 Yates Petroleum Corporation 025575 3. Address of Operator 10. Pool name or Wildcat ACD-AH I BOM 105 S. 4th Street, Artesia, NM 88210 Collins Ranch; Wolfcamp 4. Well Location Surface 660 feet from the North line and 660 feet from the West line BHL 660 1980 South West 33 Township 17S **NMPM** Section Range 24E Eddv County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3818'GR Pit or Below-grade Tank Application 🔲 or Closure 🔲 Depth to Groundwater ___ Distance from nearest fresh water well ___ ___ Distance from nearest surface water ___ Below-Grade Tank: Volume Pit Liner Thickness: mil bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING □ TEMPORARILY ABANDON CHANGE PLANS COMMENCE DRILLING OPNS.□ PLUG AND ABANDON | **PULL OR ALTER CASING** MULTIPLE COMPL CASING/CEMENT JOB OTHER: Production casing 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 9/30/05 - TD 8-3/4" pilot hole to 5200' at 6:45 PM. 10/1/05 - Cement kickoff plug at 4613' with 260 sx "C" + 2/10% CD-31. Cemented LCM plug at 1424' with 125 sx "H" + 10% A-10B + 2% CaCl2 + 10# LCM-1 + 1/4# Celloflake. Tagged cement at 1086'. Drilled LCM plug from 1086'-1491'. Tagged kickoff plug at 4055'. Drilled kickoff plug from 4055'-4185'. WOC. Cement did not set up at kickoff point. Drilled out remaining plug. Circulated. Tagged cement at 4432'. Drilled cement from 4432'-4452'. 10/5/05 – Picked up directional tools and orient same. Slide from 4480'-4750'. 10/9/05 – TD 8-3/4" hole to 5118'. Continued to drill with 7-7/8" bit and directional tools. 10/20/05 - TD 7-7/8" hole to 8838' at 2:45 AM 10/22/05 - Set 5-1/2" 17# P-110 LT&C casing at 8600'. Worked 5-1/2" casing to bottom. Worked 5-1/2" casing to bottom from 8174'-8600'. Cemented with 650 sx 35:65:6 Poz "C" + .25#/sx Cellophane flakes + .25% FL-52 + 5#/sx LCM-1 + 5% Salt (yld 2.05, wt 12.5). Tailed in with 1418 sx MagnePlus + 1.5% CD-32 + 1% FL-52 (yld 1.05, wt 13). I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed of closed according to NMOCD guidelines _, a general permit _ or an (attached) alternative OCD-approved plan _. SIGNATURE (TITLE Regulatory Compliance Supervisor DATE October 25, 2005 Type or print name Tina Huerta E-mail address: tinah@ypcnm.com Telephone No. 505-748-1471

NOV 0 1 2005

Conditions of Approval (if any):

FOR RECORDS ONLYTLE

For State Use Only

APPROVED BY: