| Form 3160-5<br>(August 2007)   | DEPARTMEN'I' OF THE INTERIOR  |   | 5 Lang Social )   | FORM APPROVED<br>OMB No. 1004-0137<br>Expires: July 31, 2010  |  |  |
|--|---|---|---|---|--|--|
| BUREAU OF LAND MANAGEMENT<br>SUNDRY NOTICES AND REPORTS ON WELL<br>Do not use this form for proposals to drill or to re-e<br>abandoned well. Use Form 3160-3 (APD) for such pr   |   |   | 5. Lease Serial No.<br>SHL NM067132 BHL: NM30752<br>6. If Indian, Allottee or Tribe Name<br>Iter an<br>Oposals.   |   |  |  |
| SUBMIT IN TRIPLICATE – Other instructions on page 2.   |   |   |   | 7. If Unit of CA/Agreement, Name and/or No.   |  |  |
| 1. Type of Well  |   |   | N/A   | - N/A   |  |  |
| ☑ Oil Well   |   |   | 8. Well Name ar<br>War Horse Fee  | War Horse Fed Com 3H  |  |  |
| 2. Name of Operator<br>Murchioson Oll and Gas, Inc   |   |   | 9. API Well No.<br>30-015-41227   | 9. API Well No.<br>30-015-41227 -   |  |  |
| 3a. Address     3b. Phone No. (include area code)       100 Mira Vista Blvd. Plano, Texas 75093     972-931-0700   |   |   | de) 10. Field and Po<br>Wildcat G-04 5  | 10. Field and Pool or Exploratory Area<br>Wildcat G-04 5182927m; B.S.   |  |  |
| 4. Location of Well (Footage, S<br>Surface Location 2200 FSL & 175 FEL   | lec., T.,R.,M., or Survey Description)<br>Soction 21, T18S R29E   | 11, Country or P<br>Eddy  | 11. Country or Parish, State<br>Eddy  |   |  |  |
| 12.  | CHECK THE APPROPRIATE BOX(ES  | ) TO INDICATE NATUR   | E OF NOTICE, REPORT OR  | OTHER DATA  |  |  |
| TYPE OF SUBMISSION   | TYPE OF SUBMISSION TYPE OF ACTION   |   |   |   |  |  |
| Notice of Intent   | Acidize   | Deepen<br>[] Fracture Treat   | Production (Start/Resu:   | me) Water Shut-Off<br>Well Integrity  |  |  |
| Subsequent Report  | Casing Repair   | New Construction  | Recumpleto  | Oilier  |  |  |
| The Sheets and Station   | Change Plans  | Plug and Abandon  | Temporarily Abandon   |   |  |  |
| Today, BLM recieved an emai<br>on-site burlal of drilling waste<br>agreement between Murchisc<br>and the C-144 application wa<br>BLM approved the use of a re<br>3H conforms with the 2013 N<br>under the 2012 Pit Rule. | il-transmission of a C-144 Permit for a<br>- probably due to the lack of a surface<br>in and Concho is now in place and pro-<br>s also transmitted to Concho.<br>serve pit for War Horse Fed Com 1H,<br>MOCD Pit Rule and is nearly identical<br><i>J</i> See<br><i>N</i> W C b | reserve pit at this local<br>a use agreement with the<br>wides for the use of res<br>which lies about $1/2$ mit<br>to the previously appro- | on. The current APD for the surface owner (Concho O) erve pits with on-site burial of erver pits with on-site burial of this well. The curred pit permit for the War Herchard A | Is well did not allow reserve pits and<br>il and Gas). The surface use<br>of waste. Note that this sundry notice<br>rrent C-144 for the War Horse Fed Com<br>orse Fed Com 1H, which was submitted |  |  |
| <ol> <li>I hereby certify that the foregon<br/>Name (Printed/Typed)<br/>Greg Boans</li> </ol>  | ing is true and correct.  | Title Product   | on Superintendent   |   |  |  |
| Signature My 13  |   | Date 10/21/2  | )13   | ·   |  |  |
|  | THIS SPACE FOR  | FEDERAL OR ST   | ATE OFFICE USE  |   |  |  |
| Approved by<br>Conditions of approval, if any, are<br>that the applicant holds legal or equ<br>entitle the applicant to conduct oper<br>Title 18 U.S.C. Section 1001 and T<br>fictitious or fraudulent statements of     | tached. Approval of this notice does not we<br>itable title to those rights in the subject lease<br>ations thereon.<br>itle 43 U.S.C. Section 1212, make it a crime<br>or representations as to any matter within its   | Title<br>Title<br>Which would<br>for any person knowingly a<br>jurisdiction.  | NRS<br>CFO<br>nd willfully to make to any depa  | Date 11/09/13   |  |  |
| (Instructions on page 2)   |   |   |   |   |  |  |

ài

# PECOS DISTRICT CONDITIONS OF APPROVAL

| <b>OPERATOR'S NAME:</b>    | Murchison Oil & Gas, Inc.           |
|----------------------------|-------------------------------------|
| LEASE NO.:                 | NMNM-030752                         |
| WELL NAME & NO.:           | War Horse Fed Com 3H                |
| SURFACE HOLE FOOTAGE:      | 2290' FSL & 0175' FEL               |
| <b>BOTTOM HOLE FOOTAGE</b> | 2290' FSL & 0330' FWL               |
| LOCATION:                  | Section 21, T. 18 S., R 29 E., NMPM |
| COUNTY:                    | Eddy County, New Mexico             |

# **TABLE OF CONTENTS**

Standard Conditions of Approval (COA) apply to this APD. If any deviations to these standards exist or special COAs are required, the section with the deviation or requirement will be checked below.

| General Provisions                              |
|---|
| Permit Expiration                               |
| Archaeology, Paleontology, and Historical Sites |
| Noxious Weeds                                   |
| 🔀 Special Requirements                          |
| Communitization Agreement                       |
| <b>Construction</b>                             |
| Notification                                    |
| Topsoil   |
| Reserve Pits                                    |
| Federal Mineral Material Pits                   |
| Well Pads                                       |
| Roads   |
| Road Section Diagram                            |
| ⊠ Drilling                                      |
| H2S requirements                                |
| Logging Requirements                            |
| Waste Material and Fluids                       |
| Production (Post Drilling)                      |
| Well Structures & Facilities                    |
| Interim Reclamation                             |
| Final Abandonment & Reclamation                 |

## I. GENERAL PROVISIONS

The approval of the Application For Permit To Drill (APD) is in compliance with all applicable laws and regulations: 43 Code of Federal Regulations 3160, the lease terms, Onshore Oil and Gas Orders, Notices To Lessees, New Mexico Oil Conservation Division (NMOCD) Rules, National Historical Preservation Act As Amended, and instructions and orders of the Authorized Officer. Any request for a variance shall be submitted to the Authorized Officer on Form 3160-5, Sundry Notices and Report on Wells.

## **II. PERMIT EXPIRATION**

If the permit terminates prior to drilling and drilling cannot be commenced within 60 days after expiration, an operator is required to submit Form 3160-5, Sundry Notices and Reports on Wells, requesting surface reclamation requirements for any surface disturbance. However, if the operator will be able to initiate drilling within 60 days after the expiration of the permit, the operator must have set the conductor pipe in order to allow for an extension of 60 days beyond the expiration date of the APD. (Filing of a Sundry Notice is required for this 60 day extension.)

## III. ARCHAEOLOGICAL, PALEONTOLOGY & HISTORICAL SITES

Any cultural and/or paleontological resource discovered by the operator or by any person working on the operator's behalf shall immediately report such findings to the Authorized Officer. The operator is fully accountable for the actions of their contractors and subcontractors. The operator shall suspend all operations in the immediate area of such discovery until written authorization to proceed is issued by the Authorized Officer. An evaluation of the discovery shall be made by the Authorized Officer to determine the appropriate actions that shall be required to prevent the loss of significant cultural or scientific values of the discovery. The operator shall be held responsible for the cost of the proper mitigation measures that the Authorized Officer assesses after consultation with the operator on the evaluation and decisions of the discovery. Any unauthorized collection or disturbance of cultural or paleontological resources may result in a shutdown order by the Authorized Officer.

## **IV. NOXIOUS WEEDS**

The operator shall be held responsible if noxious weeds become established within the areas of operations. Weed control shall be required on the disturbed land where noxious weeds exist, which includes the roads, pads, associated pipeline corridor, and adjacent land affected by the establishment of weeds due to this action. The operator shall consult with the Authorized Officer for acceptable weed control methods, which include following EPA and BLM requirements and policies.

# V. SPECIAL REQUIREMENT(S)

## **Communitization Agreement**

A Communitization Agreement covering the acreage dedicated to this well must be filed for approval with the BLM. The effective date of the agreement shall be prior to any sales.

## Communitization Agreement Wells

The well sign for a communitization agreement (CA) wells shall include the CA number in addition to the surface and bottom hole lease numbers.

# VI. CONSTRUCTION

## A. NOTIFICATION

The BLM shall administer compliance and monitor construction of the access road and well pad. Notify the Carlsbad Field Office at (575) 234-5909 at least 3 working days prior to commencing construction of the access road and/or well pad.

When construction operations are being conducted on this well, the operator shall have the approved APD and Conditions of Approval (COA) on the well site and they shall be made available upon request by the Authorized Officer.

## B. TOPSOIL

The operator shall strip the top portion of the soil (root zone) from the entire well pad area and stockpile the topsoil along the edge of the well pad as depicted in the APD. The root zone is typically six (6) inches in depth. All the stockpiled topsoil will be redistributed over the interim reclamation areas. Topsoil shall not be used for berming the pad or facilities. For final reclamation, the topsoil shall be spread over the entire pad area for seeding preparation.

Other subsoil (below six inches) stockpiles must be completely segregated from the topsoil stockpile. Large rocks or subsoil clods (not evident in the surrounding terrain) must be buried within the approved area for interim and final reclamation.

## C. RESERVE PITS

The pit will be closed in accordance with NMOCD pit rules, with the following additional stipulations:

## **Construction:**

<u>Burial</u>

The reserve pit shall be constructed, so that upon completion of drilling operations, the dried pit contents shall be buried a minimum depth of <u>four (4) feet</u> below ground level. Should the pit content level not meet the four foot minimum depth requirement, the excess contents shall be removed until the required minimum depth of four feet below ground level has been met. The operator shall properly dispose of the excess contents at an authorized disposal site.

### **Below Ground Level**

The reserve pit will be constructed entirely below ground level (as opposed to pushing up dirt to form the sides of the pit).

### Liner and Contents

All pits that may contain liquid material shall be lined with a 20 ml liner or greater to prevent seepage into the ground. The pit liner shall be maintained in good working condition, with no tears or holes, until the pit is closed. No trash, pipe, barrels, wireline, or metal equipment is permitted in the pit.

## <u>Freeboard</u>

Pits shall be constructed to preclude the accumulation of precipitation runoff and maintain a minimum of 2 feet of freeboard between the maximum fluid level and the lowest point of containment at all times. If pit fluids threaten to rise to a level allowing less than 2 feet of freeboard, steps shall immediately be taken to prevent introduction of additional fluids until sufficient pit capacity has been restored through fluid removal or an alternative containment method is approved and installed.

## **Exclosure** Netting

The operator will prevent humans, wildlife (*including avian wildlife*), and livestock access to fluid pits that contain or have potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will install approved netting in accordance with the requirements below. (*Note: The BLM does not approve of the use of flagging, strobe lights, metal reflectors, or noise makers as techniques for deterring wildlife.*)

Minimum Netting Requirements - The operator will:

- Construct a rigid structure made of steel tubing or wooden posts with cable strung across the pit at no more than seven (7) foot intervals along the X- and Y-axes to form a grid of 7 foot squares.
- Suspend netting a minimum of 4 to 5 feet above the fluid surface.
- Use a maximum netting mesh size of  $1\frac{1}{2}$  inches to exclude most birds.
- Cover the top and all sides of the netting support frame with netting and secure the netting at the ground surface around the entire pit to prevent wildlife entry at the netting edges. (*Note:* Hog wire panels or other wire mesh panels or fencing used on the sides of the netting support frame is ineffective in excluding small wildlife and birds unless covered by the smaller mesh netting.)
- Monitor and maintain the netting sufficiently to ensure the netting is functioning as intended, has not entrapped wildlife, and is free of holes and gaps greater than 1 ½ inches.

## Exclosure Fence

The operator will install and maintain exclosure fencing on all sides of the reserve pit to prevent access to public, livestock, and large forms of wildlife. Only one side of the

reserve pit fence may be set aside during drilling or fracturing operations, but must be reconstructed when these operations are not being performed.

- The fence shall be installed at least two (2) feet from the edge of the pit.
- Construction of the fence shall consist of steel and/or wooden posts set firmly into the ground.
- All corners shall be braced.
- Use a fence with five separate wires (smooth or barbed) or hog panel (16 ft. length by 50 in. height) with connectors such as fence staples, clips, hog rings, hose clamps, twisted wire, etc. The fencing must be secured to the posts.
- The wire (if used) must be stretched tightly and spaced evenly to effectively exclude animals.
- Do not use electric fences.
- The crected fence shall be maintained in adequate condition until the dried reserve pit undergoes backfilling.
- (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

## Escape Ramps

The operator will construct and maintain reserve pits to prevent livestock, wildlife, and humans from becoming entrapped. At a minimum, the operator will construct and maintain escape ramps, ladders, or other methods of avian and terrestrial wildlife escape in reserve pit. Escape ramps must be installed at every corner of the reserve pit and in the center of each side if that side exceeds 100 feet in length. Escape ramps must be in contact with the side of the reserve pit, bottom of the reserve pit, and the top of the reserve pit berm. Escape ramps cannot be made of metal and cannot be steeper than a 3:1 slope (Horizontal Distance: Vertical Distance) or 30% slope. (*Examples of escape ramps: 12" wide wooden planks wrapped in matting, felt lining, etc.*)

## Maintenance:

## **Hydrocarbons**

Any hydrocarbons (condensate, paraffin, diesel, etc.) introduced to the reserve pit shall be removed within 24 hours.

## **Closure:**

## <u>NMOCD</u>

The pit will be closed in accordance with NMOCD pit closure rules, with the following additional stipulations:

## <u>Drying</u>

When drilling is completed, the fluids must be drawn off the pit within 30 days and the pit reclaimed within six months. The pit should also be fully enclosed with fencing on 4 sides during the drying process.

## **Notificaiton**

The operator will notify a BLM Environmental Protection Specialist (575-234-5972) three days prior to beginning closure operations.

## Sampling

The BLM may wish to witness the sampling of the pit contents and excavation bottoms. The operator will notify a BLM Environmental Protection Specialist three days prior to sampling pit contents or excavation bottoms.

## Solidifying Pit Contents

Only mineral materials can be used to solidify pit contents. The operator is prohibited from using topsoil materials stockpiled on location for this purpose.

### Burial (Onsite)

If onsite burial is approved by the NMOCD, the pit liner sides will be folded over the pit contents and a separate liner installed atop the encapsulated pit materials. The top liner must be located four feet below the natural ground surface. Should the pit content level not meet the four foot minimum depth requirement, the excess contents shall be removed until the required minimum depth of four feet below ground level has been met. The operator shall properly dispose of the excess contents at an authorized disposal site.

## **Burial** (Trench)

If trench burial is elected as a closure method, the trench burial must be located within the confines of the approved pad. The operator should consider where the trench burial will be located in advance of pad and facility construction in order to accommodate this requirement. The trench will be fully lined, the reserve pit materials fully encapsulated, and liner installed over the top of the containment. The top liner must be located four feet below the natural ground surface.

## **Surface Restoration:**

## **Backfilling**

For both onsite and trench burials: clean mineral materials may be used to backfill on top of the liner installation or to backfill excavated pit areas to a backfill level that reaches the natural topsoil depth of the surrounding terrain or 1 foot below surface level, whichever is greater. (In sandy soils, 2 feet of topsoil material is required.) Clean and viable topsoil must be used as the top fill on the excavations and reclamation areas in order to establish vegetation. Topsoil materials must be a good match to that of the surrounding terrain.

## Contouring

The surface of the reserve pit reclamation and/or trench burial should be recontoured to match that of the native terrain.

## **Erosion Control**

Erosion control measures must be installed to ensure that reclamation stabilizes and establishes vegetation. If erosion issues develop, the erosion issues must be addressed immediately by bringing in additional backfill material and re-establishing erosion control measures.

## Seeding

The location must be seeded with an appropriate BLM seed mix for the soil type of the area.

#### D. FEDERAL MINERAL MATERIALS PIT

Payment shall be made to the BLM prior to removal of any federal mineral materials. Call the Carlsbad Field Office at (575) 234-5972.

### E. WELL PAD SURFACING

Surfacing of the well pad is not required.

If the operator elects to surface the well pad, the surfacing material may be required to be removed at the time of reclamation.

The well pad shall be constructed in a manner which creates the smallest possible surface disturbance, consistent with safety and operational needs.

### F. EXCLOSURE FENCING (CELLARS & PITS)

#### **Exclosure Fencing**

The operator will install and maintain exclosure fencing for all open well cellars to prevent access to public, livestock, and large forms of wildlife before and after drilling operations until the pit is free of fluids and the operator initiates backfilling. (For examples of exclosure fencing design, refer to BLM's Oil and Gas Gold Book, Exclosure Fence Illustrations, Figure 1, Page 18.)

### G. ON LEASE ACCESS ROADS

#### **Road Width**

The access road shall have a driving surface that creates the smallest possible surface disturbance and does not exceed fourteen (14) feet in width. The maximum width of surface disturbance, when constructing the access road, shall not exceed twenty-five (25) feet.

### Surfacing

Surfacing material is not required on the new access road driving surface. If the operator elects to surface the new access road or pad, the surfacing material may be required to be removed at the time of reclamation.

Where possible, no improvements should be made on the unsurfaced access road other than to remove vegetation as necessary, road irregularities, safety issues, or to fill low areas that may sustain standing water.

The Authorized Officer reserves the right to require surfacing of any portion of the access road at any time deemed necessary. Surfacing may be required in the event the road deteriorates, erodes, road traffic increases, or it is determined to be beneficial for future field development. The surfacing depth and type of material will be determined at the time of notification.

### Crowning

Crowning shall be done on the access road driving surface. The road crown shall have a grade of approximately 2% (i.e., a 1" crown on a 14' wide road). The road shall conform to Figure 1; cross section and plans for typical road construction.

### Ditching

Ditching shall be required on both sides of the road.

### Turnouts

Vehicle turnouts shall be constructed on the road. Turnouts shall be intervisible with interval spacing distance less than 1000 feet. Turnouts shall be constructed on all blind curves. Turnouts shall conform to the following diagram:



### Drainage

Drainage control systems shall be constructed on the entire length of road (e.g. ditches, sidehill outsloping and insloping, lead-off ditches, culvert installation, and low water crossings).

A typical lead-off ditch has a minimum depth of 1 foot below and a berm of 6 inches above natural ground level. The berm shall be on the down-slope side of the lead-off ditch.

## **Cross Section of a Typical Lead-off Ditch**



All lead-off ditches shall be graded to drain water with a 1 percent minimum to 3 percent maximum ditch slope. The spacing interval are variable for lead-off ditches and shall be determined according to the formula for spacing intervals of lead-off ditches, but may be amended depending upon existing soil types and centerline road slope (in %);

### Formula for Spacing Interval of Lead-off Ditches

Example - On a 4% road slope that is 400 feet long, the water flow shall drain water into a lead-off ditch. Spacing interval shall be determined by the following formula:

400 foot road with 4% road slope: 400' + 100' = 200' lead-off ditch interval 4%

## **Culvert Installations**

Appropriately sized culvert(s) shall be installed at the deep waterway channel flow crossing.

#### Cattleguards

An appropriately sized cattleguard(s) sufficient to carry out the project shall be installed and maintained at fence crossing(s).

Any existing cattleguard(s) on the access road shall be repaired or replaced if they are damaged or have deteriorated beyond practical use. The operator shall be responsible for the condition of the existing cattleguard(s) that are in place and are utilized during lease operations.

A gate shall be constructed and fastened securely to H-braces.

### **Fence Requirement**

Where entry is required across a fence line, the fence shall be braced and tied off on both sides of the passageway prior to cutting.

The operator shall notify the private surface landowner or the grazing allotment holder prior to crossing any fence(s).

### Public Access

Public access on this road shall not be restricted by the operator without specific written approval granted by the Authorized Officer.



Figure 1 - Cross Sections and Plans For Typical Road Sections

# VII. DRILLING

## A. DRILLING OPERATIONS REQUIREMENTS

The BLM is to be notified a minimum of 4 hours in advance for a representative to witness:

- a. Spudding well
- b. Setting and/or Cementing of all casing strings
- c. BOPE tests
  - **Eddy County**

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220, (575) 361-2822

- 1. A Hydrogen Sulfide (H2S) Drilling Plan shall be activated prior to drilling out the surface shoe. As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.
- 2. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval. If the drilling rig is removed without approval an Incident of Non-Compliance will be written and will be a "Major" violation.
- 3. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works is located, this does not include the dog house or stairway area.
- 4. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

## **B.** CASING

Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.).

Centralizers required on surface casing per Onshore Order 2.III.B.1.f.

Wait on cement (WOC) time prior to drilling out for a primary cement job will be a minimum 18 hours for a water basin, 24 hours in the potash area, or 500 pounds compressive strength, whichever is greater for all casing strings. DURING THIS WOC TIME, NO DRILL PIPE, ETC. SHALL BE RUN IN THE HOLE. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. See individual casing strings for details regarding lead cement slurry requirements.

No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.

Possibility of water and brine flows in the Salado and Artesia Groups. Possibility of lost circulation in the Grayburg and San Andres formations.

- 1. The 13-3/8 inch surface casing shall be set at approximately 280 feet (a minimum of 25 feet into the Rustler Anhydrite and above the salt) and cemented to the surface. If salt is encountered, set casing at least 25 feet above the salt.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry.
  - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Formation below the 13-3/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight anticipated to control the formation pressure to the next casing depth. Report results to BLM office.

2. The minimum required fill of cement behind the 9-5/8 inch intermediate casing is:

Cement to surface. If cement does not circulate see B.1.a, c-d above.

Formation below the 9-5/8" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight anticipated to control the formation pressure to the next casing depth. Report results to BLM office.

## Centralizers required through the curve and a minimum of one every other joint.

3. The minimum required fill of cement behind the 7 inch production casing is:

Cement to surface. If cement does not circulate see B.1.a, c-d above.

Formation below the 7" shoe to be tested according to Onshore Order 2.III.B.1.i. Test to be done as a mud equivalency test using the mud weight necessary for the pore pressure of the formation below the shoe (not the mud weight required to prevent dissolving the salt formation) and the mud weight anticipated to control the formation pressure to the next casing depth. Report results to BLM office.

- 4. Cement not required on the 4-1/2" casing. Packer system being used.
- 5. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.

## C. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.

Ċ.

- Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 5000 (5M) psi.
   5M system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
- 3. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).
  - b. The tests shall be done by an independent service company utilizing a test plug **not a cup or J-packer**.
  - c. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock.
  - d. The results of the test shall be reported to the appropriate BLM office.
  - e. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
  - f. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.

## D. DRILL STEM TEST

If drill stem tests are performed, Onshore Order 2.III.D shall be followed.

## E. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

## JAM 031813

# VIII. PRODUCTION (POST DRILLING)

## A. WELL STRUCTURES & FACILITIES

### Placement of Production Facilities

Production facilities should be placed on the well pad to allow for maximum interim recontouring and revegetation of the well location.

## **Exclosure Netting (Open-top Tanks)**

Immediately following active drilling or completion operations, the operator will take actions necessary to prevent wildlife and livestock access, including avian wildlife, to all open-topped tanks that contain or have the potential to contain salinity sufficient to cause harm to wildlife or livestock, hydrocarbons, or Resource Conservation and Recovery Act of 1976-exempt hazardous substances. At a minimum, the operator will net, screen, or cover open-topped tanks to exclude wildlife and livestock and prevent mortality. If the operator uses netting, the operator will cover and secure the open portion of the tank to prevent wildlife entry. The operator will net, screen, or cover the tanks until the operator removes the tanks from the location or the tanks no longer contain substances that could be harmful to wildlife or livestock. Use a maximum netting mesh size of 1 ½ inches. The netting must not be in contact with fluids and must not have holes or gaps.

## Chemical and Fuel Secondary Containment and Exclosure Screening

The operator will prevent all hazardous, poisonous, flammable, and toxic substances from coming into contact with soil and water. At a minimum, the operator will install and maintain an impervious secondary containment system for any tank or barrel containing hazardous, poisonous, flammable, or toxic substances sufficient to contain the contents of the tank or barrel and any drips, leaks, and anticipated precipitation. The operator will dispose of fluids within the containment system that do not meet applicable state or U. S. Environmental Protection Agency livestock water standards in accordance with state law; the operator must not drain the fluids to the soil or ground. The operator will design, construct, and maintain all secondary containment systems to prevent wildlife and livestock exposure to harmful substances. At a minimum, the operator will install effective wildlife and livestock exclosure systems such as fencing, netting, expanded metal mesh, lids, and grate covers. Use a maximum netting mesh size of 1 ½ inches.

## **Open-Vent Exhaust Stack Exclosures**

The operator will construct, modify, equip, and maintain all open-vent exhaust stacks on production equipment to prevent birds and bats from entering, and to discourage perching, roosting, and nesting. (*Recommended exclosure structures on open-vent exhaust stacks are in the shape of a cone.*) Production equipment includes, but may not be limited to, tanks, heater-treaters, separators, dehydrators, flare stacks, in-line units, and compressor mufflers.

## **Containment Structures**

Proposed production facilities such as storage tanks and other vessels will have a secondary containment structure that is constructed to hold the capacity of 1.5 times the

largest tank, plus freeboard to account for precipitation, unless more stringent protective requirements are deemed necessary.

### **Painting Requirement**

All above-ground structures including meter housing that are not subject to safety requirements shall be painted a flat non-reflective paint color, <u>Shale Green</u> from the BLM Standard Environmental Color Chart (CC-001: June 2008).

## IX. INTERIM RECLAMATION

During the life of the development, all disturbed areas not needed for active support of production operations should undergo interim reclamation in order to minimize the environmental impacts of development on other resources and uses.

Within six (6) months of well completion, operators should work with BLM surface management specialists (Jim Amos: 575-234-5909) to devise the best strategies to reduce the size of the location. Interim reclamation should allow for remedial well operations, as well as safe and efficient removal of oil and gas.

During reclamation, the removal of caliche is important to increasing the success of revegetating the site. Removed caliche that is free of contaminants may be used for road repairs, fire walls or for building other roads and locations. In order to operate the well or complete workover operations, it may be necessary to drive, park and operate on restored interim vegetation within the previously disturbed area. Disturbing revegetated areas for production or workover operations will be allowed. If there is significant disturbance and loss of vegetation, the area will need to be revegetated. Communicate with the appropriate BLM office for any exceptions/exemptions if needed.

All disturbed areas after they have been satisfactorily prepared need to be reseeded with the seed mixture provided below.

Upon completion of interim reclamation, the operator shall submit a Sundry Notices and Reports on Wells, Subsequent Report of Reclamation (Form 3160-5).

## X. FINAL ABANDONMENT & RECLAMATION

At final abandonment, well locations, production facilities, and access roads must undergo "final" reclamation so that the character and productivity of the land are restored.

Earthwork for final reclamation must be completed within six (6) months of well plugging. All pads, pits, facility locations and roads must be reclaimed to a satisfactory revegetated, safe, and stable condition, unless an agreement is made with the landowner or BLM to keep the road and/or pad intact.

After all disturbed areas have been satisfactorily prepared, these areas need to be revegetated with the seed mixture provided below. Seeding should be accomplished by drilling on the contour whenever practical or by other approved methods. Seeding may need to be repeated until revegetation is successful, as determined by the BLM.

Operators shall contact a BLM surface protection specialist prior to surface abandonment operations for site specific objectives (Jim Amos: 575-234-5909).

#### Seed Mixture 2, for Sandy Sites

The holder shall seed all disturbed areas with the seed mixture listed below. The seed mixture shall be planted in the amounts specified in pounds of pure live seed (PLS)\* per acre. There shall be <u>no</u> primary or secondary noxious weeds in the seed mixture. Seed will be tested and the viability testing of seed will be done in accordance with State law (s) and within nine (9) months prior to purchase. Commercial seed will be either certified or registered seed. The seed container will be tagged in accordance with State law(s) and available for inspection by the authorized officer.

Seed will be planted using a drill equipped with a depth regulator to ensure proper depth of planting where drilling is possible. The seed mixture will be evenly and uniformly planted over the disturbed area (smaller/heavier seeds have a tendency to drop the bottom of the drill and are planted first). The holder shall take appropriate measures to ensure this does not occur. Where drilling is not possible, seed will be broadcast and the area shall be raked or chained to cover the seed. When broadcasting the seed, the pounds per acre are to be doubled. The seeding will be repeated until a satisfactory stand is established as determined by the authorized officer. Evaluation of growth will not be made before completion of at least one full growing season after seeding.

Species to be planted in pounds of pure live seed\* per acre:

| Species                                    |   | l <u>b/acre</u> |
|--|---|-----------------|
| Sand dropseed (Sporobolus cryptandrus)     | 2 | 1.0             |
| Sand love grass (Eragrostis trichodes)     |   | 1.0             |
| Plains bristlegrass (Setaria macrostachya) |   | 2.0             |

\*Pounds of pure live seed: Pounds of seed **x** percent purity **x** percent germination = pounds pure live seed

ALL 11/4/13