Form 3160-5 (August 2007)

## UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPRO	VED
OMB No. 1004-	-0137
Evnires: July 31	2010

5. Lease Serial No.

				NMLC-029435B		
SUNDRY NOTICES AND REPORTS ON WELLS		6. If Indian, Allottee or Tribe Name				
Do not u	ise this form for proj	posals to drill or to	re-enter and			
Abandon	ed well. Use Form 3	3160-3 (APD) for si	ıch proposals			
SUBMIT IN TRIPLICATE – Other instructions on page 2.		7. If Unit of CA/Agreement, Name and/or No				
1. Type of Well		8. Well Name and No.				
☐ Oil Well ☐ Gas Well ☐ Other		NFE FEDERAL #29H <308724>				
2. Name of Operator	CORPORATION <873>			9. API Well No. <b>30-015-42585</b>		
3. Address 3b. Phone No. (include area Code)		10. Field and Pool or Exploratory Area				
303 VETERANS AIRPARK LN, #3000 432-818-1000 / 432-818-1943 MIDLAND, TX 79705		CEDAR LAKE; GLORIETA-YESO <96831>				
4. Location of Well (Footage,				11. County or Parish	, State ····	
At Surface UL P, SEC 6, T 17 S, R 31 E, 985' FSL & 155' FEL		EDDY COUNTY, NM				
At proposed prod. zone Lot 7, SEC 6, T 17 S, R 31 E, 985' FSL & 330' FWL  12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTIC						
2 4.4 1 3 14	THE 7 II THOT RUTTLE BOX					
TYPE OF SUBMISSION			- TYPE OF ACTIC	<u> </u>	Water Shi	ut Off
Notice of Intent	Acidize .	Deepen	· —	on (Start/Resume)	Water Site	
Subsequent Report	Alter Casing Casing Repair	Facture Treat  New Construction	n Reclamat		Other	
	Change Plans	Plug and Abando		rily Abandon	DRILLING O	
Final Abandonment Notice	Convert to Injection	Plug Back	Water Dis		& CEMENT	REPORT
13. Describe Proposed or Completed C	Operation: Clearly state all per	rtinent details, including es	timated starting date of	any proposed work and ap	proximate durati	ion thereof
If the proposal is to deepen directi	onal or recomplete horizontal	ly, give subsurface location	is and measured and tru	e vertical depths of all pert	tinent markers an	id zones.
Attached the Bond under which the following completion of the invol-	e work will be performed or p	provide the Bond No. on fil	e with BLM/BIA. Required	uired subsequent reports m	ust be filed within	in 30 days
testing has been completed. Final	Abandonment Notices must b					
determined that the site is ready for	_			(125	) 9/1/ <sub>1</sub>	15.
Bond No: BLM-CO-1463	3/10/2015 SPUD;			ACCEP	and kindan	Ord :
-	RFACE 91' -420' TD;					
<u>SU</u>	RFACE CSG 13.375" I	HOLE 17.5", H40, 48	# CSG SET 420'; ]	FC @ 380'; RAN 5	CENTRALIZ	ŒRS;
CN	MT: TAIL: 470 SX; (	14.8 PPG, 1.34 YLD,	C CL)			
CIRC 215 SX;		NM OIL CONSERVATION				
	CIRC 213 5A,			<b>A</b> RTESIA DI	STRICT	
		٠		SEP 01	2015	
SURFACE	CSG PRESSURE TEST	2000 PSI/30 MIN –	OK			
	'			RECEIV	<b>VED</b>	,
REPORT CO	ONTINUED ON PAGE 2.					
4. I hereby certify that the foregoin	g is true and correct.			ACCEPTED F	<del>:OR REC</del> (	)RDI —
Name (Printed/Typed)			557 ( INS			1
SHATARA		Title	DRILLING TECH	1110 1	4 0012	
Signature Maran	a Brown	Date	4/6/2015	AUG ]	<u>,4 2015                                    </u>	<del> </del>
	THIS SPAC	E FOR FEDERAL OR S	STATE OFFICE USE	1 1 K. H	W_	
pproved by		Title		BUREAU OF LAN CARLSBAD	D MANAGEME JELD OFFICE	NT
onditions of approval, if any, are attach		oes not warrant				<del></del>
certify that the applicant holds legal or ase which would entitle the applicant to		in the subject Offic	e			
1001 1001	277.0.0.0.1. 1010. 1					

Title 18 U>S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

## NFE FEDERAL #29H End of Well Sundry

3/11-3/14 TAGGED CEMENT @ 355'; DRILL CEMENT AND FLOAT; START INTERMEDIATE DRLG F/420 T/3500' TD

3/15 <u>INTERMEDIATE CSG 9.625" HOLE 12.250", J55/HCK-55, 36# CSG SET 3500'; FC @ 3457';</u> RAN 22 CENTRALIZERS

LEAD: 1200 SX; (12.9 PPG, 1.92 YLD, C CL)

TAIL: 300 SX; (14.8 PPG, 1.32 YLD, C CL)

CIRC 175 SX

INTERMEDIATE CSG PRESSURE TEST 2000 PSI/30 MIN- OK

3/16-3/22 WOC CMT; DRILL CEMENT & SHOE TRACK F/ 3457'- T/ 3500'; TAG SHOE @ 3457'; START PRODUCTION HOLE; DRLG F/3500'-T/9580'TD;

NOTIFIED BLM OF CSG & CMT

3/23 RU & LOG; NOTIFIED BLM RUN CSG & CMT

RAN TAPERED STRING

3/23-3/25 PRODUCTION CSG 104 JTS OF **5.5**"20# L-80 & CSG 115 JTS OF 7" 29# L-80; HOLE 8.5", L-80, 20# CSG SET 9,557'; FC @ 9,549';

W/ PACKERS PLUS PACKERS SYSTEM ON 5.5"; DV TOOL @ 4809' MD; RAN 29 CENTRALIZERS

LEAD: 400 SX; (12.6 PPG, 2.05 YLD, C CL)

TAIL: 210 SX; (13 PPG, 1.48 YLD, C CL)

CIRC 71 SX

PRODUCTION CSG PRESSURE TEST 2500 PSI/ 30 MIN- OK

3/26/2015 RIG RELEASED